



KEYLESS LOCKING DEVICES - 2 pg

PULLEYS, SPROCKETS & TENSIONERS - 58 pg

POWER TRANSMISSION & CONVEYOR BELTING- 70 pg



KEYLESS LOCKING DEVICES



B-LOC Trantorque®

B-LOC[®]



The B-LOC brand is synonymous with world class quality, engineering excellence and unrivaled customer support. Fenner Drives B-LOC Keyless Bushings provide a high capacity, zero-backlash shaft-to-hub connection by using the simple wedge principle. An axial force is applied by series of annular screws to engage circular steel rings and mating tapers. The resulting wedge action creates a radial force on the tapered rings, one of which contracts to squeeze the shaft while the other expands and presses into the component bore.

Trantorque[®]

From gears to cams, timing belt sprockets to conveyor rolls, climate control fan hubs to grinding wheels, the extensive range of Trantorque Keyless Bushings—all with a single locking nut—offers easy to use options for mounting and adjusting position sensitive, zero backlash drive components and accessories.

Count on Fenner Drives[®]. We've got the right product for your application.

With over 100 years of manufacturing, technical and commercial expertise, Fenner Drives is a global leader in value-adding, problem-solving products for conveying and power transmission applications. Recognized widely for our expertise and innovation, we blend reliability, quality and value in our products while providing unsurpassed technical support and service.



INDEX

| | |
|--|--------------|
| Trantorque® or B-LOC® | 4-5 |
| Engineering Data (Keyless Locking Devices) | 6-11 |
| Power Transmission Trantorque | 12-20 |
| Power Transmission B-LOC | 21-34 |
| Engineering Data (B-LOC Compression Hubs) | 35 |
| B-LOC Compression Hubs | 36-39 |
| Engineering Data (B-LOC Shrink Discs) | 40-41 |
| B-LOC Shrink Discs | 42-44 |
| B-LOC Split and Half Shrink Discs Data | 45 |
| B-LOC Split and Half Shrink Discs | 46-49 |
| B-LOC Single Taper Shrink Discs Data | 50 |
| B-LOC Single Taper Shrink Discs | 51 |
| Engineering Data (B-LOC WK Rigid Couplings) | 52-53 |
| B-LOC WK Rigid Couplings | 54-55 |

Keyless Locking Devices

Trantorque® or B-LOC®: the Enduring Question

Once you have decided that a keyless locking device is the right solution, your next big decision is which series of Fenner Drives Trantorque or B-LOC Keyless Locking Device to choose. While the underlying engineering principle for both Trantorque and B-LOC is exactly the same, the functionality of each may appeal to different applications and situations.

| SELECTION ASSISTANCE | Shaft Size Range | Overall Length Range | Torque Transmission | Axial Movement | Self Centering | Concentricity | Balance | Self-Locking Tapers | Recessed Installation Without Counterbore | RoHS Compliant |
|-------------------------------|---------------------------------|------------------------------------|---|---------------------|----------------|-------------------|-----------|---------------------|---|----------------|
| Trantorque GT | 5/8 – 3 in; 15 – 75mm | 1 1/2 – 4 1/4 in; 38.1 – 108mm | 164 – 1,549 ft lb; 210 – 2,079 Nm | ~0.075 in (1.9mm) | Yes | Excellent | Excellent | Yes | No | Yes |
| Trantorque Mini | 1/8 – 5/8 in; 3 – 16mm | 3/4 – 1 1/8 in; 19 – 29mm | 100 – 2,079 in lb; 11 – 155 Nm | ~0.045 in (1.1mm) | Yes | Excellent | Very Good | Yes | No | Yes |
| Trantorque Micro | 1/8 – 5/8 in; 3 – 16mm | 5/8 – 1 1/2 in; 15.8 – 38.1mm | 46 – 280 in lb; 5 – 32 Nm | ~0.0375 in (0.95mm) | Yes | Excellent | Very Good | No | No | Yes |
| Trantorque OE | 1 1/16 – 1 1/2 in; 17 – 35mm | 1 5/8 – 1 23/32 in; 29 – 43mm | 166 – 512 ft lb; 218 – 676 Nm | ~0.075 in (1.9mm) | Yes | Excellent | Excellent | Yes | No | Yes |
| Trantorque NT | 3/16 – 2 in | 1 1/16 – 4 3/64 in | 7 – 586 ft lb | No | Yes | Excellent | Very Good | Yes | No | Yes |
| B-LOC B109 | 1/4 – 1 3/8 in; 6 – 35mm | 0.650 – 1.102 in; 16.5 – 28.5mm | 167 – 5,929 in lb; 19 – 683 Nm | No | Yes | Excellent | Excellent | Yes | No | Yes |
| B-LOC B103 | 3/4 – 8 in; 15 – 400mm | 1.122 – 2.559 in; 21.5 – 116mm | 247 – 48,913 ft lb; 115 – 489,701 Nm | ~0.032 in (0.8mm) | Yes | Excellent | Excellent | Yes | Yes | Yes |
| B-LOC B106 | 5/8 – 8 in; 14 – 400mm | 0.846 – 2.559 in; 20.5 – 116mm | 55 – 37,959 ft lb; 68 – 372,590 Nm | No | Yes | Excellent | Excellent | Yes | No | Yes |
| B-LOC B800 | 1/4 – 4 15/16 in; 6 – 130mm | 0.866 – 5.039 in; 22 – 128mm | 16 – 18,362 ft lb; 22 – 25,742 Nm | No | Yes | Excellent | Excellent | Yes | No | Yes |
| B-LOC B400 | 3/4 – 8 in; 18 – 500mm | 0.787 – 2.047 in; 20 – 102mm | 234 – 53,827 ft lb; 302 – 814,734 Nm | No | No | Fair | Very Good | No | Yes | No |
| B-LOC B112 | 1 – 8 in; 24 – 600mm | 1.575 – 5.866 in; 40 – 203mm | 600 – 110,469 ft lb; 755 – 1,756,139 Nm | No | Yes | Excellent | Excellent | Yes | Yes | Yes |
| B-LOC B115 | 2 3/4 – 8 in; 70 – 600mm | 2.441 – 4.134 in; 62 – 160mm | 5,261 – 70,109 ft lb; 7,118 – 1,228,856 Nm | No | Yes | Excellent | Excellent | Yes | Yes | Yes |
| B-LOC B113 | 180 – 560mm | 231 – 280mm | 223,566 – 2,342,897 Nm | No | Yes | Excellent | Excellent | Yes | Yes | Yes |
| B-LOC B117 | 180 – 600mm | 122 – 178mm | 84,697 – 1,055,107 Nm | No | Yes | Excellent | Excellent | Yes | No | Yes |
| B-LOC Compression Hubs | 1/2 – 3 in; 12 – 75mm | 0.708 – 2.224 in 18.1 – 56.6mm | 48 - 4797 ft lb; 65 – 6400 Nm | No | Yes | Fair to Excellent | Excellent | No | N/A | Yes |
| B-LOC Shrink Discs | 5/8 – 21.26 in; 15 – 540mm | 0.71 – 11.26 in; 22 – 286 mm | 138 – 3,267,568 ft lb | No | Yes | Excellent | Excellent | No | N/A | No |
| B-LOC WK Couplings | 5/8 - 4-1/4 in; 16 – 105mm | 1.339 – 4.960 in; 34 -126mm | 132 – 19810 ft-lb; 179 – 26859 Nm | No | Yes | Excellent | Excellent | No | N/A | Yes |

Internal or External

At the broadest level, keyless locking devices may be split into two categories, internal locking devices (Trantorque and B-LOC Keyless Bushings) and external locking devices (B-LOC Shrink Discs, WK Couplings, and Compression Hubs). Selecting an external locking device is relatively straightforward. If you are joining two solid shafts at their ends, see the section on B-LOC WK Couplings. To connect most industry standard coupling hubs or flanges, gearboxes with hollow-shaft outputs, or other similar geometries see the B-LOC Shrink Disc section. If the component you are mounting has a narrow hub or has a short length through-bore, like a plate sprocket, see the section on B-LOC Compression Hubs.

Most applications, however, consist of a shaft and bored component that require the use of a keyless bushing. Many more factors play into the proper selection of a keyless bushing and are briefly addressed below and in the accompanying table.

Shaft Size

Shaft size may immediately determine whether you use a Trantorque or B-LOC Keyless Bushing. A Trantorque can accommodate shaft sizes as small as 1/8" (3mm) while the smallest shaft a B-LOC will fit is 1/4" (6mm). At the other end of the spectrum, Trantorque tops out at 3" (75mm) and the largest B-LOC will accommodate shafts approaching 24" (600mm). Larger and smaller versions of all units may be available as MTOs (Made To Order).

As a practical matter, under most circumstances our Application Engineers will recommend a Trantorque for shaft sizes 1-1/2" and under and a B-LOC for shaft sizes over 1-1/2". These are considered the optimal ranges for the product lines taking maximum advantage of each product's unique installation method.

Installation

The most obvious difference when comparing a B-LOC to a Trantorque Keyless Bushing is the installation method. All B-LOC units use a plurality of screws; all Trantorque units use a single hex nut. Your particular application will be your guide as to which method is preferred.

The advantages of a single hex nut, as used in a Trantorque Keyless Bushing, are speed and simplicity of installation and removal. For installation, simply tighten the single hex nut to the specified installation torque and your connection is complete. Removal is just as straightforward. Merely loosen the same hex nut and the unit will disengage. The cost for this simplicity is a relatively high installation torque requirement, which may present a challenge for larger units.

Since the force needed to draw the mating tapers of a B-LOC Keyless Bushing together is distributed among many screws, the installation torque of an individual screw is relatively low. This allows for effortless installation of even the largest units. The price paid for this low installation torque is a more timely and complex installation and removal process. The screws must be slowly and equally tightened in series until the final installation torque is achieved. Since most B-LOC units have self locking tapers, the removal process requires loosening all screws and backing off the unit.

Other Considerations

There are several other design points that may help guide you in your selection process. OD to ID ratios vary widely from product to product. If your design requires a small OD/ID ratio, consider either a B-LOC B800 or a Trantorque OE. While all Fenner Drives Keyless Bushings are designed to transmit high torque loads, if you have an extremely demanding application, a double taper B-LOC B112, B113 or B115 may be required. If you are mounting plate sprockets or other thin components, B-LOC Compression Hubs could be the solution. Other factors to consider include axial movement, recessed installation, corrosion protection, and RoHS compliance. The table is designed to help make your selection process easier, but if you are ever in doubt, please contact a Fenner Drives Applications Engineer at AE@fennerdrives.com. We will be happy to guide you to the perfect keyless locking device solution.

Keyless Locking Devices

SURFACE FINISH

Recommended surface finish for shafts and hub bores to be used with Fenner Drives Keyless Bushings is between 32 and 125 micro-inch (0.8 and 3.2 micro-meter) RMS. A smoother finish — such as that found on components supplied TG&P (turned, ground and polished) — is NOT recommended and can result in a failure of the connection. Note that surface finishes below 32 micro-inch (0.8 micro-meter) RMS can be roughened using longitudinal abrasion with a bastard file, emery paper or similar to achieve a surface finish within the recommended range.

CONCENTRICITY

Fenner Drives Keyless Bushings are precision machined to maximize concentricity and minimize runout. The final installed concentricity of mounted components depends on several variables, including the components themselves and the installation technique employed. Special attention to proper installation will be required for B-LOC® B400 series units. Overall, however, concentricity is typically excellent for the majority of Fenner Drives Keyless Bushings.

POLYMERIC DRIVE COMPONENTS

Fenner Drives Keyless Locking Devices are only recommended for use with drive components constructed of polymers if a metal sleeve of sufficient size and strength is incorporated into the bore of the mounted component. For design and manufacturing support of a suitable sleeve consult with a Fenner Drives Applications Engineer.

TEMPERATURE INFLUENCE

Similar to conventional shrink or press fits, connections using Fenner Drives Keyless Bushings are generally not affected by temperature changes as long as the shaft, hub and bushing are made of the same material and temperatures are applied uniformly to each. For situations where one or more of the components are made of a material with a different coefficient of thermal expansion or where thermal gradients/cycles are present, fit pressures can be impacted. Please consult a Fenner Drives Applications Engineer.

MOUNTING BEARINGS WITH FENNER DRIVES KEYLESS BUSHINGS

Mounting bearings with a Fenner Drives Keyless Bushing is not recommended. The expansion forces generated will distort the bearing's inner race, causing premature failure.

INSTALLING MULTIPLE FENNER DRIVES KEYLESS BUSHINGS IN SERIES

Additional torque capacity can be achieved by arranging two or more B-LOC Keyless Bushings in series. In these situations, where access to locking screws is available from one side only, the total torque capacity of the connection is not a linear function of the number of units applied. For applications involving B-LOC Keyless Bushings in series, please consult with a Fenner Drives Applications Engineer.

ANAEROBIC ADHESIVES (THREADLOCKER)

Do not use anaerobic adhesives such as Loctite®, Permatex® or similar compounds with Fenner Drives Keyless Bushings. Doing so results in unknown contact pressures and capacities. Further, disassembly may be compromised when such compounds are applied to the keyless bushing, the shaft and/or the hub bore. Proper installation assures sufficient pre-load so that threads are self-locking, even in cases where the keyless bushing is subjected to extreme vibratory conditions.

HOLLOW SHAFTS

Hollow shafts with bores exceeding 35% of outside diameter usually require a reduction of contact pressures in order to avoid permanent shaft deformation. Special considerations arise when installing Fenner Drives Keyless Bushings onto hollow shafts. Please consult with a Fenner Drives Applications Engineer for a trouble free hollow shaft connection.

LUBRICANTS

Trantorque® and B-LOC Keyless Locking Devices are supplied with an oil specific to the product line. The listed performance data requires the use of these lubricants to provide the necessary coefficient of friction to the sliding surfaces. Some products have strategically applied grease or oil (in some cases food grade) to achieve performance.

MATERIALS

Trantorque and B-LOC Keyless Locking Devices are made from carbon and heat treated alloy steels. B-LOC Keyless Bushings are manufactured from heat treated carbon and alloy steels. For applications in corrosive environments, corrosion resistance can be improved through sealing with grease or silicone, the use of protective cover plates, application of industry standard plating materials (e.g., nickel, thin dense chrome, etc.) or by specifying the product in stainless steel or other corrosion resistant materials. Please consult with a Fenner Drives Applications Engineer for more details.

TORQUE

T = peak drive torque = nominal torque multiplied by a variable safety factor to account for stall or start-up conditions, mass accelerations, impact loads, etc. Nominal drive torque can be calculated as follows:

$$M_{t_{nom}} \text{ (ft lb)} = \frac{5252 \times \text{HP}}{\text{rpm}}$$

$$M_{t_{nom}} \text{ (Nm)} = \frac{9550 \times \text{kW}}{\text{rpm}}$$

Consult with a Fenner Drives Applications Engineer in cases where “T” is uncertain.

M_t = The rated torque capacity of one Fenner Drives Keyless Bushing installed according to our instructions. Published torque capacities are calculated without using a safety factor and should be considered as the point where a connection could slip if a higher torque is applied. Therefore, always select a unit where $M_t \geq T$.

MODIFIED INSTALLATION TORQUE

The installation torque shown in the data tables is the maximum installation torque recommended for the product. Torque capacity and contact pressures are a linear function of installation torque (M_a) and can be adjusted if necessary by changing M_a within the following limits:

| Series | M_a |
|----------------------|-------------------------------------|
| Trantorque | up to 50% lower |
| B-LOC B103/B106/B109 | up to 20% lower |
| B-LOC B400 | up to 20% higher or up to 20% lower |
| B-LOC B800 | up to 20% lower |
| B-LOC B112/B113 | up to 40% lower |
| B-LOC B115 | up to 30% lower |
| B-LOC B117 | up to 20% lower |

THRUST

T_h = transmissible thrust, determined by using the following equation:

$$T_h = \frac{2 \times M_t}{d}$$

where: d = shaft diameter

M_t = rated torque capacity

TORQUE AND THRUST COMBINED

Simultaneous transmission of torque and thrust requires calculating a resultant torque:

$$M_{t_{res}} = \sqrt{T^2 + \left(\frac{F \times d}{2}\right)^2}$$

where: T = peak drive torque

F = peak thrust load

d = shaft diameter

Select a unit where $M_t \geq M_{t_{res}}$

BENDING MOMENTS

Bending moments are a crucial sizing factor in applications where a radial load from chain pull, the weight of components, etc. acts significantly outside the keyless bushing centerline. Typical applications include rolls or conveyor pulleys where shaft deflection due to radial loads results in a bending moment between shaft and end disc. Generally, bending moments change from a positive to a negative value during each rotation and are designated as rotating or reversing bending moments.

Fenner Drives Keyless Bushings are well suited to transmit rotating/reversing bending moments. Compiled using relevant data gleaned from numerous successful heavy-duty applications in conveyor pulleys as well as pertinent investigations by independent institutions, the following bending moment capacities apply:

| Series | Bending Moment Capacity (M_b) |
|----------------------|-----------------------------------|
| Trantorque | $0.28 \times M_t$ |
| B-LOC B103/B106/B109 | $0.28 \times M_t$ |
| B-LOC B400 | $0.22 \times M_t$ |
| B-LOC B800 | $0.28 \times M_t$ |
| B-LOC B115 | $0.32 \times M_t$ |
| B-LOC B112/B113 | $0.35 \times M_t$ |
| B-LOC B117 | $0.65 \times M_t$ |

where: M_t = rated torque capacity (from specification tables)

Consult with a Fenner Drives Applications Engineer on applications where the actual bending moment exceeds these recommended limits.

TORQUE AND BENDING COMBINED

Simultaneous transmission of torque and bending requires calculating a resultant torque:

$$M_{tb} = \sqrt{T^2 + (2 \times M_b)^2}$$

where: T = peak drive torque

M_b = bending moment

Always select a unit where $M_t \geq M_{tb}$ and M_b is within the limits appearing under **Bending Moment Capacity** above.


FENNER DRIVES® KEYLESS BUSHINGS WITH SHAFT ADAPTOR SLEEVES

When an existing shaft diameter does not fit the bore of a standard Fenner Drives Keyless Bushing, we recommend using an adapter sleeve that can be sized to allow for the use of a standard unit and the existing shaft. The maximum wall thickness of the adapter sleeve should be approximately 10% of the existing shaft diameter.

Note that in order to maximize the torque capacity of a sleeved keyless bushing connection, the shaft/sleeve bore interface must be free of any lubricant. This makes the sleeve outside diameter/keyless bushing bore the point of lowest torque capacity (provided the sleeve outside diameter is less than 1.25 times the shaft diameter) and allows for full use of the larger keyless bushing's higher torque capacity.

Notes:

1. Sleeve ID = $d_s - 0/+0.001"$ (.025mm)
where d_s = shaft diameter
2. Sleeve OD = $d + 0/-T_L$ for keyless bushing to be used
3. Install dry (cleaned with non-petroleum-based solvent) at shaft/sleeve bore interface for coefficient of friction $\mu = 0.15$
4. Torque capacity at sleeve OD = M_t for keyless bushing to be used
5. Torque capacity on shaft = $M_t \times \frac{d_s}{d} \times 1.25$
6. Sleeve to be manufactured with one lengthwise slit (after machining) and from material equal to or better than shaft material
7. Sleeve can be installed over existing keyway; position slit approximately opposite keyway



RADIAL LOADS

Radial loads are generated when force is applied perpendicular to the centerline of the shaft and are frequently associated with pin or axle connections (see illustration below). Fenner Drives Keyless Bushings are well suited to provide tight, backlash-free connections for this type of application, as explained below.

$$F_{rad} = \text{radial load capacity} = d \times L \times P_s$$

where: d = shaft diameter


D = hub bore

L = contact length

P_h = hub pressure

P_s = shaft contact pressure = $P_h \times \frac{D}{d}$

Typical pressure distribution in backlash-free pin connections



Explanations:

p = contact pressure provided by keyless bushing

p_L = contact pressure on projected contact area

$$= \frac{\text{load}}{d \times \text{contact length}}$$

Y.P. = yield point of pin material

HUB SIZING

Fenner Drives Keyless Bushings transmit torque and other loads by means of mechanical interference generated by pressure exerted on both the shaft and mounted component hub. Therefore, consideration must be given to the amount of hub material (wall thickness) required to prevent permanent expansion (i.e., yielding). The following information is provided to assist you in determining the required hub diameter D_N for any keyless bushing application.

Following standard industry practice, the criterion $\sigma_{ti} < S_y$ is used to determine D_N as follows:

$$D_N = D \sqrt{\frac{S_y + (P_h \times C)}{S_y - (P_h \times C)}}$$


where: D = hub bore diameter (from product specifications)

P_h = contact pressure applied to hub bore
(from product specifications)

S_y = yield strength of hub material and

C = Stress Reduction Factor which assumes the value of 1.0, 0.8 or 0.6 depending upon the relationship of your actual hub width H_w to the contact length L of the keyless bushing selected. Use the illustrations on the right to determine C for your application.

Trantorque® B-LOC® B109, B103, B106, B117, B400 & B800



B-LOC® B112, B113, & B115





Table 1
Note: Keyless Locking Device outer ring axial position must be roughly centered in the hub.

THICK WALLED CYLINDER SUBJECTED TO INTERNAL PRESSURE



TANGENTIAL STRESSES "s_t"

$$\sigma_{tx} = P \frac{Q}{1-Q} \left[1 + \frac{d_o^2}{d_x^2} \right]$$

$$\sigma_{ti} = P \frac{1+Q}{1-Q}$$

$$\sigma_{to} = 2P \frac{Q}{1-Q}$$

RADIAL STRESSES "s_r"

$$\sigma_{rx} = P \frac{Q}{1-Q} \left[1 - \frac{d_o^2}{d_x^2} \right]$$

$$\sigma_{ri} = -P$$


$$\sigma_{ro} = 0$$

EXPANSION/ CONTRACTION

$$\Delta d_i = \frac{P d_i}{E} \left[\frac{(1+Q)}{(1-Q)} + \nu \right]$$

$$\Delta d_o = 2P \frac{d_o Q}{E(1-Q)}$$

THICK WALLED CYLINDER SUBJECTED TO EXTERNAL PRESSURE



TANGENTIAL STRESSES "s_t"

$$\sigma_{tx} = -\frac{P}{1-Q} \left[1 + \frac{d_i^2}{d_x^2} \right]$$

$$\sigma_{ti} = -\frac{2P}{1-Q}$$

$$\sigma_{to} = -P \frac{1+Q}{1-Q}$$

RADIAL STRESSES "s_r"

$$\sigma_{rx} = -\frac{P}{1-Q} \left[1 - \frac{d_i^2}{d_x^2} \right]$$

$$\sigma_{ri} = 0$$

$$\sigma_{ro} = -P$$

EXPANSION/ CONTRACTION

$$\Delta d_i = 2P \frac{d_i}{E(1-Q)}$$

$$\Delta d_o = \frac{P d_o}{E} \left[\frac{(1+Q)}{(1-Q)} - \nu \right]$$

$$\tau = T \left(\frac{12}{2 \pi \left(\frac{d_o^4 - d_i^4}{32 x d_o} \right)} \right)$$

COMBINED HUB STRESSES

$$\sigma_v = \sqrt{\sigma_t^2 + \sigma_r^2 - (\sigma_t \sigma_r) + 3\tau^2}$$

KEY i = inside of cylinder
o = outside of cylinder

ν = Poisson's ratio for steel: 0.29
E = modulus of elasticity for steel: 3.0 × 10⁷ psi (2.07 × 10⁵ N/mm²)

P = pressure
τ = torsional hub stress
T = Applied Torque

$$Q = \left(\frac{d_i}{d_o} \right)^2$$

Example for calculating minimum hub diameter:

Trantorque OE 1", assuming a 2" wide hub made of 55,000 psi yield strength material.

Locate part number 6410100 on page 18.

Record the values for outside diameter D, contact length L, and hub pressure P_h and return to this page.

D = 1½"
 L = 1"
 P_h = 19,639 psi

Determine the Stress Reduction Factor C, by first calculating the ratio of hub width to contact length (H_w/L). Next, locate the appropriate product line in Table 1 on previous page to determine C.

NOTE: Contact Fenner Drives Applications Engineering if $\frac{H_w}{L} < 1$

$\frac{H_w}{L} = 2 \rightarrow C = 0.6$

The last item required is the yield strength of your mounted component, S_y. This value should be obtainable from the manufacturer of the mounted component or raw material supplier. For this example, the yield strength is 55,000 psi.

Substitute the values obtained above into the minimum hub diameter equation, D_N to obtain your result.


$D_N = 1.5 \sqrt{\frac{55,000 + (19,639 \times 0.6)}{55,000 - (19,639 \times 0.6)}} = 1.865"$

Worksheet for calculating minimum hub diameter:

| | <i>Above Example</i> | <i>Your Example</i> |
|---|----------------------|--|
| Series | Trantorque OE | |
| Part Number | 6410400 | |
| Size | 1" | |
| Outside diameter, D | 1.5 | |
| Contact Length, L | 1 | |
| Hub Pressure, P _h | 19,639 | |
| Hub Size, H _w | 2" | |
| Yield Strength, S _y | 55,000 psi | |
| $\frac{H_w}{L} = \frac{2}{1} = 2 \rightarrow C = 0.6$ C is obtained from Table 1 on previous page for Trantorque where $\frac{H_w}{L} \geq 2$ | | $\frac{H_w}{L} = \frac{\square}{\square} = \square \rightarrow C = \square$ |
| $D_N = D \sqrt{\frac{S_y + (P_h \times C)}{S_y - (P_h \times C)}}$ $= 1.5 \sqrt{\frac{55,000 + (19,639 \times 0.6)}{55,000 - (19,639 \times 0.6)}} = 1.865"$ | | $D_N = D \sqrt{\frac{S_y + (P_h \times C)}{S_y - (P_h \times C)}}$ $= \square \sqrt{\frac{\square + (\square \times \square)}{\square - (\square \times \square)}} = \square$ |

Power Transmission - Trantorque®

Trantorque®
GT
Inch



TOLERANCE (T_L)

T_L for shaft and bore is $\pm .003$ "
for all sizes

Trantorque GT – Inch

| Part Number | | | | | | | | Wrench Size | | | | M_a | Shipping Weight (lb) |
|-------------|---------------------------------|--------------------------------|-----------------|----------|----------|----------|--------------|-------------|--------------|----------|--------------|------------------------|----------------------|
| Steel | Electroless Nickel Plated Steel | Thin Dense Chrome Coated Steel | Stainless Steel | d (inch) | D (inch) | L (inch) | L_1 (inch) | A (inch) | A_1 (inch) | B (inch) | B_1 (inch) | Install Torque (ft lb) | |
| 6202120UP | 6202120EN | 6202120DC | 6990120 | 5/8 | 1 1/2 | 3/4 | 1 1/2 | 1 1/4 | 1 1/2 | 5/16 | 5/16 | 100 | 0.5 |
| 6202140UP | 6202140EN | 6202140DC | 6990140 | 11/16 | 1 1/2 | 3/4 | 1 1/2 | 1 1/4 | 1 1/2 | 5/16 | 5/16 | 100 | 0.5 |
| 6202160UP | 6202160EN | 6202160DC | 6990160 | 3/4 | 1 1/2 | 3/4 | 1 1/2 | 1 1/4 | 1 1/2 | 5/16 | 5/16 | 100 | 0.5 |
| 6202190UP | 6202190EN | 6202190DC | 6990190 | 13/16 | 1 3/4 | 7/8 | 1 7/8 | 1 1/2 | 1 3/4 | 7/16 | 3/8 | 125 | 0.7 |
| 6202200UP | 6202200EN | 6202200DC | 6990200 | 7/8 | 1 3/4 | 7/8 | 1 7/8 | 1 1/2 | 1 3/4 | 7/16 | 3/8 | 125 | 0.7 |
| 6202220UP | 6202220EN | 6202220DC | 6990220 | 15/16 | 1 3/4 | 7/8 | 1 7/8 | 1 1/2 | 1 3/4 | 7/16 | 3/8 | 125 | 0.7 |
| 6202240UP | 6202240EN | 6202240DC | 6990240 | 1 | 1 3/4 | 7/8 | 1 7/8 | 1 1/2 | 1 3/4 | 7/16 | 3/8 | 125 | 0.7 |
| 6202270UP | 6202270EN | 6202270DC | 6990270 | 1 1/16 | 2 | 1 | 2 1/4 | 1 3/4 | 2 | 1/2 | 9/16 | 167 | 1.1 |
| 6202280UP | 6202280EN | 6202280DC | 6990280 | 1 1/8 | 2 | 1 | 2 1/4 | 1 3/4 | 2 | 1/2 | 9/16 | 167 | 1.1 |
| 6202300UP | 6202300EN | 6202300DC | 6990300 | 1 3/16 | 2 | 1 | 2 1/4 | 1 3/4 | 2 | 1/2 | 9/16 | 167 | 1.1 |
| 6202320UP | 6202320EN | 6202320DC | 6990320 | 1 1/4 | 2 | 1 | 2 1/4 | 1 3/4 | 2 | 1/2 | 9/16 | 167 | 1.1 |
| 6202350UP | 6202350EN | 6202350DC | 6990350 | 1 5/16 | 2 3/8 | 1 1/2 | 2 3/4 | 2 | 2 3/8 | 9/16 | 1/2 | 192 | 1.1 |
| 6202360UP | 6202360EN | 6202360DC | 6990360 | 1 3/8 | 2 3/8 | 1 1/2 | 2 3/4 | 2 | 2 3/8 | 9/16 | 1/2 | 192 | 1.9 |
| 6202380UP | 6202380EN | 6202380DC | 6990380 | 1 7/16 | 2 3/8 | 1 1/2 | 2 3/4 | 2 | 2 3/8 | 9/16 | 1/2 | 192 | 1.8 |
| 6202400UP | 6202400EN | 6202400DC | 6990400 | 1 1/2 | 2 3/8 | 1 1/2 | 2 3/4 | 2 | 2 3/8 | 9/16 | 1/2 | 192 | 1.8 |
| 6202430UP | 6202430EN | 6202430DC | 6990430 | 1 9/16 | 2 5/8 | 1 11/16 | 3 1/8 | 2 1/4 | 2 5/8 | 9/16 | 11/16 | 234 | 2.5 |
| 6202440UP | 6202440EN | 6202440DC | 6990440 | 1 5/8 | 2 5/8 | 1 11/16 | 3 1/8 | 2 1/4 | 2 5/8 | 9/16 | 11/16 | 234 | 2.4 |
| 6202460UP | 6202460EN | 6202460DC | 6990460 | 1 11/16 | 2 5/8 | 1 11/16 | 3 1/8 | 2 1/4 | 2 5/8 | 9/16 | 11/16 | 234 | 2.4 |
| 6202480UP | 6202480EN | 6202480DC | 6990480 | 1 3/4 | 2 5/8 | 1 11/16 | 3 1/8 | 2 1/4 | 2 5/8 | 9/16 | 11/16 | 234 | 2.3 |
| 6202510UP | 6202510EN | 6202510DC | 6990510 | 1 13/16 | 2 7/8 | 2 | 3 9/16 | 2 1/2 | 2 7/8 | 5/8 | 3/4 | 409 | 3.5 |
| 6202520UP | 6202520EN | 6202520DC | 6990520 | 1 7/8 | 2 7/8 | 2 | 3 9/16 | 2 1/2 | 2 7/8 | 5/8 | 3/4 | 409 | 3.4 |
| 6202540UP | 6202540EN | 6202540DC | 6990540 | 1 15/16 | 2 7/8 | 2 | 3 9/16 | 2 1/2 | 2 7/8 | 5/8 | 3/4 | 409 | 3.3 |
| 6202560UP | 6202560EN | 6202560DC | 6990560 | 2 | 2 7/8 | 2 | 3 9/16 | 2 1/2 | 2 7/8 | 5/8 | 3/4 | 409 | 3.2 |
| 6202562UP | 6202562EN | 6202562DC | 6990562 | 2 1/16 | 3 1/8 | 2 1/8 | 3 3/4 | 2 3/4 | 3 1/8 | 5/8 | 13/16 | 442 | 3.8 |
| 6202564UP | 6202564EN | 6202564DC | 6990564 | 2 1/8 | 3 1/8 | 2 1/8 | 3 3/4 | 2 3/4 | 3 1/8 | 5/8 | 13/16 | 442 | 4 |
| 6202566UP | 6202566EN | 6202566DC | 6990566 | 2 3/16 | 3 1/8 | 2 1/8 | 3 3/4 | 2 3/4 | 3 1/8 | 5/8 | 13/16 | 442 | 3.8 |
| 6202568UP | 6202568EN | 6202568DC | 6990568 | 2 1/4 | 3 1/8 | 2 1/8 | 3 3/4 | 2 3/4 | 3 1/8 | 5/8 | 13/16 | 442 | 3.7 |
| 6202570UP | 6202570EN | 6202570DC | 6990570 | 2 5/16 | 3 3/8 | 2 1/4 | 3 7/8 | 3 | 3 3/8 | 11/16 | 3/4 | 467 | 4.4 |
| 6202572UP | 6202572EN | 6202572DC | 6990572 | 2 3/8 | 3 3/8 | 2 1/4 | 3 7/8 | 3 | 3 3/8 | 11/16 | 3/4 | 467 | 4.5 |
| 6202574UP | 6202574EN | 6202574DC | 6990574 | 2 7/16 | 3 3/8 | 2 1/4 | 3 7/8 | 3 | 3 3/8 | 11/16 | 3/4 | 467 | 4.4 |
| 6202576UP | 6202576EN | 6202576DC | 6990576 | 2 1/2 | 3 3/8 | 2 1/4 | 3 7/8 | 3 | 3 3/8 | 11/16 | 3/4 | 467 | 4.2 |
| 6202580UP | 6202580EN | 6202580DC | 6990580 | 2 9/16 | 3 5/8 | 2 3/8 | 4 1/16 | 3 1/4 | 3 5/8 | 11/16 | 13/16 | 500 | 5 |
| 6202582UP | 6202582EN | 6202582DC | 6990582 | 2 5/8 | 3 5/8 | 2 3/8 | 4 1/16 | 3 1/4 | 3 5/8 | 11/16 | 13/16 | 500 | 5.1 |
| 6202584UP | 6202584EN | 6202584DC | 6990584 | 2 11/16 | 3 5/8 | 2 3/8 | 4 1/16 | 3 1/4 | 3 5/8 | 11/16 | 13/16 | 500 | 5 |
| 6202586UP | 6202586EN | 6202586DC | 6990586 | 2 3/4 | 3 5/8 | 2 3/8 | 4 1/16 | 3 1/4 | 3 5/8 | 11/16 | 13/16 | 500 | 5 |
| 6202590UP | 6202590EN | 6202590DC | 6990590 | 2 13/16 | 3 7/8 | 2 1/2 | 4 1/4 | 3 1/2 | 3 7/8 | 3/4 | 13/16 | 550 | 6 |
| 6202592UP | 6202592EN | 6202592DC | 6990592 | 2 7/8 | 3 7/8 | 2 1/2 | 4 1/4 | 3 1/2 | 3 7/8 | 3/4 | 13/16 | 550 | 6 |
| 6202594UP | 6202594EN | 6202594DC | 6990594 | 2 15/16 | 3 7/8 | 2 1/2 | 4 1/4 | 3 1/2 | 3 7/8 | 3/4 | 13/16 | 550 | 6 |
| 6202596UP | 6202596EN | 6202596DC | 6990596 | 3 | 3 7/8 | 2 1/2 | 4 1/4 | 3 1/2 | 3 7/8 | 3/4 | 13/16 | 550 | 5 |

Trantorque®
GT
 Inch



Performance Data Table

| d (inch) | M_t | T_h | P_h^* |
|-------------|---------------------|-----------------|--------------------------|
| | Maximum Transmitted | | Hub Pressure (psi) |
| | Torque (ft lb) | Thrust (lbs) | |
| 5/8 | 164 | 6282 | 14316 |
| 11/16 | 180 | 6282 | 14316 |
| 3/4 | 196 | 6282 | 14316 |
| 13/16 | 222 | 6554 | 10015 |
| 7/8 | 239 | 6554 | 10015 |
| 15/16 | 256 | 6554 | 10015 |
| 1 | 273 | 6554 | 10015 |
| 1 1/16 | 333 | 7524 | 8917 |
| 1 1/8 | 353 | 7524 | 8917 |
| 1 3/16 | 372 | 7524 | 8917 |
| 1 1/4 | 392 | 7524 | 8917 |
| 1 5/16 | 412 | 7529 | 5194 |
| 1 3/8 | 431 | 7529 | 5194 |
| 1 7/16 | 452 | 7529 | 5194 |
| 1 1/2 | 471 | 7529 | 5194 |
| 1 9/16 | 535 | 8219 | 4599 |
| 1 5/8 | 557 | 8219 | 4599 |
| 1 11/16 | 578 | 8219 | 4599 |
| 1 3/4 | 599 | 8219 | 4599 |
| 1 13/16 | 979 | 12963 | 5639 |
| 1 7/8 | 1013 | 12963 | 5639 |
| 1 15/16 | 1047 | 12963 | 5639 |
| 2 | 1080 | 12963 | 5639 |
| 2 1/16 | 1087 | 12650 | 4781 |
| 2 1/8 | 1120 | 12650 | 4781 |
| 2 3/16 | 1153 | 12650 | 4781 |
| 2 1/4 | 1186 | 12650 | 4781 |
| 2 5/16 | 1181 | 12260 | 4064 |
| 2 3/8 | 1213 | 12260 | 4064 |
| 2 7/16 | 1245 | 12260 | 4064 |
| 2 1/2 | 1277 | 12260 | 4064 |
| 2 9/16 | 1295 | 12127 | 3554 |
| 2 5/8 | 1326 | 12127 | 3554 |
| 2 11/16 | 1358 | 12127 | 3554 |
| 2 3/4 | 1390 | 12127 | 3554 |
| 2 13/16 | 1452 | 12394 | 3233 |
| 2 7/8 | 1485 | 12394 | 3233 |
| 2 15/16 | 1517 | 12394 | 3233 |
| 3 | 1549 | 12394 | 3233 |

MULTIPLIERS

| | |
|------------------------------------|-----|
| Steel | 1.0 |
| Electroless Nickel Plated Steel | 0.6 |
| Thin Dense Chrome Coated Steel | 1.1 |
| Stainless Steel | 0.3 |

The data in the Performance Data Table is for a steel unit. To obtain data for other materials, use the multiplier provided.

For example, you require a 2" (d) Electroless Nickel Plated Trantorque GT.

Find 2" (d) in Performance Data Table and use the multiplier of 0.6 for Electroless Nickel Plated Steel.

$$M_t: 1080 \times 0.6 = 648$$



$$T_h: 12963 \times 0.6 = 7778$$

$$*P_h: 5639 \times 0.6 = 3383$$

***IMPORTANT:**

After hub pressure (P_h) is determined, record D, L and P_h and refer to page 9 and 10 to calculate the minimum hub diameter.

Trantorque®
GT
Metric



TOLERANCE (T_L)

T_L for shaft and bore is $\pm .08\text{mm}$
for all sizes

Trantorque GT – Metric

| Part Number | | | | d (mm) | D (mm) | L (mm) | L ₁ (mm) | Wrench Size | | B (mm) | B ₁ (mm) | M _a Install Torque (Nm) | Shipping Weight (kg) |
|-------------|--|---|--------------------|-----------|-----------|-----------|------------------------|-------------|--------------------------|-----------|------------------------|---|----------------------------|
| Steel | Electroless Nickel Plated Steel | Thin Dense Chrome Coated Steel | Stainless Steel | | | | | A (mm) | A ₁ (inch) | | | | |
| 6202800UP | 6202800EN | 6202800DC | 6990800 | 15 | 38.0 | 19.1 | 38.1 | 32 | 1 1/2 | 8.0 | 8.9 | 136 | 0.2 |
| 6202803UP | 6202803EN | 6202803DC | 6990803 | 16 | 38.0 | 19.1 | 38.1 | 32 | 1 1/2 | 8.0 | 8.9 | 136 | 0.2 |
| 6202804UP | 6202804EN | 6202804DC | 6990804 | 17 | 38.0 | 19.1 | 38.1 | 32 | 1 1/2 | 8.0 | 8.9 | 136 | 0.2 |
| 6202805UP | 6202805EN | 6202805DC | 6990805 | 18 | 38.0 | 19.1 | 38.1 | 32 | 1 1/2 | 8.0 | 8.9 | 136 | 0.2 |
| 6202808UP | 6202808EN | 6202808DC | 6990808 | 19 | 38.0 | 19.1 | 38.1 | 32 | 1 1/2 | 8.0 | 8.9 | 136 | 0.2 |
| 6202811UP | 6202811EN | 6202811DC | 6990811 | 20 | 45.0 | 22.2 | 47.6 | 38 | 1 3/4 | 11.1 | 9.5 | 170 | 0.4 |
| 6202815UP | 6202815EN | 6202815DC | 6990815 | 22 | 45.0 | 22.2 | 47.6 | 38 | 1 3/4 | 11.1 | 9.5 | 170 | 0.4 |
| 6202820UP | 6202820EN | 6202820DC | 6990820 | 24 | 45.0 | 22.2 | 47.6 | 38 | 1 3/4 | 11.1 | 9.5 | 170 | 0.3 |
| 6202825UP | 6202825EN | 6202825DC | 6990825 | 25 | 45.0 | 22.2 | 47.6 | 38 | 1 3/4 | 11.1 | 9.5 | 170 | 0.3 |
| 6202830UP | 6202830EN | 6202830DC | 6990830 | 28 | 51.0 | 25.4 | 57.2 | 46 | 2 | 12.7 | 14.3 | 225 | 0.5 |
| 6202835UP | 6202835EN | 6202835DC | 6990835 | 30 | 51.0 | 25.4 | 57.2 | 46 | 2 | 12.7 | 14.3 | 225 | 0.5 |
| 6202840UP | 6202840EN | 6202840DC | 6990840 | 32 | 51.0 | 25.4 | 57.2 | 46 | 2 | 12.7 | 14.3 | 225 | 0.5 |
| 6202845UP | 6202845EN | 6202845DC | 6990845 | 34 | 60.5 | 38.1 | 69.9 | 50 | 2 3/8 | 14.3 | 12.7 | 260 | 0.9 |
| 6202850UP | 6202850EN | 6202850DC | 6990850 | 35 | 60.5 | 38.1 | 69.9 | 50 | 2 3/8 | 14.3 | 12.7 | 260 | 0.9 |
| 6202855UP | 6202855EN | 6202855DC | 6990855 | 36 | 60.5 | 38.1 | 69.9 | 50 | 2 3/8 | 14.3 | 12.7 | 260 | 0.9 |
| 6202860UP | 6202860EN | 6202860DC | 6990860 | 38 | 60.5 | 38.1 | 69.9 | 50 | 2 3/8 | 14.3 | 12.7 | 260 | 0.8 |
| 6202865UP | 6202865EN | 6202865DC | 6990865 | 40 | 67.0 | 42.9 | 79.4 | 60 | 2 5/8 | 14.3 | 17.4 | 316 | 1.2 |
| 6202870UP | 6202870EN | 6202870DC | 6990870 | 42 | 67.0 | 42.9 | 79.4 | 60 | 2 5/8 | 14.3 | 17.4 | 316 | 1.1 |
| 6202876UP | 6202876EN | 6202876DC | 6990876 | 45 | 73.0 | 50.8 | 90.5 | 65 | 2 7/8 | 15.9 | 19.1 | 554 | 1.6 |
| 6202880UP | 6202880EN | 6202880DC | 6990880 | 48 | 73.0 | 50.8 | 90.5 | 65 | 2 7/8 | 15.9 | 19.1 | 554 | 1.6 |
| 6202885UP | 6202885EN | 6202885DC | 6990885 | 50 | 73.0 | 50.8 | 90.5 | 65 | 2 7/8 | 15.9 | 19.1 | 554 | 1.5 |
| 6202900UP | 6202900EN | 6202900DC | 6990900 | 55 | 80.0 | 54.0 | 95.3 | 70 | 3 1/8 | 15.9 | 20.7 | 600 | 1.8 |
| 6202910UP | 6202910EN | 6202910DC | 6990910 | 60 | 86.0 | 57.2 | 98.4 | 75 | 3 3/8 | 17.5 | 19.1 | 635 | 2 |
| 6202920UP | 6202920EN | 6202920DC | 6990920 | 65 | 92.0 | 60.3 | 103.2 | 82 | 3 5/8 | 17.5 | 20.7 | 680 | 2 |
| 6202930UP | 6202930EN | 6202930DC | 6990930 | 70 | 92.0 | 60.3 | 103.2 | 82 | 3 5/8 | 17.5 | 20.7 | 680 | 2 |
| 6202940UP | 6202940EN | 6202940DC | 6990940 | 75 | 100.0 | 63.5 | 108.0 | 90 | 3 7/8 | 19.1 | 20.7 | 750 | 3 |

Trantorque®
GT
Metric



Performance Data Table

| d (mm) | M _t | Th | P _h * |
|-----------|---------------------|----------------|---|
| | Maximum Transmitted | | Hub Pressure (N/mm ²) |
| | Torque (Nm) | Thrust (kN) | |
| 15 | 210 | 28 | 99 |
| 16 | 224 | 28 | 99 |
| 17 | 238 | 28 | 99 |
| 18 | 252 | 28 | 99 |
| 19 | 266 | 28 | 99 |
| 20 | 292 | 29 | 68 |
| 22 | 322 | 29 | 68 |
| 24 | 351 | 29 | 68 |
| 25 | 366 | 29 | 68 |
| 28 | 466 | 33 | 61 |
| 30 | 499 | 33 | 61 |
| 32 | 532 | 33 | 61 |
| 34 | 569 | 33 | 36 |
| 35 | 585 | 33 | 36 |
| 36 | 602 | 33 | 36 |
| 38 | 636 | 33 | 36 |
| 40 | 728 | 36 | 31 |
| 42 | 765 | 36 | 31 |
| 45 | 1296 | 58 | 39 |
| 48 | 1383 | 58 | 39 |
| 50 | 1440 | 58 | 39 |
| 55 | 1549 | 56 | 33 |
| 60 | 1641 | 55 | 28 |
| 65 | 1759 | 54 | 25 |
| 70 | 1894 | 54 | 25 |
| 75 | 2079 | 55 | 22 |

MULTIPLIERS

| | |
|------------------------------------|-----|
| Steel | 1.0 |
| Electroless Nickel Plated Steel | 0.6 |
| Thin Dense Chrome Coated Steel | 1.1 |
| Stainless Steel | 0.3 |

The data in the Performance Data Table is for a steel unit. To obtain data for other materials, use the multiplier provided.

For example, you require a 30mm (d) Electroless Nickel Plated Trantorque GT.

Find 30mm (d) in Performance Data Table and use the multiplier of 0.6 for Electroless Nickel Plated Steel.

$$M_t: 499 \times 0.6 = 266$$

$$T_H: 33 \times 0.6 = 20$$



$$*P_h: 61 \times 0.6 = 37$$

***IMPORTANT:**

After hub pressure (P_h) is determined, record D, L and P_h and refer to page 9 and 10 to calculate the minimum hub diameter.

Power Transmission - Trantorque®

Trantorque®
Mini
Inch and Metric



TOLERANCE (T_L)

T_L for shaft and bore is $\pm .0015"$
(.04mm) for all sizes

Trantorque Mini – Inch

| Part Number | | | | d (inch) | D (inch) | L (inch) | L ₁ (inch) | Wrench Size | | M _a † Install Torque (in lb) | Shipping Weight (lb) |
|-------------|---------------------------------------|--------------------------------------|--------------------|-------------|-------------|-------------|--------------------------|-------------|-------------|---|----------------------------|
| Steel | Electroless Nickel Plated Steel | Thin Dense Chrome Coated Steel | Stainless Steel | | | | | A (inch) | B (inch) | | |
| 6410013 | 6202102EN | 6410013DC | 6990102 | 1/8 | 5/8 | 3/8 | 3/4 | 1/2 | 1/8 | 125 | 0.1 |
| 6410019 | 6202103EN | 6410019DC | 6990103 | 3/16 | 5/8 | 3/8 | 3/4 | 1/2 | 1/8 | 125 | 0.1 |
| 6410025 | 6202105EN | 6410025DC | 6990105 | 1/4 | 5/8 | 3/8 | 3/4 | 1/2 | 1/8 | 125 | 0.1 |
| 6410031 | 6202107EN | 6410031DC | 6990107 | 5/16 | 3/4 | 7/16 | 7/8 | 5/8 | 1/8 | 250 | 0.1 |
| 6410038 | 6202109EN | 6410038DC | 6990109 | 3/8 | 3/4 | 7/16 | 7/8 | 5/8 | 1/8 | 250 | 0.1 |
| 6410044 | 6202110EN | 6410044DC | 6990110 | 7/16 | 7/8 | 1/2 | 1 | 3/4 | 3/16 | 390 | 0.1 |
| 6410050 | 6202112EN | 6410050DC | 6990112 | 1/2 | 7/8 | 1/2 | 1 | 3/4 | 3/16 | 390 | 0.1 |
| 6410056 | 6202114EN | 6410056DC | 6990114 | 9/16 | 1 | 5/8 | 1 1/8 | 7/8 | 3/16 | 585 | 0.1 |
| 6410063 | 6202115EN | 6410063DC | 6990115 | 5/8 | 1 | 5/8 | 1 1/8 | 7/8 | 3/16 | 585 | 0.1 |

Trantorque Mini – Metric

| Part Number | | | | d (mm) | D (mm) | L (mm) | L ₁ (mm) | Wrench Size | | M _a † Install Torque (Nm) | Shipping Weight (kg) |
|-------------|---------------------------------------|--------------------------------------|--------------------|-----------|-----------|-----------|------------------------|-------------|-----------|--|----------------------------|
| Steel | Electroless Nickel Plated Steel | Thin Dense Chrome Coated Steel | Stainless Steel | | | | | A (mm) | B (mm) | | |
| TTQM0316 | TTQM0316EN | TTQM0316DC | TTQM0316SS | 3 | 16 | 10 | 19 | 13 | 3 | 14 | 0.02 |
| TTQM0416 | TTQM0416EN | TTQM0416DC | TTQM0416SS | 4 | 16 | 10 | 19 | 13 | 3 | 14 | 0.02 |
| TTQM0516 | TTQM0516EN | TTQM0516DC | TTQM0516SS | 5 | 16 | 10 | 19 | 13 | 3 | 14 | 0.02 |
| TTQM0616 | TTQM0616EN | TTQM0616DC | TTQM0616SS | 6 | 16 | 10 | 19 | 13 | 3 | 14 | 0.02 |
| TTQM0720 | TTQM0720EN | TTQM0720DC | TTQM0720SS | 7 | 20 | 11 | 22 | 16 | 3 | 28 | 0.03 |
| TTQM0820 | TTQM0820EN | TTQM0820DC | TTQM0820SS | 8 | 20 | 11 | 22 | 16 | 3 | 28 | 0.03 |
| TTQM0920 | TTQM0920EN | TTQM0920DC | TTQM0920SS | 9 | 20 | 11 | 22 | 16 | 3 | 28 | 0.03 |
| TTQM1023 | TTQM1023EN | TTQM1023DC | TTQM1023SS | 10 | 23 | 13 | 26 | 19 | 5 | 44 | 0.05 |
| TTQM1123 | TTQM1123EN | TTQM1123DC | TTQM1123SS | 11 | 23 | 13 | 26 | 19 | 5 | 44 | 0.05 |
| TTQM1223 | TTQM1223EN | TTQM1223DC | TTQM1223SS | 12 | 23 | 13 | 26 | 19 | 5 | 44 | 0.05 |
| TTQM1426 | TTQM1426EN | TTQM1426DC | TTQM1426SS | 14 | 26 | 16 | 29 | 22 | 5 | 66 | 0.06 |
| TTQM1526 | TTQM1526EN | TTQM1526DC | TTQM1526SS | 15 | 26 | 16 | 29 | 22 | 5 | 66 | 0.06 |
| TTQM1626 | TTQM1626EN | TTQM1626DC | TTQM1626SS | 16 | 26 | 16 | 29 | 22 | 5 | 66 | 0.06 |

Performance Data Tables

| d (inch) | M _t † | Th | P _h * |
|-------------|---------------------|-----------------|--------------------------|
| | Maximum Transmitted | | Hub Pressure (psi) |
| | Torque (in lb) | Thrust (lbs) | |
| 1/8 | 100 | 1608 | 18193 |
| 3/16 | 151 | 1608 | 18193 |
| 1/4 | 201 | 1608 | 18193 |
| 5/16 | 404 | 2584 | 20890 |
| 3/8 | 485 | 2584 | 20890 |
| 7/16 | 737 | 3368 | 20421 |
| 1/2 | 842 | 3368 | 20421 |
| 9/16 | 1223 | 4349 | 18459 |
| 5/8 | 1359 | 4349 | 18459 |

| d (mm) | M _t † | Th | P _h * |
|-----------|---------------------|----------------|---|
| | Maximum Transmitted | | Hub Pressure (N/mm ²) |
| | Torque (Nm) | Thrust (kN) | |
| 3 | 11 | 7 | 123 |
| 4 | 14 | 7 | 123 |
| 5 | 18 | 7 | 123 |
| 6 | 21 | 7 | 123 |
| 7 | 40 | 11 | 136 |
| 8 | 46 | 11 | 136 |
| 9 | 51 | 11 | 136 |
| 10 | 75 | 15 | 136 |
| 11 | 82 | 15 | 136 |
| 12 | 90 | 15 | 136 |
| 14 | 135 | 19 | 124 |
| 15 | 145 | 19 | 124 |
| 16 | 155 | 19 | 124 |

MULTIPLIERS

| | |
|------------------------------------|------|
| Steel | 1.0 |
| Electroless Nickel Plated Steel | 0.8 |
| Thin Dense Chrome Coated Steel | 1.0 |
| Stainless Steel | 0.35 |

(continued on page 17)

Trantorque Mini Performance Data (continued from page 16)

The data in the Performance Data Table is for a steel unit. To obtain data for other materials, use the multiplier provided.

For example, you require a 1/4" (d) Electroless Nickel Plated Trantorque Mini.


Find 1/4" (d) in Performance Data Table and use the multiplier of 0.8 for Electroless Nickel Plated Steel.

$M_t: 201 \times 0.8 = 161$
 $T_h: 1608 \times 0.8 = 1286$
 $*P_h: 18193 \times 0.8 = 14554$

***IMPORTANT:**

After hub pressure (P_h) is determined, record D, L and Ph and refer to page 9 and 10 to calculate the minimum hub diameter.

† When installing Trantorque Mini with an open-ended wrench, a reduction in installation torque by 50% is recommended. This will result in a Transmitted Torque (M_t) reduced by 50%.



Trantorque®
Micro
 Inch and Metric

Trantorque Micro – Inch



| Size (in) | d (in) | Integrated Bore Di (in) | Smooth Bore Ds (in) | L (in) | L1 (in) | Wrench Size | | B (in) | B1 (in) | Ma Install Torque (in-lb) | Shipping Weight (lb) | Maximum Transmitted | | Smooth Bore Hub Pressure (psi) | A | A1 |
|--------------|-----------|-------------------------------|---------------------------|-----------|------------|-------------|------------|-----------|------------|---------------------------------|-------------------------|---------------------|----------------|--------------------------------------|--------|--------|
| | | | | | | A (in) | A1 (in) | | | | | Torque (in-lb) | Thrust (lb) | | | |
| | | | | | | | | | | | | | | | | |
| 1/8 | 0.125 | 0.369 | 0.563 | 0.38 | 0.67 | 7/16 | 11/16 | 0.06 | 0.22 | 125 | 0.050 | 46 | 738 | 9275 | 0.4375 | 0.6875 |
| 3/16 | 0.188 | 0.369 | 0.613 | 0.38 | 0.67 | 7/16 | 11/16 | 0.06 | 0.22 | 150 | 0.052 | 83 | 885 | 10221 | 0.4375 | 0.6875 |
| 1/4 | 0.250 | 0.369 | 0.613 | 0.38 | 0.67 | 7/16 | 11/16 | 0.06 | 0.22 | 150 | 0.048 | 111 | 885 | 10221 | 0.4375 | 0.6875 |
| 5/16 | 0.313 | 0.431 | 0.625 | 0.44 | 0.76 | 1/2 | 3/4 | 0.06 | 0.25 | 150 | 0.057 | 120 | 771 | 7478 | 0.5 | 0.75 |
| 3/8 | 0.375 | 0.550 | 0.750 | 0.44 | 0.83 | 5/8 | 15/16 | 0.06 | 0.31 | 150 | 0.099 | 116 | 620 | 5008 | 0.625 | 0.9375 |
| 7/16 | 0.438 | 0.550 | 0.750 | 0.50 | 0.92 | 5/8 | 15/16 | 0.09 | 0.31 | 150 | 0.096 | 136 | 620 | 4387 | 0.625 | 0.9375 |
| 1/2 | 0.500 | 0.666 | 0.875 | 0.63 | 1.11 | 3/4 | 1 1/8 | 0.09 | 0.38 | 225 | 0.167 | 194 | 777 | 3767 | 0.75 | 1.125 |
| 9/16 | 0.563 | 0.666 | 0.875 | 0.75 | 1.25 | 3/4 | 1 1/8 | 0.11 | 0.38 | 225 | 0.164 | 218 | 777 | 3139 | 0.75 | 1.125 |
| 5/8 | 0.625 | 0.791 | 1.000 | 0.94 | 1.52 | 7/8 | 1 5/16 | 0.13 | 0.44 | 300 | 0.276 | 280 | 895 | 2533 | 0.875 | 1.3125 |

Trantorque Micro – Metric

| 16Size (mm) | d (mm) | Integrated Bore Di (mm) | Smooth Bore Ds (mm) | L (mm) | L1 (mm) | Wrench Size | | B (mm) | B1 (mm) | Ma Install Torque (Nm) | Shipping Weight (kg) | Maximum Transmitted | | Smooth Bore Hub Pressure (N/mm^2) | A | A1 |
|----------------|-----------|-------------------------------|---------------------------|-----------|------------|-------------|------------|-----------|------------|------------------------------|-------------------------|---------------------|----------------|---|--------|--------|
| | | | | | | A (mm) | A1 (mm) | | | | | Torque (Nm) | Thrust (kN) | | | |
| | | | | | | | | | | | | | | | | |
| 3 | 3 | 9.37 | 14.29 | 9.5 | 17.0 | 12.0 | 17.0 | 1.5 | 5.6 | 14 | 0.023 | 5 | 3.3 | 64 | 0.4375 | 0.6875 |
| 4 | 4 | 9.37 | 14.29 | 9.5 | 17.0 | 12.0 | 17.0 | 1.5 | 5.6 | 17 | 0.022 | 8 | 3.9 | 77 | 0.4375 | 0.6875 |
| 5 | 5 | 9.37 | 15.56 | 9.5 | 17.0 | 12.0 | 17.0 | 1.5 | 5.6 | 17 | 0.023 | 10 | 3.9 | 70 | 0.4375 | 0.6875 |
| 6 | 6 | 9.37 | 15.56 | 9.5 | 17.0 | 12.0 | 17.0 | 1.5 | 5.6 | 17 | 0.022 | 12 | 3.9 | 70 | 0.4375 | 0.6875 |
| 7 | 7 | 10.95 | 15.56 | 9.5 | 17.8 | 13.0 | 19.0 | 1.5 | 6.4 | 17 | 0.025 | 12 | 3.4 | 61 | 0.5 | 0.75 |
| 8 | 8 | 10.95 | 15.88 | 11.1 | 19.4 | 13.0 | 19.0 | 1.5 | 6.4 | 17 | 0.026 | 14 | 3.4 | 52 | 0.5 | 0.75 |
| 9 | 9 | 13.97 | 19.05 | 11.1 | 21.0 | 16.0 | 23.0 | 1.5 | 7.9 | 17 | 0.046 | 12 | 2.8 | 35 | 0.625 | 0.9375 |
| 10 | 10 | 13.97 | 19.05 | 12.7 | 23.4 | 16.0 | 23.0 | 2.4 | 7.9 | 17 | 0.047 | 14 | 2.8 | 30 | 0.625 | 0.9375 |
| 11 | 11 | 13.97 | 19.05 | 12.7 | 23.4 | 16.0 | 23.0 | 2.4 | 7.9 | 17 | 0.044 | 15 | 2.8 | 30 | 0.625 | 0.9375 |
| 12 | 12 | 13.97 | 19.05 | 12.7 | 23.4 | 16.0 | 23.0 | 2.4 | 7.9 | 17 | 0.041 | 17 | 3.6 | 40 | 0.625 | 0.9375 |
| 13 | 13 | 16.92 | 22.23 | 15.9 | 28.2 | 20.0 | 28.0 | 2.4 | 9.5 | 25 | 0.074 | 22 | 3.5 | 26 | 0.75 | 1.125 |
| 14 | 14 | 16.92 | 22.23 | 19.1 | 31.8 | 20.0 | 28.0 | 2.8 | 9.5 | 25 | 0.076 | 24 | 3.5 | 22 | 0.75 | 1.125 |
| 15 | 15 | 16.92 | 22.23 | 19.1 | 31.8 | 20.0 | 28.0 | 2.8 | 9.5 | 25 | 0.071 | 26 | 3.5 | 22 | 0.75 | 1.125 |
| 16 | 16 | 20.09 | 25.40 | 23.8 | 38.5 | 23.0 | 33.0 | 3.2 | 11.1 | 34 | 0.124 | 32 | 4.0 | 17 | 0.875 | 1.3125 |

*All Trantorque Micro orders are subject to a 25 piece minimum.

Trantorque®
OE
Inch



TOLERANCE (T_L)
T_L for shaft and bore is ± .003"
for all sizes

Trantorque OE – Inch

| Part Number | | | | d (inch) | D (inch) | L (inch) | L ₁ (inch) | Wrench Size A (inch) | B (inch) | M _a † Install Torque (ft lb) | Shipping Weight (lb) |
|-------------|---------------------------------------|---|--------------------|-------------|-------------|-------------|--------------------------|-------------------------------|-------------|--|----------------------------|
| Steel | Electroless Nickel Plated Steel | Thin Dense Chrome Coated Steel | Stainless Steel | | | | | | | | |
| 6410069 | 6410069EN | 6410069DC | 6410069SS | 11/16 | 1 1/4 | 7/8 | 1 5/32 | 1 1/8 | 1/4 | 82 | 0.2 |
| 6410075 | 6410075EN | 6410075DC | 6410075SS | 3/4 | 1 1/4 | 7/8 | 1 5/32 | 1 1/8 | 1/4 | 82 | 0.2 |
| 6410081 | 6410081EN | 6410081DC | 6410081SS | 13/16 | 1 3/8 | 15/16 | 1 1/4 | 1 1/4 | 1/4 | 111 | 0.2 |
| 6410088 | 6410088EN | 6410088DC | 6410088SS | 7/8 | 1 3/8 | 15/16 | 1 1/4 | 1 1/4 | 1/4 | 111 | 0.2 |
| 6410094 | 6410094EN | 6410094DC | 6410094SS | 15/16 | 1 1/2 | 1 | 1 11/32 | 1 3/8 | 5/16 | 137 | 0.4 |
| 6410100 | 6410100EN | 6410100DC | 6410100SS | 1 | 1 1/2 | 1 | 1 11/32 | 1 3/8 | 5/16 | 137 | 0.3 |
| 6410106 | 6410106EN | 6410106DC | 6410106SS | 1 1/16 | 1 5/8 | 1 1/16 | 1 15/32 | 1 1/2 | 3/8 | 155 | 0.4 |
| 6410113 | 6410113EN | 6410113DC | 6410113SS | 1 1/8 | 1 5/8 | 1 1/16 | 1 15/32 | 1 1/2 | 3/8 | 155 | 0.4 |
| 6410119 | 6410119EN | 6410119DC | 6410119SS | 1 3/16 | 1 3/4 | 1 1/8 | 1 19/32 | 1 5/8 | 7/16 | 177 | 0.5 |
| 6410125 | 6410125EN | 6410125DC | 6410125SS | 1 1/4 | 1 3/4 | 1 1/8 | 1 19/32 | 1 5/8 | 7/16 | 177 | 0.5 |
| 6410131 | 6410131EN | 6410131DC | 6410131SS | 1 5/16 | 1 7/8 | 1 3/16 | 1 11/16 | 1 3/4 | 1/2 | 196 | 0.6 |
| 6410138 | 6410138EN | 6410138DC | 6410138SS | 1 3/8 | 1 7/8 | 1 3/16 | 1 11/16 | 1 3/4 | 1/2 | 196 | 0.6 |
| 6410144 | 6410144EN | 6410144DC | 6410144SS | 1 7/16 | 2 | 1 1/4 | 1 25/32 | 1 7/8 | 1/2 | 196 | 0.7 |
| 6410150 | 6410150EN | 6410150DC | 6410150SS | 1 1/2 | 2 | 1 1/4 | 1 25/32 | 1 7/8 | 1/2 | 196 | 0.6 |

Performance Data Table

| d (inch) | M _t † | T _h | P _h * Hub Pressure (psi) |
|-------------|---------------------|-----------------|--|
| | Maximum Transmitted | | Torque (ft lb) |
| | Torque (ft lb) | Thrust (lbs) | |
| 11/16 | 166 | 5805 | 20843 |
| 3/4 | 181 | 5805 | 20843 |
| 13/16 | 241 | 7113 | 21014 |
| 7/8 | 259 | 7113 | 21014 |
| 15/16 | 311 | 7963 | 19639 |
| 1 | 332 | 7963 | 19639 |
| 1 1/16 | 364 | 8224 | 17211 |
| 1 1/8 | 386 | 8224 | 17211 |
| 1 3/16 | 431 | 8712 | 15664 |
| 1 1/4 | 454 | 8712 | 15664 |
| 1 5/16 | 489 | 8938 | 14004 |
| 1 3/8 | 512 | 8938 | 14004 |
| 1 7/16 | 500 | 8336 | 11469 |
| 1 1/2 | 512 | 8336 | 11469 |

MULTIPLIERS

| | |
|------------------------------------|-----|
| Steel | 1.0 |
| Electroless Nickel Plated Steel | 0.6 |
| Thin Dense Chrome Coated Steel | 0.9 |
| Stainless Steel | 0.3 |

The data in the Performance Data Table is for a steel unit. To obtain data for other materials, use the multiplier provided.

For example, you require a 1" (d) Electroless Nickel Plated Trantorque OE.

Find 1" (d) in Performance Data Table and use the multiplier of 0.6 for Electroless Nickel Plated Steel.

$$M_t: 332 \times 0.6 = 199$$

$$T_h: 7963 \times 0.6 = 4778$$

$$*P_h: 19639 \times 0.6 = 11783$$

*IMPORTANT:

After hub pressure (P_h) is determined, record D, L and P_h and refer to page 9 and 10 to calculate the minimum hub diameter.

† When installing Trantorque OE with an open-ended wrench, a reduction in installation torque by 50% is recommended. This will result in a Transmitted Torque (M_t) reduced by 50%.

TOLERANCE (T_L)T_L for shaft and bore is ± .08mm
for all sizes

Trantorque OE – Metric

| Part Number | | | | d (mm) | D (mm) | L (mm) | L ₁ (mm) | Wrench Size | B (mm) | M _a † | Shipping Weight (kg) |
|-------------|---------------------------------------|--------------------------------------|--------------------|-----------|-----------|-----------|------------------------|----------------|-----------|---------------------------|----------------------------|
| Steel | Electroless Nickel Plated Steel | Thin Dense Chrome Coated Steel | Stainless Steel | | | | | A (mm) | | Install Torque (Nm) | |
| TTQM1732 | TTQM1732EN | TTQM1732DC | TTQM1732SS | 17 | 32 | 22 | 29 | 30 | 6 | 110 | 0.1 |
| TTQM1832 | TTQM1832EN | TTQM1832DC | TTQM1832SS | 18 | 32 | 22 | 29 | 30 | 6 | 110 | 0.1 |
| TTQM1932 | TTQM1932EN | TTQM1932DC | TTQM1932SS | 19 | 32 | 22 | 29 | 30 | 6 | 110 | 0.1 |
| TTQM2035 | TTQM2035EN | TTQM2035DC | TTQM2035SS | 20 | 35 | 24 | 32 | 32 | 7 | 150 | 0.1 |
| TTQM2235 | TTQM2235EN | TTQM2235DC | TTQM2235SS | 22 | 35 | 24 | 32 | 32 | 7 | 150 | 0.1 |
| TTQM2438 | TTQM2438EN | TTQM2438DC | TTQM2438SS | 24 | 38 | 25 | 34 | 36 | 7 | 185 | 0.2 |
| TTQM2538 | TTQM2538EN | TTQM2538DC | TTQM2538SS | 25 | 38 | 25 | 34 | 36 | 7 | 185 | 0.2 |
| TTQM2845 | TTQM2845EN | TTQM2845DC | TTQM2845SS | 28 | 45 | 29 | 41 | 46 | 11 | 240 | 0.3 |
| TTQM3045 | TTQM3045EN | TTQM3045DC | TTQM3045SS | 30 | 45 | 29 | 41 | 46 | 11 | 240 | 0.3 |
| TTQM3250 | TTQM3250EN | TTQM3250DC | TTQM3250SS | 32 | 50 | 30 | 43 | 50 | 11 | 265 | 0.4 |
| TTQM3550 | TTQM3550EN | TTQM3550DC | TTQM3550SS | 35 | 50 | 30 | 43 | 50 | 11 | 265 | 0.3 |

Performance Data Table

| d (mm) | M _t † | Th | P _h * |
|-----------|---------------------|----------------|---|
| | Maximum Transmitted | | Hub Pressure (N/mm ²) |
| | Torque (Nm) | Thrust (kN) | |
| 17 | 218 | 26 | 142 |
| 18 | 231 | 26 | 142 |
| 19 | 244 | 26 | 142 |
| 20 | 315 | 32 | 144 |
| 22 | 347 | 32 | 144 |
| 24 | 425 | 35 | 136 |
| 25 | 443 | 35 | 136 |
| 28 | 539 | 38 | 106 |
| 30 | 577 | 38 | 106 |
| 32 | 618 | 39 | 84 |
| 35 | 676 | 39 | 84 |

MULTIPLIERS

| | |
|------------------------------------|-----|
| Steel | 1.0 |
| Electroless Nickel Plated Steel | 0.6 |
| Thin Dense Chrome Coated Steel | 0.9 |
| Stainless Steel | 0.3 |

The data in the Performance Data Table is for a steel unit. To obtain data for other materials, use the multiplier provided.

For example, you require a 20mm (d) Electroless Nickel Plated Trantorque OE.

Find 20mm (d) in Performance Data Table and use the multiplier of 0.6 for Electroless Nickel Plated Steel.

$$M_t: 315 \times 0.6 = 189$$

$$T_h: 32 \times 0.6 = 19$$


$$*P_h: 144 \times 0.6 = 86$$

*IMPORTANT:

After hub pressure (P_h) is determined, record D, L and P_h and refer to page 9 and 10 to calculate the minimum hub diameter.

† When installing Trantorque OE with an open-ended wrench, a reduction in installation torque by 50% is recommended. This will result in a Transmitted Torque (M_t) reduced by 50%.

Trantorque® NT Inch



TOLERANCE (T_L)

T_L for shaft and bore is .0015" for Part Numbers 6980103UP – 6980119UP

T_L for shaft and bore is .003" for all other Trantorque NT

Trantorque NT – Inch

| Part Number | Steel | d (inch) | D (inch) | L (inch) | L ₁ (inch) | Wrench Size A (inch) | B (inch) | M _a | M _t | T _h | P _H * |
|-------------|-------|----------|----------|----------|-----------------------|-------------------------|----------|------------------------|---------------------|----------------|--------------------|
| | | | | | | | | Install Torque (in lb) | Maximum Transmitted | | Hub Pressure (psi) |
| | | | | | | | | Torque (ft lb) | Thrust (lbs) | | |
| 6980103UP | | 3/16 | 5/8 | 3/8 | 1 1/16 | 1/2 | 1/8 | 125 | 7 | 876 | 9918 |
| 6980105UP | | 1/4 | 5/8 | 3/8 | 1 1/16 | 1/2 | 1/8 | 125 | 9 | 876 | 9918 |
| 6980107UP | | 5/16 | 3/4 | 7/16 | 1 3/16 | 5/8 | 1/8 | 150 | 11 | 845 | 6833 |
| 6980109UP | | 3/8 | 3/4 | 7/16 | 1 3/16 | 5/8 | 1/8 | 150 | 13 | 845 | 6833 |
| 6980110UP | | 7/16 | 7/8 | 1/2 | 1 5/16 | 3/4 | 3/16 | 175 | 15 | 824 | 4995 |
| 6980112UP | | 1/2 | 7/8 | 1/2 | 1 5/16 | 3/4 | 3/16 | 175 | 17 | 824 | 4995 |
| 6980114UP | | 9/16 | 1 | 5/8 | 1 7/16 | 7/8 | 3/16 | 200 | 19 | 811 | 3440 |
| 6980115UP | | 5/8 | 1 | 5/8 | 1 7/16 | 7/8 | 3/16 | 200 | 21 | 811 | 3440 |
| 6980119UP | | 3/4 | 1 1/4 | 3/4 | 1 11/16 | 1 1/16 | 1/4 | 700 | 73 | 2326 | 6581 |
| 6980120UP | | 5/8 | 1 1/2 | 11/16 | 1 13/16 | 1 1/4 | 5/16 | 1200 | 91 | 3484 | 8960 |
| 6980140UP | | 11/16 | 1 1/2 | 11/16 | 1 13/16 | 1 1/4 | 5/16 | 1200 | 100 | 3484 | 8960 |
| 6980160UP | | 3/4 | 1 1/2 | 11/16 | 1 13/16 | 1 1/4 | 5/16 | 1200 | 109 | 3484 | 8960 |
| 6980190UP | | 13/16 | 1 3/4 | 13/16 | 2 3/16 | 1 1/2 | 7/16 | 1500 | 122 | 3594 | 6704 |
| 6980200UP | | 7/8 | 1 3/4 | 13/16 | 2 3/16 | 1 1/2 | 7/16 | 1500 | 131 | 3594 | 6704 |
| 6980220UP | | 15/16 | 1 3/4 | 13/16 | 2 3/16 | 1 1/2 | 7/16 | 1500 | 140 | 3594 | 6704 |
| 6980240UP | | 1 | 1 3/4 | 13/16 | 2 3/16 | 1 1/2 | 7/16 | 1500 | 150 | 3594 | 6704 |
| 6980270UP | | 1 1/16 | 2 | 15/16 | 2 9/16 | 1 3/4 | 1/2 | 2000 | 183 | 4137 | 5853 |
| 6980280UP | | 1 1/8 | 2 | 15/16 | 2 9/16 | 1 3/4 | 1/2 | 2000 | 194 | 4137 | 5853 |
| 6980300UP | | 1 3/16 | 2 | 15/16 | 2 9/16 | 1 3/4 | 1/2 | 2000 | 205 | 4137 | 5853 |
| 6980320UP | | 1 1/4 | 2 | 15/16 | 2 9/16 | 1 3/4 | 1/2 | 2000 | 215 | 4137 | 5853 |
| 6980350UP | | 1 5/16 | 2 3/8 | 1 7/16 | 3 3/32 | 2 | 9/16 | 2300 | 225 | 4113 | 3196 |
| 6980360UP | | 1 3/8 | 2 3/8 | 1 7/16 | 3 3/32 | 2 | 9/16 | 2300 | 236 | 4113 | 3196 |
| 6980380UP | | 1 7/16 | 2 3/8 | 1 7/16 | 3 3/32 | 2 | 9/16 | 2300 | 246 | 4113 | 3196 |
| 6980400UP | | 1 1/2 | 2 3/8 | 1 7/16 | 3 3/32 | 2 | 9/16 | 2300 | 257 | 4113 | 3196 |
| 6980430UP | | 1 9/16 | 2 5/8 | 1 5/8 | 3 15/32 | 2 1/4 | 9/16 | 2800 | 291 | 4466 | 2777 |
| 6980440UP | | 1 5/8 | 2 5/8 | 1 5/8 | 3 15/32 | 2 1/4 | 9/16 | 2800 | 302 | 4466 | 2777 |
| 6980460UP | | 1 11/16 | 2 5/8 | 1 5/8 | 3 15/32 | 2 1/4 | 9/16 | 2800 | 314 | 4466 | 2777 |
| 6980480UP | | 1 3/4 | 2 5/8 | 1 5/8 | 3 15/32 | 2 1/4 | 9/16 | 2800 | 326 | 4466 | 2777 |
| 6980510UP | | 1 13/16 | 2 7/8 | 1 15/16 | 4 3/64 | 2 1/2 | 5/8 | 4900 | 531 | 7029 | 3347 |
| 6980520UP | | 1 7/8 | 2 7/8 | 1 15/16 | 4 3/64 | 2 1/2 | 5/8 | 4900 | 549 | 7029 | 3347 |
| 6980540UP | | 1 15/16 | 2 7/8 | 1 15/16 | 4 3/64 | 2 1/2 | 5/8 | 4900 | 567 | 7029 | 3347 |
| 6980560UP | | 2 | 2 7/8 | 1 15/16 | 4 3/64 | 2 1/2 | 5/8 | 4900 | 586 | 7029 | 3347 |

*IMPORTANT: Please refer to page 9 and 10 to calculate your minimum hub diameter.


Consult factory for weights and availability.



Locking screws transfer to integrated push-off holes for disassembly.

Metric socket head locking screws ISO 4762 grade 12.9 (See M_a for install torque).

Screw head height = screw diameter (mm)



B-LOC® B109 Inch and Metric

TOLERANCE (T_1)

Tolerance (T_1) for shaft and bore is $\pm .001"$ (.025mm) for all sizes.

B109 — Inch



| Part Number | d (inch) | D (inch) | D ₁ (inch) | L (inch) | L ₁ (inch) | L ₂ (inch) | Locking Screws | | M _a Install Torque (in lb) | M _t Maximum Transmitted Torque (in lb) | Th Thrust (lbs) | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|-----------------------|----------|-----------------------|-----------------------|----------------|---------|--|--|--------------------|--------------------------------------|----------------------|
| | | | | | | | Qty | Size | | | | | |
| | | | | | | | | | | | | | |
| T902004 | 1/4 | 13/16 | 15/16 | 0.394 | 0.650 | 0.516 | 3 | M4 x 12 | 36.0 | 167 | 1336 | 11073 | 0.1 |
| T902005 | 5/16 | 7/8 | 1 | 0.394 | 0.650 | 0.516 | 3 | M4 x 12 | 42.5 | 246 | 1572 | 12096 | 0.1 |
| T902006 | 3/8 | 15/16 | 1 1/16 | 0.394 | 0.650 | 0.516 | 3 | M4 x 12 | 42.5 | 295 | 1572 | 11290 | 0.1 |
| B902008 | 1/2 | 1 1/16 | 1 3/16 | 0.394 | 0.650 | 0.516 | 4 | M4 x 12 | 42.5 | 524 | 2096 | 13282 | 0.1 |
| T902010 | 5/8 | 1 3/16 | 1 5/16 | 0.472 | 0.807 | 0.594 | 6 | M4 x 14 | 42.5 | 983 | 3144 | 14880 | 0.2 |
| B902012 | 3/4 | 1 5/16 | 1 7/16 | 0.472 | 0.807 | 0.594 | 6 | M4 x 14 | 42.5 | 1179 | 3144 | 13463 | 0.2 |
| T902014 | 7/8 | 1 9/16 | 1 3/4 | 0.591 | 0.984 | 0.754 | 6 | M5 x 18 | 87.0 | 2264 | 5174 | 14863 | 0.4 |
| B902100 | 1 | 1 11/16 | 1 7/8 | 0.591 | 0.984 | 0.754 | 8 | M5 x 18 | 87.0 | 3449 | 6899 | 18349 | 0.4 |
| T902102 | 1 1/8 | 1 7/8 | 2 | 0.669 | 1.102 | 0.829 | 9 | M5 x 18 | 87.0 | 4366 | 7761 | 16412 | 0.6 |
| T902103 | 1 3/16 | 1 15/16 | 2 1/16 | 0.669 | 1.102 | 0.829 | 10 | M5 x 18 | 87.0 | 5120 | 8623 | 17647 | 0.6 |
| B902104 | 1 1/4 | 2 | 2 1/8 | 0.669 | 1.102 | 0.829 | 10 | M5 x 18 | 87.0 | 5390 | 8623 | 17096 | 0.6 |
| B902106 | 1 3/8 | 2 1/8 | 2 1/4 | 0.669 | 1.102 | 0.829 | 10 | M5 x 18 | 87.0 | 5929 | 8623 | 16090 | 0.6 |

B109 — Metric

| Part Number | d (mm) | D (mm) | D ₁ (mm) | L (mm) | L ₁ (mm) | L ₂ (mm) | Locking Screws | | M _a Install Torque (Nm) | M _t Maximum Transmitted Torque (Nm) | Th Thrust (N) | P _h Hub Pressure (N/mm ²) | Shipping Weight (kg) |
|-------------|--------|--------|---------------------|--------|---------------------|---------------------|----------------|---------|---------------------------------------|---|------------------|---|----------------------|
| | | | | | | | Qty | Size | | | | | |
| | | | | | | | | | | | | | |
| T901006 | 6 | 20.64 | 23.81 | 10 | 16.5 | 13.1 | 3 | M4 x 12 | 4.3 | 19 | 6192 | 80 | 0.05 |
| T901008 | 8 | 22.23 | 25.40 | 10 | 16.5 | 13.1 | 3 | M4 x 12 | 5 | 29 | 7285 | 87 | 0.05 |
| B901010 | 10 | 23.81 | 27.00 | 10 | 16.5 | 13.1 | 3 | M4 x 12 | 5 | 36 | 7285 | 81 | 0.05 |
| T901011 | 11 | 26.99 | 30.16 | 10 | 16.5 | 13.1 | 4 | M4 x 12 | 5 | 53 | 9713 | 95 | 0.05 |
| T901012 | 12 | 26.99 | 30.16 | 10 | 16.5 | 13.1 | 4 | M4 x 12 | 5 | 58 | 9713 | 95 | 0.05 |
| T901014 | 14 | 30.16 | 33.34 | 12 | 20.5 | 15.1 | 6 | M4 x 14 | 5 | 102 | 14569 | 107 | 0.05 |
| T901015 | 15 | 30.16 | 33.34 | 12 | 20.5 | 15.1 | 6 | M4 x 14 | 5 | 109 | 14569 | 107 | 0.09 |
| T901016 | 16 | 30.16 | 33.34 | 12 | 20.5 | 15.1 | 6 | M4 x 14 | 5 | 117 | 14569 | 107 | 0.09 |
| T901019 | 19 | 33.34 | 36.51 | 12 | 20.5 | 15.1 | 6 | M4 x 14 | 5 | 138 | 14569 | 97 | 0.09 |
| T901020 | 20 | 39.69 | 44.45 | 15 | 25 | 19.2 | 6 | M5 x 18 | 10 | 234 | 23414 | 104 | 0.18 |
| T901022 | 22 | 39.69 | 44.45 | 15 | 25 | 19.2 | 6 | M5 x 18 | 10 | 258 | 23414 | 104 | 0.18 |
| T901024 | 24 | 42.86 | 47.62 | 15 | 25 | 19.2 | 8 | M5 x 18 | 10 | 375 | 31219 | 129 | 0.18 |
| T901025 | 25 | 42.86 | 47.62 | 15 | 25 | 19.2 | 8 | M5 x 18 | 10 | 390 | 31219 | 129 | 0.18 |
| T901028 | 28 | 47.62 | 50.80 | 17 | 28 | 21.06 | 9 | M5 x 18 | 10 | 492 | 35121 | 115 | 0.27 |
| T901030 | 30 | 49.21 | 52.39 | 17 | 28 | 21.06 | 10 | M5 x 18 | 10 | 585 | 39024 | 124 | 0.27 |
| T901032 | 32 | 50.80 | 53.97 | 17 | 28 | 21.06 | 10 | M5 x 18 | 10 | 624 | 39024 | 120 | 0.27 |
| T901035 | 35 | 53.98 | 57.15 | 17 | 28 | 21.06 | 10 | M5 x 18 | 10 | 683 | 39024 | 113 | 0.27 |

Power Transmission - B-LOC®

B-LOC® B103 Inch



B103 – Inch

| Part Number | d (inch) | D (inch) | L (inch) | L ₁ (inch) | L ₂ (inch) | Locking Screws | | M _a Install Torque (ft lb) | M _t Maximum Transmitted Torque (ft lb) | T _h Thrust (lbs) | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|----------|-----------------------|-----------------------|----------------|----------|--|--|--------------------------------|--------------------------------------|----------------------|
| | | | | | | Qty | Size | | | | | |
| | | | | | | B302012 | 3/4 | 1.850 | 0.669 | 1.122 | 0.886 | |
| T302014 | 7/8 | 1.850 | 0.669 | 1.122 | 0.886 | 5 | M6 x 20 | 10 | 289 | 7918 | 16959 | 0.6 |
| B302100 | 1 | 1.969 | 0.669 | 1.122 | 0.886 | 6 | M6 x 20 | 10 | 396 | 9502 | 19130 | 0.7 |
| B302102 | 1 1/8 | 2.165 | 0.669 | 1.122 | 0.886 | 6 | M6 x 20 | 10 | 445 | 9502 | 17391 | 0.8 |
| B302103 | 1 3/16 | 2.165 | 0.669 | 1.122 | 0.886 | 6 | M6 x 20 | 10 | 470 | 9502 | 17391 | 0.7 |
| B302104 | 1 1/4 | 2.362 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 10 | 660 | 12669 | 21256 | 0.9 |
| B302106 | 1 3/8 | 2.362 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 10 | 726 | 12669 | 21256 | 0.8 |
| B302107 | 1 7/16 | 2.559 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 10 | 759 | 12669 | 19621 | 1.0 |
| B302108 | 1 1/2 | 2.559 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 10 | 792 | 12669 | 19621 | 1.0 |
| B302110 | 1 5/8 | 2.953 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 25 | 1439 | 21250 | 24245 | 1.7 |
| T302111 | 1 11/16 | 2.953 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 25 | 1494 | 21250 | 24245 | 1.6 |
| B302112 | 1 3/4 | 2.953 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 25 | 1550 | 21250 | 24245 | 1.6 |
| T302114 | 1 7/8 | 3.150 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 25 | 1660 | 21250 | 22729 | 1.8 |
| B302115 | 1 15/16 | 3.150 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 25 | 1716 | 21250 | 22729 | 1.7 |
| B302200 | 2 | 3.150 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 25 | 1771 | 21250 | 22729 | 1.6 |
| T302202 | 2 1/8 | 3.346 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 25 | 2150 | 24286 | 24448 | 1.9 |
| B302203 | 2 3/16 | 3.346 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 25 | 2214 | 24286 | 24448 | 1.8 |
| B302204 | 2 1/4 | 3.543 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 25 | 2277 | 24286 | 23090 | 2.1 |
| T302206 | 2 3/8 | 3.543 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 25 | 2403 | 24286 | 23090 | 1.9 |
| B302207 | 2 7/16 | 3.740 | 0.787 | 1.358 | 1.043 | 9 | M8 x 25 | 25 | 2775 | 27322 | 24609 | 2.2 |
| B302208 | 2 1/2 | 3.740 | 0.787 | 1.358 | 1.043 | 9 | M8 x 25 | 25 | 2846 | 27322 | 24609 | 2.2 |
| T302209 | 2 9/16 | 3.740 | 0.787 | 1.358 | 1.043 | 9 | M8 x 25 | 25 | 2917 | 27322 | 24609 | 2.1 |
| T302211 | 2 11/16 | 4.331 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 50 | 4411 | 39387 | 25532 | 3.8 |
| T302212 | 2 3/4 | 4.331 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 50 | 4513 | 39387 | 25532 | 3.7 |
| T302214 | 2 7/8 | 4.528 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 50 | 4718 | 39387 | 24422 | 4.0 |
| B302215 | 2 15/16 | 4.528 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 50 | 4821 | 39387 | 24422 | 3.9 |
| B302300 | 3 | 4.724 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 50 | 4923 | 39387 | 23404 | 4.4 |
| T302304 | 3 1/4 | 4.921 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 50 | 6000 | 44311 | 25277 | 4.5 |
| T302306 | 3 3/8 | 4.921 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 50 | 6231 | 44311 | 25277 | 4.3 |
| B302307 | 3 7/16 | 5.118 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 50 | 6347 | 44311 | 24305 | 4.8 |
| T302308 | 3 1/2 | 5.118 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 50 | 6462 | 44311 | 24305 | 4.6 |
| T302312 | 3 3/4 | 5.315 | 0.945 | 1.594 | 1.201 | 10 | M10 x 30 | 50 | 7693 | 49234 | 26005 | 4.7 |
| T302315 | 3 15/16 | 5.709 | 1.024 | 1.772 | 1.299 | 8 | M12 x 35 | 90 | 9944 | 60608 | 27512 | 6 |
| T302400 | 4 | 5.709 | 1.024 | 1.772 | 1.299 | 8 | M12 x 35 | 90 | 10101 | 60608 | 27512 | 6 |
| T302407 | 4 7/16 | 6.102 | 1.024 | 1.772 | 1.299 | 8 | M12 x 35 | 90 | 11206 | 60608 | 25737 | 6 |
| T302412 | 4 3/4 | 6.496 | 1.024 | 1.772 | 1.299 | 9 | M12 x 35 | 90 | 13495 | 68184 | 27200 | 7 |
| T302415 | 4 15/16 | 7.087 | 1.339 | 2.165 | 1.614 | 9 | M14 x 40 | 135 | 18113 | 88043 | 24620 | 11 |
| B302500 | 5 | 7.087 | 1.339 | 2.165 | 1.614 | 9 | M14 x 40 | 135 | 18342 | 88043 | 24620 | 11 |
| T302507 | 5 7/16 | 7.480 | 1.339 | 2.165 | 1.614 | 9 | M14 x 40 | 135 | 19947 | 88043 | 23324 | 12 |
| T302515 | 5 15/16 | 7.874 | 1.339 | 2.165 | 1.614 | 10 | M14 x 40 | 135 | 24202 | 97825 | 24620 | 12 |
| T302607 | 6 7/16 | 8.858 | 1.732 | 2.559 | 2.008 | 12 | M14 x 40 | 135 | 31488 | 117391 | 20292 | 20 |
| T302615 | 6 15/16 | 9.252 | 1.732 | 2.559 | 2.008 | 12 | M14 x 40 | 135 | 33933 | 117391 | 19429 | 20 |
| B302700 | 7 | 9.252 | 1.732 | 2.559 | 2.008 | 12 | M14 x 40 | 135 | 34239 | 117391 | 19429 | 20 |
| T302707 | 7 7/16 | 9.843 | 1.732 | 2.559 | 2.008 | 15 | M14 x 40 | 135 | 45474 | 146738 | 22829 | 22 |
| T302715 | 7 15/16 | 10.236 | 1.732 | 2.559 | 2.008 | 15 | M14 x 40 | 135 | 48531 | 146738 | 21951 | 23 |
| T302800 | 8 | 10.236 | 1.732 | 2.559 | 2.008 | 15 | M14 x 40 | 135 | 48913 | 146738 | 21951 | 21 |

B-LOC® B103 Metric

TOLERANCE (T_L)

Bore diameter machined to $D -0/+T_L$
 $T_L =$.05mm for bores up to 120mm
 .08mm for bores up to 305mm
 .10mm for bores over 305mm


$d =$ Shaft diameter machined to $d +0/-T_L$

B103 — Metric

| Part Number | d (mm) | D (mm) | L (mm) | L ₁ (mm) | L ₂ (mm) | Locking Screws | | M _a Install Torque (Nm) | M _t Maximum Transmitted Torque (Nm) | Th Thrust (N) | P _h Hub Pressure (N/mm ²) | Shipping Weight (kg) |
|-------------|--------|--------|--------|---------------------|---------------------|----------------|----------|---------------------------------------|---|------------------|---|----------------------|
| | | | | | | Qty | Size | | | | | |
| | | | | | | | | T301015 | 15 | 32 | 14 | |
| T301018 | 18 | 47 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 14 | 327 | 36371 | 121 | 0.3 |
| T301019 | 19 | 47 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 14 | 346 | 36371 | 121 | 0.3 |
| T301020 | 20 | 47 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 14 | 364 | 36371 | 121 | 0.3 |
| T301022 | 22 | 47 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 14 | 400 | 36371 | 121 | 0.2 |
| T301024 | 24 | 50 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 14 | 524 | 43645 | 136 | 0.3 |
| B301025 | 25 | 50 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 14 | 546 | 43645 | 136 | 0.3 |
| T301028 | 28 | 55 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 14 | 611 | 43645 | 124 | 0.3 |
| B301030 | 30 | 55 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 14 | 655 | 43645 | 124 | 0.3 |
| T301032 | 32 | 60 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 14 | 931 | 58193 | 151 | 0.4 |
| B301035 | 35 | 60 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 14 | 1018 | 58193 | 151 | 0.3 |
| T301038 | 38 | 65 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 14 | 1106 | 58193 | 140 | 0.4 |
| B301040 | 40 | 65 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 14 | 1164 | 58193 | 140 | 0.4 |
| T301042 | 42 | 75 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 34 | 1991 | 94822 | 168 | 0.7 |
| B301045 | 45 | 75 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 34 | 2133 | 94822 | 168 | 0.6 |
| B301050 | 50 | 80 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 34 | 2371 | 94822 | 157 | 0.7 |
| T301055 | 55 | 85 | 20 | 34.5 | 26.5 | 8 | M8 x 25 | 34 | 2980 | 108368 | 169 | 0.8 |
| B301060 | 60 | 90 | 20 | 34.5 | 26.5 | 8 | M8 x 25 | 34 | 3251 | 108368 | 160 | 0.8 |
| T301065 | 65 | 95 | 20 | 34.5 | 26.5 | 9 | M8 x 25 | 34 | 3962 | 121914 | 170 | 0.9 |
| B301070 | 70 | 110 | 24 | 40.5 | 30.5 | 8 | M10 x 30 | 68 | 6151 | 175750 | 177 | 1.6 |
| T301075 | 75 | 115 | 24 | 40.5 | 30.5 | 8 | M10 x 30 | 68 | 6591 | 175750 | 169 | 1.6 |
| T301080 | 80 | 120 | 24 | 40.5 | 30.5 | 8 | M10 x 30 | 68 | 7030 | 175750 | 162 | 1.7 |
| B301085 | 85 | 125 | 24 | 40.5 | 30.5 | 9 | M10 x 30 | 68 | 8403 | 197719 | 175 | 1.8 |
| B301090 | 90 | 130 | 24 | 40.5 | 30.5 | 9 | M10 x 30 | 68 | 8897 | 197719 | 168 | 1.9 |
| T301095 | 95 | 135 | 24 | 40.5 | 30.5 | 10 | M10 x 30 | 68 | 10435 | 219688 | 180 | 2 |
| B301100 | 100 | 145 | 26 | 45 | 33 | 8 | M12 x 35 | 122 | 13478 | 269557 | 190 | 3 |
| T301110 | 110 | 155 | 26 | 45 | 33 | 8 | M12 x 35 | 122 | 14826 | 269557 | 177 | 3 |
| B301120 | 120 | 165 | 26 | 45 | 33 | 9 | M12 x 35 | 122 | 18195 | 303251 | 188 | 3 |
| T301130 | 130 | 180 | 34 | 55 | 41 | 9 | M14 x 40 | 183 | 25452 | 391574 | 170 | 5 |
| T301140 | 140 | 190 | 34 | 55 | 41 | 9 | M14 x 40 | 183 | 27410 | 391574 | 161 | 5 |
| T301150 | 150 | 200 | 34 | 55 | 41 | 10 | M14 x 40 | 183 | 32631 | 435082 | 170 | 5 |
| T301160 | 160 | 210 | 34 | 55 | 41 | 11 | M14 x 40 | 183 | 38287 | 478591 | 178 | 6 |
| T301170 | 170 | 225 | 44 | 65 | 51 | 12 | M14 x 40 | 183 | 44378 | 522099 | 140 | 8 |
| T301180 | 180 | 235 | 44 | 65 | 51 | 12 | M14 x 40 | 183 | 46989 | 522099 | 134 | 8 |
| T301190 | 190 | 250 | 44 | 65 | 51 | 15 | M14 x 40 | 183 | 61999 | 652624 | 157 | 9 |
| T301200 | 200 | 260 | 44 | 65 | 51 | 15 | M14 x 40 | 183 | 65262 | 652624 | 151 | 10 |
| T301220 | 220 | 285 | 50 | 73 | 57 | 12 | M16 x 45 | 297 | 82145 | 746770 | 139 | 13 |
| T301240 | 240 | 305 | 50 | 73 | 57 | 15 | M16 x 45 | 297 | 112016 | 933463 | 162 | 14 |
| T301260 | 260 | 325 | 50 | 73 | 57 | 18 | M16 x 45 | 297 | 145620 | 1120155 | 183 | 15 |
| T301280 | 280 | 355 | 60 | 85 | 67 | 16 | M18 x 50 | 393 | 163726 | 1169473 | 146 | 23 |
| T301300 | 300 | 375 | 60 | 85 | 67 | 18 | M18 x 50 | 393 | 197349 | 1315657 | 155 | 24 |
| T301320 | 320 | 405 | 74 | 102 | 82 | 18 | M20 x 50 | 569 | 274346 | 1714665 | 152 | 34 |
| T301340 | 340 | 425 | 74 | 102 | 82 | 21 | M20 x 50 | 569 | 340075 | 2000443 | 169 | 36 |
| T301360 | 360 | 455 | 86 | 116 | 94 | 18 | M22 x 60 | 759 | 377769 | 2098718 | 142 | 49 |
| T301380 | 380 | 475 | 86 | 116 | 94 | 21 | M22 x 60 | 759 | 465216 | 2448505 | 159 | 52 |
| T301400 | 400 | 495 | 86 | 116 | 94 | 21 | M22 x 60 | 759 | 489701 | 2448505 | 153 | 55 |

Power Transmission - B-LOC®


B-LOC® B106 Inch



Locking screws transfer to integrated push-off holes for disassembly.

Metric socket head locking screws
ISO 4762 grade 12.9
(See M_a for install torque).

Screw head height = screw diameter (mm)



TOLERANCE (T_L)

Bore dia. machined to $D - 0/+T_L$
 $T_L = .002$ " for bores up to 4.724"
 $.003$ " for bores up to 12.008"
 $.004$ " for bores over 12.008"

d = Shaft diameter machined to $d + 0/+T_L$

B106 – Inch


| Part Number | d (inch) | D (inch) | D ₁ (inch) | L (inch) | L ₁ (inch) | L ₂ (inch) | Locking Screws | | M _a Install Torque (ft lb) | M _t Maximum Transmitted Torque (ft lb) | T _h Thrust (lbs) | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|-----------------------|----------|-----------------------|-----------------------|----------------|----------|--|--|--------------------------------|--------------------------------------|----------------------|
| | | | | | | | Qty | Size | | | | | |
| | | | | | | | T602010 | 5/8 | 1.260 | 1.457 | 0.551 | 0.846 | 0.709 |
| B602012 | 3/4 | 1.850 | 2.047 | 0.669 | 1.122 | 0.886 | 5 | M6 x 20 | 12 | 187 | 5997 | 12845 | 0.6 |
| B602014 | 7/8 | 1.850 | 2.047 | 0.669 | 1.122 | 0.886 | 5 | M6 x 20 | 12 | 219 | 5997 | 12845 | 0.7 |
| T602015 | 15/16 | 1.969 | 2.224 | 0.669 | 1.122 | 0.886 | 5 | M6 x 20 | 12 | 234 | 5997 | 12071 | 0.6 |
| B602100 | 1 | 1.969 | 2.224 | 0.669 | 1.122 | 0.886 | 6 | M6 x 20 | 12 | 300 | 7196 | 14489 | 0.7 |
| B602102 | 1 1/8 | 2.165 | 2.421 | 0.669 | 1.122 | 0.886 | 6 | M6 x 20 | 12 | 337 | 7196 | 13172 | 0.8 |
| B602103 | 1 3/16 | 2.165 | 2.421 | 0.669 | 1.122 | 0.886 | 6 | M6 x 20 | 12 | 356 | 7196 | 13172 | 0.7 |
| B602104 | 1 1/4 | 2.362 | 2.618 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 12 | 500 | 9595 | 16099 | 0.9 |
| B602106 | 1 3/8 | 2.362 | 2.618 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 12 | 550 | 9595 | 16099 | 0.8 |
| B602107 | 1 7/16 | 2.559 | 2.815 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 12 | 575 | 9595 | 14860 | 1.0 |
| B602108 | 1 1/2 | 2.559 | 2.815 | 0.669 | 1.122 | 0.886 | 8 | M6 x 20 | 12 | 600 | 9595 | 14860 | 1.0 |
| B602110 | 1 5/8 | 2.953 | 3.287 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 30 | 1090 | 16094 | 18362 | 1.7 |
| B602111 | 1 11/16 | 2.953 | 3.287 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 30 | 1132 | 16094 | 18362 | 1.6 |
| B602112 | 1 3/4 | 2.953 | 3.287 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 30 | 1174 | 16094 | 18362 | 1.6 |
| B602114 | 1 7/8 | 3.150 | 3.484 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 30 | 1257 | 16094 | 17214 | 1.8 |
| B602115 | 1 15/16 | 3.150 | 3.484 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 30 | 1299 | 16094 | 17214 | 1.7 |
| B602200 | 2 | 3.150 | 3.484 | 0.787 | 1.358 | 1.043 | 7 | M8 x 25 | 30 | 1341 | 16094 | 17214 | 1.6 |
| T602202 | 2 1/8 | 3.346 | 3.681 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 30 | 1629 | 18393 | 18516 | 1.9 |
| B602203 | 2 3/16 | 3.346 | 3.681 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 30 | 1676 | 18393 | 18516 | 1.8 |
| B602204 | 2 1/4 | 3.543 | 3.898 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 30 | 1724 | 18393 | 17487 | 2.1 |
| B602206 | 2 3/8 | 3.543 | 3.898 | 0.787 | 1.358 | 1.043 | 8 | M8 x 25 | 30 | 1820 | 18393 | 17487 | 1.9 |
| B602207 | 2 7/16 | 3.740 | 4.016 | 0.787 | 1.358 | 1.043 | 9 | M8 x 25 | 30 | 2102 | 20693 | 18638 | 2.2 |
| B602208 | 2 1/2 | 3.740 | 4.016 | 0.787 | 1.358 | 1.043 | 9 | M8 x 25 | 30 | 2155 | 20693 | 18638 | 2.2 |
| T602209 | 2 9/16 | 3.740 | 4.016 | 0.787 | 1.358 | 1.043 | 9 | M8 x 25 | 30 | 2209 | 20693 | 18638 | 2.1 |
| T602211 | 2 11/16 | 4.331 | 4.685 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 60 | 3340 | 29831 | 19337 | 3.8 |
| B602212 | 2 3/4 | 4.331 | 4.685 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 60 | 3418 | 29831 | 19337 | 3.7 |
| B602214 | 2 7/8 | 4.528 | 4.882 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 60 | 3573 | 29831 | 18496 | 4.0 |
| B602215 | 2 15/16 | 4.528 | 4.882 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 60 | 3651 | 29831 | 18496 | 3.9 |
| B602300 | 3 | 4.724 | 5.079 | 0.945 | 1.594 | 1.201 | 8 | M10 x 30 | 60 | 3729 | 29831 | 17726 | 4.4 |
| B602304 | 3 1/4 | 4.921 | 5.276 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 60 | 4545 | 33559 | 19144 | 4.5 |
| T602306 | 3 3/8 | 4.921 | 5.276 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 60 | 4719 | 33559 | 19144 | 4.3 |
| B602307 | 3 7/16 | 5.118 | 5.472 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 60 | 4807 | 33559 | 18408 | 4.8 |
| B602308 | 3 1/2 | 5.118 | 5.472 | 0.945 | 1.594 | 1.201 | 9 | M10 x 30 | 60 | 4894 | 33559 | 18408 | 4.6 |
| T602312 | 3 3/4 | 5.315 | 5.669 | 0.945 | 1.594 | 1.201 | 10 | M10 x 30 | 60 | 5826 | 37288 | 19695 | 4.7 |
| T602315 | 3 15/16 | 5.709 | 6.063 | 1.024 | 1.772 | 1.299 | 8 | M12 x 35 | 105 | 7322 | 44627 | 20258 | 6 |
| B602400 | 4 | 5.709 | 6.063 | 1.024 | 1.772 | 1.299 | 8 | M12 x 35 | 105 | 7438 | 44627 | 20258 | 6 |
| B602407 | 4 7/16 | 6.102 | 6.457 | 1.024 | 1.772 | 1.299 | 8 | M12 x 35 | 105 | 8251 | 44627 | 18951 | 6 |
| T602412 | 4 3/4 | 6.496 | 6.850 | 1.024 | 1.772 | 1.299 | 9 | M12 x 35 | 105 | 9936 | 50205 | 20028 | 7 |
| B602415 | 4 15/16 | 7.087 | 7.441 | 1.339 | 2.165 | 1.614 | 9 | M14 x 40 | 166 | 14057 | 68327 | 19106 | 11 |
| T602500 | 5 | 7.087 | 7.441 | 1.339 | 2.165 | 1.614 | 9 | M14 x 40 | 166 | 14235 | 68327 | 19106 | 11 |
| B602507 | 5 7/16 | 7.480 | 7.835 | 1.339 | 2.165 | 1.614 | 9 | M14 x 40 | 166 | 15480 | 68327 | 18101 | 12 |
| B602515 | 5 15/16 | 7.874 | 8.228 | 1.339 | 2.165 | 1.614 | 10 | M14 x 40 | 166 | 18782 | 75918 | 19106 | 12 |
| B602607 | 6 7/16 | 8.858 | 9.213 | 1.732 | 2.559 | 2.008 | 12 | M14 x 40 | 166 | 24436 | 91102 | 15748 | 20 |
| T602615 | 6 15/16 | 9.252 | 9.606 | 1.732 | 2.559 | 2.008 | 12 | M14 x 40 | 166 | 26334 | 91102 | 15078 | 20 |
| B602700 | 7 | 9.252 | 9.606 | 1.732 | 2.559 | 2.008 | 12 | M14 x 40 | 166 | 26571 | 91102 | 15078 | 20 |
| B602707 | 7 7/16 | 9.843 | 10.197 | 1.732 | 2.559 | 2.008 | 15 | M14 x 40 | 166 | 35290 | 113878 | 17717 | 22 |
| T602715 | 7 15/16 | 10.236 | 10.591 | 1.732 | 2.559 | 2.008 | 15 | M14 x 40 | 166 | 37663 | 113878 | 17035 | 23 |
| T602800 | 8 | 10.236 | 10.591 | 1.732 | 2.559 | 2.008 | 15 | M14 x 40 | 166 | 37959 | 113878 | 17035 | 21 |

B-LOC® B106 Metric

TOLERANCE (T_L)

Bore diameter machined to D $-0/+T_L$
 $T_L =$.05mm for bores up to 120mm
 .08mm for bores up to 305mm
 .10mm for bores over 305mm

d = Shaft diameter machined to d $+0/-T_L$





Note: Series B106 also available with optional integrated spacer sleeve (ideal for very narrow drive elements). Spacers are 0.275" wide for B106 sizes with D=2.559" (65mm) and smaller, and 0.315" wide for all others.

B106 – Metric

| Part Number | d (mm) | D (mm) | D ₁ (mm) | L (mm) | L ₁ (mm) | L ₂ (mm) | Locking Screws | | M _a Install Torque (Nm) | M _t Maximum Transmitted Torque (Nm) | T _h Thrust (N) | P _h Hub Pressure (N/mm ²) | Shipping Weight (kg) |
|-------------|--------|--------|---------------------|--------|---------------------|---------------------|----------------|----------|---------------------------------------|---|------------------------------|---|----------------------|
| | | | | | | | Qty | Size | | | | | |
| | | | | | | | | | | | | | |
| T601014 | 14 | 28 | 32 | 14 | 20.5 | 17 | 4 | M4 x 12 | 5 | 68 | 9713 | 66 | 0.1 |
| T601015 | 15 | 28 | 32 | 14 | 20.5 | 17 | 4 | M4 x 12 | 5 | 73 | 9713 | 66 | 0.1 |
| T601018 | 18 | 47 | 52 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 16 | 236 | 26234 | 87 | 0.3 |
| T601019 | 19 | 47 | 52 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 16 | 249 | 26234 | 87 | 0.3 |
| T601020 | 20 | 47 | 52 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 16 | 262 | 26234 | 87 | 0.3 |
| B601022 | 22 | 47 | 52 | 17 | 28.5 | 22.5 | 5 | M6 x 20 | 16 | 289 | 26234 | 87 | 0.3 |
| T601024 | 24 | 50 | 56.5 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 16 | 378 | 31481 | 98 | 0.3 |
| B601025 | 25 | 50 | 56.5 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 16 | 394 | 31481 | 98 | 0.3 |
| B601028 | 28 | 55 | 61.5 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 16 | 441 | 31481 | 89 | 0.4 |
| B601030 | 30 | 55 | 61.5 | 17 | 28.5 | 22.5 | 6 | M6 x 20 | 16 | 472 | 31481 | 89 | 0.3 |
| T601032 | 32 | 60 | 66.5 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 16 | 672 | 41975 | 109 | 0.4 |
| B601035 | 35 | 60 | 66.5 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 16 | 735 | 41975 | 109 | 0.4 |
| T601038 | 38 | 65 | 71.5 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 16 | 798 | 41975 | 101 | 0.5 |
| B601040 | 40 | 65 | 71.5 | 17 | 28.5 | 22.5 | 8 | M6 x 20 | 16 | 839 | 41975 | 101 | 0.5 |
| T601042 | 42 | 75 | 83.5 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 41 | 1515 | 72167 | 128 | 0.8 |
| B601045 | 45 | 75 | 83.5 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 41 | 1624 | 72167 | 128 | 0.7 |
| T601048 | 48 | 80 | 88.5 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 41 | 1732 | 72167 | 120 | 0.8 |
| B601050 | 50 | 80 | 88.5 | 20 | 34.5 | 26.5 | 7 | M8 x 25 | 41 | 1804 | 72167 | 120 | 0.8 |
| B601055 | 55 | 85 | 93.5 | 20 | 34.5 | 26.5 | 8 | M8 x 25 | 41 | 2268 | 82476 | 129 | 0.8 |
| B601060 | 60 | 90 | 98 | 20 | 34.5 | 26.5 | 8 | M8 x 25 | 41 | 2474 | 82476 | 122 | 0.9 |
| T601063 | 63 | 95 | 102 | 20 | 34.5 | 26.5 | 9 | M8 x 25 | 41 | 2923 | 92786 | 130 | 0.9 |
| T601065 | 65 | 95 | 102 | 20 | 34.5 | 26.5 | 9 | M8 x 25 | 41 | 3016 | 92786 | 130 | 0.9 |
| T601070 | 70 | 110 | 119 | 24 | 40.5 | 30.5 | 8 | M10 x 30 | 81 | 4624 | 132127 | 133 | 1.7 |
| B601075 | 75 | 115 | 124 | 24 | 40.5 | 30.5 | 8 | M10 x 30 | 81 | 4955 | 132127 | 127 | 1.8 |
| B601080 | 80 | 120 | 129 | 24 | 40.5 | 30.5 | 8 | M10 x 30 | 81 | 5285 | 132127 | 122 | 1.9 |
| T601085 | 85 | 125 | 134 | 24 | 40.5 | 30.5 | 9 | M10 x 30 | 81 | 6317 | 148643 | 131 | 2 |
| B601090 | 90 | 130 | 139 | 24 | 40.5 | 30.5 | 9 | M10 x 30 | 81 | 6689 | 148643 | 126 | 2 |
| T601095 | 95 | 135 | 144 | 24 | 40.5 | 30.5 | 10 | M10 x 30 | 81 | 7845 | 165159 | 135 | 2 |
| B601100 | 100 | 145 | 154 | 26 | 45 | 33 | 8 | M12 x 35 | 142 | 9901 | 198016 | 139 | 3 |
| B601110 | 110 | 155 | 164 | 26 | 45 | 33 | 8 | M12 x 35 | 142 | 10891 | 198016 | 130 | 3 |
| B601120 | 120 | 165 | 174 | 26 | 45 | 33 | 9 | M12 x 35 | 142 | 13366 | 222768 | 138 | 3 |
| T601130 | 130 | 180 | 189 | 34 | 55 | 41 | 9 | M14 x 40 | 225 | 19751 | 303855 | 132 | 5 |
| B601140 | 140 | 190 | 199 | 34 | 55 | 41 | 9 | M14 x 40 | 225 | 21270 | 303855 | 125 | 5 |
| T601150 | 150 | 200 | 209 | 34 | 55 | 41 | 10 | M14 x 40 | 225 | 25321 | 337617 | 132 | 6 |
| B601160 | 160 | 210 | 219 | 34 | 55 | 41 | 11 | M14 x 40 | 225 | 29710 | 371379 | 138 | 6 |
| B601170 | 170 | 225 | 234 | 44 | 65 | 51 | 12 | M14 x 40 | 225 | 34437 | 405140 | 109 | 8 |
| B601180 | 180 | 235 | 244 | 44 | 65 | 51 | 12 | M14 x 40 | 225 | 36463 | 405140 | 104 | 9 |
| T601190 | 190 | 250 | 259 | 44 | 65 | 51 | 15 | M14 x 40 | 225 | 48110 | 506425 | 122 | 10 |
| B601200 | 200 | 260 | 269 | 44 | 65 | 51 | 15 | M14 x 40 | 225 | 50643 | 506425 | 117 | 10 |
| T601220 | 220 | 285 | 294 | 50 | 73 | 57 | 12 | M16 x 45 | 348 | 60747 | 552244 | 103 | 14 |
| T601240 | 240 | 305 | 314 | 50 | 73 | 57 | 15 | M16 x 45 | 348 | 82837 | 690305 | 120 | 15 |
| T601260 | 260 | 325 | 334 | 50 | 73 | 57 | 18 | M16 x 45 | 348 | 107688 | 828366 | 135 | 16 |
| T601280 | 280 | 355 | 364 | 60 | 85 | 67 | 16 | M18 x 50 | 475 | 124894 | 892098 | 111 | 23 |
| T601300 | 300 | 375 | 384 | 60 | 85 | 67 | 18 | M18 x 50 | 475 | 150542 | 1003610 | 118 | 25 |
| T601320 | 320 | 405 | 414 | 74 | 102 | 82 | 18 | M20 x 50 | 678 | 206318 | 1289490 | 114 | 35 |
| T601340 | 340 | 425 | 434 | 74 | 102 | 82 | 21 | M20 x 50 | 678 | 255749 | 1504405 | 127 | 37 |
| T601360 | 360 | 455 | 464 | 86 | 116 | 94 | 18 | M22 x 60 | 915 | 287427 | 1596815 | 108 | 51 |
| T601380 | 380 | 475 | 484 | 86 | 116 | 94 | 21 | M22 x 60 | 915 | 353961 | 1862951 | 121 | 53 |
| T601400 | 400 | 495 | 504 | 86 | 116 | 94 | 21 | M22 x 60 | 915 | 372590 | 1862951 | 116 | 57 |

Power Transmission - B-LOC®

B-LOC® B800 Inch



TOLERANCE (T_L)

Bore diameter machined to $D - 0/+T_L$
 $T_L = .002"$ for bores up to 2.559"
 $.003"$ for bores over 2.559"

$d =$ Shaft diameter machined to $d + 0/-T_L$

B800 – Inch

| Part Number | d (inch) | D (inch) | D ₁ (inch) | D ₂ (inch) | L (inch) | L ₁ (inch) | L ₂ (inch) | Locking Screws | | M _a Install Torque (ft lb) | Th | | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|-----------------------|-----------------------|----------|-----------------------|-----------------------|----------------|----------|--|---------------------|-------|--------------------------------------|----------------------|
| | | | | | | | | Qty | Size | | Maximum Transmitted | | | |
| | | | | | | | | | | Torque (ft lb) | Thrust (lbs) | | | |
| B802004 | 1/4 | 0.551 | 0.984 | 0.906 | 0.394 | 0.866 | 0.748 | 3 | M4 x 10 | 3.5 | 16 | 1572 | 19217 | 0.2 |
| B802005 | 5/16 | 0.591 | 1.063 | 0.945 | 0.472 | 0.984 | 0.866 | 3 | M4 x 10 | 3.5 | 20 | 1572 | 14947 | 0.3 |
| B802006 | 3/8 | 0.630 | 1.142 | 1.024 | 0.551 | 1.063 | 0.945 | 4 | M4 x 10 | 3.5 | 33 | 2096 | 16014 | 0.4 |
| T82007 | 7/16 | 0.709 | 1.260 | 1.102 | 0.551 | 1.083 | 0.945 | 4 | M4 x 10 | 3.5 | 38 | 2096 | 14235 | 0.5 |
| B802008 | 1/2 | 0.906 | 1.496 | 1.299 | 0.551 | 1.083 | 0.945 | 4 | M4 x 10 | 3.5 | 44 | 2096 | 11140 | 0.5 |
| B802010 | 5/8 | 0.945 | 1.732 | 1.575 | 0.630 | 1.437 | 1.161 | 3 | M6 x 16 | 12 | 94 | 3598 | 16036 | 0.6 |
| B802012 | 3/4 | 1.063 | 1.929 | 1.693 | 0.709 | 1.555 | 1.280 | 4 | M6 x 16 | 12 | 150 | 4798 | 16893 | 0.7 |
| T82014 | 7/8 | 1.260 | 2.126 | 1.890 | 0.984 | 1.850 | 1.575 | 4 | M6 x 16 | 12 | 175 | 4798 | 10263 | 0.8 |
| B802015 | 15/16 | 1.339 | 2.205 | 1.969 | 0.984 | 1.850 | 1.575 | 6 | M6 x 16 | 12 | 281 | 7196 | 14489 | 0.9 |
| B802100 | 1 | 1.339 | 2.205 | 1.969 | 0.984 | 1.850 | 1.575 | 6 | M6 x 16 | 12 | 300 | 7196 | 14489 | 0.9 |
| B802102 | 1 1/8 | 1.535 | 2.402 | 2.165 | 0.984 | 1.850 | 1.575 | 6 | M6 x 16 | 12 | 337 | 7196 | 12631 | 1.0 |
| T82103 | 1 3/16 | 1.614 | 2.441 | 2.244 | 0.984 | 1.850 | 1.575 | 6 | M6 x 16 | 12 | 356 | 7196 | 12015 | 1.1 |
| B802104 | 1 1/4 | 1.693 | 2.559 | 2.323 | 0.984 | 1.850 | 1.575 | 8 | M6 x 16 | 12 | 500 | 9595 | 15275 | 1.2 |
| T82106 | 1 3/8 | 1.850 | 2.677 | 2.441 | 1.260 | 2.126 | 1.850 | 8 | M6 x 18 | 12 | 550 | 9595 | 10918 | 1.4 |
| B802107 | 1 7/16 | 1.969 | 2.835 | 2.598 | 1.260 | 2.126 | 1.850 | 8 | M6 x 18 | 12 | 575 | 9595 | 10263 | 1.5 |
| B802108 | 1 1/2 | 1.969 | 2.835 | 2.598 | 1.260 | 2.126 | 1.850 | 8 | M6 x 18 | 12 | 600 | 9595 | 10263 | 1.5 |
| B802110 | 1 5/8 | 2.165 | 3.071 | 2.795 | 1.260 | 2.126 | 1.850 | 8 | M6 x 18 | 12 | 650 | 9595 | 9330 | 1.7 |
| T82111 | 1 11/16 | 2.323 | 3.386 | 3.150 | 1.772 | 2.756 | 2.441 | 8 | M8 x 22 | 30 | 1293 | 18393 | 11856 | 2.7 |
| T82112 | 1 3/4 | 2.323 | 3.386 | 3.150 | 1.772 | 2.756 | 2.441 | 8 | M8 x 22 | 30 | 1341 | 18393 | 11856 | 2.7 |
| T82114 | 1 7/8 | 2.441 | 3.425 | 3.189 | 1.772 | 2.756 | 2.441 | 8 | M8 x 22 | 30 | 1437 | 18393 | 11282 | 2.7 |
| T82115 | 1 15/16 | 2.559 | 3.622 | 3.386 | 1.772 | 2.756 | 2.441 | 8 | M8 x 22 | 30 | 1485 | 18393 | 10762 | 3.1 |
| B802200 | 2 | 2.795 | 3.858 | 3.622 | 2.165 | 3.189 | 2.874 | 9 | M8 x 22 | 30 | 1724 | 20693 | 9068 | 3.8 |
| T82202 | 2 1/8 | 2.795 | 3.858 | 3.622 | 2.165 | 3.189 | 2.874 | 9 | M8 x 22 | 30 | 1832 | 20693 | 9068 | 3.8 |
| T82203 | 2 3/16 | 3.031 | 4.094 | 3.858 | 2.165 | 3.189 | 2.874 | 9 | M8 x 22 | 30 | 1886 | 20693 | 8362 | 4.2 |
| T82206 | 2 3/8 | 3.031 | 4.094 | 3.858 | 2.165 | 3.189 | 2.874 | 9 | M8 x 22 | 30 | 2048 | 20693 | 8362 | 4.2 |
| B802207 | 2 7/16 | 3.307 | 4.370 | 4.134 | 2.165 | 3.189 | 2.874 | 9 | M8 x 22 | 30 | 2102 | 20693 | 7665 | 4.9 |
| B802208 | 2 1/2 | 3.307 | 4.370 | 4.134 | 2.165 | 3.189 | 2.874 | 9 | M8 x 22 | 30 | 2155 | 20693 | 7665 | 4.9 |
| T82210 | 2 5/8 | 3.543 | 4.685 | 4.449 | 2.559 | 3.780 | 3.386 | 9 | M10 x 25 | 60 | 3671 | 33559 | 9817 | 7 |
| T82212 | 2 3/4 | 3.543 | 4.685 | 4.449 | 2.559 | 3.780 | 3.386 | 9 | M10 x 25 | 60 | 3845 | 33559 | 9817 | 7 |
| T82214 | 2 7/8 | 3.740 | 4.961 | 4.685 | 2.559 | 3.780 | 3.386 | 9 | M10 x 25 | 60 | 4020 | 33559 | 9301 | 7 |
| T82215 | 2 15/16 | 3.740 | 4.961 | 4.685 | 2.559 | 3.780 | 3.386 | 9 | M10 x 25 | 60 | 4108 | 33559 | 9301 | 7 |
| B802300 | 3 | 3.740 | 4.961 | 4.685 | 2.559 | 3.780 | 3.386 | 9 | M10 x 25 | 60 | 4195 | 33559 | 9301 | 7 |
| T82302 | 3 1/8 | 3.937 | 5.157 | 4.921 | 2.559 | 3.780 | 3.386 | 12 | M10 x 25 | 60 | 5826 | 44746 | 11781 | 8 |
| T82304 | 3 1/4 | 4.173 | 5.394 | 5.157 | 2.559 | 3.780 | 3.386 | 12 | M10 x 25 | 60 | 6059 | 44746 | 11114 | 8 |
| T82306 | 3 3/8 | 4.173 | 5.394 | 5.157 | 2.559 | 3.780 | 3.386 | 12 | M10 x 25 | 60 | 6292 | 44746 | 11114 | 8 |
| T82307 | 3 7/16 | 4.409 | 5.669 | 5.394 | 2.559 | 3.780 | 3.386 | 12 | M10 x 25 | 60 | 6409 | 44746 | 10519 | 9 |
| T82308 | 3 1/2 | 4.409 | 5.669 | 5.394 | 2.559 | 3.780 | 3.386 | 12 | M10 x 25 | 60 | 6525 | 44746 | 10519 | 9 |
| T82310 | 3 5/8 | 4.409 | 5.669 | 5.394 | 2.559 | 3.780 | 3.386 | 12 | M10 x 25 | 60 | 6758 | 44746 | 10519 | 9 |
| T82312 | 3 3/4 | 4.724 | 5.866 | 5.591 | 2.559 | 3.780 | 3.386 | 14 | M10 x 25 | 60 | 8157 | 52204 | 11454 | 10 |
| T82314 | 3 7/8 | 4.921 | 6.299 | 6.024 | 2.756 | 4.213 | 3.701 | 12 | M12 x 30 | 105 | 10808 | 66940 | 13092 | 12 |
| B802315 | 3 15/16 | 4.921 | 6.299 | 6.024 | 2.756 | 4.213 | 3.701 | 12 | M12 x 30 | 105 | 10982 | 66940 | 13092 | 12 |
| B802400 | 4 | 4.921 | 6.299 | 6.024 | 2.756 | 4.213 | 3.701 | 12 | M12 x 30 | 105 | 11157 | 66940 | 13092 | 12 |
| T82404 | 4 1/4 | 5.512 | 6.850 | 6.614 | 2.756 | 4.213 | 3.701 | 12 | M12 x 30 | 105 | 11854 | 66940 | 11690 | 15 |
| T82406 | 4 3/8 | 5.512 | 6.850 | 6.614 | 2.756 | 4.213 | 3.701 | 12 | M12 x 30 | 105 | 12203 | 66940 | 11690 | 15 |
| T82407 | 4 7/16 | 6.102 | 7.795 | 7.362 | 3.543 | 5.039 | 4.528 | 16 | M12 x 30 | 105 | 16503 | 89254 | 10949 | 21 |
| T82408 | 4 1/2 | 6.102 | 7.795 | 7.362 | 3.543 | 5.039 | 4.528 | 16 | M12 x 30 | 105 | 16735 | 89254 | 10949 | 21 |
| T82412 | 4 3/4 | 6.102 | 7.795 | 7.362 | 3.543 | 5.039 | 4.528 | 16 | M12 x 30 | 105 | 17665 | 89254 | 10949 | 21 |
| T82415 | 4 15/16 | 6.496 | 8.189 | 7.756 | 3.543 | 5.039 | 4.528 | 16 | M12 x 30 | 105 | 18362 | 89254 | 10286 | 23 |

B-LOC® B800 Metric

TOLERANCE (T_L)

Bore diameter machined to D -0/+T_L
 T_L = .05mm for bores up to 65mm
 .08mm for bores over 65mm

d = Shaft diameter machined to d +0/-T_L.



B800 – Metric

| Part Number | d (mm) | D (mm) | D ₁ (mm) | D ₂ (mm) | L (mm) | L ₁ (mm) | L ₂ (mm) | Locking Screws | | M _a Install Torque (Nm) | M _t Maximum Transmitted Torque (Nm) | T _h Thrust (N) | P _h Hub Pressure (N/mm ²) | Shipping Weight (kg) |
|-------------|--------|--------|---------------------|---------------------|--------|---------------------|---------------------|----------------|----------|---------------------------------------|---|------------------------------|---|----------------------|
| | | | | | | | | Qty | Size | | | | | |
| | | | | | | | | T8006 | 6 | 14 | 25 | 23 | 10 | |
| T8007 | 7 | 15 | 27 | 24 | 12 | 25 | 22 | 3 | M4 x 10 | 5 | 25 | 7285 | 107 | 0.1 |
| T8008 | 8 | 15 | 27 | 24 | 12 | 25 | 22 | 3 | M4 x 10 | 5 | 29 | 7285 | 107 | 0.1 |
| T8009 | 9 | 16 | 29 | 26 | 14 | 27 | 24 | 4 | M4 x 10 | 5 | 44 | 9713 | 115 | 0.1 |
| B801010 | 10 | 16 | 29 | 26 | 14 | 27 | 24 | 4 | M4 x 10 | 5 | 49 | 9713 | 115 | 0.1 |
| T8011 | 11 | 18 | 32 | 28 | 14 | 28 | 24 | 4 | M4 x 10 | 5 | 53 | 9713 | 102 | 0.1 |
| T8012 | 12 | 18 | 32 | 28 | 14 | 28 | 24 | 4 | M4 x 10 | 5 | 58 | 9713 | 102 | 0.1 |
| B801014 | 14 | 23 | 38 | 33 | 14 | 28 | 24 | 4 | M4 x 10 | 5 | 68 | 9713 | 80 | 0.1 |
| T8015 | 15 | 24 | 44 | 40 | 16 | 37 | 30 | 3 | M6 x 16 | 16 | 118 | 15740 | 109 | 0.2 |
| B801016 | 16 | 24 | 44 | 40 | 16 | 37 | 30 | 3 | M6 x 16 | 16 | 126 | 15740 | 109 | 0.2 |
| B801018 | 18 | 26 | 47 | 42 | 18 | 40 | 33 | 4 | M6 x 16 | 16 | 189 | 20987 | 119 | 0.3 |
| B801019 | 19 | 27 | 49 | 43 | 18 | 40 | 33 | 4 | M6 x 16 | 16 | 199 | 20987 | 115 | 0.3 |
| B801020 | 20 | 28 | 50 | 44 | 18 | 40 | 33 | 4 | M6 x 16 | 16 | 210 | 20987 | 110 | 0.3 |
| B801022 | 22 | 32 | 54 | 48 | 25 | 47 | 40 | 4 | M6 x 16 | 16 | 231 | 20987 | 70 | 0.4 |
| B801024 | 24 | 34 | 56 | 50 | 25 | 47 | 40 | 6 | M6 x 16 | 16 | 378 | 31481 | 98 | 0.4 |
| B801025 | 25 | 34 | 56 | 50 | 25 | 47 | 40 | 6 | M6 x 16 | 16 | 394 | 31481 | 98 | 0.4 |
| T8028 | 28 | 39 | 61 | 55 | 25 | 47 | 40 | 6 | M6 x 16 | 16 | 441 | 31481 | 86 | 0.4 |
| B801030 | 30 | 41 | 62 | 57 | 25 | 47 | 40 | 6 | M6 x 16 | 16 | 472 | 31481 | 81 | 0.4 |
| B801032 | 32 | 43 | 65 | 59 | 25 | 47 | 40 | 8 | M6 x 16 | 16 | 672 | 41975 | 104 | 0.5 |
| T8035 | 35 | 47 | 68 | 62 | 32 | 54 | 47 | 8 | M6 x 18 | 16 | 735 | 41975 | 74 | 0.5 |
| B801038 | 38 | 50 | 72 | 66 | 32 | 54 | 47 | 8 | M6 x 18 | 16 | 798 | 41975 | 70 | 0.6 |
| B801040 | 40 | 53 | 75 | 69 | 32 | 54 | 47 | 8 | M6 x 18 | 16 | 839 | 41975 | 66 | 0.7 |
| T8042 | 42 | 55 | 78 | 71 | 32 | 54 | 47 | 8 | M6 x 18 | 16 | 881 | 41975 | 63 | 0.7 |
| T8045 | 45 | 59 | 86 | 80 | 45 | 70 | 62 | 8 | M8 x 22 | 41 | 1856 | 82476 | 82 | 1.1 |
| T8048 | 48 | 62 | 87 | 81 | 45 | 70 | 62 | 8 | M8 x 22 | 41 | 1979 | 82476 | 78 | 1.1 |
| T8050 | 50 | 65 | 92 | 86 | 45 | 70 | 62 | 8 | M8 x 22 | 41 | 2062 | 82476 | 75 | 1.3 |
| T8055 | 55 | 71 | 98 | 92 | 55 | 81 | 73 | 9 | M8 x 22 | 41 | 2552 | 92786 | 63 | 1.6 |
| T8060 | 60 | 77 | 104 | 98 | 55 | 81 | 73 | 9 | M8 x 22 | 41 | 2783 | 92786 | 58 | 1.8 |
| T8065 | 65 | 84 | 111 | 105 | 55 | 81 | 73 | 9 | M8 x 22 | 41 | 3015 | 92786 | 53 | 2 |
| T8070 | 70 | 90 | 119 | 113 | 65 | 96 | 86 | 9 | M10 x 25 | 81 | 5203 | 148643 | 67 | 3 |
| T8075 | 75 | 95 | 126 | 119 | 65 | 96 | 86 | 9 | M10 x 25 | 81 | 5575 | 148643 | 64 | 3 |
| T8080 | 80 | 100 | 131 | 125 | 65 | 96 | 86 | 12 | M10 x 25 | 81 | 7928 | 198191 | 81 | 3 |
| T8085 | 85 | 106 | 137 | 131 | 65 | 96 | 86 | 12 | M10 x 25 | 81 | 8423 | 198191 | 76 | 4 |
| B801090 | 90 | 112 | 144 | 137 | 65 | 96 | 86 | 12 | M10 x 25 | 81 | 8919 | 198191 | 72 | 4 |
| T8095 | 95 | 120 | 149 | 142 | 65 | 96 | 86 | 14 | M10 x 25 | 81 | 10983 | 231223 | 79 | 4 |
| T8100 | 100 | 125 | 160 | 153 | 70 | 107 | 94 | 12 | M12 x 30 | 142 | 14851 | 297024 | 90 | 6 |
| T8110 | 110 | 140 | 174 | 168 | 70 | 107 | 94 | 12 | M12 x 30 | 142 | 16336 | 297024 | 80 | 7 |
| T8120 | 120 | 155 | 198 | 187 | 90 | 128 | 115 | 16 | M12 x 30 | 142 | 23762 | 396032 | 75 | 10 |
| T8130 | 130 | 165 | 208 | 197 | 90 | 128 | 115 | 16 | M12 x 30 | 142 | 25742 | 396032 | 71 | 11 |

Power Transmission - B-LOC®

B-LOC® B400 Inch

B400 – Inch



| Part Number | d (inch) | D (inch) | L (inch) | L ₁ (inch) | L _s (inch) | Locking Screws | | M _a Install Torque (ft lb) | d _B | M _t Maximum Transmitted | | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|----------|-----------------------|-----------------------|----------------|----------|--|----------------|---------------------------------------|--------------|--------------------------------------|----------------------|
| | | | | | | Qty | Size | | | Torque (ft lb) | Thrust (lbs) | | |
| | | | | | | B402012 | 3/4 | 1.850 | 0.669 | 0.787 | 1.024 | 8 | M6 x 18 |
| B402014 | 7/8 | 1.850 | 0.669 | 0.787 | 1.024 | 8 | M6 x 18 | 11 | M8 | 273 | 7501 | 16067 | 0.5 |
| B402100 | 1 | 1.969 | 0.669 | 0.787 | 1.024 | 9 | M6 x 18 | 11 | M8 | 352 | 8439 | 16991 | 0.5 |
| B402102 | 1 1/8 | 2.165 | 0.669 | 0.787 | 1.024 | 10 | M6 x 18 | 11 | M8 | 440 | 9377 | 17162 | 0.6 |
| T402103 | 1 3/16 | 2.159 | 0.669 | 0.787 | 1.024 | 10 | M6 x 18 | 11 | M8 | 464 | 9377 | 17212 | 0.6 |
| B402104 | 1 1/4 | 2.362 | 0.669 | 0.787 | 1.024 | 12 | M6 x 18 | 11 | M8 | 586 | 11252 | 18880 | 0.7 |
| T402106 | 1 3/8 | 2.365 | 0.669 | 0.787 | 1.024 | 12 | M6 x 18 | 11 | M8 | 645 | 11252 | 18856 | 0.6 |
| B402107 | 1 7/16 | 2.559 | 0.669 | 0.787 | 1.024 | 14 | M6 x 18 | 11 | M8 | 786 | 13127 | 20331 | 0.8 |
| B402108 | 1 1/2 | 2.559 | 0.669 | 0.787 | 1.024 | 14 | M6 x 18 | 11 | M8 | 820 | 13127 | 20331 | 0.7 |
| B402110 | 1 5/8 | 2.953 | 0.787 | 0.945 | 1.260 | 12 | M8 x 22 | 26 | M10 | 1381 | 20393 | 23267 | 1.3 |
| B402111 | 1 11/16 | 2.953 | 0.787 | 0.945 | 1.260 | 12 | M8 x 22 | 26 | M10 | 1434 | 20393 | 23267 | 1.2 |
| B402112 | 1 3/4 | 2.953 | 0.787 | 0.945 | 1.260 | 12 | M8 x 22 | 26 | M10 | 1487 | 20393 | 23267 | 1.2 |
| B402114 | 1 7/8 | 3.150 | 0.787 | 0.945 | 1.260 | 12 | M8 x 22 | 26 | M10 | 1593 | 20393 | 21812 | 1.3 |
| B402115 | 1 15/16 | 3.150 | 0.787 | 0.945 | 1.260 | 12 | M8 x 22 | 26 | M10 | 1646 | 20393 | 21812 | 1.3 |
| B402200 | 2 | 3.346 | 0.787 | 0.945 | 1.260 | 14 | M8 x 22 | 26 | M10 | 1983 | 23792 | 23951 | 1.5 |
| B402202 | 2 1/8 | 3.346 | 0.787 | 0.945 | 1.260 | 14 | M8 x 22 | 26 | M10 | 2107 | 23792 | 23951 | 1.4 |
| B402203 | 2 3/16 | 3.543 | 0.787 | 0.945 | 1.260 | 14 | M8 x 22 | 26 | M10 | 2169 | 23792 | 22622 | 1.6 |
| B402204 | 2 1/4 | 3.543 | 0.787 | 0.945 | 1.260 | 14 | M8 x 22 | 26 | M10 | 2231 | 23792 | 22620 | 1.5 |
| T402206 | 2 3/8 | 3.531 | 0.787 | 0.945 | 1.260 | 14 | M8 x 22 | 26 | M10 | 2354 | 23792 | 22699 | 1.4 |
| B402207 | 2 7/16 | 3.740 | 0.787 | 0.945 | 1.260 | 16 | M8 x 22 | 26 | M10 | 2762 | 27191 | 24491 | 1.6 |
| B402208 | 2 1/2 | 3.740 | 0.787 | 0.945 | 1.260 | 16 | M8 x 22 | 26 | M10 | 2832 | 27191 | 24491 | 1.6 |
| T402209 | 2 9/16 | 3.737 | 0.787 | 0.945 | 1.260 | 16 | M8 x 22 | 26 | M10 | 2903 | 27191 | 24512 | 1.5 |
| B402210 | 2 5/8 | 4.331 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4139 | 37844 | 24532 | 2.8 |
| B402211 | 2 11/16 | 4.331 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4238 | 37844 | 24532 | 2.8 |
| T402212 | 2 3/4 | 4.337 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4336 | 37844 | 24496 | 2.7 |
| T402214 | 2 7/8 | 4.528 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4533 | 37844 | 23465 | 2.9 |
| B402215 | 2 15/16 | 4.528 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4632 | 37844 | 23465 | 2.8 |
| B402300 | 3 | 4.724 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4730 | 37844 | 22487 | 3.2 |
| B402302 | 3 1/8 | 4.724 | 0.945 | 1.102 | 1.496 | 14 | M10 x 25 | 51 | M12 | 4928 | 37844 | 22487 | 3.0 |
| T402304 | 3 1/4 | 4.921 | 0.945 | 1.102 | 1.496 | 16 | M10 x 25 | 51 | M12 | 5857 | 43250 | 24672 | 3.3 |
| B402306 | 3 3/8 | 4.921 | 0.945 | 1.102 | 1.496 | 16 | M10 x 25 | 51 | M12 | 6082 | 43250 | 24672 | 3.1 |
| B402307 | 3 7/16 | 5.118 | 0.945 | 1.102 | 1.496 | 16 | M10 x 25 | 51 | M12 | 6195 | 43250 | 23723 | 3.4 |
| B402308 | 3 1/2 | 5.118 | 0.945 | 1.102 | 1.496 | 16 | M10 x 25 | 51 | M12 | 6307 | 43250 | 23723 | 3.4 |
| T402312 | 3 3/4 | 5.305 | 0.945 | 1.102 | 1.496 | 18 | M10 x 25 | 51 | M12 | 7603 | 48656 | 25748 | 3.5 |
| T402314 | 3 7/8 | 5.709 | 1.024 | 1.299 | 1.772 | 14 | M12 x 30 | 91 | M14 | 9320 | 57726 | 26204 | 4.8 |
| T402315 | 3 15/16 | 5.709 | 1.024 | 1.299 | 1.772 | 14 | M12 x 30 | 91 | M14 | 9471 | 57726 | 26204 | 4.7 |
| B402400 | 4 | 5.843 | 1.024 | 1.299 | 1.772 | 14 | M12 x 30 | 91 | M14 | 9621 | 57726 | 25602 | 5 |
| T402403 | 4 3/16 | 6.102 | 1.024 | 1.299 | 1.772 | 14 | M12 x 30 | 91 | M14 | 10072 | 57726 | 24513 | 6 |
| B402407 | 4 7/16 | 6.496 | 1.024 | 1.299 | 1.772 | 16 | M12 x 30 | 91 | M14 | 12198 | 65972 | 26317 | 6 |
| B402408 | 4 1/2 | 6.496 | 1.024 | 1.299 | 1.772 | 16 | M12 x 30 | 91 | M14 | 12370 | 65972 | 26317 | 6 |
| B402415 | 4 15/16 | 7.087 | 1.339 | 1.496 | 1.969 | 20 | M12 x 35 | 91 | M14 | 16966 | 82466 | 23060 | 8 |
| T402500 | 5 | 7.087 | 1.339 | 1.496 | 1.969 | 20 | M12 x 35 | 91 | M14 | 17180 | 82466 | 23060 | 8 |
| B402507 | 5 7/16 | 7.480 | 1.339 | 1.496 | 1.969 | 22 | M12 x 35 | 91 | M14 | 20552 | 90712 | 24031 | 9 |
| T402508 | 5 1/2 | 7.492 | 1.339 | 1.496 | 1.969 | 22 | M12 x 35 | 91 | M14 | 20788 | 90712 | 23993 | 8 |
| B402600 | 6 | 8.268 | 1.339 | 1.496 | 1.969 | 26 | M12 x 35 | 91 | M14 | 26801 | 107205 | 25695 | 10 |
| T402607 | 6 7/16 | 8.858 | 1.496 | 1.732 | 2.283 | 22 | M14 x 40 | 138 | M16 | 31764 | 118419 | 23702 | 14 |
| B402608 | 6 1/2 | 8.858 | 1.496 | 1.732 | 2.283 | 22 | M14 x 40 | 138 | M16 | 32072 | 118419 | 23702 | 13 |
| B402615 | 6 15/16 | 9.252 | 1.496 | 1.732 | 2.283 | 24 | M14 x 40 | 138 | M16 | 37343 | 129185 | 24757 | 14 |
| B402700 | 7 | 9.252 | 1.496 | 1.732 | 2.283 | 24 | M14 x 40 | 138 | M16 | 37679 | 129185 | 24757 | 14 |
| T402708 | 7 1/2 | 9.823 | 1.811 | 2.047 | 2.598 | 28 | M14 x 45 | 138 | M16 | 47099 | 150716 | 22473 | 18 |
| T402714 | 7 7/8 | 10.236 | 1.811 | 2.047 | 2.598 | 30 | M14 x 45 | 138 | M16 | 52986 | 161481 | 23106 | 19 |
| T402715 | 7 15/16 | 10.504 | 1.811 | 2.047 | 2.598 | 30 | M14 x 45 | 138 | M16 | 53407 | 161481 | 22517 | 19 |
| T402800 | 8 | 10.504 | 1.811 | 2.047 | 2.598 | 30 | M14 x 45 | 138 | M16 | 53827 | 161481 | 22517 | 19 |

TOLERANCE (T_L) Bore diameter machined to D -0/+T_L

T_L = .05mm for bores up to 50mm
 .08mm for bores up to 120mm
 .10mm for bores up to 235mm
 .13mm for bores up to 375mm
 .15mm for bores over 375mm

d = Shaft diameter machined to d +0/-T_L

B-LOC®
B400
 Metric


B400 – Metric

| Part Number | d (mm) | D (mm) | L (mm) | L ₁ (mm) | L _S (mm) | Locking Screws | | M _a | d _g | Maximum Transmitted | | P _h | Shipping Weight (kg) |
|-------------|--------|--------|--------|---------------------|---------------------|----------------|----------|----------------|----------------|---------------------|----------------|----------------|----------------------|
| | | | | | | Qty | Size | | | Install Torque (Nm) | M _t | | |
| | | | | | | | | Torque (Nm) | Thrust (N) | | | | |
| T401018 | 18 | 47 | 17 | 20 | 26 | 8 | M6 x 18 | 15 | M8 | 302 | 33561 | 111 | 0.2 |
| T401019 | 19 | 47 | 17 | 20 | 26 | 8 | M6 x 18 | 15 | M8 | 319 | 33561 | 111 | 0.2 |
| B401020 | 20 | 47 | 17 | 20 | 26 | 8 | M6 x 18 | 15 | M8 | 335 | 33561 | 111 | 0.2 |
| T401022 | 22 | 47 | 17 | 20 | 26 | 8 | M6 x 18 | 15 | M8 | 369 | 33561 | 111 | 0.2 |
| B401024 | 24 | 50 | 17 | 20 | 26 | 9 | M6 x 18 | 15 | M8 | 453 | 37756 | 118 | 0.2 |
| B401025 | 25 | 50 | 17 | 20 | 26 | 9 | M6 x 18 | 15 | M8 | 472 | 37756 | 118 | 0.2 |
| B401028 | 28 | 55 | 17 | 20 | 26 | 10 | M6 x 18 | 15 | M8 | 587 | 41952 | 119 | 0.3 |
| B401030 | 30 | 55 | 17 | 20 | 26 | 10 | M6 x 18 | 15 | M8 | 629 | 41952 | 119 | 0.3 |
| B401032 | 32 | 60 | 17 | 20 | 26 | 12 | M6 x 18 | 15 | M8 | 806 | 50342 | 131 | 0.3 |
| B401035 | 35 | 60 | 17 | 20 | 26 | 12 | M6 x 18 | 15 | M8 | 881 | 50342 | 131 | 0.3 |
| B401038 | 38 | 65 | 17 | 20 | 26 | 14 | M6 x 18 | 15 | M8 | 1116 | 58732 | 141 | 0.3 |
| B401040 | 40 | 65 | 17 | 20 | 26 | 14 | M6 x 18 | 15 | M8 | 1175 | 58732 | 141 | 0.3 |
| B401042 | 42 | 75 | 20 | 24 | 32 | 12 | M8 x 22 | 35 | M10 | 1892 | 90071 | 159 | 0.6 |
| B401045 | 45 | 75 | 20 | 24 | 32 | 12 | M8 x 22 | 35 | M10 | 2027 | 90071 | 159 | 0.5 |
| T401048 | 48 | 80 | 20 | 24 | 32 | 12 | M8 x 22 | 35 | M10 | 2162 | 90071 | 149 | 0.6 |
| B401050 | 50 | 80 | 20 | 24 | 32 | 12 | M8 x 22 | 35 | M10 | 2252 | 90071 | 149 | 0.6 |
| B401055 | 55 | 85 | 20 | 24 | 32 | 14 | M8 x 22 | 35 | M10 | 2889 | 105083 | 164 | 0.6 |
| B401060 | 60 | 90 | 20 | 24 | 32 | 14 | M8 x 22 | 35 | M10 | 3152 | 105083 | 155 | 0.7 |
| B401065 | 65 | 95 | 20 | 24 | 32 | 16 | M8 x 22 | 35 | M10 | 3903 | 120095 | 168 | 0.7 |
| B401070 | 70 | 110 | 24 | 28 | 38 | 14 | M10 x 25 | 69 | M12 | 5880 | 167988 | 169 | 1.2 |
| B401075 | 75 | 115 | 24 | 28 | 38 | 14 | M10 x 25 | 69 | M12 | 6300 | 167988 | 161 | 1.3 |
| B401080 | 80 | 120 | 24 | 28 | 38 | 14 | M10 x 25 | 69 | M12 | 6720 | 167988 | 155 | 1.4 |
| T401085 | 85 | 125 | 24 | 28 | 38 | 16 | M10 x 25 | 69 | M12 | 8158 | 191986 | 170 | 1.4 |
| B401090 | 90 | 130 | 24 | 28 | 38 | 16 | M10 x 25 | 69 | M12 | 8639 | 191986 | 163 | 1.5 |
| B401095 | 95 | 135 | 24 | 28 | 38 | 18 | M10 x 25 | 69 | M12 | 10259 | 215984 | 177 | 1.6 |
| B401100 | 100 | 145 | 26 | 33 | 45 | 14 | M12 x 30 | 123 | M14 | 12800 | 255998 | 180 | 2 |
| B401110 | 110 | 155 | 26 | 33 | 45 | 14 | M12 x 30 | 123 | M14 | 14081 | 255998 | 169 | 2 |
| B401120 | 120 | 165 | 26 | 33 | 45 | 16 | M12 x 30 | 123 | M14 | 17553 | 292569 | 181 | 3 |
| B401130 | 130 | 180 | 34 | 38 | 50 | 20 | M12 x 35 | 123 | M14 | 23771 | 365712 | 159 | 4 |
| B401140 | 140 | 190 | 34 | 38 | 50 | 22 | M12 x 35 | 123 | M14 | 28161 | 402283 | 165 | 4 |
| T401150 | 150 | 200 | 34 | 38 | 50 | 24 | M12 x 35 | 123 | M14 | 32917 | 438854 | 171 | 4 |
| B401160 | 160 | 210 | 34 | 38 | 50 | 26 | M12 x 35 | 123 | M14 | 38033 | 475425 | 177 | 4 |
| B401170 | 170 | 225 | 38 | 44 | 58 | 22 | M14 x 40 | 187 | M16 | 44752 | 526487 | 163 | 6 |
| B401180 | 180 | 235 | 38 | 44 | 58 | 24 | M14 x 40 | 187 | M16 | 51694 | 574350 | 171 | 6 |
| B401190 | 190 | 250 | 46 | 52 | 66 | 28 | M14 x 45 | 187 | M16 | 63654 | 670075 | 155 | 8 |
| B401200 | 200 | 260 | 46 | 52 | 66 | 30 | M14 x 45 | 187 | M16 | 71794 | 717937 | 159 | 9 |
| B401220 | 220 | 285 | 50 | 56 | 72 | 26 | M16 x 50 | 290 | M20 | 93540 | 850401 | 158 | 11 |
| B401240 | 240 | 305 | 50 | 56 | 72 | 30 | M16 x 50 | 290 | M20 | 117750 | 981232 | 171 | 12 |
| B401260 | 260 | 325 | 50 | 56 | 72 | 34 | M16 x 50 | 290 | M20 | 144565 | 1112063 | 182 | 13 |
| T401280 | 280 | 355 | 60 | 66 | 84 | 32 | M18 x 60 | 397 | M22 | 178059 | 1271808 | 158 | 19 |
| T401300 | 300 | 375 | 60 | 66 | 84 | 36 | M18 x 60 | 397 | M22 | 214617 | 1430784 | 169 | 21 |
| T401320 | 320 | 405 | 72 | 78 | 98 | 36 | M20 x 70 | 569 | M24 | 295337 | 1845919 | 168 | 29 |
| T401340 | 340 | 425 | 72 | 78 | 98 | 36 | M20 x 70 | 569 | M24 | 313810 | 1845919 | 160 | 31 |
| T401360 | 360 | 455 | 84 | 90 | 112 | 36 | M22 x 80 | 766 | M27 | 410431 | 2280208 | 158 | 43 |
| T401380 | 380 | 475 | 84 | 90 | 112 | 36 | M22 x 80 | 766 | M27 | 433250 | 2280208 | 152 | 45 |
| T401400 | 400 | 495 | 84 | 90 | 112 | 36 | M22 x 80 | 766 | M27 | 456041 | 2280208 | 145 | 47 |
| T401420 | 420 | 515 | 84 | 90 | 112 | 40 | M22 x 80 | 766 | M27 | 532035 | 2533564 | 155 | 49 |
| T401440 | 440 | 545 | 96 | 102 | 126 | 40 | M24 x 90 | 983 | M30 | 651795 | 2962675 | 150 | 65 |
| T401460 | 460 | 565 | 96 | 102 | 126 | 40 | M24 x 90 | 983 | M30 | 681406 | 2962675 | 145 | 67 |
| T401480 | 480 | 585 | 96 | 102 | 126 | 42 | M24 x 90 | 983 | M30 | 746608 | 3110809 | 147 | 71 |
| T401500 | 500 | 605 | 96 | 102 | 126 | 44 | M24 x 90 | 983 | M30 | 814734 | 3258942 | 149 | 72 |

B400 – Pilot Bushings

B-LOC pilot bushings: for series B400 Keyless Bushings to provide pre-centering in applications with either straight through hub bores or narrow hubs. Pilot bushings are supplied in sets consisting of three (3) bushings and three (3) longer screws (replacing plated locking screws). For more information refer to www.fennerdrives.com or contact Applications Engineering at AE@fennerdrives.com.

Recommended pre-centering length in installations without pilot bushings. Provide a minimum .001" clearance (hub concentricity depends on fit clearance).



Power Transmission - B-LOC®


B-LOC® B112 Inch



Locking screws transfer to integrated push-off holes for disassembly.

Metric socket head locking screws ISO 4762 grade 12.9 (See M_a for install torque).

Screw head height = screw diameter (mm)



TOLERANCE (T_L)

Bore diameter machined to $D - 0/+T_L$
 $T_L = .002"$ for bores up to 4.724"
 $.003"$ for bores up to 12.008"
 $.004"$ for bores up to 25.000"
 $.005"$ for bores over 25.000"

$d =$ shaft diameter machined to $d + 0/-T_L$.

B112 – Heavy Duty – Inch

| Part Number | d (inch) | D (inch) | L (inch) | L ₁ (inch) | Locking Screws | | M _a Install Torque (ft lb) | M _t Maximum Transmitted Torque (ft lb) | Th Thrust (lbs) | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|----------|-----------------------|----------------|-----------|--|--|--------------------|--------------------------------------|----------------------|
| | | | | | Qty | Size | | | | | |
| B122100 | 1 | 2.165 | 1.260 | 1.575 | 6 | M6 x 35 | 12 | 600 | 14390 | 18656 | 1.0 |
| T122102 | 1 1/8 | 2.165 | 1.260 | 1.575 | 6 | M6 x 35 | 12 | 675 | 14390 | 18656 | 1.0 |
| B122103 | 1 3/16 | 2.165 | 1.260 | 1.575 | 6 | M6 x 35 | 12 | 712 | 14390 | 18656 | 0.9 |
| B122104 | 1 1/4 | 2.362 | 1.732 | 2.126 | 7 | M6 x 45 | 12 | 874 | 16788 | 14083 | 1.5 |
| B122106 | 1 3/8 | 2.362 | 1.732 | 2.126 | 7 | M6 x 45 | 12 | 962 | 16788 | 14083 | 1.4 |
| B122107 | 1 7/16 | 2.362 | 1.732 | 2.126 | 7 | M6 x 45 | 12 | 1006 | 16788 | 14083 | 1.3 |
| B122108 | 1 1/2 | 2.953 | 1.732 | 2.126 | 7 | M8 x 50 | 30 | 2011 | 32182 | 21598 | 2.4 |
| B122110 | 1 5/8 | 2.953 | 1.732 | 2.126 | 7 | M8 x 50 | 30 | 2179 | 32182 | 21598 | 2.3 |
| T122111 | 1 11/16 | 2.953 | 1.732 | 2.126 | 7 | M8 x 50 | 30 | 2263 | 32182 | 21598 | 2.3 |
| B122112 | 1 3/4 | 2.953 | 1.732 | 2.126 | 7 | M8 x 50 | 30 | 2347 | 32182 | 21598 | 2.1 |
| B122114 | 1 7/8 | 3.150 | 2.205 | 2.598 | 8 | M8 x 55 | 30 | 2873 | 36779 | 17881 | 2.9 |
| B122115 | 1 15/16 | 3.150 | 2.205 | 2.598 | 8 | M8 x 55 | 30 | 2969 | 36779 | 17881 | 2.8 |
| B122200 | 2 | 3.150 | 2.205 | 2.598 | 8 | M8 x 55 | 30 | 3065 | 36779 | 17881 | 2.6 |
| B122202 | 2 1/8 | 3.346 | 2.205 | 2.598 | 9 | M8 x 55 | 30 | 3664 | 41377 | 18933 | 2.9 |
| B122203 | 2 3/16 | 3.346 | 2.205 | 2.598 | 9 | M8 x 55 | 30 | 3771 | 41377 | 18933 | 2.8 |
| B122204 | 2 1/4 | 3.543 | 2.205 | 2.598 | 10 | M8 x 55 | 30 | 4310 | 45974 | 19868 | 3.3 |
| B122206 | 2 3/8 | 3.543 | 2.205 | 2.598 | 10 | M8 x 55 | 30 | 4550 | 45974 | 19868 | 3.1 |
| B122207 | 2 7/16 | 3.740 | 2.205 | 2.598 | 10 | M8 x 55 | 30 | 4669 | 45974 | 18822 | 3.6 |
| B122208 | 2 1/2 | 3.740 | 2.205 | 2.598 | 10 | M8 x 55 | 30 | 4789 | 45974 | 18822 | 3.4 |
| B122209 | 2 9/16 | 3.740 | 2.205 | 2.598 | 10 | M8 x 55 | 30 | 4909 | 45974 | 18822 | 3.3 |
| B122210 | 2 5/8 | 4.331 | 2.756 | 3.150 | 10 | M10 x 60 | 60 | 8155 | 74561 | 20714 | 7 |
| T122211 | 2 11/16 | 4.331 | 2.756 | 3.150 | 10 | M10 x 60 | 60 | 8349 | 74561 | 20714 | 7 |
| B122212 | 2 3/4 | 4.331 | 2.756 | 3.150 | 10 | M10 x 60 | 60 | 8543 | 74561 | 20714 | 6 |
| B122214 | 2 7/8 | 4.331 | 2.756 | 3.150 | 10 | M10 x 60 | 60 | 8932 | 74561 | 20714 | 6 |
| B122215 | 2 15/16 | 4.724 | 2.756 | 3.150 | 11 | M10 x 60 | 60 | 10039 | 82017 | 20887 | 8 |
| B122300 | 3 | 4.724 | 2.756 | 3.150 | 11 | M10 x 60 | 60 | 10252 | 82017 | 20887 | 7 |
| T122302 | 3 1/8 | 4.724 | 2.756 | 3.150 | 11 | M10 x 60 | 60 | 10679 | 82017 | 20887 | 7 |
| B122304 | 3 1/4 | 4.724 | 2.756 | 3.150 | 11 | M10 x 60 | 60 | 11107 | 82017 | 20887 | 7 |
| B122306 | 3 3/8 | 5.118 | 2.756 | 3.150 | 12 | M10 x 60 | 60 | 12582 | 89474 | 21033 | 8 |
| B122307 | 3 7/16 | 5.118 | 2.756 | 3.150 | 12 | M10 x 60 | 60 | 12815 | 89474 | 21033 | 8 |
| B122308 | 3 1/2 | 5.118 | 2.756 | 3.150 | 12 | M10 x 60 | 60 | 13048 | 89474 | 21033 | 8 |
| T122310 | 3 5/8 | 5.118 | 2.756 | 3.150 | 12 | M10 x 60 | 60 | 13514 | 89474 | 21033 | 7 |
| B122312 | 3 3/4 | 5.709 | 3.543 | 4.016 | 11 | M12 x 80 | 105 | 19172 | 122699 | 20688 | 13 |
| B122314 | 3 7/8 | 5.709 | 3.543 | 4.016 | 11 | M12 x 80 | 105 | 19811 | 122699 | 20688 | 12 |
| T122315 | 3 15/16 | 5.709 | 3.543 | 4.016 | 11 | M12 x 80 | 105 | 20130 | 122699 | 20688 | 13 |
| B122400 | 4 | 5.709 | 3.543 | 4.016 | 11 | M12 x 80 | 105 | 20450 | 122699 | 20688 | 12 |
| T122404 | 4 1/4 | 6.102 | 3.543 | 4.016 | 12 | M12 x 80 | 105 | 23703 | 133853 | 21112 | 14 |
| T122406 | 4 3/8 | 6.102 | 3.543 | 4.016 | 12 | M12 x 80 | 105 | 24400 | 133853 | 21112 | 13 |
| B122407 | 4 7/16 | 6.496 | 3.543 | 4.016 | 14 | M12 x 80 | 105 | 28874 | 156162 | 23138 | 16 |
| B122408 | 4 1/2 | 6.496 | 3.543 | 4.016 | 14 | M12 x 80 | 105 | 29280 | 156162 | 23138 | 16 |
| T122412 | 4 3/4 | 6.496 | 3.543 | 4.016 | 14 | M12 x 80 | 105 | 30907 | 156162 | 23138 | 14 |
| B122415 | 4 15/16 | 7.087 | 4.094 | 4.567 | 12 | M14 x 90 | 166 | 37477 | 182167 | 20618 | 21 |
| B122500 | 5 | 7.087 | 4.094 | 4.567 | 12 | M14 x 90 | 166 | 37952 | 182167 | 20618 | 21 |
| B122504 | 5 1/4 | 7.480 | 4.094 | 4.567 | 14 | M14 x 90 | 166 | 46491 | 212528 | 22789 | 24 |
| B122507 | 5 7/16 | 7.480 | 4.094 | 4.567 | 14 | M14 x 90 | 166 | 48151 | 212528 | 22789 | 22 |
| T122508 | 5 1/2 | 7.480 | 4.094 | 4.567 | 14 | M14 x 90 | 166 | 48704 | 212528 | 22789 | 21 |
| T122512 | 5 3/4 | 7.874 | 4.094 | 4.567 | 15 | M14 x 90 | 166 | 54555 | 227709 | 23196 | 24 |
| B122515 | 5 15/16 | 7.874 | 4.094 | 4.567 | 15 | M14 x 90 | 166 | 56334 | 227709 | 23196 | 22 |
| B122600 | 6 | 8.268 | 4.094 | 4.567 | 16 | M14 x 90 | 166 | 60722 | 242890 | 23564 | 26 |
| T122607 | 6 7/16 | 8.858 | 5.276 | 5.866 | 14 | M16 x 110 | 257 | 77782 | 289982 | 20051 | 40 |
| T122608 | 6 1/2 | 8.858 | 5.276 | 5.866 | 14 | M16 x 110 | 257 | 78537 | 289982 | 20051 | 39 |
| B122615 | 6 15/16 | 9.252 | 5.276 | 5.866 | 15 | M16 x 110 | 257 | 89810 | 310695 | 20569 | 40 |
| B122700 | 7 | 9.252 | 5.276 | 5.866 | 15 | M16 x 110 | 257 | 90619 | 310695 | 20569 | 38 |
| T122704 | 7 1/4 | 9.843 | 5.276 | 5.866 | 16 | M16 x 110 | 257 | 100113 | 331408 | 20624 | 47 |
| T122707 | 7 7/16 | 9.843 | 5.276 | 5.866 | 16 | M16 x 110 | 257 | 102702 | 331408 | 20624 | 44 |
| T122708 | 7 1/2 | 9.843 | 5.276 | 5.866 | 16 | M16 x 110 | 257 | 103565 | 331408 | 20624 | 43 |
| T122712 | 7 3/4 | 10.236 | 5.276 | 5.866 | 16 | M16 x 110 | 257 | 107017 | 331408 | 19830 | 48 |
| T122715 | 7 15/16 | 10.236 | 5.276 | 5.866 | 16 | M16 x 110 | 257 | 109606 | 331408 | 19830 | 45 |
| T122800 | 8 | 10.236 | 5.276 | 5.866 | 16 | M16 x 110 | 257 | 110469 | 331408 | 19830 | 44 |

B-LOC® B112 Metric

TOLERANCE (T_L)

Bore diameter machined to D -0/+T_L
 T_L = .05mm for bores up to 120mm
 .08mm for bores up to 305mm
 .10mm for bores up to 635mm
 .13mm for bores over 635mm

d = shaft diameter machined to d +0/-T_L.

B112 – Heavy Duty – Metric

| Part Number | d (mm) | D (mm) | L (mm) | L ₁ (mm) | Locking Screws | | M _a | M _t | Th | P _h | Shipping Weight (kg) |
|-------------|--------|--------|--------|---------------------|----------------|-----------|---------------------|---------------------|------------|-----------------------------------|----------------------|
| | | | | | Qty | Size | Install Torque (Nm) | Maximum Transmitted | | Hub Pressure (N/mm ²) | |
| | | | | | | | | Torque (Nm) | Thrust (N) | | |
| T121024 | 24 | 55 | 32 | 40 | 6 | M6 x 35 | 16 | 755 | 62949 | 126 | 0.4 |
| B121025 | 25 | 55 | 32 | 40 | 6 | M6 x 35 | 16 | 787 | 62949 | 126 | 0.4 |
| T121028 | 28 | 55 | 32 | 40 | 6 | M6 x 35 | 16 | 881 | 62949 | 126 | 0.4 |
| B121030 | 30 | 55 | 32 | 40 | 6 | M6 x 35 | 16 | 944 | 62949 | 126 | 0.4 |
| T121032 | 32 | 60 | 44 | 54 | 7 | M6 x 45 | 16 | 1175 | 73440 | 95 | 0.6 |
| B121035 | 35 | 60 | 44 | 54 | 7 | M6 x 45 | 16 | 1285 | 73440 | 95 | 0.6 |
| T121038 | 38 | 75 | 44 | 54 | 7 | M8 x 50 | 41 | 2742 | 144304 | 150 | 1.0 |
| B121040 | 40 | 75 | 44 | 54 | 7 | M8 x 50 | 41 | 2886 | 144304 | 150 | 1.0 |
| T121042 | 42 | 75 | 44 | 54 | 7 | M8 x 50 | 41 | 3030 | 144304 | 150 | 1.0 |
| B121045 | 45 | 75 | 44 | 54 | 7 | M8 x 50 | 41 | 3247 | 144304 | 150 | 0.9 |
| T121048 | 48 | 80 | 56 | 66 | 8 | M8 x 55 | 41 | 3958 | 164918 | 124 | 1.3 |
| B121050 | 50 | 80 | 56 | 66 | 8 | M8 x 55 | 41 | 4123 | 164918 | 124 | 1.2 |
| B121055 | 55 | 85 | 56 | 66 | 9 | M8 x 55 | 41 | 5102 | 185533 | 132 | 1.3 |
| B121060 | 60 | 90 | 56 | 66 | 10 | M8 x 55 | 41 | 6184 | 206148 | 138 | 1.4 |
| B121065 | 65 | 95 | 56 | 66 | 10 | M8 x 55 | 41 | 6700 | 206148 | 131 | 1.5 |
| B121070 | 70 | 110 | 70 | 80 | 10 | M10 x 60 | 81 | 11559 | 330251 | 142 | 3 |
| T121075 | 75 | 115 | 70 | 80 | 10 | M10 x 60 | 81 | 12384 | 330251 | 136 | 3 |
| B121080 | 80 | 120 | 70 | 80 | 11 | M10 x 60 | 81 | 14531 | 363276 | 143 | 3 |
| T121085 | 85 | 125 | 70 | 80 | 11 | M10 x 60 | 81 | 15439 | 363276 | 138 | 3 |
| B121090 | 90 | 130 | 70 | 80 | 12 | M10 x 60 | 81 | 17834 | 396302 | 144 | 4 |
| T121095 | 95 | 135 | 70 | 80 | 12 | M10 x 60 | 81 | 18824 | 396302 | 139 | 4 |
| B121100 | 100 | 145 | 90 | 102 | 11 | M12 x 80 | 142 | 27222 | 544433 | 142 | 6 |
| B121110 | 110 | 155 | 90 | 102 | 12 | M12 x 80 | 142 | 32666 | 593927 | 145 | 6 |
| B121120 | 120 | 165 | 90 | 102 | 14 | M12 x 80 | 142 | 41575 | 692914 | 159 | 7 |
| B121130 | 130 | 180 | 104 | 116 | 12 | M14 x 90 | 225 | 52658 | 810116 | 142 | 9 |
| B121140 | 140 | 190 | 104 | 116 | 14 | M14 x 90 | 225 | 66159 | 945135 | 157 | 10 |
| B121150 | 150 | 200 | 104 | 116 | 15 | M14 x 90 | 225 | 75948 | 1012645 | 160 | 10 |
| B121160 | 160 | 210 | 104 | 116 | 16 | M14 x 90 | 225 | 86412 | 1080154 | 162 | 11 |
| T121170 | 170 | 225 | 134 | 149 | 14 | M16 x 110 | 348 | 109506 | 1288307 | 138 | 16 |
| T121180 | 180 | 235 | 134 | 149 | 15 | M16 x 110 | 348 | 124230 | 1380329 | 142 | 17 |
| T121190 | 190 | 250 | 134 | 149 | 16 | M16 x 110 | 348 | 139873 | 1472351 | 142 | 20 |
| B121200 | 200 | 260 | 134 | 149 | 16 | M16 x 110 | 348 | 147235 | 1472351 | 137 | 21 |
| B121220 | 220 | 285 | 134 | 150 | 18 | M16 x 110 | 348 | 182203 | 1656395 | 140 | 25 |
| B121240 | 240 | 305 | 134 | 150 | 20 | M16 x 110 | 348 | 220853 | 1840439 | 146 | 27 |
| T121260 | 260 | 325 | 134 | 150 | 21 | M16 x 110 | 348 | 251220 | 1932460 | 143 | 29 |
| T121280 | 280 | 355 | 165 | 177 | 18 | M20 x 130 | 678 | 360984 | 2578456 | 146 | 43 |
| T121300 | 300 | 375 | 165 | 177 | 20 | M20 x 130 | 678 | 429743 | 2864951 | 154 | 47 |
| T121320 | 320 | 405 | 165 | 177 | 21 | M20 x 130 | 678 | 481312 | 3008198 | 149 | 56 |
| T121340 | 340 | 425 | 165 | 177 | 22 | M20 x 130 | 678 | 535746 | 3151446 | 149 | 60 |
| T121360 | 360 | 455 | 190 | 203 | 21 | M22 x 150 | 915 | 670526 | 3725144 | 143 | 80 |
| T121380 | 380 | 475 | 190 | 203 | 22 | M22 x 150 | 915 | 741481 | 3902532 | 143 | 85 |
| T121400 | 400 | 495 | 190 | 203 | 24 | M22 x 150 | 915 | 851462 | 4257308 | 150 | 88 |
| T121420 | 420 | 515 | 190 | 203 | 24 | M22 x 150 | 915 | 894035 | 4257308 | 144 | 92 |
| T121440 | 440 | 535 | 190 | 203 | 24 | M22 x 150 | 915 | 936608 | 4257308 | 139 | 96 |
| T121460 | 460 | 555 | 190 | 203 | 24 | M22 x 150 | 915 | 979181 | 4257308 | 134 | 101 |
| T121480 | 480 | 575 | 190 | 203 | 28 | M22 x 150 | 915 | 1192046 | 4966859 | 151 | 103 |
| T121500 | 500 | 595 | 190 | 203 | 28 | M22 x 150 | 915 | 1241715 | 4966859 | 146 | 108 |
| T121520 | 520 | 615 | 190 | 203 | 30 | M22 x 150 | 915 | 1383625 | 5321634 | 151 | 111 |
| T121540 | 540 | 635 | 190 | 203 | 30 | M22 x 150 | 915 | 1436841 | 5321634 | 146 | 114 |
| T121560 | 560 | 655 | 190 | 203 | 32 | M22 x 150 | 915 | 1589395 | 5676410 | 151 | 119 |
| T121580 | 580 | 675 | 190 | 203 | 32 | M22 x 150 | 915 | 1646159 | 5676410 | 147 | 123 |
| T121600 | 600 | 695 | 190 | 203 | 33 | M22 x 150 | 915 | 1756139 | 5853798 | 147 | 128 |


Power Transmission - B-LOC®

B-LOC® B115

Inch and Metric



Locking screws transfer to integrated push-off holes for disassembly.
Metric socket head locking screws ISO 4762 grade 12.9 (See M_a for install torque).
Screw head height = screw diameter (mm)



TOLERANCE (T_L)

Bore diameter machined to D -0/+T_L
T_L = .002" for bores up to 4.724"
.003" for bores up to 12.008"
.004" for bores up to 25.000"
.005" for bores over 25.000"

T_L = .05mm for bores up to 120mm
.08mm for bores up to 305mm
.10mm for bores up to 635mm
.13mm for bores over 635mm

d = shaft diameter machined to d +0/-T_L


B115 – Medium Duty – Inch

| Part Number | d (inch) | D (inch) | L (inch) | L ₁ (inch) | Locking Screws | | M _a Install Torque (ft lb) | M _t Maximum Transmitted Torque (ft lb) | T _h Thrust (lbs) | P _h Hub Pressure (psi) | Shipping Weight (lb) |
|-------------|----------|----------|----------|-----------------------|----------------|----------|--|--|--------------------------------|--------------------------------------|----------------------|
| | | | | | Qty | Size | | | | | |
| B152212 | 2 3/4 | 4.331 | 1.969 | 2.441 | 8 | M10 x 50 | 60 | 5261 | 45913 | 17858 | 5 |
| B152215 | 2 15/16 | 4.528 | 1.969 | 2.441 | 8 | M10 x 50 | 60 | 5620 | 45913 | 17079 | 5 |
| T152307 | 3 7/16 | 5.118 | 1.969 | 2.441 | 11 | M10 x 50 | 60 | 9042 | 63131 | 20777 | 7 |
| B152308 | 3 1/2 | 5.118 | 1.969 | 2.441 | 11 | M10 x 50 | 60 | 9207 | 63131 | 20777 | 6 |
| B152315 | 3 15/16 | 5.709 | 2.362 | 2.835 | 10 | M12 x 60 | 105 | 14086 | 85858 | 21111 | 9 |
| B152407 | 4 7/16 | 6.496 | 2.362 | 2.835 | 11 | M12 x 60 | 105 | 17462 | 94444 | 20408 | 12 |
| T152408 | 4 1/2 | 6.496 | 2.362 | 2.835 | 11 | M12 x 60 | 105 | 17708 | 94444 | 20408 | 11 |
| T152415 | 4 15/16 | 7.087 | 2.559 | 3.189 | 14 | M12 x 70 | 105 | 24729 | 120202 | 21162 | 15 |
| T152500 | 5 | 7.087 | 2.559 | 3.189 | 14 | M12 x 70 | 105 | 25042 | 120202 | 21162 | 15 |
| B152507 | 5 7/16 | 7.480 | 2.559 | 3.228 | 15 | M12 x 70 | 105 | 29178 | 128787 | 21482 | 15 |
| B152515 | 5 15/16 | 7.874 | 2.559 | 3.228 | 15 | M12 x 70 | 105 | 31861 | 128787 | 20407 | 16 |
| T152600 | 6 | 8.268 | 2.559 | 3.228 | 16 | M12 x 70 | 105 | 34343 | 137373 | 20731 | 19 |
| T152607 | 6 7/16 | 8.858 | 3.071 | 3.661 | 15 | M14 x 80 | 166 | 47013 | 175273 | 20830 | 25 |
| B152615 | 6 15/16 | 9.252 | 3.071 | 3.661 | 15 | M14 x 80 | 166 | 50665 | 175273 | 19944 | 25 |
| B152715 | 7 15/16 | 10.236 | 3.465 | 4.134 | 18 | M14 x 80 | 166 | 69561 | 210328 | 18216 | 31 |
| T152800 | 8 | 10.236 | 3.465 | 4.134 | 18 | M14 x 80 | 166 | 70109 | 210328 | 18216 | 32 |

B115 – Medium Duty – Metric

| Part Number | d (mm) | D (mm) | L (mm) | L ₁ (mm) | Locking Screws | | M _a Install Torque (Nm) | M _t Maximum Transmitted Torque (Nm) | T _h Thrust (N) | P _h Hub Pressure (N/mm ²) | Shipping Weight (kg) |
|-------------|--------|--------|--------|---------------------|----------------|-----------|---------------------------------------|---|------------------------------|---|----------------------|
| | | | | | Qty | Size | | | | | |
| B151070 | 70 | 110 | 50 | 62 | 8 | M10 x 50 | 81 | 7118 | 203362 | 123 | 2 |
| T151075 | 75 | 115 | 50 | 62 | 8 | M10 x 50 | 81 | 7626 | 203362 | 117 | 2 |
| T151080 | 80 | 120 | 50 | 62 | 10 | M10 x 50 | 81 | 10168 | 254202 | 140 | 3 |
| T151090 | 90 | 130 | 50 | 62 | 11 | M10 x 50 | 81 | 12583 | 279622 | 143 | 3 |
| T151095 | 95 | 135 | 50 | 62 | 11 | M10 x 50 | 81 | 13282 | 279622 | 137 | 4 |
| B151100 | 100 | 145 | 60 | 72 | 10 | M12 x 60 | 142 | 19048 | 380966 | 145 | 4 |
| T151110 | 110 | 155 | 60 | 72 | 10 | M12 x 60 | 142 | 20953 | 380966 | 136 | 4 |
| B151120 | 120 | 165 | 60 | 72 | 11 | M12 x 60 | 142 | 25144 | 419063 | 140 | 5 |
| T151130 | 130 | 180 | 65 | 81 | 14 | M12 x 70 | 142 | 34668 | 533353 | 146 | 6 |
| B151140 | 140 | 190 | 65 | 82 | 15 | M12 x 70 | 142 | 40001 | 571449 | 148 | 7 |
| B151150 | 150 | 200 | 65 | 82 | 15 | M12 x 70 | 142 | 42859 | 571449 | 140 | 7 |
| B151160 | 160 | 210 | 65 | 82 | 16 | M12 x 70 | 142 | 48764 | 609546 | 143 | 8 |
| B151170 | 170 | 225 | 78 | 93 | 15 | M14 x 80 | 225 | 66254 | 779456 | 144 | 11 |
| B151180 | 180 | 235 | 78 | 93 | 15 | M14 x 80 | 225 | 70151 | 779456 | 137 | 11 |
| B151190 | 190 | 250 | 88 | 105 | 16 | M14 x 80 | 225 | 78985 | 831420 | 116 | 14 |
| B151200 | 200 | 260 | 88 | 105 | 18 | M14 x 80 | 225 | 93535 | 935348 | 126 | 15 |
| B151220 | 220 | 285 | 96 | 111 | 15 | M16 x 90 | 348 | 116872 | 1062472 | 121 | 19 |
| B151240 | 240 | 305 | 96 | 111 | 20 | M16 x 90 | 348 | 169995 | 1416629 | 150 | 20 |
| T151260 | 260 | 325 | 96 | 111 | 21 | M16 x 90 | 348 | 193370 | 1487460 | 148 | 22 |
| T151280 | 280 | 355 | 96 | 111 | 15 | M20 x 90 | 678 | 231548 | 1653915 | 163 | 27 |
| T151300 | 300 | 375 | 96 | 111 | 15 | M20 x 90 | 678 | 248087 | 1653915 | 154 | 30 |
| T151320 | 320 | 405 | 124 | 136 | 20 | M20 x 110 | 678 | 352835 | 2205220 | 150 | 44 |
| T151340 | 340 | 425 | 124 | 136 | 20 | M20 x 110 | 678 | 374887 | 2205220 | 143 | 47 |
| T151360 | 360 | 455 | 140 | 160 | 20 | M22 x 130 | 915 | 491542 | 2730791 | 133 | 66 |
| T151380 | 380 | 475 | 140 | 160 | 20 | M22 x 130 | 915 | 518850 | 2730791 | 127 | 69 |
| T151400 | 400 | 495 | 140 | 160 | 22 | M22 x 130 | 915 | 600774 | 3003871 | 134 | 72 |
| T151420 | 420 | 515 | 140 | 160 | 24 | M22 x 130 | 915 | 688159 | 3276950 | 141 | 75 |
| T151440 | 440 | 535 | 140 | 160 | 24 | M22 x 130 | 915 | 720929 | 3276950 | 135 | 78 |
| T151460 | 460 | 555 | 140 | 160 | 24 | M22 x 130 | 915 | 753698 | 3276950 | 131 | 82 |
| T151480 | 480 | 575 | 140 | 160 | 25 | M22 x 130 | 915 | 819237 | 3413489 | 131 | 84 |
| T151500 | 500 | 595 | 140 | 160 | 25 | M22 x 130 | 915 | 853372 | 3413489 | 127 | 88 |
| T151520 | 520 | 615 | 140 | 160 | 28 | M22 x 130 | 915 | 994008 | 3823108 | 137 | 91 |
| T151540 | 540 | 635 | 140 | 160 | 28 | M22 x 130 | 915 | 1032239 | 3823108 | 133 | 94 |
| T151560 | 560 | 655 | 140 | 160 | 30 | M22 x 130 | 915 | 1146932 | 4096187 | 138 | 97 |
| T151580 | 580 | 675 | 140 | 160 | 30 | M22 x 130 | 915 | 1187894 | 4096187 | 134 | 100 |
| T151600 | 600 | 695 | 140 | 160 | 30 | M22 x 130 | 915 | 1228856 | 4096187 | 130 | 103 |

B-LOC® B113 Metric



B113 – Extra Heavy Duty – Metric

| Part Number | d (mm) | D (mm) | L (mm) | L ₁ (mm) | Locking Screws | | M _a | M _t | Th | P _h | Shipping Weight (kg) |
|-------------|--------|--------|--------|---------------------|----------------|-----------|---------------------|---------------------|------------|-----------------------------------|----------------------|
| | | | | | Qty | Size | Install Torque (Nm) | Maximum Transmitted | | Hub Pressure (N/mm ²) | |
| | | | | | | | | Torque (Nm) | Thrust (N) | | |
| T131180 | 180 | 285 | 205 | 229 | 14 | M22 x 180 | 915 | 223566 | 2483935 | 139 | 62 |
| T131200 | 200 | 305 | 205 | 229 | 16 | M22 x 180 | 915 | 283878 | 2838783 | 149 | 67 |
| T131220 | 220 | 325 | 205 | 229 | 16 | M22 x 180 | 915 | 312251 | 2838783 | 141 | 73 |
| T131240 | 240 | 355 | 208 | 238 | 16 | M24 x 180 | 1180 | 400322 | 3335957 | 147 | 88 |
| T131260 | 260 | 375 | 208 | 238 | 18 | M24 x 180 | 1180 | 487873 | 3752951 | 156 | 93 |
| T131280 | 280 | 405 | 208 | 238 | 20 | M24 x 180 | 1180 | 583812 | 4169946 | 163 | 110 |
| T131300 | 300 | 425 | 208 | 238 | 20 | M24 x 180 | 1180 | 625491 | 4169946 | 153 | 117 |
| T131320 | 320 | 455 | 250 | 280 | 18 | M27 x 220 | 1763 | 803261 | 5020549 | 149 | 161 |
| T131340 | 340 | 475 | 250 | 280 | 20 | M27 x 220 | 1763 | 948338 | 5578387 | 156 | 170 |
| T131360 | 360 | 495 | 250 | 280 | 22 | M27 x 220 | 1763 | 1104503 | 6136226 | 164 | 177 |
| T131380 | 380 | 515 | 250 | 280 | 22 | M27 x 220 | 1763 | 1165912 | 6136226 | 160 | 186 |
| T131400 | 400 | 535 | 250 | 280 | 22 | M27 x 220 | 1763 | 1227243 | 6136226 | 152 | 192 |
| T131420 | 420 | 555 | 250 | 280 | 24 | M27 x 220 | 1763 | 1405717 | 6694065 | 160 | 202 |
| T131440 | 440 | 575 | 250 | 280 | 24 | M27 x 220 | 1763 | 1472708 | 6694065 | 154 | 210 |
| T131460 | 460 | 595 | 250 | 280 | 24 | M27 x 220 | 1763 | 1539615 | 6694065 | 149 | 220 |
| T131480 | 480 | 615 | 250 | 280 | 28 | M27 x 220 | 1763 | 1874374 | 7809742 | 168 | 227 |
| T131500 | 500 | 635 | 250 | 280 | 28 | M27 x 220 | 1763 | 1952432 | 7809742 | 163 | 233 |
| T131520 | 520 | 655 | 250 | 280 | 28 | M27 x 220 | 1763 | 2030489 | 7809742 | 158 | 244 |
| T131540 | 540 | 675 | 250 | 280 | 30 | M27 x 220 | 1763 | 2259264 | 8367581 | 164 | 251 |
| T131560 | 560 | 695 | 250 | 280 | 30 | M27 x 220 | 1763 | 2342897 | 8367581 | 160 | 260 |

B-LOC® B117 Metric



Metric socket head locking screws
ISO 4762 grade 12.9
(See M_a for install torque).

Screw head height = screw diameter (mm)

TOLERANCE (T_L)


Bore diameter machined to $D - 0/-T_L$
 $T_L =$.05mm for bores up to 120mm
 .08mm for bores up to 305mm
 .10mm for bores over 305mm

$d =$ Shaft diameter machined to $d + 0/-T_L$


B117 – High-Bending – Metric

| Part Number | d (mm) | D (mm) | D ₁ (mm) | L (mm) | L ₁ (mm) | L ₂ (mm) | Locking Screws | | | | | | M _{t1} | M _{t2} | M _{ttot} | Th ₁ | Th ₂ | Th _{tot} | Ph ₁ | Ph ₂ | Shipping Weight (kg) | | | | | | | | |
|-------------|--------|--------|---------------------|--------|---------------------|---------------------|----------------|-----------|------------------------------------|--------|-----------|------------------------------------|-----------------|-----------------|-------------------|-----------------|-----------------|-------------------|-----------------|-----------------|----------------------|---------------------|-------------|-------------|---------------------|------------|------------|-----------------------------------|-----------------------------------|
| | | | | | | | SIZE 1 | | | SIZE 2 | | | | | | | | | | | | Maximum Transmitted | | | Maximum Transmitted | | | | |
| | | | | | | | Qty. | Size | M _a Install Torque (Nm) | Qty. | Size | M _a Install Torque (Nm) | | | | | | | | | | Torque (Nm) | Torque (Nm) | Torque (Nm) | Thrust (N) | Thrust (N) | Thrust (N) | Hub Pressure (N/mm ²) | Hub Pressure (N/mm ²) |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| B171180 | 180 | 250 | 256 | 40 | 122 | 92 | 8 | M20 x 70 | 678 | 8 | M16 x 110 | 348 | 51569 | 33128 | 84697 | 572990 | 368088 | 941078 | 152 | 98 | 21 | | | | | | | | |
| B171190 | 190 | 260 | 266 | 40 | 122 | 92 | 10 | M20 x 70 | 678 | 10 | M16 x 110 | 348 | 68043 | 43710 | 111753 | 716238 | 460110 | 1176347 | 176 | 113 | 22 | | | | | | | | |
| B171200 | 200 | 270 | 276 | 40 | 122 | 92 | 10 | M20 x 70 | 678 | 10 | M16 x 110 | 348 | 71624 | 46011 | 117635 | 716238 | 460110 | 1176347 | 176 | 113 | 23 | | | | | | | | |
| B171220 | 220 | 290 | 296 | 40 | 122 | 92 | 10 | M20 x 70 | 678 | 10 | M16 x 110 | 348 | 78786 | 50612 | 129398 | 716238 | 460110 | 1176347 | 164 | 105 | 25 | | | | | | | | |
| B171240 | 240 | 310 | 316 | 40 | 122 | 92 | 12 | M20 x 70 | 678 | 12 | M16 x 110 | 348 | 103138 | 66256 | 169394 | 859485 | 552132 | 1411617 | 184 | 118 | 28 | | | | | | | | |
| B171260 | 260 | 330 | 336 | 40 | 122 | 92 | 12 | M20 x 70 | 678 | 12 | M16 x 110 | 348 | 111733 | 71777 | 183510 | 859485 | 552132 | 1411617 | 173 | 111 | 29 | | | | | | | | |
| B171280 | 280 | 365 | 371 | 45 | 144 | 108 | 10 | M24 x 80 | 1180 | 10 | M20 x 130 | 678 | 145918 | 100273 | 246192 | 1042274 | 716238 | 1758512 | 168 | 116 | 45 | | | | | | | | |
| B171300 | 300 | 385 | 391 | 45 | 144 | 108 | 10 | M24 x 80 | 1180 | 10 | M20 x 130 | 678 | 156341 | 107436 | 263777 | 1042274 | 716238 | 1758512 | 160 | 110 | 48 | | | | | | | | |
| B171340 | 340 | 425 | 431 | 45 | 144 | 108 | 14 | M24 x 80 | 1180 | 14 | M20 x 130 | 678 | 248061 | 170465 | 418526 | 1459184 | 1002733 | 2461917 | 202 | 139 | 54 | | | | | | | | |
| B171380 | 380 | 465 | 471 | 45 | 144 | 108 | 16 | M24 x 80 | 1180 | 16 | M20 x 130 | 678 | 316851 | 217736 | 534588 | 1667639 | 1145980 | 2813619 | 211 | 145 | 58 | | | | | | | | |
| B171400 | 400 | 485 | 491 | 45 | 144 | 108 | 16 | M24 x 80 | 1180 | 16 | M20 x 130 | 678 | 333528 | 229196 | 562724 | 1667639 | 1145980 | 2813619 | 203 | 139 | 62 | | | | | | | | |
| B171420 | 420 | 505 | 511 | 45 | 144 | 108 | 16 | M24 x 80 | 1180 | 16 | M20 x 130 | 678 | 350204 | 240656 | 590860 | 1667639 | 1145980 | 2813619 | 195 | 134 | 65 | | | | | | | | |
| B171440 | 440 | 525 | 531 | 59 | 178 | 147 | 16 | M24 x 100 | 1180 | 16 | M20 x 150 | 678 | 366881 | 252116 | 618996 | 1667639 | 1145980 | 2813619 | 143 | 98 | 82 | | | | | | | | |
| B171460 | 460 | 545 | 551 | 59 | 178 | 147 | 16 | M24 x 100 | 1180 | 16 | M20 x 150 | 678 | 383557 | 263575 | 647132 | 1667639 | 1145980 | 2813619 | 138 | 95 | 85 | | | | | | | | |
| B171480 | 480 | 565 | 571 | 59 | 178 | 147 | 16 | M24 x 100 | 1180 | 16 | M20 x 150 | 678 | 400233 | 275035 | 675269 | 1667639 | 1145980 | 2813619 | 133 | 91 | 90 | | | | | | | | |
| B171500 | 500 | 585 | 591 | 59 | 178 | 147 | 18 | M24 x 100 | 1180 | 18 | M20 x 150 | 678 | 469023 | 322307 | 791330 | 1876094 | 1289228 | 3165322 | 144 | 99 | 93 | | | | | | | | |
| B171520 | 520 | 605 | 611 | 59 | 178 | 147 | 18 | M24 x 100 | 1180 | 18 | M20 x 150 | 678 | 487784 | 335199 | 822984 | 1876094 | 1289228 | 3165322 | 139 | 96 | 97 | | | | | | | | |
| B171540 | 540 | 625 | 631 | 59 | 178 | 147 | 18 | M24 x 100 | 1180 | 18 | M20 x 150 | 678 | 506545 | 348092 | 854637 | 1876094 | 1289228 | 3165322 | 135 | 93 | 100 | | | | | | | | |
| B171560 | 560 | 645 | 651 | 59 | 178 | 147 | 18 | M24 x 100 | 1180 | 18 | M20 x 150 | 678 | 525306 | 360984 | 886290 | 1876094 | 1289228 | 3165322 | 131 | 90 | 103 | | | | | | | | |
| B171580 | 580 | 665 | 671 | 59 | 178 | 147 | 20 | M24 x 100 | 1180 | 20 | M20 x 150 | 678 | 604519 | 415418 | 1019937 | 2084549 | 1432475 | 3517024 | 141 | 97 | 107 | | | | | | | | |
| B171600 | 600 | 685 | 691 | 59 | 178 | 147 | 20 | M24 x 100 | 1180 | 20 | M20 x 150 | 678 | 625365 | 429743 | 1055107 | 2084549 | 1432475 | 3517024 | 137 | 94 | 110 | | | | | | | | |


Additional sizes available upon request.



B117 Units, $d \leq 420\text{mm}$



B117 Units, $d \geq 440\text{mm}$



Principles of Operation

B-LOC® Compression Hubs differ from other keyless locking devices in how they engage the mounted component. Rather than creating a radial force on the mounted component, the outer tapered rings are drawn together to generate an axial clamping force. In this way, the mounted component is not subjected to tensile (hoop) stresses. This operating principle also allows narrow components to be mounted with excellent runout.

Surface Finish

Recommended surface finish for shafts to be used with B-LOC Compression Hubs is between 32 and 125 microinch (0.8 and 3.2 micrometer) RMS. A smoother finish — such as that found on components supplied TG&P (turned, ground and polished) — is NOT recommended and can result in a failure of the connection. Note that surface finishes below 32 microinch (0.8 micrometer) RMS can be roughened using longitudinal abrasion with a bastard file, emery paper or similar to achieve a surface finish within the recommended range. The recommended surface finish on the contact faces of the mounted component is between 32 and 250 microinch (0.8 – 6.4 micrometer).

Concentricity

Fenner Drives Keyless Locking Devices are precision machined to maximize concentricity and minimize runout. The final installed concentricity of mounted components depends on several variables, including the components themselves and the installation technique employed. In the case of B-LOC Compression Hubs, total runout can be minimized by machining the bore and contacting faces of the mounted component to tight tolerances.

Adhesives & Lubricants

B-LOC Keyless Locking Devices are supplied with an oil specific to the product line. The listed performance data requires the use of these lubricants to provide the necessary coefficient of friction to the sliding surfaces. Likewise, do not use anaerobic adhesives such as Loctite®, Permatex® or similar compounds with Fenner Drives Keyless Locking Devices. Doing so results in unknown contact pressures and capacities. Furthermore, disassembly may be compromised when such compounds are applied to the keyless bushing, the shaft and/or the hub bore. The approved lubricant for use with B-LOC Compression Hubs is CRC3-36.

Materials

B-LOC Keyless Locking Devices are made from carbon steels and heat treated alloy steels. For applications in corrosive environments, corrosion resistance can be improved through sealing with grease or silicone, the use of protective cover plates, application of industry standard plating materials (e.g., nickel, thin dense chrome, etc.) or by specifying the product in stainless steel or other corrosion resistant materials. Please consult with a Fenner Drives Applications Engineer for more details.

Torque

T = peak drive torque = nominal torque multiplied by a safety factor to account for stall or start-up conditions, mass accelerations, impact loads, etc. Nominal drive torque can be calculated as follows:

$$M_{t_{nom}} \text{ (ft lb)} = \frac{5252 \times \text{HP}}{\text{rpm}}$$


$$M_{t_{nom}} \text{ (Nm)} = \frac{9550 \times \text{kW}}{\text{rpm}}$$

Consult with a Fenner Drives Applications Engineer in cases where “T” is uncertain.


M_t = The rated torque capacity of one Fenner Drives Keyless Locking Device installed according to our instructions. Published torque capacities are calculated without using a safety factor and should be considered as the point where a connection could slip if a higher torque is applied. Therefore, always select a unit where $M_t \geq T$.

Made to Order


B-LOC Compression Hubs offer a unique design that can provide solutions for applications beyond the standard, single chain sprocket application. Because compression hubs function by clamping the mounted components in the axial direction, cost savings can be realized by stacking together lower cost individual components. The compression hub simultaneously clamps the assembly together and attaches the assembly to the shaft.



A double strand chain sprocket can be easily made by adding a spacer between two A-plate sprockets.




Applications that require spacing between thin end discs can be accommodated by extending the pilot surface through the end discs so that it engages a spacer and keeps the entire assembly aligned.



Split sprocket designs are simplified by utilizing an A-plate sprocket which is split in a way that provides positive engagement between the two halves.

B-LOC® Compression Hubs


B-LOC® BCH 20 Inch



Metric socket head locking screws ISO 4762 grade 12.9 (See M_A for install torque).

Locking screws transfer to integrated push-off holes for disassembly.

Screw head height = screw diameter (mm)



TOLERANCE (T_L)

Recommended bore diameter $d_1 +.001" / +.003"$

$T_L = .002"$ for shafts up to 3"

Shaft diameter machined to $d +0/-T_L$

Parallelism machined to $X \pm .005"$

BCH20 – Light Duty – Inch

| Base Part Number | d (inch) | D (inch) | H_1 (inch) | A (inch) | d_1 (inch) | Locking Screws | | Mounted Component Thickness (X) | | | | M_A | M_T | Th | P_S | Ship Weight (lb) |
|------------------|----------|----------|--------------|----------|--------------|----------------|------|---------------------------------|---------------------|---------------|---------------------|----------------|--------------|----------------------|-------|------------------|
| | | | | | | Qty | Size | Range 1 | | Range 2 | | | | | | |
| | | | | | | | | X (inch) | Screw Length 1 (mm) | X (inch) | Screw Length 2 (mm) | Torque (ft lb) | Thrust (lbs) | Shaft Pressure (ksi) | | |
| BCH202008 | 1/2 | 1.496 | 0.305 | 0.925 | 1.280 | 4 | M4 | 0.098 – 0.161 | 16 | 0.161 – 0.319 | 20 | 3.5 | 48 | 2320 | 24.7 | 0.2 |
| BCH202010 | 5/8 | 1.496 | 0.305 | 0.925 | 1.280 | 4 | M4 | 0.098 – 0.161 | 16 | 0.161 – 0.319 | 20 | 3.5 | 60 | 2320 | 19.7 | 0.2 |
| BCH202012 | 3/4 | 1.732 | 0.305 | 1.122 | 1.535 | 4 | M4 | 0.098 – 0.161 | 16 | 0.161 – 0.319 | 20 | 3.5 | 72 | 2320 | 16.5 | 0.4 |
| BCH202014 | 7/8 | 1.969 | 0.384 | 1.339 | 1.732 | 4 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 84 | 2320 | 11.3 | 0.4 |
| BCH202015 | 15/16 | 1.969 | 0.384 | 1.339 | 1.732 | 4 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 90 | 2320 | 10.6 | 0.4 |
| BCH202100 | 1 | 1.969 | 0.384 | 1.339 | 1.732 | 4 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 97 | 2320 | 9.9 | 0.4 |
| BCH202102 | 1 1/8 | 2.165 | 0.384 | 1.535 | 1.969 | 5 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 136 | 2990 | 11.3 | 0.7 |
| BCH202103 | 1 3/16 | 2.165 | 0.384 | 1.535 | 1.969 | 5 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 136 | 2990 | 10.7 | 0.7 |
| BCH202104 | 1 1/4 | 2.362 | 0.384 | 1.732 | 2.126 | 6 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 180 | 3570 | 12.2 | 0.7 |
| BCH202106 | 1 3/8 | 2.362 | 0.384 | 1.732 | 2.126 | 6 | M4 | 0.098 – 0.240 | 20 | 0.240 – 0.437 | 25 | 3.5 | 180 | 3570 | 11.2 | 0.7 |
| BCH202107 | 1 7/16 | 2.756 | 0.482 | 2.008 | 2.520 | 4 | M5 | 0.098 – 0.276 | 25 | 0.276 – 0.472 | 30 | 7 | 237 | 4020 | 10.0 | 1.1 |
| BCH202108 | 1 1/2 | 2.756 | 0.482 | 2.008 | 2.520 | 4 | M5 | 0.098 – 0.276 | 25 | 0.276 – 0.472 | 30 | 7 | 237 | 4020 | 9.6 | 1.1 |
| BCH202110 | 1 5/8 | 2.992 | 0.482 | 2.205 | 2.677 | 6 | M5 | 0.098 – 0.276 | 25 | 0.276 – 0.472 | 30 | 7 | 385 | 6050 | 13.2 | 1.3 |
| BCH202111 | 1 11/16 | 2.992 | 0.482 | 2.205 | 2.677 | 6 | M5 | 0.098 – 0.276 | 25 | 0.276 – 0.472 | 30 | 7 | 385 | 6050 | 12.8 | 1.3 |
| BCH202112 | 1 3/4 | 2.992 | 0.482 | 2.205 | 2.677 | 6 | M5 | 0.098 – 0.276 | 25 | 0.276 – 0.472 | 30 | 7 | 385 | 6050 | 12.3 | 1.3 |
| BCH202114 | 1 7/8 | 3.543 | 0.561 | 2.598 | 3.071 | 9 | M5 | 0.098 – 0.394 | 30 | 0.394 – 0.512 | 40 | 7 | 683 | 9060 | 14.8 | 2.2 |
| BCH202115 | 1 15/16 | 3.543 | 0.561 | 2.598 | 3.071 | 9 | M5 | 0.098 – 0.394 | 30 | 0.394 – 0.512 | 40 | 7 | 683 | 9060 | 14.4 | 2.2 |
| BCH202200 | 2 | 3.543 | 0.561 | 2.598 | 3.071 | 9 | M5 | 0.098 – 0.394 | 30 | 0.394 – 0.512 | 40 | 7 | 683 | 9060 | 13.8 | 2.2 |
| BCH202202 | 2 1/8 | 3.543 | 0.561 | 2.598 | 3.071 | 9 | M5 | 0.098 – 0.394 | 30 | 0.394 – 0.512 | 40 | 7 | 683 | 9060 | 13.1 | 2 |
| BCH202203 | 2 3/16 | 3.543 | 0.561 | 2.598 | 3.071 | 9 | M5 | 0.098 – 0.394 | 30 | 0.394 – 0.512 | 40 | 7 | 683 | 9060 | 12.6 | 2 |
| BCH202204 | 2 1/4 | 4.134 | 0.679 | 3.031 | 3.622 | 9 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1066 | 12190 | 13.6 | 3.5 |
| BCH202206 | 2 3/8 | 4.134 | 0.679 | 3.031 | 3.622 | 9 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1066 | 12190 | 12.9 | 3.3 |
| BCH202207 | 2 7/16 | 4.134 | 0.679 | 3.031 | 3.622 | 9 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1066 | 12190 | 12.6 | 3.3 |
| BCH202208 | 2 1/2 | 4.134 | 0.679 | 3.031 | 3.622 | 9 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1066 | 12190 | 12.3 | 3.3 |
| BCH202209 | 2 9/16 | 4.134 | 0.679 | 3.031 | 3.622 | 9 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1066 | 12190 | 12.0 | 3.1 |
| BCH202210 | 2 5/8 | 4.724 | 0.679 | 3.465 | 4.016 | 12 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1617 | 16250 | 15.5 | 4.6 |
| BCH202212 | 2 3/4 | 4.724 | 0.679 | 3.465 | 4.016 | 12 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1617 | 16250 | 14.9 | 4.4 |
| BCH202214 | 2 7/8 | 4.724 | 0.679 | 3.465 | 4.016 | 12 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1617 | 16250 | 14.2 | 4.2 |
| BCH202215 | 2 15/16 | 4.724 | 0.679 | 3.465 | 4.016 | 12 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1617 | 16250 | 13.9 | 4.2 |
| BCH202300 | 3 | 4.724 | 0.679 | 3.465 | 4.016 | 12 | M6 | 0.098 – 0.429 | 35 | 0.429 – 0.591 | 45 | 12 | 1617 | 16250 | 13.6 | 4 |

Part Number Ordering Guide

| Base Part Number | + | Screw Length (based on X) | = | Complete Part Number |
|--|---|---------------------------|---|----------------------|
| BCH202110 | | 025 | | BCH202110-025 |
| 3 digit whole number Always in mm 25 = 025 | | | | |

NOTES

- B-LOC Compression Hubs exert a maximum pressure on the face of the mounted component of 250 N/mm² (36 ksi).
- B-LOC pilot diameter d_1 machined to ISO tolerance h8.

TOLERANCE (T_L)Recommended bore diameter d₁ +.03mm / +.08mmT_L = .05mm for shafts up to 75mmShaft diameter machined to d +0/-T_L

Parallelism machined to X +/- 0.13mm

BCH20 – Light Duty – Metric

| Base Part Number | d (mm) | D (mm) | H ₁ (mm) | A (mm) | d ₁ (mm) | Locking Screws | | Mounted Component Thickness (X) | | | | M _a | M _t | Th | P _s | Ship Weight (kg) |
|------------------|--------|--------|---------------------|--------|---------------------|----------------|------|---------------------------------|---------------------|------------|---------------------|---------------------|---------------------|-------------|-------------------------------------|------------------|
| | | | | | | Qty | Size | Range 1 | | Range 2 | | Install Torque (Nm) | Maximum Transmitted | | Shaft Pressure (N/mm ²) | |
| | | | | | | | | X (mm) | Screw Length 1 (mm) | X (mm) | Screw Length 2 (mm) | | Torque (Nm) | Thrust (kN) | | |
| BCH201012 | 12 | 38 | 7.8 | 23.5 | 32.5 | 4 | M4 | 2.5 – 4.1 | 16 | 4.1 – 8.1 | 20 | 5 | 65 | 10.8 | 189 | 0.1 |
| BCH201014 | 14 | 38 | 7.8 | 23.5 | 32.5 | 4 | M4 | 2.5 – 4.1 | 16 | 4.1 – 8.1 | 20 | 5 | 76 | 10.8 | 136 | 0.1 |
| BCH201015 | 15 | 38 | 7.8 | 23.5 | 32.5 | 4 | M4 | 2.5 – 4.1 | 16 | 4.1 – 8.1 | 20 | 5 | 81 | 10.8 | 114 | 0.2 |
| BCH201018 | 18 | 44 | 7.8 | 28.5 | 39 | 4 | M4 | 2.5 – 4.1 | 16 | 4.1 – 8.1 | 20 | 5 | 97 | 10.8 | 78 | 0.2 |
| BCH201019 | 19 | 44 | 7.8 | 28.5 | 39 | 4 | M4 | 2.5 – 4.1 | 16 | 4.1 – 8.1 | 20 | 5 | 103 | 10.8 | 73 | 0.2 |
| BCH201020 | 20 | 44 | 7.8 | 28.5 | 39 | 4 | M4 | 2.5 – 4.1 | 16 | 4.1 – 8.1 | 20 | 5 | 108 | 10.8 | 68 | 0.2 |
| BCH201022 | 22 | 50 | 9.8 | 34 | 44 | 4 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 122 | 11.2 | 78 | 0.3 |
| BCH201024 | 24 | 50 | 9.8 | 34 | 44 | 4 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 134 | 11.2 | 74 | 0.3 |
| BCH201025 | 25 | 50 | 9.8 | 34 | 44 | 4 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 140 | 11.2 | 84 | 0.3 |
| BCH201028 | 28 | 55 | 9.8 | 39 | 50 | 5 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 195 | 13.9 | 77 | 0.3 |
| BCH201030 | 30 | 55 | 9.8 | 39 | 50 | 5 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 195 | 13.9 | 69 | 0.5 |
| BCH201032 | 32 | 60 | 9.8 | 44 | 54 | 6 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 257 | 16.7 | 66 | 0.5 |
| BCH201035 | 35 | 60 | 9.8 | 44 | 54 | 6 | M4 | 2.5 – 6.1 | 20 | 6.1 – 11.1 | 25 | 5 | 257 | 16.7 | 91 | 0.6 |
| BCH201038 | 38 | 70 | 12.3 | 51 | 64 | 4 | M5 | 2.5 – 7 | 25 | 7 – 12 | 30 | 10 | 321 | 17.9 | 88 | 0.6 |
| BCH201040 | 40 | 70 | 12.3 | 51 | 64 | 4 | M5 | 2.5 – 7 | 25 | 7 – 12 | 30 | 10 | 321 | 17.9 | 85 | 0.6 |
| BCH201042 | 42 | 76 | 12.3 | 56 | 68 | 6 | M5 | 2.5 – 7 | 25 | 7 – 12 | 30 | 10 | 522 | 26.9 | 102 | 1 |
| BCH201045 | 45 | 76 | 12.3 | 56 | 68 | 6 | M5 | 2.5 – 7 | 25 | 7 – 12 | 30 | 10 | 522 | 26.9 | 99 | 1 |
| BCH201048 | 48 | 90 | 14.3 | 66 | 78 | 9 | M5 | 2.5 – 10 | 30 | 10 – 13 | 40 | 10 | 926 | 40.3 | 95 | 1 |
| BCH201050 | 50 | 90 | 14.3 | 66 | 78 | 9 | M5 | 2.5 – 10 | 30 | 10 – 13 | 40 | 10 | 926 | 40.3 | 90 | 0.9 |
| BCH201055 | 55 | 90 | 14.3 | 66 | 78 | 9 | M5 | 2.5 – 10 | 30 | 10 – 13 | 40 | 10 | 926 | 40.3 | 87 | 0.9 |
| BCH201060 | 60 | 105 | 17.3 | 77 | 92 | 9 | M6 | 2.5 – 10.9 | 35 | 10.9 – 15 | 45 | 16 | 1445 | 54.2 | 94 | 1.6 |
| BCH201065 | 65 | 105 | 17.3 | 77 | 92 | 9 | M6 | 2.5 – 10.9 | 35 | 10.9 – 15 | 45 | 16 | 1445 | 54.2 | 89 | 1.5 |
| BCH201070 | 70 | 120 | 17.3 | 88 | 102 | 12 | M6 | 2.5 – 10.9 | 35 | 10.9 – 15 | 45 | 16 | 2192 | 72.3 | 87 | 1.5 |
| BCH201075 | 75 | 120 | 17.3 | 88 | 102 | 12 | M6 | 2.5 – 10.9 | 35 | 10.9 – 15 | 45 | 16 | 2192 | 72.3 | 85 | 1.5 |

Contact our Application Engineers:

- Larger and smaller bore sizes available upon request
- Larger mounted component thickness (outside of X Ranges 1 and 2) can be easily accommodated. Fully-threaded screws are required for mounted component thicknesses larger than X Range 2.
- Fenner Drives can engineer a custom B-LOC Compression Hub to meet your needs.
- Email: AE@fennerdrives.com

B-LOC® Compression Hubs


B-LOC® BCH 50 Inch



Metric socket head locking screws ISO 4762 grade 12.9 (See M_a for install torque).

Locking screws transfer to integrated push-off holes for disassembly.

Screw head height = screw diameter (mm)



TOLERANCE (T_L)

Recommended bore diameter $d_1 +.001" / +.003"$

$T_L = .002"$ for shafts up to 3"

Shaft diameter machined to $d +0/-T_L$

Parallelism machined to $X +/- .005"$

BCH50 – Heavy Duty – Inch

| Base Part Number | d (inch) | D (inch) | H ₁ (inch) | A (inch) | d ₁ (inch) | Locking Screws | | Mounted Component Thickness (X) | | | | M _a | M _t | Th | P _s | Ship Weight (lb) | | |
|------------------|----------|----------|-----------------------|----------|-----------------------|----------------|-----|---------------------------------|------|---------------|---------------------|----------------|----------------|-------|----------------|------------------|---------------------|---------------------|
| | | | | | | | | Range 1 | | Range 2 | | | | | | | Maximum Transmitted | |
| | | | | | | | | Qty | Size | X (inch) | Screw Length 1 (mm) | | | | | | X (inch) | Screw Length 2 (mm) |
| BCH502008 | 1/2 | 1.85 | 0.384 | 0.984 | 1.457 | 5 | M5 | 0.098 – 0.197 | 20 | 0.197 – 0.394 | 25 | 7 | 104 | 4970 | 42.5 | 0.7 | | |
| BCH502010 | 5/8 | 1.85 | 0.384 | 0.984 | 1.457 | 5 | M5 | 0.098 – 0.197 | 20 | 0.197 – 0.394 | 25 | 7 | 129 | 5510 | 33.9 | 0.4 | | |
| BCH502012 | 3/4 | 2.047 | 0.384 | 1.181 | 1.654 | 6 | M5 | 0.098 – 0.197 | 20 | 0.197 – 0.394 | 25 | 7 | 186 | 6610 | 33.9 | 0.7 | | |
| BCH502014 | 7/8 | 2.283 | 0.463 | 1.398 | 1.890 | 6 | M5 | 0.098 – 0.315 | 25 | 0.315 – 0.512 | 30 | 7 | 217 | 6610 | 24.2 | 0.9 | | |
| BCH502015 | 15/16 | 2.283 | 0.463 | 1.398 | 1.890 | 6 | M5 | 0.098 – 0.315 | 25 | 0.315 – 0.512 | 30 | 7 | 233 | 6610 | 22.6 | 0.9 | | |
| BCH502100 | 1 | 2.283 | 0.463 | 1.398 | 1.890 | 6 | M5 | 0.098 – 0.315 | 25 | 0.315 – 0.512 | 30 | 7 | 248 | 6610 | 21.2 | 0.9 | | |
| BCH502102 | 1 1/8 | 2.559 | 0.463 | 1.594 | 2.126 | 8 | M5 | 0.098 – 0.315 | 25 | 0.315 – 0.512 | 30 | 7 | 385 | 9130 | 26.0 | 1.1 | | |
| BCH502103 | 1 3/16 | 2.559 | 0.463 | 1.594 | 2.126 | 8 | M5 | 0.098 – 0.315 | 25 | 0.315 – 0.512 | 30 | 7 | 406 | 9130 | 24.7 | 1.1 | | |
| BCH502104 | 1 1/4 | 2.953 | 0.561 | 1.850 | 2.362 | 8 | M6 | 0.098 – 0.350 | 30 | 0.350 – 0.547 | 35 | 12 | 564 | 12030 | 26.5 | 1.8 | | |
| BCH502106 | 1 3/8 | 2.953 | 0.561 | 1.850 | 2.362 | 8 | M6 | 0.098 – 0.350 | 30 | 0.350 – 0.547 | 35 | 12 | 621 | 12030 | 24.1 | 1.8 | | |
| BCH502107 | 1 7/16 | 3.307 | 0.561 | 2.047 | 2.598 | 10 | M6 | 0.098 – 0.350 | 30 | 0.350 – 0.547 | 35 | 12 | 811 | 15040 | 28.7 | 2.2 | | |
| BCH502108 | 1 1/2 | 3.307 | 0.561 | 2.047 | 2.598 | 10 | M6 | 0.098 – 0.350 | 30 | 0.350 – 0.547 | 35 | 12 | 846 | 15040 | 27.6 | 2.2 | | |
| BCH502110 | 1 5/8 | 3.78 | 0.699 | 2.362 | 2.992 | 7 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1261 | 20710 | 28.0 | 3.5 | | |
| BCH502111 | 1 11/16 | 3.78 | 0.699 | 2.362 | 2.992 | 7 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1310 | 20710 | 27.0 | 3.5 | | |
| BCH502112 | 1 3/4 | 3.78 | 0.699 | 2.362 | 2.992 | 7 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1358 | 20710 | 26.0 | 3.5 | | |
| BCH502114 | 1 7/8 | 4.528 | 0.699 | 2.756 | 3.386 | 8 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1663 | 23650 | 27.7 | 5.3 | | |
| BCH502115 | 1 15/16 | 4.528 | 0.699 | 2.756 | 3.386 | 8 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1719 | 23650 | 26.8 | 5.1 | | |
| BCH502200 | 2 | 4.528 | 0.699 | 2.756 | 3.386 | 8 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1774 | 23650 | 26.0 | 5.1 | | |
| BCH502202 | 2 1/8 | 4.528 | 0.699 | 2.756 | 3.386 | 8 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1885 | 23650 | 24.5 | 4.9 | | |
| BCH502203 | 2 3/16 | 4.528 | 0.699 | 2.756 | 3.386 | 8 | M8 | 0.098 – 0.323 | 35 | 0.323 – 0.630 | 45 | 30 | 1940 | 23650 | 23.8 | 4.9 | | |
| BCH502204 | 2 1/4 | 5.433 | 0.797 | 3.268 | 4.016 | 8 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 3198 | 37900 | 32.5 | 8.6 | | |
| BCH502206 | 2 3/8 | 5.433 | 0.797 | 3.268 | 4.016 | 8 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 3375 | 37900 | 30.7 | 8.4 | | |
| BCH502207 | 2 7/16 | 5.433 | 0.797 | 3.268 | 4.016 | 8 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 3464 | 37900 | 29.9 | 8.4 | | |
| BCH502208 | 2 1/2 | 5.433 | 0.797 | 3.268 | 4.016 | 8 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 3553 | 37900 | 29.1 | 8.2 | | |
| BCH502209 | 2 9/16 | 5.433 | 0.797 | 3.268 | 4.016 | 8 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 3642 | 37900 | 28.4 | 8.2 | | |
| BCH502210 | 2 5/8 | 6.142 | 0.797 | 3.740 | 4.409 | 9 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 4197 | 42630 | 31.3 | 10.8 | | |
| BCH502212 | 2 3/4 | 6.142 | 0.797 | 3.740 | 4.409 | 9 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 4396 | 42630 | 29.9 | 10.6 | | |
| BCH502214 | 2 7/8 | 6.142 | 0.797 | 3.740 | 4.409 | 9 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 4596 | 42630 | 28.6 | 10.4 | | |
| BCH502215 | 2 15/16 | 6.142 | 0.797 | 3.740 | 4.409 | 9 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 4696 | 42630 | 28.0 | 10.1 | | |
| BCH502300 | 3 | 6.142 | 0.797 | 3.740 | 4.409 | 9 | M10 | 0.098 – 0.335 | 40 | 0.335 – 0.630 | 50 | 60 | 4796 | 42630 | 27.4 | 10.1 | | |

Part Number Ordering Guide

| | | | | |
|--|---|---------------------------|---|----------------------|
| Base Part Number | + | Screw Length (based on X) | = | Complete Part Number |
| BCH502110 | | 035 | | BCH502110-035 |
| 3 digit whole number Always in mm 35 = 035 | | | | |

NOTES

- B-LOC Compression Hubs exert a maximum pressure on the face of the mounted component of 250 N/mm² (36 ksi).
- B-LOC pilot diameter d_1 machined to ISO tolerance h8.

B-LOC® BCH 50 Metric

TOLERANCE (T_L)Recommended bore diameter d₁ +.03mm / +.08mmT_L = .05mm for shafts up to 75mmShaft diameter machined to d +0/-T_L

Parallelism machined to X +/- 0.13mm

BCH50 – Heavy Duty – Metric

| Base Part Number | d (mm) | D (mm) | H ₁ (mm) | A (mm) | d ₁ (mm) | Locking Screws | | Mounted Component Thickness (X) | | | | M _a | M _t | Th | P _s | Ship Weight (kg) |
|------------------|--------|--------|---------------------|--------|---------------------|----------------|------|---------------------------------|---------------------|------------|---------------------|---------------------|----------------|-------------|-------------------------------------|------------------|
| | | | | | | | | Range 1 | | Range 2 | | | | | | |
| | | | | | | Qty | Size | X (mm) | Screw Length 1 (mm) | X (mm) | Screw Length 2 (mm) | Install Torque (Nm) | Torque (Nm) | Thrust (kN) | Shaft Pressure (N/mm ²) | |
| BCH501012 | 12 | 47 | 9.8 | 25 | 37.0 | 5 | M5 | 2.5 – 5.0 | 20 | 5.0 – 10.0 | 25 | 10 | 132 | 22.1 | 310 | 0.3 |
| BCH501014 | 14 | 47 | 9.8 | 25 | 37.0 | 5 | M5 | 2.5 – 5.0 | 20 | 5.0 – 10.0 | 25 | 10 | 155 | 22.1 | 266 | 0.2 |
| BCH501015 | 15 | 47 | 9.8 | 25 | 37.0 | 5 | M5 | 2.5 – 5.0 | 20 | 5.0 – 10.0 | 25 | 10 | 166 | 22.1 | 248 | 0.2 |
| BCH501018 | 18 | 52 | 9.8 | 30 | 42.0 | 6 | M5 | 2.5 – 5.0 | 20 | 5.0 – 10.0 | 25 | 10 | 239 | 26.5 | 248 | 0.3 |
| BCH501019 | 19 | 52 | 9.8 | 30 | 42.0 | 6 | M5 | 2.5 – 5.0 | 20 | 5.0 – 10.0 | 25 | 10 | 252 | 26.5 | 235 | 0.3 |
| BCH501020 | 20 | 52 | 9.8 | 30 | 42.0 | 6 | M5 | 2.5 – 5.0 | 20 | 5.0 – 10.0 | 25 | 10 | 265 | 26.5 | 223 | 0.3 |
| BCH501022 | 22 | 58 | 11.8 | 35.5 | 48.0 | 6 | M5 | 2.5 – 8.0 | 25 | 8.0 – 13.0 | 30 | 10 | 302 | 27.4 | 175 | 0.4 |
| BCH501024 | 24 | 58 | 11.8 | 35.5 | 48.0 | 6 | M5 | 2.5 – 8.0 | 25 | 8.0 – 13.0 | 30 | 10 | 329 | 27.4 | 160 | 0.4 |
| BCH501025 | 25 | 58 | 11.8 | 35.5 | 48.0 | 6 | M5 | 2.5 – 8.0 | 25 | 8.0 – 13.0 | 30 | 10 | 342 | 27.4 | 154 | 0.4 |
| BCH501028 | 28 | 65 | 11.8 | 40.5 | 54.0 | 8 | M5 | 2.5 – 8.0 | 25 | 8.0 – 13.0 | 30 | 10 | 511 | 36.5 | 183 | 0.5 |
| BCH501030 | 30 | 65 | 11.8 | 40.5 | 54.0 | 8 | M5 | 2.5 – 8.0 | 25 | 8.0 – 13.0 | 30 | 10 | 548 | 36.5 | 171 | 0.5 |
| BCH501032 | 32 | 75 | 14.3 | 47 | 60.0 | 8 | M6 | 2.5 – 8.9 | 30 | 8.9 – 13.9 | 35 | 16 | 771 | 48.2 | 181 | 0.8 |
| BCH501035 | 35 | 75 | 14.3 | 47 | 60.0 | 8 | M6 | 2.5 – 8.9 | 30 | 8.9 – 13.9 | 35 | 16 | 843 | 48.2 | 166 | 0.8 |
| BCH501038 | 38 | 84 | 14.3 | 52 | 66.0 | 10 | M6 | 2.5 – 8.9 | 30 | 8.9 – 13.9 | 35 | 16 | 1145 | 60.2 | 191 | 1 |
| BCH501040 | 40 | 84 | 14.3 | 52 | 66.0 | 10 | M6 | 2.5 – 8.9 | 30 | 8.9 – 13.9 | 35 | 16 | 1205 | 60.2 | 181 | 0.9 |
| BCH501042 | 42 | 96 | 17.8 | 60 | 76.0 | 7 | M8 | 2.5 – 8.2 | 35 | 8.2 – 16.0 | 45 | 41 | 1740 | 82.9 | 190 | 1.6 |
| BCH501045 | 45 | 96 | 17.8 | 60 | 76.0 | 7 | M8 | 2.5 – 8.2 | 35 | 8.2 – 16.0 | 45 | 41 | 1864 | 82.9 | 177 | 1.6 |
| BCH501048 | 48 | 115 | 17.8 | 70 | 86.0 | 8 | M8 | 2.5 – 8.2 | 35 | 8.2 – 16.0 | 45 | 41 | 2273 | 94.7 | 190 | 2.4 |
| BCH501050 | 50 | 115 | 17.8 | 70 | 86.0 | 8 | M8 | 2.5 – 8.2 | 35 | 8.2 – 16.0 | 45 | 41 | 2367 | 94.7 | 182 | 2.3 |
| BCH501055 | 55 | 115 | 17.8 | 70 | 86.0 | 8 | M8 | 2.5 – 8.2 | 35 | 8.2 – 16.0 | 45 | 41 | 2604 | 94.7 | 166 | 2.2 |
| BCH501060 | 60 | 138 | 20.3 | 83 | 102.0 | 8 | M10 | 2.5 – 8.5 | 40 | 8.5 – 16.0 | 50 | 81 | 4551 | 152 | 213 | 3.8 |
| BCH501065 | 65 | 138 | 20.3 | 83 | 102.0 | 8 | M10 | 2.5 – 8.5 | 40 | 8.5 – 16.0 | 50 | 81 | 4930 | 152 | 197 | 3.7 |
| BCH501070 | 70 | 156 | 20.3 | 95 | 112.0 | 9 | M10 | 2.5 – 8.5 | 40 | 8.5 – 16.0 | 50 | 81 | 5973 | 171 | 205 | 4.8 |
| BCH501075 | 75 | 156 | 20.3 | 95 | 112.0 | 9 | M10 | 2.5 – 8.5 | 40 | 8.5 – 16.0 | 50 | 81 | 6400 | 171 | 192 | 4.6 |

Contact our Application Engineers:

- Larger and smaller bore sizes available upon request
- Larger mounted component thickness (outside of X Ranges 1 and 2) can be easily accommodated. Fully-threaded screws are required for mounted component thicknesses larger than X Range 2.
- Fenner Drives can engineer a custom B-LOC Compression Hub to meet your needs.
- Email: AE@fennerdrives.com

DESIGN FEATURES

External locking devices for keyless frictional shaft/hub connections on shafts from 5/8" to 40" diameter, B-LOC® Shrink Discs...


- Provide a high capacity interference fit with all the positive features of conventional interference fits, but without their assembly and disassembly problems.
- Offer extremely concentric and well-balanced connections, ideal for high-speed applications.
- Permit simple axial positioning and angular timing.
- Are available in standard, light, and heavy-duty series to suit any application.

WORKING PRINCIPLE

B-LOC Shrink Discs provide a high-ratio conversion of screw clamp loads into radial contact pressures when the tapered collars are pulled together by tightening of the integrated high-strength locking screws. These radial contact pressures in turn accomplish the following:

1. Contract the inner ring and hub to close the clearance between shaft and hub bore.
2. Generate a defined shaft/hub contact pressure for a high capacity mechanical interference fit.

This frictional bond transmits torque, bending and/or thrust loads directly from the hub to the shaft; the shrink disc itself does not carry any torque or thrust load.



TORQUE

M_t = rated torque capacity of one B-LOC Shrink Disc with all screws tightened to specified torque M_a as listed in specifications, based on a coefficient of friction $\mu = 0.15$ and specified tolerances and clearances. Torque capacities for Half Shrink Discs = $\frac{M_t}{2}$

- Torque capacities for connections using shaft diameters between the minimum and maximum sizes listed can be approximated through interpolation.
- Transmissible torque decreases if tolerances and/or clearances are larger than specified; or if hollow shafts with bores exceeding approximately 35% of shaft diameter are used.

THRUST

T_h = transmissible thrust, determined by using the following equation:

$$T_h = \frac{2 \times M_t}{d}$$

where: d = shaft diameter

M_t = rated torque capacity

TORQUE AND THRUST COMBINED

Simultaneous transmission of torque and thrust requires calculating a resultant torque:

$$M_{tres} = \sqrt{T^2 + \left(\frac{F \times d}{2}\right)^2}$$

where: T = peak drive torque

F = peak thrust load

d = shaft diameter


Select a unit where $M_t \geq M_{tres}$

BENDING MOMENTS

Shrink discs will generally transmit a continuous bending moment equal to 25% of rated torque capacity M_t .

RELEASABILITY

Since the tapers of a B-LOC Shrink Disc are self-releasing and stresses from radial contractions of the hub are well within elastic limits, loosening the locking screws results in hub expansion back to its original dimensions, thereby restoring fit clearance for simple disassembly. The SD40 is manufactured with self-releasing tapers, however, it is possible the outer ring may need disengaging from the inner ring. This can be easily done by loosening the bolts in sequence, transferring the appropriate number of bolts over to the threaded back-off holes in the face of the shrink disc and progressively tightening these bolts until the shrink disc becomes loose. The hub and shaft will return to their original fit clearances.



MATERIAL

Shrink disc inner rings are manufactured from high-carbon steel. Outer rings are made from forged and heat treated alloy steel.

LUBRICANTS

Shrink discs are supplied with Molybdenum Disulphide based lubricant applied to the tapers and to the locking screw threads and head contact areas.


SHAFT AND HUB MATERIAL

Listed specifications assume shaft and hub material with a yield point of at least 45 ksi (310 N/mm²). Cast iron hubs are well suited for compressive stresses exerted by B-LOC Shrink Discs. However, a lower torsional hub strength generally requires the selection of a shrink disc at least one size larger than listed if full torque (i.e., that applicable to a steel hub) is to be transmitted.

LENGTH OF FIT


The most recent research on length of fit for a shrink disc connection* indicates that the hub bore-to-shaft interface should be relieved using a non-toleranced clearance except for that portion directly under the shrink disc inner ring, for a fit length equal to “L” for a standard shrink disc (see illustration right). This approach eliminates fretting corrosion between shaft and hub which can make the separation of components difficult.

* (see Casper, Thomas: Reibkorrosionsverhalten von Spanelementverbindungen - Aachen: Mainz, 1999)



LOCATING AGAINST HUB FACE

In applications subjected to reversing bending moments, we recommend the configuration at right which requires a hub undercut where $R \geq e$ for smooth transition.




B-LOC® Shrink Discs

B-LOC® Shrink Disc SD10



Metric hex head locking screws
DIN 931 grade 10.9
(See M_a for install torque).



See Table I on the next page for maximum diametrical clearance between shaft and hub bore.


SD10 – Standard Duty

| Part Number | Size | SD bore (Hub OD) d (inch) | Hub OD Tolerance T_{hd} (inch) | Shaft Diameter Range | | Locking Screws Qty Size | M_a Install Torque (ft lb) | M_t Max. Transmitted Torque | | A (inch) | D (inch) | L (inch) | H (inch) | e (inch) | d_1 (inch) | R (inch) | Ship wt (lb) |
|-------------|--------|------------------------------|-------------------------------------|----------------------|---------------|----------------------------|---------------------------------|----------------------------------|----------------|----------|----------|----------|----------|----------|--------------|----------|--------------|
| | | | | ds-MIN (inch) | ds-MAX (inch) | | | ds-MIN (ft lb) | ds-MAX (ft lb) | | | | | | | | |
| B0241 | 24-10 | 0.945 | + 0 / -0.002 | 0.625 | 0.774 | 6 M5 x 16 | 3.6 | 138 | 278 | 1.417 | 1.97 | 0.551 | 0.71 | 0.080 | 1.023 | 1/16 | 0.5 |
| B0301 | 30-10 | 1.181 | + 0 / -0.002 | 0.750 | 0.967 | 7 M5 x 18 | 3.6 | 177 | 407 | 1.732 | 2.36 | 0.629 | 0.79 | 0.081 | 1.259 | 1/16 | 0.7 |
| B0361 | 36-10 | 1.417 | + 0 / -0.002 | 0.875 | 1.161 | 5 M6 x 20 | 8.7 | 315 | 666 | 2.047 | 2.83 | 0.700 | 0.87 | 0.085 | 1.496 | 1/16 | 0.9 |
| B0441 | 44-10 | 1.732 | + 0 / -0.002 | 1.125 | 1.419 | 7 M6 x 20 | 8.7 | 683 | 1198 | 2.402 | 3.15 | 0.787 | 0.94 | 0.077 | 1.850 | 1/16 | 1.4 |
| B0501 | 50-10 | 1.969 | + 0 / -0.002 | 1.375 | 1.612 | 8 M6 x 22 | 8.7 | 964 | 1565 | 2.756 | 3.54 | 0.866 | 1.02 | 0.077 | 2.086 | 1/16 | 1.8 |
| B0551 | 55-10 | 2.165 | + 0 / -0.002 | 1.500 | 1.773 | 8 M6 x 25 | 8.7 | 1014 | 1707 | 2.953 | 3.94 | 0.905 | 1.14 | 0.118 | 2.283 | 3/32 | 2.4 |
| B0621 | 62-10 | 2.441 | + 0 / -0.002 | 1.750 | 1.999 | 10 M6 x 25 | 8.7 | 1718 | 2375 | 3.386 | 4.33 | 0.905 | 1.14 | 0.118 | 2.598 | 3/32 | 2.9 |
| B0681 | 68-10 | 2.677 | + 0 / -0.002 | 1.875 | 2.193 | 10 M6 x 25 | 8.7 | 1760 | 2606 | 3.386 | 4.53 | 0.905 | 1.14 | 0.118 | 2.834 | 3/32 | 3 |
| B0751 | 75-10 | 2.953 | + 0 / -0.002 | 2.125 | 2.418 | 7 M8 x 25 | 22 | 2792 | 4057 | 3.937 | 5.43 | 0.984 | 1.22 | 0.118 | 3.110 | 1/8 | 3.8 |
| B0801 | 80-10 | 3.150 | + 0 / -0.002 | 2.375 | 2.580 | 7 M8 x 25 | 22 | 3416 | 4331 | 3.937 | 5.71 | 0.984 | 1.22 | 0.118 | 3.307 | 1/8 | 4.2 |
| B0901 | 90-10 | 3.543 | + 0 / -0.004 | 2.500 | 2.902 | 10 M8 x 30 | 22 | 4751 | 7139 | 4.488 | 6.10 | 1.181 | 1.49 | 0.155 | 3.700 | 1/8 | 7 |
| H0951 | 95-10 | 3.740 | + 0 / -0.004 | 2.750 | 3.063 | 12 M8 x 30 | 22 | 6832 | 9108 | 4.882 | 6.69 | 1.338 | 1.69 | 0.176 | 4.094 | 1/8 | 10 |
| B1001 | 100-10 | 3.937 | + 0 / -0.004 | 2.875 | 3.224 | 12 M8 x 35 | 22 | 7059 | 9586 | 4.882 | 6.69 | 1.338 | 1.69 | 0.176 | 4.094 | 1/8 | 10 |
| B1101 | 110-10 | 4.331 | + 0 / -0.004 | 3.125 | 3.547 | 9 M10 x 40 | 44 | 9013 | 12602 | 5.354 | 7.28 | 1.535 | 1.93 | 0.198 | 4.488 | 1/8 | 13 |
| B1251 | 125-10 | 4.921 | + 0 / -0.004 | 3.500 | 4.031 | 12 M10 x 40 | 44 | 13710 | 19540 | 6.299 | 8.46 | 1.653 | 2.04 | 0.194 | 5.275 | 1/8 | 18 |
| B1401 | 140-10 | 5.512 | + 0 / -0.004 | 4.000 | 4.514 | 10 M12 x 45 | 74 | 19648 | 26440 | 6.890 | 9.06 | 1.811 | 2.28 | 0.235 | 5.708 | 3/16 | 23 |
| B1551 | 155-10 | 6.102 | + 0 / -0.004 | 4.500 | 4.998 | 12 M12 x 50 | 74 | 27515 | 34049 | 7.559 | 10.36 | 1.968 | 2.44 | 0.236 | 6.496 | 3/16 | 31 |
| H1651 | 165-10 | 6.496 | + 0 / -0.004 | 4.875 | 5.320 | 8 M16 x 55 | 185 | 37737 | 47135 | 8.268 | 11.42 | 2.204 | 2.67 | 0.233 | 6.889 | 3/16 | 49 |
| B1751 | 175-10 | 6.890 | + 0 / -0.004 | 5.250 | 5.643 | 8 M16 x 55 | 185 | 41620 | 50005 | 8.661 | 11.81 | 2.204 | 2.67 | 0.233 | 7.283 | 3/16 | 50 |
| B1851 | 185-10 | 7.283 | + 0 / -0.004 | 5.625 | 5.965 | 10 M16 x 65 | 185 | 56802 | 65965 | 9.291 | 12.99 | 2.795 | 3.34 | 0.273 | 7.677 | 3/16 | 82 |
| H1951 | 195-10 | 7.677 | + 0 / -0.004 | 5.875 | 6.288 | 12 M16 x 65 | 185 | 71908 | 84926 | 9.685 | 13.78 | 2.795 | 3.34 | 0.273 | 8.110 | 3/16 | 91 |
| B2001 | 200-10 | 7.874 | + 0 / -0.004 | 6.250 | 6.449 | 12 M16 x 65 | 185 | 80674 | 87096 | 9.685 | 13.78 | 2.795 | 3.34 | 0.273 | 8.110 | 3/16 | 90 |
| B2201 | 220-10 | 8.661 | + 0 / -0.004 | 6.375 | 7.094 | 15 M16 x 80 | 185 | 92230 | 116425 | 10.630 | 14.57 | 3.464 | 4.06 | 0.298 | 8.897 | 1/4 | 119 |
| B2401 | 240-10 | 9.449 | + 0 / -0.004 | 7.000 | 7.739 | 12 M20 x 80 | 362 | 130645 | 161818 | 11.614 | 15.95 | 3.622 | 4.22 | 0.299 | 9.763 | 1/4 | 148 |
| B2601 | 260-10 | 10.236 | + 0 / -0.004 | 7.625 | 8.383 | 14 M20 x 90 | 362 | 162198 | 205263 | 12.638 | 16.93 | 4.055 | 4.72 | 0.318 | 10.551 | 1/4 | 181 |
| H2801 | 280-10 | 11.024 | + 0 / -0.005 | 8.375 | 9.028 | 16 M20 x 100 | 362 | 210581 | 253378 | 13.622 | 18.11 | 4.488 | 5.20 | 0.356 | 11.338 | 5/16 | 225 |
| H3001 | 300-10 | 11.811 | + 0 / -0.005 | 9.000 | 9.673 | 18 M20 x 100 | 362 | 257278 | 306749 | 14.331 | 19.10 | 4.803 | 5.52 | 0.359 | 12.125 | 5/16 | 260 |
| H3201 | 320-10 | 12.598 | + 0 / -0.005 | 9.625 | 10.318 | 20 M20 x 100 | 362 | 310492 | 359728 | 15.197 | 20.48 | 4.803 | 5.52 | 0.359 | 12.913 | 5/16 | 288 |
| H3401 | 340-10 | 13.386 | + 0 / -0.005 | 10.250 | 10.963 | 24 M20 x 110 | 362 | 392088 | 462391 | 16.063 | 22.44 | 5.276 | 6.14 | 0.432 | 13.700 | 5/16 | 409 |
| H3501 | 350-10 | 13.780 | + 0 / -0.005 | 10.875 | 11.285 | 24 M20 x 110 | 362 | 432685 | 474097 | 17.008 | 22.84 | 5.511 | 6.30 | 0.395 | 14.488 | 5/16 | 429 |
| H3601 | 360-10 | 14.173 | + 0 / -0.005 | 11.250 | 11.608 | 24 M20 x 110 | 362 | 451405 | 487702 | 17.008 | 23.23 | 5.511 | 6.30 | 0.395 | 14.488 | 5/16 | 449 |
| H3801 | 380-10 | 14.961 | + 0 / -0.005 | 11.500 | 12.253 | 20 M24 x 120 | 620 | 535005 | 623051 | 18.031 | 25.40 | 5.669 | 6.46 | 0.396 | 15.276 | 5/16 | 526 |
| H3901 | 390-10 | 15.354 | + 0 / -0.005 | 12.250 | 12.575 | 21 M24 x 120 | 620 | 633184 | 673847 | 18.425 | 25.99 | 5.669 | 6.46 | 0.396 | 15.629 | 3/8 | 572 |
| H4201 | 420-10 | 16.535 | + 0 / -0.006 | 12.500 | 13.543 | 24 M24 x 130 | 620 | 685493 | 829666 | 19.843 | 27.17 | 6.456 | 7.25 | 0.397 | 16.929 | 3/8 | 630 |
| H4401 | 440-10 | 17.323 | + 0 / -0.006 | 13.500 | 14.187 | 24 M24 x 130 | 620 | 768743 | 852536 | 20.748 | 29.53 | 6.969 | 7.95 | 0.491 | 17.716 | 3/8 | 835 |
| H4601 | 460-10 | 18.110 | + 0 / -0.006 | 14.125 | 14.832 | 28 M24 x 130 | 620 | 934194 | 1051580 | 21.535 | 30.32 | 6.969 | 7.95 | 0.491 | 18.425 | 3/8 | 924 |
| H4801 | 480-10 | 18.898 | + 0 / -0.006 | 14.750 | 15.477 | 30 M24 x 150 | 620 | 1047086 | 1176357 | 22.441 | 31.50 | 7.401 | 8.39 | 0.495 | 19.291 | 1/2 | 1110 |
| H5001 | 500-10 | 19.685 | + 0 / -0.006 | 15.375 | 16.122 | 24 M27 x 150 | 922 | 1169590 | 1310148 | 23.228 | 33.46 | 7.401 | 8.39 | 0.495 | 19.999 | 1/2 | 1265 |


Notes:

- Inner rings of all shrink discs are supplied with one lengthwise slit.
- Shrink discs are available for shafts up to 40" diameter and in a variety of special designs.
- Maximum shaft sizes listed for Shrink Disc Series SD10 and SD30 reflect equal section moduli of shaft and hub (maximum shaft diameter = $\frac{d}{1.221}$).
- Larger shrink discs for shafts up to 40" diameter are available on request.


B-LOC®
Shrink Disc
SD20



SD10
Standard Duty



SD20
Light Duty



SD30
Heavy Duty

SD20 – Light Duty


| Part Number | Size | SD bore (Hub OD) | | Shaft Diameter Range | | Locking Screws | | M _a | | M _t | | A (inch) | D (inch) | L (inch) | H (inch) | e (inch) | d _t (inch) | R (inch) | Ship wt (lb) |
|-------------|--------|------------------|-------------------------|----------------------|---------------|----------------|-----------|------------------------|-------------------------|----------------|--------|----------|----------|----------|----------|----------|-----------------------|----------|--------------|
| | | d (inch) | T ₁ d (inch) | ds-MIN (inch) | ds-MAX (inch) | Qty | Size | Install Torque (ft lb) | Max. Transmitted Torque | | | | | | | | | | |
| | | | | | | | | ds-MIN (ft lb) | ds-MAX (ft lb) | | | | | | | | | | |
| H1252 | 125-20 | 4.921 | + 0 / -0.004 | 3.625 | 4.125 | 8 | M10 x 40 | 44 | 9380 | 13343 | 6.220 | 7.28 | 1.535 | 2.01 | 0.238 | 5.118 | 1/8 | 13 | |
| H1402 | 140-20 | 5.512 | + 0 / -0.004 | 4.250 | 5.000 | 9 | M10 x 40 | 44 | 13691 | 20328 | 6.889 | 8.67 | 1.535 | 2.01 | 0.238 | 5.669 | 1/8 | 18 | |
| H1552 | 155-20 | 6.102 | + 0 / -0.004 | 5.000 | 5.500 | 11 | M10 x 40 | 44 | 21144 | 27447 | 7.559 | 9.65 | 1.535 | 2.01 | 0.238 | 6.259 | 1/8 | 22 | |
| H1652 | 165-20 | 6.496 | + 0 / -0.004 | 5.375 | 5.750 | 10 | M12 x 50 | 74 | 30652 | 36677 | 8.267 | 10.24 | 1.811 | 2.44 | 0.315 | 6.653 | 3/16 | 31 | |
| H1752 | 175-20 | 6.890 | + 0 / -0.004 | 5.625 | 6.125 | 11 | M12 x 50 | 74 | 34940 | 43588 | 8.661 | 10.83 | 1.811 | 2.44 | 0.315 | 7.047 | 3/16 | 35 | |
| H1852 | 185-20 | 7.283 | + 0 / -0.004 | 6.000 | 6.500 | 12 | M12 x 50 | 74 | 41643 | 51035 | 8.858 | 11.62 | 1.811 | 2.44 | 0.315 | 7.440 | 3/16 | 44 | |
| H1952 | 195-20 | 7.677 | + 0 / -0.004 | 6.500 | 7.000 | 15 | M12 x 60 | 74 | 58979 | 71073 | 9.330 | 12.40 | 2.204 | 2.84 | 0.318 | 7.834 | 3/16 | 60 | |
| H2202 | 220-20 | 8.661 | + 0 / -0.004 | 7.000 | 7.875 | 10 | M16 x 70 | 185 | 76454 | 100895 | 10.433 | 13.59 | 2.598 | 3.31 | 0.356 | 8.818 | 3/16 | 77 | |
| H2402 | 240-20 | 9.449 | + 0 / -0.004 | 7.875 | 8.500 | 12 | M16 x 70 | 185 | 107011 | 129864 | 11.417 | 14.57 | 2.598 | 3.31 | 0.356 | 9.606 | 1/4 | 97 | |
| H2602 | 260-20 | 10.236 | + 0 / -0.004 | 8.625 | 9.250 | 14 | M16 x 70 | 185 | 139939 | 166618 | 12.204 | 15.55 | 2.834 | 3.63 | 0.398 | 10.433 | 1/4 | 106 | |
| H2802 | 280-20 | 11.024 | + 0 / -0.005 | 9.000 | 9.875 | 16 | M16 x 75 | 185 | 158724 | 200396 | 13.110 | 16.74 | 3.307 | 4.10 | 0.397 | 11.220 | 1/4 | 132 | |
| H3002 | 300-20 | 11.811 | + 0 / -0.005 | 9.875 | 10.625 | 18 | M16 x 75 | 185 | 229935 | 271288 | 14.094 | 18.11 | 3.307 | 4.10 | 0.397 | 12.007 | 1/4 | 165 | |
| H3202 | 320-20 | 12.598 | + 0 / -0.005 | 10.500 | 11.375 | 20 | M16 x 75 | 185 | 238939 | 292045 | 14.881 | 19.49 | 3.307 | 4.18 | 0.437 | 12.795 | 1/4 | 185 | |
| H3402 | 340-20 | 13.386 | + 0 / -0.005 | 11.375 | 12.000 | 21 | M16 x 75 | 185 | 281000 | 320857 | 15.826 | 21.07 | 3.307 | 4.18 | 0.437 | 13.582 | 1/4 | 220 | |
| H3602 | 360-20 | 14.173 | + 0 / -0.005 | 11.875 | 12.625 | 16 | M20 x 90 | 362 | 341876 | 398029 | 16.653 | 21.85 | 3.937 | 4.81 | 0.437 | 14.370 | 5/16 | 275 | |
| H3802 | 380-20 | 14.961 | + 0 / -0.005 | 12.500 | 13.000 | 18 | M20 x 100 | 362 | 403340 | 444630 | 17.401 | 23.03 | 4.409 | 5.35 | 0.471 | 15.236 | 5/16 | 301 | |
| H3902 | 390-20 | 15.354 | + 0 / -0.005 | 12.625 | 13.750 | 20 | M20 x 100 | 362 | 446171 | 549086 | 17.795 | 23.43 | 4.409 | 5.36 | 0.476 | 15.629 | 5/16 | 344 | |
| H4202 | 420-20 | 16.535 | + 0 / -0.006 | 13.750 | 14.625 | 22 | M20 x 100 | 362 | 544495 | 625817 | 19.094 | 24.81 | 4.724 | 5.67 | 0.473 | 16.810 | 5/16 | 407 | |
| H4602 | 460-20 | 18.110 | + 0 / -0.006 | 14.625 | 16.375 | 28 | M20 x 110 | 362 | 704454 | 927856 | 20.747 | 26.97 | 5.196 | 6.22 | 0.512 | 18.425 | 3/8 | 517 | |
| H5002 | 500-20 | 19.685 | + 0 / -0.006 | 16.250 | 17.375 | 30 | M20 x 120 | 362 | 860127 | 1014952 | 22.519 | 29.53 | 5.984 | 7.01 | 0.513 | 19.999 | 3/8 | 704 | |

Table 1

For Series SD10, SD20 and SD30

| Shaft Sizes (inch) | | Maximum Diametrical Clearance Between Shaft and Hub Bore |
|--------------------|---------|--|
| > | ≤ | |
| | 1 1/8 | 0.0010 |
| 1 1/8 | 1 15/16 | 0.0015 |
| 1 15/16 | 4 3/4 | 0.0020 |
| 4 3/4 | 7 | 0.0030 |
| 7 | 10 | 0.0040 |
| 10 | 14 | 0.0050 |
| 14 | | 0.0060 |

B-LOC® Shrink Disc SD30



SD30 – Heavy Duty


| Part Number | Size | SD bore (Hub OD) | | Shaft Diameter Range | | Locking Screws | | Ma Install Torque (ft lb) | Mt Max. Transmitted Torque | | A (inch) | D (inch) | L (inch) | H (inch) | e (inch) | d ₁ (inch) | R (inch) | Ship wt (lb) |
|-------------|--------|------------------|----------------------------|----------------------|------------------|----------------|-----------|---------------------------------|-------------------------------|-------------------|-------------|-------------|-------------|-------------|-------------|--------------------------|-------------|-----------------|
| | | d (inch) | T ₁ d (inch) | ds-MIN (inch) | ds-MAX (inch) | Qty | Size | | ds-MIN (ft lb) | ds-MAX (ft lb) | | | | | | | | |
| H0443 | 44-30 | 1.732 | + 0 / -0.002 | 1.125 | 1.419 | 5 | M8 x 30 | 22 | 941 | 1653 | 2.598 | 3.35 | 1.102 | 1.34 | 0.119 | 1.890 | 1/16 | 1.4 |
| H0503 | 50-30 | 1.969 | + 0 / -0.002 | 1.375 | 1.612 | 7 | M8 x 35 | 22 | 1761 | 2749 | 2.874 | 3.74 | 1.181 | 1.54 | 0.180 | 1.984 | 1/16 | 1.8 |
| H0553 | 55-30 | 2.165 | + 0 / -0.002 | 1.500 | 1.773 | 7 | M8 x 35 | 22 | 1892 | 3023 | 3.071 | 4.13 | 1.181 | 1.54 | 0.180 | 2.323 | 3/32 | 2.4 |
| B0623 | 62-30 | 2.441 | + 0 / -0.002 | 1.750 | 1.999 | 7 | M8 x 35 | 22 | 2353 | 3244 | 3.346 | 4.53 | 1.181 | 1.54 | 0.180 | 2.598 | 3/32 | 2.9 |
| B0683 | 68-30 | 2.677 | + 0 / -0.002 | 1.875 | 2.193 | 8 | M8 x 35 | 22 | 2861 | 4173 | 3.622 | 4.72 | 1.181 | 1.54 | 0.180 | 2.835 | 3/32 | 3 |
| B0753 | 75-30 | 2.953 | + 0 / -0.002 | 2.125 | 2.418 | 7 | M10 x 40 | 44 | 4552 | 6529 | 4.134 | 5.71 | 1.417 | 1.81 | 0.197 | 3.307 | 1/8 | 3.8 |
| B0803 | 80-30 | 3.150 | + 0 / -0.002 | 2.375 | 2.580 | 7 | M10 x 40 | 44 | 5541 | 6971 | 4.134 | 5.71 | 1.417 | 1.81 | 0.197 | 3.307 | 1/8 | 4.2 |
| B0903 | 90-30 | 3.543 | + 0 / -0.004 | 2.500 | 2.902 | 8 | M10 x 40 | 44 | 5946 | 8994 | 4.567 | 6.30 | 1.575 | 1.97 | 0.198 | 3.701 | 1/8 | 7 |
| B1003 | 100-30 | 3.937 | + 0 / -0.004 | 2.875 | 3.224 | 10 | M10 x 45 | 44 | 9370 | 12700 | 4.961 | 6.69 | 1.732 | 2.13 | 0.199 | 4.094 | 1/8 | 10 |
| H1103 | 110-30 | 4.331 | + 0 / -0.004 | 3.125 | 3.547 | 12 | M10 x 45 | 44 | 12116 | 16879 | 5.354 | 7.28 | 1.969 | 2.36 | 0.196 | 4.482 | 1/8 | 17 |
| H1253 | 125-30 | 4.921 | + 0 / -0.004 | 3.500 | 4.031 | 12 | M12 x 50 | 74 | 20092 | 28393 | 6.299 | 8.47 | 2.126 | 2.60 | 0.237 | 5.157 | 3/16 | 24 |
| B1403 | 140-30 | 5.512 | + 0 / -0.004 | 4.000 | 4.514 | 12 | M12 x 60 | 74 | 23275 | 31491 | 6.889 | 9.06 | 2.362 | 2.92 | 0.279 | 5.744 | 3/16 | 29 |
| H1553 | 155-30 | 6.102 | + 0 / -0.004 | 4.500 | 4.998 | 15 | M12 x 60 | 74 | 34154 | 42273 | 7.795 | 10.36 | 2.598 | 3.15 | 0.276 | 6.496 | 3/16 | 44 |
| H1653 | 165-30 | 6.496 | + 0 / -0.004 | 4.875 | 5.320 | 10 | M16 x 70 | 185 | 46957 | 58743 | 8.267 | 11.42 | 2.834 | 3.47 | 0.318 | 6.940 | 3/16 | 57 |
| H1753 | 175-30 | 6.890 | + 0 / -0.004 | 5.250 | 5.643 | 10 | M16 x 70 | 185 | 51804 | 62320 | 8.661 | 11.82 | 2.834 | 3.47 | 0.318 | 7.322 | 3/16 | 64 |
| H1853 | 185-30 | 7.283 | + 0 / -0.004 | 5.625 | 5.965 | 15 | M16 x 80 | 185 | 86847 | 100371 | 9.291 | 12.99 | 3.622 | 4.41 | 0.394 | 7.704 | 3/16 | 104 |
| H1953 | 195-30 | 7.677 | + 0 / -0.004 | 5.875 | 6.288 | 15 | M16 x 80 | 185 | 89488 | 105820 | 9.685 | 13.78 | 3.622 | 4.41 | 0.394 | 8.102 | 1/4 | 110 |
| H2003 | 200-30 | 7.874 | + 0 / -0.004 | 6.250 | 6.449 | 15 | M16 x 80 | 185 | 100466 | 108524 | 9.685 | 13.78 | 3.622 | 4.41 | 0.394 | 8.102 | 1/4 | 110 |
| H2203 | 220-30 | 8.661 | + 0 / -0.004 | 6.375 | 7.094 | 20 | M16 x 90 | 185 | 123458 | 155750 | 10.629 | 14.57 | 4.488 | 5.28 | 0.396 | 8.901 | 1/4 | 143 |
| B2403 | 240-30 | 9.449 | + 0 / -0.004 | 7.000 | 7.739 | 15 | M20 x 100 | 362 | 162518 | 201425 | 11.614 | 15.95 | 4.724 | 5.67 | 0.473 | 9.692 | 1/4 | 192 |
| H2603 | 260-30 | 10.236 | + 0 / -0.005 | 7.625 | 8.383 | 18 | M20 x 110 | 362 | 207733 | 263252 | 12.637 | 16.93 | 5.354 | 6.30 | 0.473 | 10.511 | 1/4 | 220 |
| H2803 | 280-30 | 11.024 | + 0 / -0.005 | 8.375 | 9.028 | 21 | M20 x 120 | 362 | 276822 | 332933 | 13.622 | 18.11 | 5.826 | 6.77 | 0.472 | 11.370 | 5/16 | 291 |
| H3003 | 300-30 | 11.811 | + 0 / -0.005 | 9.000 | 9.673 | 22 | M20 x 120 | 362 | 313789 | 374371 | 14.330 | 19.10 | 5.984 | 6.93 | 0.473 | 12.177 | 5/16 | 308 |
| H3203 | 320-30 | 12.598 | + 0 / -0.005 | 9.625 | 10.318 | 24 | M20 x 120 | 362 | 368957 | 427823 | 15.196 | 20.48 | 6.299 | 7.25 | 0.476 | 12.964 | 5/16 | 363 |
| H3403 | 340-30 | 13.386 | + 0 / -0.005 | 10.250 | 10.963 | 21 | M24 x 130 | 620 | 489329 | 577963 | 16.535 | 22.44 | 6.929 | 7.88 | 0.476 | 13.724 | 5/16 | 528 |
| H3603 | 360-30 | 14.173 | + 0 / -0.005 | 11.000 | 11.608 | 22 | M24 x 140 | 620 | 562859 | 642534 | 17.007 | 23.23 | 7.086 | 8.04 | 0.477 | 14.515 | 3/8 | 550 |
| H3903 | 390-30 | 15.354 | + 0 / -0.005 | 11.625 | 12.575 | 24 | M24 x 140 | 620 | 628949 | 762028 | 18.425 | 25.99 | 7.401 | 8.35 | 0.475 | 15.609 | 3/8 | 770 |
| H4203 | 420-30 | 16.535 | + 0 / -0.006 | 12.500 | 13.543 | 30 | M24 x 160 | 620 | 852841 | 1033732 | 19.842 | 27.17 | 8.425 | 9.37 | 0.472 | 16.811 | 3/8 | 902 |
| H4603 | 460-30 | 18.110 | + 0 / -0.006 | 13.625 | 14.832 | 28 | M27 x 170 | 922 | 1144559 | 1403894 | 21.535 | 30.32 | 8.818 | 9.93 | 0.556 | 18.503 | 1/2 | 1188 |
| H5003 | 500-30 | 19.685 | + 0 / -0.006 | 14.875 | 16.122 | 32 | M27 x 180 | 922 | 1443359 | 1749331 | 23.622 | 33.47 | 9.685 | 10.79 | 0.552 | 19.999 | 1/2 | 1650 |

- Notes:
- Inner rings of all shrink discs are supplied with one lengthwise slit.
 - Shrink discs are available for shafts up to 40" diameter and in a variety of special designs.
 - Maximum shaft sizes listed for Shrink Disc Series SD10 and SD30 reflect equal section moduli of shaft and hub (maximum shaft diameter = $\frac{d}{1.221}$).
 - See Table 1 (bottom of page 43) for maximum diametrical clearance between shaft and hub bore.

B-LOC® Split and Half Shrink Discs

To complement our standard line of B-LOC Shrink Discs, we also offer Split and Half Shrink Discs. These versions are available in all bore sizes listed for standard Shrink Discs. The Split Shrink Disc design allows greater mounting versatility on symmetrical hubs. For applications with tight space constraints and lower performance requirements, Half Shrink Discs provide several compact mounting options.

- **Reduced dimensions** – Perfect for applications with restricted space.
- **Easy Installation** – Standard screws mean installation and removal are achieved using standard tools.
- **Infinite Adjustment** – Simplified design allows hubs to be located and locked virtually anywhere on the shaft.
- **Easy Removal** – Units are self-releasing once the locking screws are loosened, making removal a breeze.
- **Reliability you can count on!** B-LOC Shrink Discs can be tightened and released as often as required.



Note: Dimension X is required when ordering Split or Half Shrink Disc Type HT. See Table 1 at bottom left of page 46 for web clearance hole data. Please consult B-LOC Applications Engineering at AE@fennerdrives.com to determine appropriate screw length for your specific application.

Split Shrink Discs

Standard and Light Duty Series: If dimension $X > 2 \times L$ then the transmissible torque may be reduced by up to 50%.


Heavy Duty Series: If dimension $X > 1 \times L$ then the transmissible torque may be reduced by up to 50%.

Half Shrink Discs

Half Shrink Discs HC/HT transmit 50% of the M_t of Shrink Discs and Split Shrink Discs.

B-LOC® Split Shrink Discs

B-LOC® Shrink Disc Split



Dimension X is required when ordering Split Shrink Discs. See Table 1 at bottom left for web clearance hole data.

SD10 – Split SD – Standard Duty

| Part Number | Size | SD bore (Hub OD) | | Shaft Diameter Range | | Locking Screws | | M _a | | | M _t | | | A (inch) | D (inch) | L (inch) | H ₁ (inch) | e (inch) | d ₁ (inch) | R (inch) | Ship wt (lb) |
|-------------|--------|------------------|-------------------------|----------------------|---------------|----------------|------|------------------------|-------------------------|----------------|----------------|-------|-------|----------|----------|----------|-----------------------|----------|-----------------------|----------|--------------|
| | | d (inch) | T ₁ d (inch) | ds-MIN (inch) | ds-MAX (inch) | Qty | Size | Install Torque (ft lb) | Max. Transmitted Torque | ds-MIN (ft lb) | ds-MAX (ft lb) | | | | | | | | | | |
| HS0241 | 24-10 | 0.945 | + 0 / -0.002 | 0.625 | 0.774 | 6 | M5 | 3.6 | 138 | 278 | 1.417 | 1.97 | 0.374 | 0.453 | 0.080 | 1.023 | 1/16 | 0.5 | | | |
| HS0301 | 30-10 | 1.181 | + 0 / -0.002 | 0.750 | 0.967 | 7 | M5 | 3.6 | 177 | 407 | 1.732 | 2.36 | 0.413 | 0.493 | 0.081 | 1.259 | 1/16 | 0.7 | | | |
| HS0361 | 36-10 | 1.417 | + 0 / -0.002 | 0.875 | 1.161 | 5 | M6 | 8.7 | 315 | 666 | 2.047 | 2.83 | 0.448 | 0.533 | 0.085 | 1.496 | 1/16 | 0.9 | | | |
| HS0441 | 44-10 | 1.732 | + 0 / -0.002 | 1.125 | 1.419 | 7 | M6 | 8.7 | 683 | 1198 | 2.402 | 3.15 | 0.492 | 0.568 | 0.077 | 1.850 | 1/16 | 1.4 | | | |
| HS0501 | 50-10 | 1.969 | + 0 / -0.002 | 1.375 | 1.612 | 8 | M6 | 8.7 | 964 | 1565 | 2.756 | 3.54 | 0.531 | 0.608 | 0.077 | 2.086 | 1/16 | 1.8 | | | |
| HS0551 | 55-10 | 2.165 | + 0 / -0.002 | 1.500 | 1.773 | 8 | M6 | 8.7 | 1014 | 1707 | 2.953 | 3.94 | 0.551 | 0.668 | 0.118 | 2.283 | 3/32 | 2.4 | | | |
| HS0621 | 62-10 | 2.441 | + 0 / -0.002 | 1.750 | 1.999 | 10 | M6 | 8.7 | 1718 | 2375 | 3.386 | 4.33 | 0.551 | 0.668 | 0.118 | 2.598 | 3/32 | 2.9 | | | |
| HS0681 | 68-10 | 2.677 | + 0 / -0.002 | 1.875 | 2.193 | 10 | M6 | 8.7 | 1760 | 2606 | 3.386 | 4.53 | 0.551 | 0.668 | 0.118 | 2.834 | 3/32 | 3 | | | |
| HS0751 | 75-10 | 2.953 | + 0 / -0.002 | 2.125 | 2.418 | 7 | M8 | 22 | 2792 | 4057 | 3.937 | 5.43 | 0.689 | 0.807 | 0.118 | 3.110 | 1/8 | 3.8 | | | |
| HS0801 | 80-10 | 3.150 | + 0 / -0.002 | 2.375 | 2.580 | 7 | M8 | 22 | 3416 | 4331 | 3.937 | 5.71 | 0.689 | 0.807 | 0.118 | 3.307 | 1/8 | 4.2 | | | |
| HS0901 | 90-10 | 3.543 | + 0 / -0.004 | 2.500 | 2.902 | 10 | M8 | 22 | 4751 | 7139 | 4.488 | 6.10 | 0.788 | 0.942 | 0.155 | 3.700 | 1/8 | 7 | | | |
| HS0951 | 95-10 | 3.740 | + 0 / -0.004 | 2.750 | 3.063 | 12 | M8 | 22 | 6832 | 9108 | 4.882 | 6.69 | 0.866 | 1.042 | 0.176 | 4.094 | 1/8 | 10 | | | |
| HS1001 | 100-10 | 3.937 | + 0 / -0.004 | 2.875 | 3.224 | 12 | M8 | 22 | 7059 | 9586 | 4.882 | 6.69 | 0.866 | 1.042 | 0.176 | 4.094 | 1/8 | 10 | | | |
| HS1101 | 110-10 | 4.331 | + 0 / -0.004 | 3.125 | 3.547 | 9 | M10 | 44 | 9013 | 12602 | 5.354 | 7.28 | 0.965 | 1.162 | 0.198 | 4.488 | 1/8 | 13 | | | |
| HS1251 | 125-10 | 4.921 | + 0 / -0.004 | 3.500 | 4.031 | 12 | M10 | 44 | 13710 | 19540 | 6.299 | 8.46 | 1.024 | 1.217 | 0.194 | 5.275 | 1/8 | 18 | | | |
| HS1401 | 140-10 | 5.512 | + 0 / -0.004 | 4.000 | 4.514 | 10 | M12 | 74 | 19648 | 26440 | 6.890 | 9.06 | 1.103 | 1.337 | 0.235 | 5.708 | 3/16 | 23 | | | |
| HS1551 | 155-10 | 6.102 | + 0 / -0.004 | 4.500 | 4.998 | 12 | M12 | 74 | 27515 | 34049 | 7.559 | 10.36 | 1.181 | 1.417 | 0.236 | 6.496 | 3/16 | 31 | | | |
| HS1651 | 165-10 | 6.496 | + 0 / -0.004 | 4.875 | 5.320 | 8 | M16 | 185 | 37737 | 47135 | 8.268 | 11.42 | 1.299 | 1.532 | 0.233 | 6.889 | 3/16 | 49 | | | |
| HS1751 | 175-10 | 6.890 | + 0 / -0.004 | 5.250 | 5.643 | 8 | M16 | 185 | 41620 | 50005 | 8.661 | 11.81 | 1.299 | 1.532 | 0.233 | 7.283 | 3/16 | 50 | | | |
| HS1851 | 185-10 | 7.283 | + 0 / -0.004 | 5.625 | 5.965 | 10 | M16 | 185 | 56802 | 65965 | 9.291 | 12.99 | 1.595 | 1.867 | 0.273 | 7.677 | 3/16 | 82 | | | |
| HS1951 | 195-10 | 7.677 | + 0 / -0.004 | 5.875 | 6.288 | 12 | M16 | 185 | 71908 | 84926 | 9.685 | 13.78 | 1.595 | 1.867 | 0.273 | 8.110 | 3/16 | 91 | | | |
| HS2001 | 200-10 | 7.874 | + 0 / -0.004 | 6.250 | 6.449 | 12 | M16 | 185 | 80674 | 87096 | 9.685 | 13.78 | 1.595 | 1.867 | 0.273 | 8.110 | 3/16 | 90 | | | |
| HS2201 | 220-10 | 8.661 | + 0 / -0.004 | 6.375 | 7.094 | 15 | M16 | 185 | 92230 | 116425 | 10.630 | 14.57 | 2.027 | 2.325 | 0.298 | 8.897 | 1/4 | 119 | | | |
| HS2401 | 240-10 | 9.449 | + 0 / -0.004 | 7.000 | 7.739 | 12 | M20 | 362 | 130645 | 161818 | 11.614 | 15.95 | 2.106 | 2.405 | 0.299 | 9.763 | 1/4 | 148 | | | |
| HS2601 | 260-10 | 10.236 | + 0 / -0.004 | 7.625 | 8.383 | 14 | M20 | 362 | 162198 | 205263 | 12.638 | 16.93 | 2.323 | 2.640 | 0.318 | 10.551 | 1/4 | 181 | | | |
| HS2801 | 280-10 | 11.024 | + 0 / -0.005 | 8.375 | 9.028 | 16 | M20 | 362 | 210581 | 253378 | 13.622 | 18.11 | 2.638 | 2.994 | 0.356 | 11.338 | 5/16 | 225 | | | |
| HS3001 | 300-10 | 11.811 | + 0 / -0.005 | 9.000 | 9.673 | 18 | M20 | 362 | 257278 | 306749 | 14.331 | 19.10 | 2.796 | 3.154 | 0.359 | 12.125 | 5/16 | 260 | | | |
| HS3201 | 320-10 | 12.598 | + 0 / -0.005 | 9.625 | 10.318 | 20 | M20 | 362 | 310492 | 359728 | 15.197 | 20.48 | 2.796 | 3.154 | 0.359 | 12.913 | 5/16 | 288 | | | |
| HS3401 | 340-10 | 13.386 | + 0 / -0.005 | 10.250 | 10.963 | 24 | M20 | 362 | 392088 | 462391 | 16.063 | 22.44 | 3.032 | 3.464 | 0.432 | 13.700 | 5/16 | 409 | | | |
| HS3501 | 350-10 | 13.780 | + 0 / -0.005 | 10.875 | 11.285 | 24 | M20 | 362 | 432685 | 474097 | 17.008 | 22.84 | 3.150 | 3.544 | 0.395 | 14.488 | 5/16 | 429 | | | |
| HS3601 | 360-10 | 14.173 | + 0 / -0.005 | 11.250 | 11.608 | 24 | M20 | 362 | 451405 | 487702 | 17.008 | 23.23 | 3.150 | 3.544 | 0.395 | 14.488 | 5/16 | 449 | | | |
| HS3801 | 380-10 | 14.961 | + 0 / -0.005 | 11.500 | 12.253 | 20 | M24 | 620 | 535005 | 623051 | 18.031 | 25.40 | 3.229 | 3.624 | 0.396 | 15.276 | 5/16 | 526 | | | |
| HS3901 | 390-10 | 15.354 | + 0 / -0.005 | 12.250 | 12.575 | 21 | M24 | 620 | 633184 | 673847 | 18.425 | 25.99 | 3.327 | 3.722 | 0.396 | 15.629 | 3/8 | 572 | | | |
| HS4201 | 420-10 | 16.535 | + 0 / -0.006 | 12.500 | 13.543 | 24 | M24 | 620 | 685493 | 829666 | 19.843 | 27.17 | 3.720 | 4.117 | 0.397 | 16.929 | 3/8 | 630 | | | |
| HS4401 | 440-10 | 17.323 | + 0 / -0.006 | 13.500 | 14.187 | 24 | M24 | 620 | 768743 | 852536 | 20.748 | 29.53 | 3.977 | 4.467 | 0.491 | 17.716 | 3/8 | 835 | | | |
| HS4601 | 460-10 | 18.110 | + 0 / -0.006 | 14.125 | 14.832 | 28 | M24 | 620 | 934194 | 1051580 | 21.535 | 30.32 | 3.977 | 4.467 | 0.491 | 18.425 | 3/8 | 924 | | | |
| HS4801 | 480-10 | 18.898 | + 0 / -0.006 | 14.750 | 15.477 | 30 | M24 | 620 | 1047086 | 1176357 | 22.441 | 31.50 | 4.292 | 4.786 | 0.495 | 19.291 | 1/2 | 1110 | | | |
| HS5001 | 500-10 | 19.685 | + 0 / -0.006 | 15.375 | 16.122 | 24 | M27 | 922 | 1169590 | 1310148 | 23.228 | 33.46 | 4.292 | 4.786 | 0.495 | 19.999 | 1/2 | 1265 | | | |

Specifications for Web Clearance Holes (diameter in inches)

| Screw Size | M5 | M6 | M8 | M10 | M12 | M16 | M20 | M24 | M27 |
|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Split Shrink Disc | 0.281 | 0.328 | 0.406 | 0.500 | 0.594 | 0.750 | 0.906 | 1.063 | 1.188 |
| Half Shrink Disc HT | 0.219 | 0.266 | 0.359 | 0.438 | 0.531 | 0.719 | 0.875 | 1.031 | 1.156 |

Table 1

Notes:




- Screw length must be determined based on your X dimension. Please consult Applications Engineering.
- Inner rings of all shrink discs are supplied with one lengthwise slit.
- Shrink discs are available for shafts up to 40" diameter and in a variety of special designs.
- Maximum shaft sizes listed for Shrink Disc Series SD10 and SD30 reflect equal section moduli of shaft and hub (maximum shaft diameter = $\sqrt{1.22T}$).
- Larger shrink discs for shafts up to 40" diameter are available on request.

For Series SD10, SD20 and SD30

| Shaft Sizes (inch) | | Maximum Diametrical Clearance Between Shaft and Hub Bore |
|--------------------|---------|--|
| > | ≤ | |
| | 1 1/8 | 0.0010 |
| 1 1/8 | 1 15/16 | 0.0015 |
| 1 15/16 | 4 3/4 | 0.0020 |
| 4 3/4 | 7 | 0.0030 |
| 7 | 10 | 0.0040 |
| 10 | 14 | 0.0050 |
| 14 | | 0.0060 |

B-LOC® Half Shrink Discs

B-LOC® Shrink Disc Half



Dimension X is required when ordering Half Shrink Disc Type HT. See Table I at bottom left for web clearance hole data.

SD10 – Half SD – Standard Duty

| Type HC Part Number | Type HT Part Number | Size | SD bore (Hub OD) | | Shaft Diameter Range | | Locking Screws | | | M _a | | M _t | | A (inch) | D (inch) | L (inch) | H _i (inch) | e (inch) | d ₁ (inch) | R (inch) | Ship wt (lb) |
|---------------------|---------------------|--------|------------------|-------------------------|----------------------|---------------|----------------|-----------|---------|------------------------|---------------------------------|----------------|----------------|----------|----------|----------|-----------------------|----------|-----------------------|----------|--------------|
| | | | d (inch) | T _i d (inch) | ds-MIN (inch) | ds-MAX (inch) | Qty | HC Size | HT Size | Install Torque (ft lb) | Max. Transmitted Torque (ft lb) | ds-MIN (ft lb) | ds-MAX (ft lb) | | | | | | | | |
| HHC0241 | HHT0241 | 24-10 | 0.945 | + 0 / -0.002 | 0.625 | 0.774 | 6 | M5 x 16 | M5 | 3.6 | 69 | 139 | 1.417 | 1.97 | 0.374 | 0.453 | 0.080 | 1.023 | 1/16 | 0.3 | |
| HHC0301 | HHT0301 | 30-10 | 1.181 | + 0 / -0.002 | 0.750 | 0.967 | 7 | M5 x 18 | M5 | 3.6 | 89 | 204 | 1.732 | 2.36 | 0.413 | 0.493 | 0.081 | 1.259 | 1/16 | 0.4 | |
| HHC0361 | HHT0361 | 36-10 | 1.417 | + 0 / -0.002 | 0.875 | 1.161 | 5 | M6 x 20 | M6 | 8.7 | 158 | 333 | 2.047 | 2.83 | 0.448 | 0.533 | 0.085 | 1.496 | 1/16 | 0.6 | |
| HHC0441 | HHT0441 | 44-10 | 1.732 | + 0 / -0.002 | 1.125 | 1.419 | 7 | M6 x 20 | M6 | 8.7 | 342 | 599 | 2.402 | 3.15 | 0.492 | 0.568 | 0.077 | 1.850 | 1/16 | 0.8 | |
| HHC0501 | HHT0501 | 50-10 | 1.969 | + 0 / -0.002 | 1.375 | 1.612 | 8 | M6 x 22 | M6 | 8.7 | 482 | 783 | 2.756 | 3.54 | 0.531 | 0.608 | 0.077 | 2.086 | 1/16 | 1 | |
| HHC0551 | HHT0551 | 55-10 | 2.165 | + 0 / -0.002 | 1.500 | 1.773 | 8 | M6 x 25 | M6 | 8.7 | 507 | 854 | 2.953 | 3.94 | 0.551 | 0.668 | 0.118 | 2.283 | 3/32 | 1.4 | |
| HHC0621 | HHT0621 | 62-10 | 2.441 | + 0 / -0.002 | 1.750 | 1.999 | 10 | M6 x 25 | M6 | 8.7 | 859 | 1188 | 3.386 | 4.33 | 0.551 | 0.668 | 0.118 | 2.598 | 3/32 | 1.6 | |
| HHC0681 | HHT0681 | 68-10 | 2.677 | + 0 / -0.002 | 1.875 | 2.193 | 10 | M6 x 25 | M6 | 8.7 | 880 | 1303 | 3.386 | 4.53 | 0.551 | 0.668 | 0.118 | 2.834 | 3/32 | 1.6 | |
| HHC0751 | HHT0751 | 75-10 | 2.953 | + 0 / -0.002 | 2.125 | 2.418 | 7 | M8 x 25 | M8 | 22 | 1396 | 2029 | 3.937 | 5.43 | 0.689 | 0.807 | 0.118 | 3.110 | 1/8 | 2.6 | |
| HHC0801 | HHT0801 | 80-10 | 3.150 | + 0 / -0.002 | 2.375 | 2.580 | 7 | M8 x 25 | M8 | 22 | 1708 | 2166 | 3.937 | 5.71 | 0.689 | 0.807 | 0.118 | 3.307 | 1/8 | 2.8 | |
| HHC0901 | HHT0901 | 90-10 | 3.543 | + 0 / -0.004 | 2.500 | 2.902 | 10 | M8 x 30 | M8 | 22 | 2376 | 3570 | 4.488 | 6.10 | 0.788 | 0.942 | 0.155 | 3.700 | 1/8 | 4 | |
| HHC0951 | HHT0951 | 95-10 | 3.740 | + 0 / -0.004 | 2.750 | 3.063 | 12 | M8 x 30 | M8 | 22 | 3416 | 4554 | 4.882 | 6.69 | 0.866 | 1.042 | 0.176 | 4.094 | 1/8 | 6 | |
| HHC1001 | HHT1001 | 100-10 | 3.937 | + 0 / -0.004 | 2.875 | 3.224 | 12 | M8 x 35 | M8 | 22 | 3530 | 4793 | 4.882 | 6.69 | 0.866 | 1.042 | 0.176 | 4.094 | 1/8 | 6 | |
| HHC1101 | HHT1101 | 110-10 | 4.331 | + 0 / -0.004 | 3.125 | 3.547 | 9 | M10 x 40 | M10 | 44 | 4507 | 6301 | 5.354 | 7.28 | 0.965 | 1.162 | 0.198 | 4.488 | 1/8 | 7 | |
| HHC1251 | HHT1251 | 125-10 | 4.921 | + 0 / -0.004 | 3.500 | 4.031 | 12 | M10 x 40 | M10 | 44 | 6855 | 9770 | 6.299 | 8.46 | 1.024 | 1.217 | 0.194 | 5.275 | 1/8 | 11 | |
| HHC1401 | HHT1401 | 140-10 | 5.512 | + 0 / -0.004 | 4.000 | 4.514 | 10 | M12 x 45 | M12 | 74 | 9824 | 13220 | 6.890 | 9.06 | 1.103 | 1.337 | 0.235 | 5.708 | 3/16 | 13 | |
| HHC1551 | HHT1551 | 155-10 | 6.102 | + 0 / -0.004 | 4.500 | 4.998 | 12 | M12 x 50 | M12 | 74 | 13758 | 17025 | 7.559 | 10.36 | 1.181 | 1.417 | 0.236 | 6.496 | 3/16 | 17 | |
| HHC1651 | HHT1651 | 165-10 | 6.496 | + 0 / -0.004 | 4.875 | 5.320 | 8 | M16 x 55 | M16 | 185 | 18869 | 23568 | 8.268 | 11.42 | 1.299 | 1.532 | 0.233 | 6.889 | 3/16 | 24 | |
| HHC1751 | HHT1751 | 175-10 | 6.890 | + 0 / -0.004 | 5.250 | 5.643 | 8 | M16 x 55 | M16 | 185 | 20810 | 25003 | 8.661 | 11.81 | 1.299 | 1.532 | 0.233 | 7.283 | 3/16 | 25 | |
| HHC1851 | HHT1851 | 185-10 | 7.283 | + 0 / -0.004 | 5.625 | 5.965 | 10 | M16 x 65 | M16 | 185 | 28401 | 32983 | 9.291 | 12.99 | 1.595 | 1.867 | 0.273 | 7.677 | 3/16 | 39 | |
| HHC1951 | HHT1951 | 195-10 | 7.677 | + 0 / -0.004 | 5.875 | 6.288 | 12 | M16 x 65 | M16 | 185 | 35954 | 42463 | 9.685 | 13.78 | 1.595 | 1.867 | 0.273 | 8.110 | 3/16 | 44 | |
| HHC2001 | HHT2001 | 200-10 | 7.874 | + 0 / -0.004 | 6.250 | 6.449 | 12 | M16 x 65 | M16 | 185 | 40337 | 43548 | 9.685 | 13.78 | 1.595 | 1.867 | 0.273 | 8.110 | 3/16 | 43 | |
| HHC2201 | HHT2201 | 220-10 | 8.661 | + 0 / -0.004 | 6.375 | 7.094 | 15 | M16 x 80 | M16 | 185 | 46115 | 58213 | 10.630 | 14.57 | 2.027 | 2.325 | 0.298 | 8.897 | 1/4 | 57 | |
| HHC2401 | HHT2401 | 240-10 | 9.449 | + 0 / -0.004 | 7.000 | 7.739 | 12 | M20 x 80 | M20 | 362 | 65323 | 80909 | 11.614 | 15.95 | 2.106 | 2.405 | 0.299 | 9.763 | 1/4 | 72 | |
| HHC2601 | HHT2601 | 260-10 | 10.236 | + 0 / -0.004 | 7.625 | 8.383 | 14 | M20 x 90 | M20 | 362 | 81099 | 102632 | 12.638 | 16.93 | 2.323 | 2.640 | 0.318 | 10.551 | 1/4 | 89 | |
| HHC2801 | HHT2801 | 280-10 | 11.024 | + 0 / -0.005 | 8.375 | 9.028 | 16 | M20 x 100 | M20 | 362 | 105291 | 126689 | 13.622 | 18.11 | 2.638 | 2.994 | 0.356 | 11.338 | 5/16 | 115 | |
| HHC3001 | HHT3001 | 300-10 | 11.811 | + 0 / -0.005 | 9.000 | 9.673 | 18 | M20 x 100 | M20 | 362 | 128639 | 153375 | 14.331 | 19.10 | 2.796 | 3.154 | 0.359 | 12.125 | 5/16 | 133 | |
| HHC3201 | HHT3201 | 320-10 | 12.598 | + 0 / -0.005 | 9.625 | 10.318 | 20 | M20 x 100 | M20 | 362 | 155246 | 179864 | 15.197 | 20.48 | 2.796 | 3.154 | 0.359 | 12.913 | 5/16 | 153 | |
| HHC3401 | HHT3401 | 340-10 | 13.386 | + 0 / -0.005 | 10.250 | 10.963 | 24 | M20 x 110 | M20 | 362 | 196044 | 231196 | 16.063 | 22.44 | 3.032 | 3.464 | 0.432 | 13.700 | 5/16 | 209 | |
| HHC3501 | HHT3501 | 350-10 | 13.780 | + 0 / -0.005 | 10.875 | 11.285 | 24 | M20 x 110 | M20 | 362 | 216343 | 237049 | 17.008 | 22.84 | 3.150 | 3.544 | 0.395 | 14.488 | 5/16 | 220 | |
| HHC3601 | HHT3601 | 360-10 | 14.173 | + 0 / -0.005 | 11.250 | 11.608 | 24 | M20 x 110 | M20 | 362 | 225703 | 243851 | 17.008 | 23.23 | 3.150 | 3.544 | 0.395 | 14.488 | 5/16 | 225 | |
| HHC3801 | HHT3801 | 380-10 | 14.961 | + 0 / -0.005 | 11.500 | 12.253 | 20 | M24 x 120 | M24 | 620 | 267503 | 311526 | 18.031 | 25.40 | 3.229 | 3.624 | 0.396 | 15.276 | 5/16 | 292 | |
| HHC3901 | HHT3901 | 390-10 | 15.354 | + 0 / -0.005 | 12.250 | 12.575 | 21 | M24 x 120 | M24 | 620 | 316592 | 336924 | 18.425 | 25.99 | 3.327 | 3.722 | 0.396 | 15.629 | 3/8 | 305 | |
| HHC4201 | HHT4201 | 420-10 | 16.535 | + 0 / -0.006 | 12.500 | 13.543 | 24 | M24 x 130 | M24 | 620 | 342747 | 414833 | 19.843 | 27.17 | 3.720 | 4.117 | 0.397 | 16.929 | 3/8 | 364 | |
| HHC4401 | HHT4401 | 440-10 | 17.323 | + 0 / -0.006 | 13.500 | 14.187 | 24 | M24 x 130 | M24 | 620 | 384372 | 426268 | 20.748 | 29.53 | 3.977 | 4.467 | 0.491 | 17.716 | 3/8 | 467 | |
| HHC4601 | HHT4601 | 460-10 | 18.110 | + 0 / -0.006 | 14.125 | 14.832 | 28 | M24 x 130 | M24 | 620 | 467097 | 525790 | 21.535 | 30.32 | 3.977 | 4.467 | 0.491 | 18.425 | 3/8 | 483 | |
| HHC4801 | HHT4801 | 480-10 | 18.898 | + 0 / -0.006 | 14.750 | 15.477 | 30 | M24 x 150 | M24 | 620 | 523543 | 588179 | 22.441 | 31.50 | 4.292 | 4.786 | 0.495 | 19.291 | 1/2 | 555 | |
| HHC5001 | HHT5001 | 500-10 | 19.685 | + 0 / -0.006 | 15.375 | 16.122 | 24 | M27 x 150 | M27 | 922 | 584795 | 655074 | 23.228 | 33.46 | 4.292 | 4.786 | 0.495 | 19.999 | 1/2 | 626 | |

Specifications for Web Clearance Holes (diameter in inches)

| Screw Size | M5 | M6 | M8 | M10 | M12 | M16 | M20 | M24 | M27 |
|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Split Shrink Disc | 0.281 | 0.328 | 0.406 | 0.500 | 0.594 | 0.750 | 0.906 | 1.063 | 1.188 |
| Half Shrink Disc HT | 0.219 | 0.266 | 0.359 | 0.438 | 0.531 | 0.719 | 0.875 | 1.031 | 1.156 |

Table I

Notes:

- Type HT: Screw length must be determined based on your X dimension. Please consult Applications Engineering.
- Inner rings of all shrink discs are supplied with one lengthwise slit.
- Shrink discs are available for shafts up to 40" diameter and in a variety of special designs.
- Maximum shaft sizes listed for Shrink Disc Series SD10 and SD30 reflect equal section moduli of shaft and hub (maximum shaft diameter = $\frac{d}{1.221}$).
- Larger shrink discs for shafts up to 40" diameter are available on request.


For Series SD10, SD20 and SD30

| Shaft Sizes (inch) | | Maximum Diametrical Clearance Between Shaft and Hub Bore |
|--------------------|---------|--|
| > | ≤ | |
| | 1 1/8 | 0.0010 |
| 1 1/8 | 1 15/16 | 0.0015 |
| 1 15/16 | 4 3/4 | 0.0020 |
| 4 3/4 | 7 | 0.0030 |
| 7 | 10 | 0.0040 |
| 10 | 14 | 0.0050 |
| 14 | | 0.0060 |

B-LOC® Single Taper Shrink Discs (SD40)

We also offer SD40 Single Taper Shrink Discs as an alternative to SD10, SD20 & SD30 Double Taper Shrink Discs. The SD40 units have the following attributes:

- **External locking device**
- **Simpler two piece design**
- **Integrated removal holes**
- **Provides extremely concentric and well-balanced mechanical interference fit**



The advantages of the SD40 over the SD10, SD20 and SD30 include:

- No torque wrench needed.* Simply tighten the screws in clockwise sequence, using several passes, until the front faces of the flange and of the outer ring are aligned
- Save up to 80% of mounting time if using a powered tool
- High transmissible torque
- Aligning the two flanges (flush mounted) ensures concentricity, reducing the need for dynamic balancing

Note: Dynamic fit pressures vary between Single Taper and Double Taper shrink discs, as this is based on effective contact length. This should be taken into consideration.

* A torque wrench is recommended for best performance.

For assistance or more information on B-LOC Single Taper Shrink Discs, contact Fenner Drives Applications Engineering group at AE@fennerdrives.com.

B-LOC® WK Rigid Couplings


DESIGN FEATURES

External keyless locking devices that simultaneously transmit high torques and bending moments that allow your drive to be overhung shaft mounted.

- Keyless, rigid, zero backlash coupling.
- Transmits high torque and bending moments.
- Eliminates the need for costly mounting brackets and structural support.
- Compact, double taper design with self-releasing tapers for easy removal.
- Exceptional concentricity.
- Installs right over existing keyways and splines.
- Not affected by shock or reversing loads.

WORKING PRINCIPLE

Drawing the two tapered collars together with the integrated tightening screws, generates radial forces that squeeze the inner ring tightly to the two shafts. The inner ring acts as a press fit sleeve, transmitting torque, thrust, and even bending loads from one shaft to the other.



TORQUE

M_t = rated torque capacity of one B-LOC® WK Coupling with all screws tightened to specified torque M_a as listed in specifications.

THRUST

T_h = transmissible thrust, determined by using the following equation:

$$T_h = \frac{2 \times M_t}{d} \quad \text{where: } d = \text{shaft diameter} \\ M_t = \text{rated torque capacity}$$

TORQUE AND THRUST COMBINED

Simultaneous transmission of torque and thrust requires calculating a resultant torque:

$$M_{t_{res}} = \sqrt{T^2 + \left(\frac{F \times d}{2}\right)^2} \quad \text{where: } T = \text{peak drive torque} \\ F = \text{peak thrust load} \\ d = \text{shaft diameter}$$

Select a unit where $M_t \geq M_{t_{res}}$

BENDING MOMENTS

WK Couplings will generally transmit a continuous bending moment equal to 25% of rated torque capacity M_t .

RELEASABILITY

Since the tapers of a B-LOC WK Coupling are self-releasing, loosening the locking screws results in releasing the shafts from the coupling. Care needs to be used by loosening each screw gradually such that the screw tension remains relatively equal on all screws.

MATERIAL

WK Coupling inner rings are manufactured from high-carbon steel. Outer rings are made from forged and heat treated alloy steel.

LUBRICANTS


WK Couplings are supplied with molybdenum disulphide based lubricant applied to the tapers and to the locking screw threads and head contact areas. The bore of WK Couplings are supplied lightly oiled and should only be used with oil supplied on the unit.

SHAFT AND HUB MATERIAL


Listed specifications assume shaft material with a yield point of at least 45 ksi (310 N/mm²).

LENGTH OF FIT

Shaft engagement inside the WK Coupling must be equal for both shafts and the gap between the shafts should not exceed 5% of the shaft diameter.




- ✗ Requires bulky frame work and supports
- ✗ Shaft misalignment issues necessitate the use of flexible couplings
- ✗ Fretted and corroded flexible couplings complicate disassembly
- ✗ Higher total cost



- ✓ Shaft mount completely eliminates shaft misalignment and frame work
- ✓ Simple torque arm prevents motor rotation
- ✓ Keyless mechanical shrink fit never corrodes to the shaft and disassembles easily
- ✓ Compact design allows for smaller drive footprint
- ✓ Lower overall cost

Plan View



CALCULATIONS **DESIGN TIPS**

Once you have selected your WK Rigid Coupling, apply the following calculations to verify that it is suitable for your application. Please reference Plan View above.

1. M_t = published max rated torque capacity of B-LOC® WK Rigid Coupling = _____ ft-lb
2. $M_{D_{MAX}}$ = maximum drive torque (stall torque where applicable) = _____ ft-lb
3. W = weight of the overhung shaft mounted drive = _____ lb
4. R = length of the torque arm = _____ ft
5. F_{TA} = torque arm reaction force = $M_{D_{MAX}} \div R$ = _____ lb
6. M_b = bending moment at the coupling
NOTE: M_b must be $< 0.25 \times M_t$

TORQUE ARM OPTIONS

Straight Torque Arm

$$M_b = (W \times X_1) + (F_{TA} \times X_2) = \text{_____ ft-lb}$$

Bent Torque Arm

$$M_b = (W \times X_1) + (F_{TA} \times X_3) = \text{_____ ft-lb}$$

Double Torque Arm

$$M_b = (W \times X_1) = \text{_____ ft-lb}$$

7. M_{rb} = resultant (torque & bending) = $\sqrt{(M_{D_{MAX}})^2 + (2 \times M_b)^2} = \text{_____ ft-lb}$
NOTE: M_{rb} must be $< M_t$

8. If the NOTES in steps 6 and 7 are both satisfied, the B-LOC WK Rigid Coupling is recommended for your application.

- For any WK Coupling design or engineering questions, contact a Fenner Drives Applications Engineer at AE@fennerdrives.com.
- Shaft mounting creates bending moments in the system; coupling, shafts, bearings etc., must be designed to handle these bending moments.
- Torque arm design and placement can be used to counteract or minimize bending moments in the system.
- Torque arm and arm stop(s) must be adequately designed to handle the forces generated by the motor.
- To achieve up to a 20% increase in coupling load capacity, using a non-petroleum based solvent, clean the shafts and coupling bore to produce a completely lubricant free interface.
- WK Couplings can typically join shafts of different sizes up to a ratio of 2:1. For shaft ratios greater than this, please contact a Fenner Drives Applications Engineer.
- WK Couplings are not recommended for applications in which motor and driven component are rigidly mounted.

The calculations on this page assume worst case placement of torque arm.
To optimize design contact a Fenner Drives Applications Engineer at AE@fennerdrives.com.

B-LOC® WK Rigid Couplings

B-LOC®
WK
SERIES




Metric hex head locking screws grade 10.9. (See M_a for install torque.)



TOLERANCE (T_L)

$T_L = .003"$ for shafts up to 1"
.006" for shafts over 1"

d = Shaft diameter machined to $d+0/-T_L$



Shaft engagement equal for both ends with gap not exceeding 5% of shaft diameter.




WK Couplings can be manufactured to accommodate different shaft diameters; this can also be accomplished using an adaptor sleeve.

WK Couplings are also available in all common metric shaft/bore diameters

WK Series

| Part Number | Type | d (in) | D (in) | H (in) | L (in) | e (in) | d ₁ (in) | A (in) | Locking Screws | | M _a | M _t | Ship wt (lb) |
|-------------|--------|---------|--------|--------|--------|--------|---------------------|--------|----------------|----------|------------------------|--------------------------------------|--------------|
| | | | | | | | | | Qty | Size | Install Torque (ft lb) | Maximum Transmissible Torque (ft lb) | |
| | | | | | | | | | | | | | |
| HWK0152010 | WK 15 | 5/8 | 2.047 | 1.339 | 1.181 | 0.079 | 0.827 | 1.378 | 3 | M6 x 30 | 8.7 | 132 | 0.9 |
| HWK0152011 | | 11/16 | | | | | | | | | | 145 | |
| HWK0152012 | | 3/4 | | | | | | | | | | 158 | |
| HWK0202013 | WK 20 | 13/16 | 2.362 | 1.575 | 1.339 | 0.118 | 1.024 | 1.614 | 5 | M6 x 35 | 8.7 | 286 | 1.4 |
| HWK0202014 | | 7/8 | | | | | | | | | | 308 | |
| HWK0202015 | | 15/16 | | | | | | | | | | 330 | |
| HWK0252100 | WK 25 | 1 | 2.598 | 1.732 | 1.496 | 0.118 | 1.260 | 1.890 | 7 | M6 x 35 | 8.7 | 492 | 1.8 |
| HWK0252101 | | 1 1/16 | | | | | | | | | | 523 | |
| HWK0252102 | | 1 1/8 | | | | | | | | | | 554 | |
| HWK0302103 | WK 30 | 1 3/16 | 2.992 | 1.890 | 1.654 | 0.118 | 1.496 | 2.126 | 8 | M6 x 40 | 8.7 | 668 | 2.7 |
| HWK0302104 | | 1 1/4 | | | | | | | | | | 703 | |
| HWK0302106 | | 1 3/8 | | | | | | | | | | 774 | |
| HWK0402107 | WK 40 | 1 7/16 | 3.780 | 2.205 | 1.969 | 0.118 | 1.850 | 2.638 | 7 | M8 x 45 | 22 | 1371 | 5 |
| HWK0402108 | | 1 1/2 | | | | | | | | | | 1430 | |
| HWK0402110 | | 1 5/8 | | | | | | | | | | 1550 | |
| HWK0402111 | | 1 11/16 | | | | | | | | | | 1609 | |
| HWK0402112 | | 1 3/4 | | | | | | | | | | 1669 | |
| HWK0502114 | WK 50 | 1 7/8 | 4.409 | 2.676 | 2.362 | 0.157 | 2.283 | 3.150 | 10 | M8 x 50 | 22 | 2554 | 8 |
| HWK0502115 | | 1 15/16 | | | | | | | | | | 2639 | |
| HWK0502200 | | 2 | | | | | | | | | | 2724 | |
| HWK0502202 | | 2 1/8 | | | | | | | | | | 2895 | |
| HWK0602203 | WK 60 | 2 3/16 | 4.724 | 3.071 | 2.756 | 0.157 | 2.598 | 3.504 | 12 | M8 x 55 | 22 | 3576 | 10 |
| HWK0602204 | | 2 1/4 | | | | | | | | | | 3678 | |
| HWK0602206 | | 2 3/8 | | | | | | | | | | 3882 | |
| HWK0602207 | | 2 7/16 | | | | | | | | | | 3984 | |
| HWK0602208 | | 2 1/2 | | | | | | | | | | 4087 | |
| HWK0702209 | WK 70 | 2 9/16 | 5.826 | 3.464 | 3.150 | 0.157 | 3.110 | 4.173 | 12 | M10 x 65 | 44 | 6642 | 19 |
| HWK0702210 | | 2 5/8 | | | | | | | | | | 6804 | |
| HWK0702211 | | 2 11/16 | | | | | | | | | | 6966 | |
| HWK0702212 | | 2 3/4 | | | | | | | | | | 7128 | |
| HWK0702214 | | 2 7/8 | | | | | | | | | | 7452 | |
| HWK0802215 | WK 80 | 2 15/16 | 6.693 | 4.095 | 3.701 | 0.197 | 3.701 | 4.961 | 10 | M12 x 80 | 74 | 9128 | 28 |
| HWK0802300 | | 3 | | | | | | | | | | 9323 | |
| HWK0802302 | | 3 1/8 | | | | | | | | | | 9711 | |
| HWK0802304 | | 3 1/4 | | | | | | | | | | 10099 | |
| HWK0802306 | | 3 3/8 | | | | | | | | | | 10488 | |
| HWK0902307 | WK 90 | 3 7/16 | 7.283 | 4.567 | 4.173 | 0.197 | 4.094 | 5.433 | 12 | M12 x 80 | 74 | 12819 | 36 |
| HWK0902308 | | 3 1/2 | | | | | | | | | | 13052 | |
| HWK0902310 | | 3 5/8 | | | | | | | | | | 13518 | |
| HWK0902312 | | 3 3/4 | | | | | | | | | | 13984 | |
| HWK0902314 | | 3 7/8 | | | | | | | | | | 14450 | |
| HWK1002315 | WK 100 | 3 15/16 | 7.756 | 4.960 | 4.488 | 0.236 | 4.488 | 5.866 | 15 | M12 x 90 | 74 | 18354 | 43 |
| HWK1002400 | | 4 | | | | | | | | | | 18645 | |
| HWK1002404 | | 4 1/4 | | | | | | | | | | 19810 | |

If your application requires increased torque transmission and/or thrust, solvent clean the interface between the bore of the WK unit and the shaft to produce an oil free connection. This in turn will result in up to a 20% increase in M_t and T_H performance values. Contact Fenner Drives Applications Engineering for additional details at AE@fennerdrives.com.



WE SOLVE PROBLEMS

Count on Fenner Drives. We've got the right product for your application.

With over 100 years of manufacturing, technical and commercial expertise, Fenner Drives is a global leader in value-adding, problem-solving products for conveying and power transmission applications. Recognized widely for our expertise and innovation, we blend reliability, quality and value in our products while providing unsurpassed technical support and service.

Visit us at www.fennerdrives.com



www.fennerdrives.com

US and Canada • 1 800 243 3374

Latin America • 1 717 665 2421

Europe, Asia, Australia and Africa • +44 0 870 757 7007



Information subject to change without prior notification. Visit www.fennerdrives.com/catalogs for the most current information.



PULLEYS, SPROCKETS &
TENSIONERS



PowerMax™ **T-Max®**




The PowerMax™ line of idler pulleys and sprockets offers superior composite design for years of successful service. PowerMax Idler Pulleys and Sprockets are available in a wide range of sizes for flat, round and V-belts and industry standard pitch chains. They are perfect for use as high-speed idlers on conveyors, packaging equipment, lawn and garden equipment, floor cleaning machines and in many other power transmission applications.



When used in power transmission drives, all V-belts and roller chains will elongate significantly over time if not properly maintained. This can cause energy losses for belt and chain drives. In addition, incorrect belt or chain tension will lead to increased downtime, lower equipment productivity and inflated maintenance costs. To achieve optimum drive performance, correct drive belt or chain tension must be maintained. The solution? A self-adjusting T-Max® Tensioner from Fenner Drives. T-Max automatic tensioners eliminate the need for regular manual retensioning of drives. The risk of inadvertently over-tensioning drive components is avoided and overall drive operating efficiency is enhanced.

Count on Fenner Drives®. We've got the right product for your application.

With over 100 years of manufacturing, technical and commercial expertise, Fenner Drives is a global leader in value-adding, problem-solving products for conveying and power transmission applications. Recognized widely for our expertise and innovation, we blend reliability, quality and value in our products while providing unsurpassed technical support and service.



INDEX

TMax
BELT & CHAIN TENSIONERS



| | |
|--|----------|
| TMax | 4 |
| Rotary Belt and Chain Tensioners | 4-5 |
| Linear Chain Tensioners | 6 |
| Tensioners, Pulleys and Sprockets Assemblies | 7 |

PowerMax
PULLEYS & IDLERS



| | |
|--|----------|
| PowerMax | 8 |
| Engineering Data | 8 |
| Belt Pulleys and Idlers | 9-10 |
| Pulleys, Carriage Roller and Sprockets | 11 |
| Mounting Adapters and Pillow Blocks | 12 |



T-Max Belt & Chain Tensioners

Automatically take up the slack and avoid the risk of over-tensioning drive components to enhance overall drive operating efficiency.


- Constructed from high-quality materials for proven durability
- Wide range of tensioners to handle single and multiple strand belt and chain drives
- Available in linear and rotary (light-duty, medium and heavy-duty) series
- A range of sizes and mounting styles available to best fit your application



T-Max® Belt & Chain Tensioners


ROTARY BELT & CHAIN TENSIONERS

RT1000 Series *†




| Part Number | Dimensions (inches) | | | | | | | | | Rotation (degrees) | Force ‡ (lbs) | | |
|-------------|---------------------|------|------|------|------|------|--------|--------|------|---|---------------|----|----|
| | A | B | C | D | E | F | G | H | I | | | | |
| RT1001 | 3.50 | 0.29 | 0.59 | 2.76 | 5.37 | 1.15 | 3/8-16 | 3/8-16 | 1.45 | 15 | 16 | | |
| | | | | | | | | | | 30 | 23 | | |
| | | | | | | | | | | 45 | 30 | | |
| RT1003 | 3.50 | 0.29 | 0.59 | 2.76 | 5.37 | 1.15 | 0.40 | 3/8-16 | 1.45 | 15 | 16 | | |
| | | | | | | | | | | 30 | 23 | | |
| | | | | | | | | | | 45 | 30 | | |
| RT1054ZF | 3.50 | 0.29 | 0.59 | 2.76 | 5.37 | 1.15 | 3/8-16 | 3/8-16 | 1.45 | 15 | 16 | | |
| | | | | | | | | | | Zerk fitted to apply grease to the spring cavity. | | 30 | 23 |
| | | | | | | | | | | 45 | 30 | | |
| RT1056ZF | 3.50 | 0.29 | 0.59 | 2.76 | 5.37 | 1.15 | 3/8-16 | 3/8-16 | 1.45 | 15 | 16 | | |
| | | | | | | | | | | Zerk fitted to apply grease to the shaft area. | | 30 | 23 |
| | | | | | | | | | | 45 | 30 | | |

RT1600 Series *†




| Part Number | Dimensions (inches) | | | | | | | | | Rotation (degrees) | Force ‡ (lbs) |
|-------------|---------------------|------|------|------|------|------|--------|--------|------|--------------------|---------------|
| | A | B | C | D | E | F | G | H | I | | |
| RT1601-L | 6.37 | 0.29 | 0.59 | 2.76 | 8.24 | 1.12 | 3/8-16 | 3/8-16 | 1.45 | 15 | 10 |
| | | | | | | | | | | 30 | 13 |
| | | | | | | | | | | 45 | 16 |
| RT1603-L | 6.37 | 0.29 | 0.59 | 2.76 | 8.24 | 1.12 | 0.40 | 3/8-16 | 1.45 | 15 | 10 |
| | | | | | | | | | | 30 | 13 |
| | | | | | | | | | | 45 | 16 |
| RT1601 | 6.37 | 0.29 | 0.59 | 2.76 | 8.24 | 1.12 | 3/8-16 | 3/8-16 | 1.45 | 15 | 20 |
| | | | | | | | | | | 25 | 23 |
| | | | | | | | | | | 35 | 26 |
| RT1603 | 6.37 | 0.29 | 0.59 | 2.76 | 8.24 | 1.12 | 0.40 | 3/8-16 | 1.45 | 15 | 20 |
| | | | | | | | | | | 25 | 23 |
| | | | | | | | | | | 35 | 26 |

RT3000 Series *




| Part Number | Dimensions (inches) | | | | | | | | Rotation (degrees) | Force ‡ (lbs) |
|-------------|---------------------|------|------|------|------|------|--------|------|--------------------|---------------|
| | A | B | C | D | E | F | G | H | | |
| RT3000 | 4.50 | 0.28 | 1.35 | 3.34 | 6.92 | 1.50 | 3/8-16 | 0.51 | 0 - 70 | 0 - 42 |
| RT3001 | 4.50 | 0.28 | 1.35 | 3.34 | 6.92 | 1.50 | 0.40 | 0.51 | 0 - 70 | 0 - 42 |

RT4100 Series *†



| Part Number | Dimensions (inches) | | | | | | | | | | | | | Rotation (degrees) | Force ‡ (lbs) |
|-------------|---------------------|------|------|------|------|------|----------|------|------|------|------|------|------|--------------------|---------------|
| | A | A1 | B | C | D | E | G | H | I | J | K | M | M1 | | |
| RT4100 | 5.40 | 4.50 | 0.47 | 1.19 | 4.00 | 8.58 | 1/2 - 13 | 0.51 | 2.60 | 2.15 | 2.46 | 2.35 | 3.25 | 0 - 85 | 0 - 85 |
| RT4101 | 5.40 | 4.50 | N/A | 1.19 | 4.00 | 8.58 | 0.51 | 0.51 | 2.60 | 2.15 | 2.46 | 2.35 | 3.25 | 0 - 85 | 0 - 85 |

RT4900 Series *†



| Part Number | Dimensions (inches) | | | | | | | | | | Rotation § (degrees) | Force § (lbs) |
|-------------|---------------------|------|------|------|------|----------|------|------|------|--------|----------------------|---------------|
| | A | B | C | D | E | G | H | I | K | | | |
| RT4900 | 5.40 | N/A | 2.37 | 4.00 | 8.58 | 0.51 | 0.51 | 2.60 | 2.46 | 0 - 85 | 0 - 70 | |
| RT4902 | 5.40 | 0.47 | 2.37 | 4.00 | 8.58 | 1/2 - 13 | 0.51 | 2.60 | 2.46 | 0 - 85 | 0 - 70 | |

* Maximum load no more than 1½" distance from front face of tensioner arm to centerline of idler.

† Requires a fixed head, hook style spanner wrench for tensioning (supplied with unit).

‡ Dimension A: 1° rotation = .83 lb. force.

Dimension A1: 1° rotation = 1 lb. force. All forces (lbs.) are nominal.


§ 1° rotation = .83 lb. force. All forces (lbs.) are nominal.

TMAX TENSIONER BRACKET



| Part Number | Bracket Compatible with | Base Compatible with |
|-------------|------------------------------|--|
| B1265 | T-MAX RT1000 T-MAX RT3000 | NEMA 48, 56, 143T IEC 63, 71, 80, 90s |


CT Series: CT1100, CT2100 & CT3100†



| Series | Tensioner Body Dimensions* | | | | | | | | Travel (in) | Force ‡ (lbs) |
|-------------|----------------------------|------|------|------|-----|------|-----|------|----------------|------------------|
| | A | B | C | D | E | G | H | K | | |
| INCH | | | | | | | | | | |
| CT11XX | 2.31 | 0.98 | 1.82 | 2.91 | 5.6 | 0.41 | 5.5 | 0.46 | 1.05 | 15 - 40 |
| CT21XX | 2.95 | 1.18 | 2.27 | 3.52 | 6.4 | 0.49 | 5.5 | 0.45 | 1.20 | 20 - 60 |
| CT31XX | 3.54 | 1.35 | 2.91 | 4.25 | 7.5 | 0.53 | 5.5 | 0.49 | 1.50 | 45 - 100 |

| Single Chain | | | Double Chain | | | Triple Chain | | | Travel (in) | Force ‡ (lbs) |
|---------------|-------|------|--------------|-------|------|--------------|-------|------|----------------|------------------|
| Part Number | Chain | M* | Part Number | Chain | N* | Part Number | Chain | O* | | |
| INCH | | | | | | | | | | |
| CT1101-L | #35 | 0.79 | CT1103-L | #35 | 0.79 | CT1105-L | #35 | 0.98 | 1.05 | 5 - 30 |
| CT1101 | #35 | 0.79 | CT1103 | #35 | 0.79 | CT1105 | #35 | 0.98 | 1.05 | 15 - 40 |
| CT1102 | #40 | 0.79 | CT1104 | #40 | 0.79 | CT1106 | #40 | 1.37 | 1.05 | 15 - 40 |
| CT2101 | #50 | 0.87 | CT2103 | #50 | 0.98 | CT2105 | #50 | 1.75 | 1.20 | 20 - 60 |
| CT2102 | #60 | 0.87 | CT2104 | #60 | 1.37 | | | | 1.20 | 20 - 60 |
| CT3101 | #80 | 0.98 | CT3103 | #80 | 1.75 | | | | 1.50 | 45 - 100 |
| CT3102 | #100 | 0.98 | | | | | | | 1.50 | 45 - 100 |
| CT3102-H | #100 | 0.98 | | | | | | | 1.00 | 30 - 200 |
| CT3196 | #81X | 2.15 | | | | | | | 1.50 | 45 - 100 |
| METRIC | | | | | | | | | | |
| CT1111-L | 06B | 20 | CT1113-L | 06B | 20 | | | | 27 | 22 - 133 |
| CT1111 | 06B | 20 | CT1113 | 06B | 20 | | | | 27 | 67 - 178 |
| CT1112 | 08B | 20 | CT1114 | 08B | 20 | | | | 27 | 67 - 178 |
| CT2111 | 10B | 22 | CT2112 | 10B | 25 | | | | 31 | 89 - 267 |
| CT2109 | 12B | 22 | CT2110 | 12B | 35 | | | | 31 | 89 - 267 |
| CT3111 | 16B | 25 | CT3113 | 16B | 44 | | | | 38 | 200 - 445 |
| CT3112 | 20B | 25 | | | | | | | 38 | 200 - 445 |
| CT3112-H | 20B | 25 | | | | | | | 25 | 134 - 890 |

CT Series: CT1200, CT2200 & CT3200†



| Series | Tensioner Body Dimensions* | | | | | | | | Travel (in) | Force ‡ (lbs) |
|-------------|----------------------------|------|------|------|------|------|-----|------|----------------|------------------|
| | A | B | C | D | E | G | H | K | | |
| INCH | | | | | | | | | | |
| CT12XX | 2.31 | 0.98 | 1.82 | 2.91 | 5.47 | 0.41 | 3 | 0.46 | 1.05 | 15 - 40 |
| CT22XX | 2.95 | 1.18 | 2.27 | 3.52 | 6.47 | 0.49 | 3.5 | 0.45 | 1.20 | 20 - 60 |

| Single Chain | | | Double Chain | | | Triple Chain | | | Travel (in) | Force ‡ (lbs) |
|---------------|-------|------|--------------|-------|------|--------------|-------|------|----------------|------------------|
| Part Number | Chain | M* | Part Number | Chain | N* | Part Number | Chain | O* | | |
| INCH | | | | | | | | | | |
| CT1201-L | #35 | 1.00 | CT1203-L | #35 | 0.79 | CT1205-L | #35 | 0.98 | 1.05 | 5 - 30 |
| CT1201 | #35 | 1.00 | CT1203 | #35 | 0.79 | CT1205 | #35 | 0.98 | 1.05 | 15 - 40 |
| CT1202 | #40 | 1.00 | CT1204 | #40 | 0.79 | CT1206 | #40 | 1.37 | 1.05 | 15 - 40 |
| CT2201 | #50 | 1.00 | CT2203 | #50 | 0.98 | CT2205 | #50 | 1.75 | 1.20 | 20 - 60 |
| CT2202 | #60 | 1.00 | CT2204 | #60 | 1.37 | | | | 1.20 | 20 - 60 |
| CT3201 | #80 | 0.98 | CT3203 | #80 | 1.75 | | | | 1.50 | 45 - 100 |
| CT3202 | #100 | 0.98 | | | | | | | 1.50 | 45 - 100 |
| CT3202-H | #100 | 0.98 | | | | | | | 1.00 | 30 - 200 |
| METRIC | | | | | | | | | | |
| CT1211-L | 06B | 20 | CT1213-L | 06B | 20 | | | | 27 | 22 - 133 |
| CT1211 | 06B | 20 | CT1213 | 06B | 20 | | | | 27 | 67 - 178 |
| CT1212 | 08B | 20 | CT1214 | 08B | 20 | | | | 27 | 67 - 178 |
| CT2208 | 10B | 22 | CT2209 | 10B | 25 | | | | 31 | 89 - 267 |
| CT2206 | 12B | 22 | CT2207 | 12B | 35 | | | | 31 | 89 - 267 |
| CT3211 | 16B | 25 | CT3213 | 16B | 44 | | | | 38 | 200 - 445 |
| CT3212 | 20B | 25 | | | | | | | 38 | 200 - 445 |
| CT3212-H | 20B | 25 | | | | | | | 25 | 134 - 890 |

* Inch dimensions are in inches; metric dimensions are in millimeters.

† These tensioners can be used on chain sizes up to ANSI #160 or BS/DIN #24B.

Contact Fenner Drives Applications Engineering group at AE@fennerdrives.com for head dimensions.

‡ All forces are nominal.

T-Max® Tensioner/Pulley Assembly



| Assembly Part Number | Component | Component Part Number | | |
|-----------------------|-----------|-----------------------|----------------------|---|
| A Section Belt | | | | |
| FS0578 | Tensioner | RT1001 | Force Range: 0-30 lb | |
| | Pulley | VA3001 | 3" OD | |
| FS0581ZF | Tensioner | RT1001 | Force Range: 0-30 lb | Zerk fitted to apply grease to the spring cavity. |
| | Pulley | VA3001 | 3" OD | |
| FS0667ZF | Tensioner | RT1001-L | Force Range: 0-30 lb | Zerk fitted to apply grease to the shaft area. |
| | Pulley | VX3012 | 3" OD | |
| FS0524 | Tensioner | RT3001 | Force Range: 0-42 lb | |
| | Pulley | VA3001 | 3" OD | |

T-Max Tensioner/Pulley Assembly




| Assembly Part Number | Component | Component Part Number | | |
|-----------------------|-----------|-----------------------|----------------------|--|
| B Section Belt | | | | |
| FS0566 | Tensioner | RT3001 | Force Range: 0-42 lb | |
| | Pulley | VA5001 | 5" OD | |
| FS0608 | Tensioner | RT3000 | Force Range: 0-42 lb | |
| | Pulley | VX0285 | 4" OD Double Groove | |

T-Max Tensioner/Sprocket Assemblies

| Assembly Part Number | Component | Component Part Number | Rotation (Degrees) | Force (lbs) |
|----------------------|--------------------|-----------------------|--------------------|-------------|
| #35 Chain | | | | |
| FS0142 | Tensioner Sprocket | RT1001 CS3502 | 15 | 16 |
| | | | 30 | 23 |
| | | | 45 | 30 |
| FS0658 | Tensioner Sprocket | RT1601-L CS3502 | 15 | 10 |
| | | | 30 | 13 |
| | | | 45 | 16 |
| #40 Chain | | | | |
| FS0651 | Tensioner Sprocket | RT1001 CS4002 | 15 | 16 |
| | | | 30 | 23 |
| | | | 45 | 30 |
| FS0652 | Tensioner Sprocket | RT1601 CS4002 | 15 | 20 |
| | | | 25 | 23 |
| | | | 35 | 26 |
| FS0644 | Tensioner Sprocket | RT1601-L CS4002 | 15 | 10 |
| | | | 30 | 13 |
| | | | 45 | 16 |
| FS0557 | Tensioner Sprocket | RT3001 CS4002 | 0 - 70 | 0 - 42 |

| Assembly Part Number | Component | Component Part Number | Rotation (Degrees) | Force (lbs) |
|----------------------|--------------------|-----------------------|--------------------|-------------|
| #50 Chain | | | | |
| FS0653 | Tensioner Sprocket | RT1001 CS5002 | 15 | 16 |
| | | | 30 | 23 |
| | | | 45 | 30 |
| FS0654 | Tensioner Sprocket | RT1601 CS5002 | 15 | 20 |
| | | | 25 | 23 |
| | | | 35 | 26 |
| FS0659 | Tensioner Sprocket | RT1601-L CS5002 | 15 | 10 |
| | | | 30 | 13 |
| | | | 45 | 16 |
| FS0567 | Tensioner Sprocket | RT3001 CS5002 | 0 - 70 | 0 - 42 |
| #60 Chain | | | | |
| FS0655 | Tensioner Sprocket | RT1001 CS6002 | 15 | 16 |
| | | | 30 | 23 |
| | | | 45 | 30 |
| FS0656 | Tensioner Sprocket | RT1601 CS6002 | 15 | 20 |
| | | | 25 | 23 |
| | | | 35 | 26 |
| FS0568 | Tensioner Sprocket | RT3001 CS6002 | 0 - 70 | 0 - 42 |
| #80 Chain | | | | |
| FS0657 | Tensioner Sprocket | RT1001 CS8002 | 15 | 16 |
| | | | 30 | 23 |
| | | | 45 | 30 |



Fenner Drives has several tensioner/sprocket assemblies not shown here. Contact us for availability.

The PowerMax Advantage

Fenner Drives is the industry leader in molded composite solutions for industrial power transmission and material handling applications. PowerMax composite products are used where dependability counts most.

- High-strength glass reinforced composite idlers and pulleys are available in a wide range of sizes for flat, round and V-belts.
- Our composite products are a lightweight, corrosion resistant alternative to steel, aluminum and cast iron.



PowerMax™ Engineering Data

Almost all PowerMax Pulleys use precision 6203-2RS chrome-alloy steel radial ball bearings (exceptions are noted). These bearings meet all ABEC-1 standards. Our bearings utilize two rubber wiping seals to keep the grease in and contaminants out. See chart for standard load ratings.

| Bearing Properties | |
|---------------------|---|
| Type | 6203-2RS |
| Seals | Rubber Wiping |
| Fit | ABEC-1 "C4" Internal Clearance |
| Lubrication | Mobil Polyrex EM or equivalent NLGI No. 2 (30% +/- 5% Fill) |
| Service Temperature | -20° – 350°F (-30° – 180°C) |
| Basic Dynamic Load | 2150 lbs. (9563N) |

| 6203 Radial Load Ratings | | | | | | | | | | | |
|--------------------------|------|------|------|------|------|------|------|------|------|------|------|
| Speed (RPM) | 33 | 100 | 200 | 300 | 500 | 1000 | 1500 | 1800 | 2500 | 3600 | 5000 |
| Load (lbs) | 2141 | 1480 | 1175 | 1026 | 866 | 687 | 601 | 565 | 507 | 449 | 402 |
| Load (N) | 9523 | 6583 | 5226 | 4566 | 3852 | 3058 | 2672 | 2514 | 2254 | 1996 | 1789 |

Load Ratings based on 500 HR minimum L₁₀ life.

Bearings are also available in stainless steel, with trash seals and shields.

Bearing Life

How long a bearing will last in an application depends on two variables: first, the bearing's physical properties (material, design, method of manufacture); and second, the conditions of operation (load, speed, temperature, lubrication). Although it is not possible to predict the exact life of a bearing, the designer can calculate the "L10 Life" of a bearing. L10 is the life, in hours or revolutions, that 90% of a group of bearings will complete or exceed. The equations for calculating L10 life are:

- Revolutions: $L_{10} = \left(\frac{C}{P}\right)^3 \times 10^6$

- Hours: $L_{10} = \left(\frac{C}{P}\right)^3 \times \frac{16667}{N}$

- Where:

L₁₀ = Rating Life

C = Basic Dynamic Capacity

P = Radial Load in lbs.

N = Speed in RPM


Material Properties

Fenner Drives uses engineering composites, which ensure the highest level of performance and consistent strength. Our standard material is 33% glass reinforced nylon 6/6. The combination of high strength, temperature resistance and abrasion resistance makes nylon a versatile engineering thermoplastic.

| 33% GLASS-REINFORCED NYLON 6/6, dry as molded | | |
|---|-----------|--------------------------------|
| PROPERTY | ASTM CODE | VALUE |
| Tensile Strength at Break | D638 | 20,000 psi |
| Flexural Modulus | D790 | 1,300,000 psi |
| Heat Deflection Temp @ 264 psi | D648 | 480°F (249°C) |
| Continuous Service Temp. (Min. – Max.) | N/A | 32° to 225°F (0° to 107°C) |
| Izod Impact Strength (notched 1/8") | D256 | 1.3 to 1.8 ft.-lb/in. of notch |


Data listed was generated using molded specimens tested under standard conditions. Many of the mechanical properties can be influenced by processing conditions, environmental factors and the application of stress. Therefore, this data characterizes typical production material, and should not be used either to establish specification limits or alone as the basis for engineering design.

PowerMax™ V Belt Idlers




| Part Number | Type | Grooves | Dimensions (inches) | | | | | Belt Size | Bearing Type | Bore Sizes |
|-------------|------|---------|---------------------|------|------|------|------|-----------|--------------|------------|
| | | | A | B | C | D | E | | | |
| VA3001† | 1 | 1 | 3.0 | 2.0 | 0.5 | 0.7 | 0.81 | A | 6203-2RS | 17mm |
| VA3002 | 1 | 1 | 3.0 | 1.84 | 0.63 | 0.78 | 0.81 | B | 6203-2RS | 17mm |
| VA4001 | 1 | 1 | 3.98 | 2.99 | 0.5 | 0.7 | 0.81 | A | 6203-2RS | 17mm |
| VA4002 | 1 | 1 | 4.0 | 2.84 | 0.64 | 0.86 | 0.81 | B | 6203-2RS | 17mm |
| VA5001 | 1 | 1 | 5.04 | 3.84 | 0.65 | 0.8 | 0.82 | B | 6203-2RS | 17mm |
| VA6001 | 1 | 1 | 6.03 | 5.12 | 0.5 | 0.72 | 0.81 | A | 6203-2RS | 17mm |
| VA6250† | 1 | 1 | 6.25 | 5.0 | 0.61 | 0.95 | 0.72 | A/B | 6203-2RS | 17mm |
| VA7501 | 1 | 1 | 7.5 | 6.6 | 0.54 | 0.72 | 0.75 | A | 6203-2RS | 17mm |
| V2B6280 | 2 | 2 | 6.28 | 5.18 | 0.64 | 1.72 | 1.85 | B/SV | 6203-2RS | .510/.520 |
| V3B6280 | 2 | 3 | 6.28 | 5.18 | 0.64 | 2.44 | 2.58 | B/SV | 6203-2RS | .510/.520 |
| V4B6280 | 2 | 4 | 6.28 | 5.18 | 0.64 | 3.16 | 3.33 | B/SV | 6203-2RS | .510/.520 |

PowerMax V Belt Idlers, Single Flange



| Part Number | Dimensions (inches) | | | | | Belt Size | Bearing Type | Bore Sizes |
|-------------|---------------------|------|------|------|------|-----------|--------------|------------|
| | A | B | C | D | E | | | |
| VA3600 | 3.6 | 2.84 | 0.59 | 0.84 | 0.8 | B | 6203-2RS | 17mm |
| VA4130* | 4.13 | 3.23 | 0.58 | 0.86 | 0.81 | B | 6203-2RS | 17mm |


PowerMax Flat Belt Idlers, Flangeless



| Part Number | Type | Crown | Dimensions (inches) | | | | | Belt Size | Bearing Type | Bore Size |
|-------------|------|-------|---------------------|------|---|------|------|-----------|--------------|-----------|
| | | | A | B | C | D | E | | | |
| FA2009† | 1 | No | — | 2.0 | — | 1.0 | 0.47 | 13/16" | 6203-2RS | 17mm |
| FA2010† | 1 | No | — | 1.98 | — | 0.75 | 0.47 | 5/8" | 6203-2DD | 17mm |
| FA2700† | 1 | No | — | 2.71 | — | 1.05 | 0.67 | 7/8" | 6203-2RS | 17mm |
| FA2900* | 1 | Yes | — | 2.91 | — | 1.22 | 0.76 | 1" | 6203-2RS | 17mm |
| FA3003* | 1 | No | — | 2.96 | — | 1.09 | 0.76 | 29/32" | 6203-2RS | 17mm |
| FA3250† | 1 | No | — | 3.2 | — | 1.01 | 0.67 | 13/16" | 6203-2DD | 17mm |
| FA4502 | 1 | No | — | 4.5 | — | 1.21 | 0.82 | 1" | 6203-2RS | 17mm |
| FX0002‡ | 1 | Yes | — | 2.33 | — | 1.39 | — | 11/8" | 6205-2RS | 1" |


* Minimums may apply
 † Insertion molded bearing
 ‡ Special 1" bore bearing with extended inner-race

PowerMax™ Flat Belt Idlers, 2 Flange




| Part Number | Type | Crown | Dimensions (inches) | | | | | Belt Size | Bearing Type | Bore Size |
|-------------|------|-------|---------------------|------|------|------|------|-----------|--------------|-----------|
| | | | A | B | C | D | E | | | |
| FA2001† | 1 | Yes | 2.07 | 1.88 | 1.37 | 1.54 | 0.47 | 1 1/8" | 6203-2RS | 17mm |
| FA2002† | 1 | Yes | 2.35 | 1.99 | 0.98 | 1.15 | 0.47 | 7/8" | 6203-2RS | 17mm |
| FA2003 | 1 | No | 2.76 | 1.94 | 0.82 | 1.15 | 0.75 | 5/8" | 6203-2RS | 17mm |
| FA2501† | 1 | No | 2.48 | 1.97 | 1.55 | 1.85 | 0.72 | 1 1/4" | 6203-2RS | 17mm |
| FA2750† | 1 | Yes | 2.75 | 1.97 | 1.09 | 1.4 | 0.67 | 29/32" | 6203-2RS | 17mm |
| FA2751 | 1 | Yes | 2.75 | 2.52 | 1 | 1.22 | 0.8 | 13/16" | 6203-2RS | 17mm |
| FA3002 | 1 | Yes | 3 | 2.5 | 1.02 | 1.31 | 0.76 | 7/8" | 6203-2RS | 17mm |
| FA3251† | 1 | Yes | 3.24 | 2.97 | 1.04 | 1.2 | 0.67 | 7/8" | 6203-2DD | 17mm |
| FA3301† | 1 | Yes | 3.38 | 2.97 | 1.38 | 1.67 | 0.78 | 1 1/8" | 6203-2RS | 17mm |
| FA3501 | 1 | Yes | 3.5 | 3 | 0.77 | 1.09 | 0.76 | 5/8" | 6203-2RS | 17mm |
| FA3502 | 1 | Yes | 3.5 | 3 | 1 | 1.22 | 0.76 | 13/16" | 6203-2RS | 17mm |
| FA3504 | 1 | Yes | 3.48 | 2.98 | 0.69 | 0.9 | 0.76 | 1/2" | 6203-2RS | 17mm |
| FA3750† | 1 | Yes | 3.75 | 2.96 | 1.09 | 1.38 | 0.67 | 29/32" | 6203-2RS | 17mm |
| FA3751† | 1 | Yes | 3.8 | 3.25 | 1.03 | 1.24 | 0.67 | 7/8" | 6203-2RS | 17mm |
| FA4501 | 1 | Yes | 4.5 | 4 | 1.09 | 1.39 | 0.76 | 29/32" | 6203-2RS | 17mm |
| FA4750† | 1 | Yes | 4.75 | 3.96 | 1.09 | 1.38 | 0.67 | 29/32" | 6203-2RS | 17mm |
| FA5501† | 1 | Yes | 5.56 | 5.03 | 1.02 | 1.29 | 0.72 | 7/8" | 6203-2RS | 17mm |
| FX0001‡ | 1 | Yes | 2.75 | 2.37 | 1.07 | 1.39 | — | 29/32" | 6205-2RS | 1" |
| F1B6280 | 2 | No | 6.28 | 6 | 1.22 | 1.63 | 1.63 | 1" | 6203-2RS | .510/.520 |
| F2B6280 | 2 | No | 6.28 | 6 | 2.1 | 2.5 | 2.5 | 2" | 6203-2RS | .510/.520 |
| F3B6280 | 2 | No | 6.28 | 6 | 2.91 | 3.31 | 3.31 | 2 3/4" | 6203-2RS | .510/.520 |
| F4B6280 | 2 | No | 6.28 | 6 | 3.85 | 4.25 | 4.25 | 3 3/4" | 6203-2RS | .510/.520 |

PowerMax Round Belt Idlers




| Part Number | Dimensions (inches) | | | | | Radius | Maximum Belt Size | Bearing Type | Bore Sizes |
|--------------|---------------------|------|------|------|------|--------|-------------------|--------------|------------|
| | A | B | C | D | E | | | | |
| RA3001 | 3.05 | 2.45 | 0.4 | 0.61 | 0.81 | 0.19 | 3/8" | 6203-2RS | 17mm |
| RA3002 | 3.05 | 2.45 | 0.42 | 0.61 | 0.63 | 0.21 | 13/32" | 6203-2RS | 17mm |
| RA3501 | 3.5 | 2.75 | 0.53 | 0.76 | 0.76 | 0.26 | 1/2" | 6203-2RS | 17mm |
| RA3502 | 3.5 | 2.75 | 0.44 | 0.76 | 0.76 | 0.19 | 3/8" | 6203-2RS | 17mm |
| RA4101 | 4.12 | 3.5 | 0.53 | 0.68 | 0.72 | 0.26 | 1/2" | 6203-2RS | 17mm |
| RA4801 | 4.8 | 4 | 0.53 | 1 | 0.77 | 0.28 | 1/2" | 6203-2RS | 17mm |
| RA4802 | 4.82 | 4 | 0.73 | 1.06 | 0.77 | 0.36 | 11/16" | 6203-2RS | 17mm |
| RA5502† | 5.38 | 4.62 | 0.38 | 0.56 | 0.7 | 0.19 | 3/8" | 6203-2RS | 17mm |
| SMALL SERIES | | | | | | | | | |
| RA1850† | 1.84 | 1.39 | 0.4 | 0.63 | 0.63 | 0.16 | 5/16" | 6902-2RS | 15mm |
| RA2540 | 2.54 | 1.9 | 0.44 | 0.63 | 0.63 | 0.16 | 5/16" | 6902-2RS | 15mm |

PowerMax Cable Pulleys



| Part Number | Dimensions (inches) | | | | | Maximum Cable Size | Bearing Type | Bore Size |
|-------------|---------------------|------|------|------|------|--------------------|--------------|-----------|
| | A | B | C | D | E | | | |
| RA2701 | 2.75 | 2.43 | 0.23 | 0.54 | 0.82 | 5/32" | 6203-2RS | 17mm |
| RA3503† | 3.55 | 2.73 | 0.39 | 0.8 | 0.77 | 1/4" | 6203-2RS | 17mm |
| RA3504 | 3.5 | 2.81 | 0.31 | 0.65 | 0.77 | 7/32" | 6203-2RS | 17mm |
| RA4501† | 4.46 | 3.74 | 0.38 | 0.86 | 0.77 | 1/4" | 6203-2RS | 17mm |
| RA4502† | 4.46 | 3.74 | 0.38 | 0.86 | 0.77 | 3/16" | 6203-2RS | 17mm |
| RA5001 | 5 | 4.31 | 0.31 | 0.65 | 0.73 | 3/16" | 6203-2RS | 17mm |
| RA5501† | 5.5 | 4.86 | 0.22 | 0.53 | 0.6 | 5/32" | 6203-2RS | 17mm |
| RA6001 | 6 | 5.2 | 0.4 | 0.8 | 0.8 | 1/4" | 6203-2RS | 17mm |


PowerMax™ Sprockets




Sprocket

| Part Number | Chain # | # Teeth | Nominal O.D. (in) | Pitch Diameter (in) | Dimensions (inches) | | | Bearing Type | Bore Size |
|-------------|---------|---------|-------------------|---------------------|---------------------|------|-------|--------------|-----------|
| | | | | | A | B | C | | |
| CS3502† | 35 | 19 | 2.48 | 2.28 | 0.67 | 1.78 | 0.164 | 6203-2RS | 17mm |
| CS4002† | 40 | 17 | 2.98 | 2.72 | 0.67 | 1.78 | 0.279 | 6203-2RS | 17mm |
| CS4003† | 40 | 17 | 2.98 | 2.72 | 0.67 | 1.78 | 0.279 | 6203-2RS-10 | 5/8" |
| CS4006*† | 40 | 17 | 2.98 | 2.72 | 0.67 | 1.78 | 0.279 | 6203-2RS-12 | 3/4" |
| CS5002† | 50 | 15 | 3.34 | 3.01 | 0.67 | 1.78 | 0.343 | 6203-2RS | 17mm |
| CS5004† | 50 | 15 | 3.34 | 3.01 | 0.67 | 1.78 | 0.343 | 6203-2RS-10 | 5/8" |
| CS5005*† | 50 | 15 | 3.34 | 3.01 | 0.67 | 1.78 | 0.343 | 6203-2RS-12 | 3/4" |
| CS6002† | 60 | 13 | 3.52 | 3.14 | 0.67 | 1.78 | 0.449 | 6203-2RS | 17mm |
| CS6003† | 60 | 13 | 3.52 | 3.14 | 0.67 | 1.78 | 0.449 | 6203-2RS-10 | 5/8" |
| CS6004† | 60 | 13 | 3.52 | 3.14 | 0.67 | 1.78 | 0.449 | 6203-2RS-12 | 3/4" |
| CS8002† | 80 | 12 | 4.39 | 3.86 | 0.67 | 1.78 | 0.58 | 6203-2RS | 17mm |
| CS8003† | 80 | 12 | 4.39 | 3.86 | 0.67 | 1.78 | 0.58 | 6203-2RS-10 | 5/8" |
| CS8004† | 80 | 12 | 4.39 | 3.86 | 0.67 | 1.78 | 0.58 | 6203-2RS-12 | 3/4" |

PowerMax Carriage Rollers




Type 1




Type 2

| Part Number | Type | Dimensions (inches) | | | | Radius | Bore Sizes |
|-------------|------|---------------------|-----|------|------|--------|------------|
| | | A | B | C | D | | |
| RA2002 | 1 | 1.36 | 1.2 | 1.95 | 1.37 | 0.53" | 1/2" |
| RA2004 | 1 | 1.48 | 1.2 | 1.95 | 1.37 | 0.53" | 1/2" |
| RX0219 | 2 | 1.48 | 1.2 | 1.95 | 1.38 | 0.53" | 3/8" |

PowerMax DriveN Pulleys



Type 1



Type 2

| Base Part Number | Type | Dimensions (inches) | | | | Belt Size | Diameter (inches) | | Number Spokes | Spoke Style |
|------------------|------|---------------------|------|------|------|-----------|-------------------|-------|---------------|-------------|
| | | E | F | H | L | | Outside | Datum | | |
| AFD44* | 1 | 0.79 | 0.74 | 2.17 | 1.53 | A/4L | 4.25 | 4 | — | — |
| AFD49 | 1 | 0.79 | 0.74 | 2.17 | 1.53 | A/4L | 4.75 | 4.5 | 4 | I-Beam |
| AFD59 | 1 | 0.79 | 0.74 | 2.17 | 1.53 | A/4L | 5.75 | 5.5 | 4 | I-Beam |
| AFD74 | 1 | 0.79 | 0.74 | 2.17 | 1.53 | A/4L | 7.25 | 7 | 4 | I-Beam |
| AFD84 | 2 | 0.76 | 0.75 | 2.22 | 1.6 | A/4L | 8.25 | 8 | 6 | Cross |
| AFD94 | 2 | 0.76 | 0.75 | 2.22 | 1.6 | A/4L | 9.25 | 9 | 6 | Cross |
| AFD104 | 2 | 0.76 | 0.75 | 2.22 | 1.6 | A/4L | 10.25 | 10 | 6 | Cross |
| AFD112 | 2 | 0.76 | 0.75 | 2.22 | 1.6 | A/4L | 10.98 | 10.73 | 6 | Cross |
| AFD124 | 2 | 0.76 | 0.75 | 2.22 | 1.6 | A/4L | 12.25 | 12 | 6 | I-Beam |

Part Number Ordering Guide

| Shaft Size | Keyseat |
|------------|---------------|
| 5/8", 3/4" | 3/16" x 3/32" |
| 1" | 1/4" x 1/8" |

| Base Part Number | + | Shaft Size | = | Complete Part Number |
|------------------|---|------------|---|----------------------|
| AFD44 | + | 5/8" | = | AFD4458 |
| AFD94 | + | 1" | = | AFD94100 |


Many idlers are, or can be, made into a driven pulley with a 5/8" or 3/4" bore. Please contact Fenner Drives for minimum order quantities, pricing, and availability.

- * Minimums may apply
- † Insertion molded bearing
- ‡ Special 1" bore bearing with extended inner-race

PowerMax™ Mounting Adapters and Pillow Block


THE POWERMAX ADVANTAGE

Clevis Adapters




| Part Number | Dimensions (inches) | | | |
|-------------|---------------------|------|-------|------|
| | A | B | W | C |
| CB0001 | .385 / .395 | 0.26 | 0.472 | 0.5 |
| CB0002 | .385 / .395 | 0.51 | 0.472 | 0.75 |
| CB0003 | .385 / .395 | 0.76 | 0.472 | 1 |
| CB0004 | .510 / .520 | 0.26 | 0.472 | 0.5 |
| CB0005 | .510 / .520 | 0.51 | 0.472 | 0.75 |
| CB0006 | .510 / .520 | 0.76 | 0.472 | 1 |
| CB0015 | .314 / .324 | 0.08 | 0.472 | 0.32 |
| CB0016 | .385 / .395 | 0.17 | 0.472 | 0.41 |
| CB0020* | .314 / .324 | 0.1 | 0.472 | 0.34 |
| CB0023 | .394 / .399 | 0.64 | 0.472 | 0.87 |
| CB0036 | .385 / .395 | 0.7 | 0.472 | 0.94 |
| CB0058 | .385 / .395 | 0.33 | 0.472 | 0.57 |
| CB0100 | .397 / .407 | 0.26 | 0.472 | 0.5 |

Shoulder Adapters



| Part Number | Dimensions (inches) | | | |
|-------------|---------------------|------|-------|------|
| | A | B | W | C |
| SB0001 | .385 / .395 | 0.26 | 0.472 | 0.5 |
| SB0002 | .385 / .395 | 0.51 | 0.472 | 0.75 |
| SB0003 | .385 / .395 | 0.76 | 0.472 | 1 |
| SB0004 | .510 / .520 | 0.26 | 0.472 | 0.5 |
| SB0005 | .510 / .520 | 0.51 | 0.472 | 0.75 |
| SB0006 | .510 / .520 | 0.76 | 0.472 | 1 |
| SB0013 | .385 / .395 | 0.15 | 0.472 | 0.38 |
| SB0018 | .385 / .395 | 0.4 | 0.472 | 0.64 |
| SB0020 | .385 / .395 | 0.59 | 0.472 | 0.83 |
| SB0032 | .385 / .395 | 0.56 | 0.472 | 0.8 |
| SB0033 | .385 / .395 | 0.95 | 0.472 | 1.19 |
| SB0052 | .385 / .395 | 0.71 | 0.472 | 0.95 |
| SB0090 | .255 / .265 | 0.31 | 0.472 | 0.55 |


Bore Reducing Adapters



| Part Number | Dimensions (inches) | |
|-------------|---------------------|-------|
| | A | W |
| RB0001 | .385 / .395 | 0.472 |
| RB0002 | .510 / .520 | 0.472 |
| RB0071 | .474 / .486 | 0.472 |

- * Minimums may apply
- † Insertion molded bearing
- ‡ Special 1" bore bearing with extended inner-race

PowerMax™ Pillow Blocks



| Part Number | Dimensions (inches) | | | | | | | Zerk | Bearing Type | Bore Size |
|-------------|---------------------|--------|-----|-----|-----|-----|------|------|--------------|-----------|
| | A | B | C | D | E | F | G | | | |
| PB1000 | 0.39 | 3.3 | 4.9 | 5.7 | 1.6 | 2.8 | 1.45 | No | SB205-16 | 1" |
| PB1032 | 0.51 | 4.38** | N/A | 5.7 | 1.6 | 2.8 | 1.45 | No | SB205-16 | 1" |
| PB2050 | 0.39 | 3.3 | 4.9 | 5.5 | 1.5 | 2.9 | 1.44 | Yes | SB205-16 | 1" |

NOTE: Also available in the following bore sizes 7/8", 15/16" and 25mm as a non catalog item. Subject to minimum order quantities.

** Dimension (B) is the hole center distance, (A) is the hole diameter

Basic Dynamic Load Rating: 3145 lbf
Static Load Rating: 1750 lbf



www.fennerdrives.com

US and Canada • 1 800 243 3374

Latin America • 1 717 665 2421


Europe, Asia, Australia and Africa • +44 0 870 757 7007



Information subject to change without prior notification. Visit www.fennerdrives.com/catalogs for the most current information.



POWER TRANSMISSION &
CONVEYOR BELTING



POWERTWIST® EAGLE®

Trackstar® *SUPERLINK*® *NUTLINK*®

CONVEYING SOLUTIONS



POWERTWIST MOVE® Conveyor Link Belting

- Install in minutes without dismantling conveyor components – no welding required
- Unaffected by extremes of temperature, water, oils, grease and common chemicals
- Whether your application requires reduced contact surface, high grip, abrasion resistance, non-marking, high temperature, oil, and chemical resistance, there's a Fenner Drives link belt to meet your need



Eagle® Polyurethane Belting

- Comprehensive range of high quality non-reinforced and reinforced belting in round and V profiles; also available with special top surfaces
- Over 400 FDA compliant products
- Custom design capabilities: special profiles, dual durometer, static dissipative, UV stabilized, tracking features, ridged profiles



Trackstar® UHMW Belt & Chain Guides

- Fight friction and reduce costs with long-wearing UHMW belt and chain guides
- Wide range of standard profiles for use in guiding belts, chain and cables
- Available from stock with same-day shipping
- Two-piece guide and channel design simplifies installation and replacement

POWER TRANSMISSION SOLUTIONS




POWERTWIST DRIVE®, SuperTLink®, and NuTLink® V-Belting



- Provide time and cost saving benefits to maintenance engineers and equipment designers
- Longer belt life in even the harshest environments
- Easier, faster installation without tear-downs or struggling with motor bases
- Install on captive drives and fixed center drives
- Make matching sets
- Better drive efficiency due to minimal belt elongation
- Reduced noise, longer bearing life due to low belt vibration

Count on Fenner Drives®. We've got the right product for your application.

With over 100 years of manufacturing, technical and commercial expertise, Fenner Drives is a global leader in value-adding, problem-solving products for conveying and power transmission applications. Recognized widely for our expertise and innovation, we blend reliability, quality and value in our products while providing unsurpassed technical support and service.



INDEX

| | |
|--|------------|
| Belting Selection | 4-5 |
| Power Transmission | 6 |
| POWERWIST® Link Belting | 7 |
| Force Deflection Gauge | 7 |
| SuperTLink® Belting | 8 |
| NuTLink® Belting | 8 |
| Conveying | 9 |
| Engineering Data | 9-15 |
| Eagle® Polyurethane Belting | 16 |
| Round Belting | 16-23 |
| V Belting | 24-27 |
| Flat Belting & Additional Products | 28 |
| Eagle Welding Kits | 29 |
| POWERWIST MOVE® | 30 |
| Round Link & V Link Belting | 30 |
| Trackstar® | 31 |
| Round Belting, V Belting & Flat Belting Guides | 31 |
| Mounting Channels & Guide Rails | 32 |
| Chain Guides | 33-35 |
| Related Items | 35 |

| | | 2 mm | 2.4 mm | 3 mm | 3/32" | 1/8" | 4 mm | 5 mm | 6 mm | 3/16" | 6.3 mm | 7 mm | 8 mm | 9 mm | 5/16" | 9.5 mm | 3/8" | 10 mm | 12 mm | 12.7 mm | 1/2" | 13 mm | 14 mm | 15 mm | 9/16" | 16 mm | 5/8" | 18 mm | 19 mm | 3/4" | 20 mm | | |
|------------------------|-------------------------------|------|--------|------|-------|------|------|------|------|-------|--------|------|------|------|-------|--------|------|-------|-------|---------|------|-------|-------|-------|-------|-------|------|-------|-------|------|-------|---|--|
| Non-Reinforced Belting | POWERTWIST MOVE® Link Belting | | | | | | | | | | | | ● | | ● | | | | | ● | | ● | | | | | | | | ● | | | |
| | Eagle® Blue 80 EC* | ● | | | ● | ● | ● | ● | ● | ● | | | ● | | | ● | ● | ● | | | | | | | | | | | | | | | |
| | Eagle Clear 80 EC* | ○ | | | ○ | ○ | ○ | ○ | ○ | ○ | | | ○ | | | ○ | ○ | ○ | | | | | | | | | | | | | | | |
| | Eagle Blue 80 MD* | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Eagle Opaque 80 | ○ | | | ○ | ○ | ○ | ○ | ○ | ○ | | | ○ | | | ○ | ○ | ○ | | | | | | | ○ | | | | | | | | |
| | Eagle Blue 85* | | | | ● | ● | ● | ● | ● | ● | | | ● | | | ● | ● | ● | | | | | | | ● | | | | | | | | |
| | Eagle Clear 85* | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | | | ○ | | | ○ | ○ | ○ | | | | | | ○ | | | ○ | | | | | | |
| | Eagle Orange 85* | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | ● | | | ● | ● | ● | | | | | | ● | | | ● | | | | | | |
| | Eagle Orange 89 SureConnect™ | | | | | | | | | | | | | | | ● | | | | | | | ● | | | | | | | | | ● | |
| | Eagle Red 85* | | | | ● | ● | | | | | | | | | | | | | | | | | | ● | | | | | | | | | |
| | Eagle Green 89 | ● | | | ● | ● | ● | ● | ● | | | ● | ● | | | ● | ● | ● | | | | | | | ● | | | ● | | | | ● | |
| | Eagle Green 89 T | ● | | | ● | ● | ● | ● | ● | | | ● | ● | | | ● | ● | ● | | | | | | | ● | | | ● | | | | ● | |
| | Eagle Green 89 T SureConnect™ | | | | | | | | | | | | | | | | | | | | | | | | ● | | | ● | | | | ● | |
| | Eagle Red 90 | ● | | | ● | ● | ● | ● | ● | | | ● | ● | ● | | ● | ● | ● | | | | | | ● | | | ● | | | | | | |
| | Eagle Beige 95* | | | | | | | | ● | | | | ● | | | | | ● | | | | | | | ● | | | | | | | | |
| | Eagle Clear 95* | | ○ | ○ | | | ○ | | ○ | | | ○ | | | ○ | | | | | | | | | ○ | | | ○ | | | ○ | | | |
| | Eagle White 40D | | | ○ | ○ | ○ | ○ | | | | | ○ | | | | | | ○ | | | | | | ○ | | | ○ | | | ○ | | | |
| | Eagle Blue 55D | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Eagle Blue 80 EC QC* | | | | | | | ● | ● | | | | ● | | | ● | | | | | | | | | | | | | | | | | |
| | Eagle Blue 85 QC* | | | | | | | ● | ● | | | | ● | | | ● | ● | | | | | | | | | | | | | | | | |
| | Eagle Clear 85 QC* | | | | | | | ○ | ○ | ○ | | | ○ | | | ○ | | | | | | | | ○ | ○ | | | ○ | | | | | |
| | Eagle Red 85 QC | | | | | | | ● | ● | | | | ● | | | ● | ● | | | | | | | ● | | | ● | | | | | | |
| | Eagle Yellow 85 QC* | | | | | | | ● | ● | | | ● | | | | ● | | | | | | | | ● | | | ● | | | | | | |
| Eagle Clear 85 TOR | | | | | | | ○ | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Reinforced | Eagle Orange 85 R* | | | | | | | | ● | ● | | | ● | | ● | ● | ● | ● | | | | | ● | ● | | | | | | | ● | | |
| | Eagle Hyfen 85 R* | | | | | | | ● | | | ● | | | | ● | | | | | | | | | ● | | | ● | | | | | ● | |
| | Eagle Green 89 R | | | | | | | ● | ● | | | ● | ● | | | ● | ● | | | | | | | ● | | | ● | | | | | ● | |
| | Eagle Green 89 RT | | | | | | | ● | ● | | | ● | ● | | | ● | ● | | | | | | | ● | | | ● | | | | | ● | |
| | Eagle Beige 95 R* | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Eagle Can Cable† | | | | | | | | | | | | | | | | ● | | | | | | | | | | | | | | | | |
| Eagle Fabricated Belts | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | |

Abbreviation Key

| | |
|-----|-----------------------------|
| CXF | Co-extruded Flat |
| CXR | Co-extruded Ribbed |
| EC | Regulation (EC) 1935/2004 |
| LCF | Low Coefficient of Friction |
| MD | Metal Detectable |
| PU | PolyUrethane |
| PVC | PolyVinyl Chloride |
| QC | Quick-Connect |

| | |
|------|--------------------------|
| R | Reinforced |
| RCS | Reduced Contact Surface |
| RSGT | Reinforced SuperGrip Top |
| RT | Reinforced Textured |
| SGT | SuperGrip Top |
| T | Textured |
| TOR | Twisted O-Rings |
| TPE | ThermoPlastic Elastomer |

* These belts are FDA compliant (unless cogged).

† Can Cable available in Red 50D LCF, Blue 55D, Blue 55D Aramid, Natural 55D, Green 63D, and Natural 63D.

‡ Eagle Ivory 85 SGT and RSGT available with PVC, PU or TPE top surface.

¶ ISO 1813:1998 inspected and certified by Fenner Drives.

- Not all product in-stock, please call for availability.
- Some diameters and cross sections may be subject to minimum orders. Dimensions are for reference only.
- Flat belting available in Eagle Orange 85. Additional cross sections, colors, and durometers are available.
- Contact Applications Engineering at AE@fennerdrives.com for design assistance.

BELTING SELECTION

V BELTING

6mm x 4mm
8mm x 5mm
10mm x 4mm T-Top
3L
3L T-Top
3L Crown-Top
3L Twin
Z/10
A/13
AA
A Twin
A/13 Lo-Ridge-Top
A/13 Ridge-Top
A/13 Hi-Ridge-Top
B/17
BB
B/17 Ribbed
B/17 Wing-Top
B/17 Ridge-Top
C/22
C/22 Ribbed
C/22 Ridge-Top
D/32
D/32 Ribbed

| 6mm x 4mm | 8mm x 5mm | 10mm x 4mm T-Top | 3L | 3L T-Top | 3L Crown-Top | 3L Twin | Z/10 | A/13 | AA | A Twin | A/13 Lo-Ridge-Top | A/13 Ridge-Top | A/13 Hi-Ridge-Top | B/17 | BB | B/17 Ribbed | B/17 Wing-Top | B/17 Ridge-Top | C/22 | C/22 Ribbed | C/22 Ridge-Top | D/32 | D/32 Ribbed | | |
|-----------|-----------|------------------|----|----------|--------------|---------|------|------|----|--------|-------------------|----------------|-------------------|------|----|-------------|---------------|----------------|------|-------------|----------------|------|-------------|-------------------------------|-------------------------------------|
| | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST MOVE® Link Belting | |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST MOVE Bridge Top™ |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST MOVE SGT PU |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST MOVE SGT PVC |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST MOVE RCS |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST MOVE Friction Top® |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST Antistatic ^{††} |
| | | | | | | | | | | | | | | | | | | | | | | | | | POWERTWIST Roller Drive™ |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle® Blue 80 EC* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Clear 80 EC* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Blue 80 MD* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Opaque 80 |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Blue 85* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Clear 85* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Ivory 85 |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Orange 85* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Red 85* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Green 89 |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Red 90 |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Beige 95* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Clear 95* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle White 40D |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Blue 55D |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Red 85 CXF |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Ivory 85 SGT* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Green 89 SGT PVC |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Red 90 SGT PVC |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle White 40D SGT PVC |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Opaque 80 R |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Orange 85 R* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Hyfen 85 R* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Ivory 85 R |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Green 89 R |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Beige 95 R* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Hyfen 95 R* |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Hyfen 85 CXF/CXR |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Ivory 85 RSGT [‡] |
| | | | | | | | | | | | | | | | | | | | | | | | | | Eagle Fabricated Belts |

Link Belting

Non-Reinforced Belting

Reinforced Belting

POWERTWIST DRIVE®, SuperTLink®, and NuTLink® V-Belting

- Provide time and cost saving benefits to maintenance engineers and equipment designers
- Longer belt life in even the harshest environments
- Easier, faster installation without tear-downs or struggling with motor bases
- Install on captive drives and fixed center drives
- Make matching sets
- Better drive efficiency due to minimal belt elongation
- Reduced noise, longer bearing life due to low belt vibration



| Product | Color | Compliancy | Material | Temperature Range | |
|--------------------------|-----------------|-------------|----------------------------------|-------------------|-------------|
| | | | | °F | °C |
| POWERTWIST DRIVE | Red (classical) | RoHS, Reach | Composite Polyester/Polyurethane | -40 to +240 | -40 to +116 |
| POWERTWIST DRIVE | Blue (wedge) | RoHS, Reach | Composite Polyester/Polyurethane | -40 to +240 | -40 to +116 |
| POWERTWIST Ground Round® | Red | RoHS, Reach | Composite Polyester/Polyurethane | -40 to +240 | -40 to +116 |
| POWERTWIST Antistatic™ * | Blue | RoHS | Composite Polyester/Polyurethane | -40 to +240 | -40 to +116 |

* ISO 1813:1998 inspected and certified by Fenner Drives.



| Product | Color | Compliancy | Material | Temperature Range | |
|-------------|-------|------------|--|-------------------|-------------|
| | | | | °F | °C |
| SuperTLink® | Blue | RoHS | Composite Polyester/Polyurethane Steel Rivets | -40 to +240 | -40 to +116 |

* ISO 1813:1998 inspected and certified by Fenner Drives.



| Product | Color | Compliancy | Material | Temperature Range | |
|----------|--------|------------|--|-------------------|-------------|
| | | | | °F | °C |
| NuTLink® | Orange | RoHS | Composite Polyester/Polyurethane Steel Rivets | -40 to +240 | -40 to +116 |

* ISO 1813:1998 inspected and certified by Fenner Drives.



POWERWIST DRIVE® Link Belting

Classical Cross Section

| | Classical Cross Section | Nominal Width | | Part Numbers | | | | | | Minimum Pulley Ø | | Ride Height Above Rim | | | | |
|-----------------|-------------------------|---------------|----|--------------|-----------|-----------|----------|---------|---------|------------------|---------|-----------------------|----------|----------|---------|---------|
| | | inches | mm | 5' Sleeve | 6' Sleeve | 2m Sleeve | 25' | 100' | 10m | 30m | inches | mm | Min(in.) | Max(in.) | Min(mm) | Max(mm) |
| POWERWIST DRIVE | 3L | 3/8 | | 0418010SL | | | 0405010 | 0408010 | | | 2.00 | | 0.12 | 0.17 | 3.0 | 4.2 |
| POWERWIST DRIVE | Z/10 | | 10 | | | | 04100202 | | | 0410020 | 0418023 | 45 | 0.14 | 0.20 | 3.6 | 5.2 |
| POWERWIST DRIVE | A/4L/13 | 1/2 | 13 | 0418030SL | | 04090502M | 0405030 | 0408030 | 0410030 | 0418033 | 3.00 | 80 | 0.08 | 0.16 | 2.1 | 4.0 |
| POWERWIST DRIVE | B/5L/17 | 5/8 | 17 | | 0418050SL | 04090302M | 0405050 | 0408050 | 0410050 | 0418053 | 5.00 | 125 | 0.14 | 0.22 | 3.4 | 5.6 |
| POWERWIST DRIVE | C/22 | 7/8 | 22 | | | | 0405070 | 0408070 | 0410070 | 0418073 | 9.00 | 229 | 0.07 | 0.22 | 1.8 | 5.6 |

POWERWIST DRIVE® Wedge Link Belting

Wedge

Wedge Cross Section

| POWERWIST DRIVE LINK BELTING | Wedge Cross Section | Nominal Width | | Part Numbers | | | | Minimum Pulley Ø | | Ride Height Above Rim | | | |
|------------------------------|---------------------|---------------|----|--------------|---------|---------|---------|------------------|-----|-----------------------|----------|---------|---------|
| | | inches | mm | 5m | 25' | 100' | 20m | inches | mm | Min(in.) | Max(in.) | Min(mm) | Max(mm) |
| POWERWIST DRIVE | 3V | 3/8 | 10 | | 0460025 | 0460000 | | 2.65 | | 0.18 | 0.30 | 4.5 | 7.5 |
| POWERWIST DRIVE | 5V | 5/8 | 17 | | 0460125 | 0460100 | | 5.5 | | 0.20 | 0.44 | 5.0 | 11.0 |
| POWERWIST DRIVE | SPZ | | 10 | 0460616 | | | 0460666 | | 67 | 0.18 | 0.30 | 4.5 | 7.5 |
| POWERWIST DRIVE | SPA | | 13 | 0460716 | | | 0460766 | | 90 | 0.16 | 0.41 | 4.1 | 10.3 |
| POWERWIST DRIVE | SPB | | 17 | 0460816 | | | 0460866 | | 140 | 0.20 | 0.44 | 5.0 | 11.0 |

POWERWIST® Specialty Link Belting

Double-V Round

Cross Section

| POWERWIST SPECIALTY LINK BELTING | Cross Section | Nominal Width | | Part Numbers | | | | Minimum Pulley Ø | |
|----------------------------------|---------------|---------------|----|--------------|----------|-----------|----------|------------------|-----|
| | | inches | mm | 25' | 100' | 10m | 30m | inches | mm |
| POWERWIST Antistatic™ | A/4L/13 | 1/2 | 13 | 0408505 | 0408501 | 040850010 | 0408500 | 3.00 | 80 |
| POWERWIST Antistatic | B/5L/17 | 5/8 | 17 | 0408605 | 0408601 | 040860010 | 0408600 | 5.00 | 125 |
| POWERWIST Double-V™ | AA | 1/2 | 13 | 0405230 | 0408230 | | 0419230 | 3.00 | 80 |
| POWERWIST Double-V | BB | 5/8 | 17 | 0405250 | 0408250 | | 0419250 | 5.00 | 125 |
| POWERWIST Double-V | CC | 7/8 | 22 | 0405270 | 0408270 | | 0418270 | 9.00 | 229 |
| POWERWIST Ground Round® | 5/16" | 5/16" | 8 | 04051050 | 04081050 | | 04191050 | 2.00 | 51 |
| POWERWIST Ground Round | 3/8" | 3/8" | 10 | 04051060 | 04081060 | | 0419110 | 3.00 | 76 |
| POWERWIST Ground Round | 1/2" | 1/2" | 13 | 04051040 | 04081040 | | 0419120 | 3.00 | 76 |
| POWERWIST Ground Round | 9/16" | 9/16" | 14 | 04051070 | 04081070 | | 04151070 | 5.50 | 140 |
| POWERWIST Ground Round | 3/4" | 3/4" | 19 | | 04081080 | | 0415110 | 8.50 | 216 |



Force Deflection Gauge


| Part Number | Max Belt Deflection (in) | Max Belt Deflection (cm) | Pounds | Kilograms |
|-------------|--------------------------|--------------------------|------------|-----------|
| 5700253 | 0 - 3 in | 0 - 7.5 cm | 0 - 35 lbs | 0 - 16 kg |



SuperTLink® Belting

Wedge Cross Section

| SUPERTLINK BELTING | Wedge Cross Section | Nominal Width | | Part Numbers | | | | Minimum Pulley Ø | | Ride Height Above Rim | | | |
|-------------------------|---------------------|---------------|----|--------------|---------|---------|---------|------------------|-----|-----------------------|----------|---------|---------|
| | | inches | mm | 5m | 25' | 100' | 20m | inches | mm | Min(in.) | Max(in.) | Min(mm) | Max(mm) |
| SuperTLink | 3V | 0.45 | 11 | | 0407025 | 0407100 | | 2.8 | | 0.18 | 0.40 | 4.6 | 10.0 |
| SuperTLink | 5V | 0.66 | 17 | | 0417025 | 0417100 | | 5.5 | | 0.06 | 0.20 | 1.4 | 5.1 |
| SuperTLink | SPZ | | 10 | L02Z5N | | | L02Z20N | | 71 | 0.18 | 0.40 | 4.6 | 10.0 |
| SuperTLink | SPA | | 13 | L02A5N | | | L02A20N | | 90 | 0.14 | 0.36 | 3.6 | 9.1 |
| SuperTLink | SPB | 0.66 | 17 | L02B5 | | | L02B20 | | 140 | 0.06 | 0.20 | 1.4 | 5.1 |
| SuperTLink | SPC | | 22 | L02C5 | | | L02C20 | | 224 | 0.05 | 0.33 | 1.3 | 8.4 |
| TLink Installation Tool | L02NT10 (10pk) | | | | | | | | | | | | |



NuTLink® Belting

Classical Cross Section

| NUTLINK BELTING | Classical Cross Section | Nominal Width | | Part Numbers | | Minimum Pulley Ø | | Ride Height Above Rim | | | |
|-------------------------|-------------------------|---------------|----|--------------|--------|------------------|-----|-----------------------|----------|---------|---------|
| | | inches | mm | 5m | 20m | inches | mm | Min(in.) | Max(in.) | Min(mm) | Max(mm) |
| NuTLink | Z/10 | | 10 | L01Z5 | L01Z20 | | 45 | 0.06 | 0.18 | 1.6 | 4.6 |
| NuTLink | A/13 | 1/2 | 13 | L01A5 | L01A20 | 3.00 | 80 | 0.08 | 0.31 | 2.0 | 7.8 |
| NuTLink | B/17 | 5/8 | 17 | L01B5 | L01B20 | 5.00 | 125 | 0.09 | 0.37 | 2.2 | 9.3 |
| NuTLink | C/22 | 7/8 | 22 | L01C5 | L01C20 | 9.00 | 229 | 0.00 | 0.23 | 0.1 | 5.8 |
| TLink Installation Tool | L02NT10 (10pk) | | | | | | | | | | |

Round Belting

Round belts are commonly run in pulleys with a round groove; see Figure 1a. In the absence of round groove pulleys, they can also be used in V-groove pulleys (Figure 1b). The table at right shows the dimensional data for a round belt used in a V-groove pulley.




Figure 1a




Figure 1b

Note: above dimensions are belt fit in groove under no tension. Dimensions in inches unless otherwise indicated.

| Pulley Size | Pulley Diameter (inches) | Groove Angle | Round Belt | Dimensions (inches) | | |
|-------------|--------------------------|--------------|------------|---------------------|-------|-------|
| | | | | w | a | b |
| 2L | Under 1.50" | 32° | 3/16" | .240 | .010 | .084 |
| 2L | 1.50" to 1.99" O.D. | 34° | 3/16" | .243 | .016 | .078 |
| | | | 1/4" | .243 | .153 | -.028 |
| 2L | 2.00" to 2.50" O.D. | 36° | 3/16" | .246 | .020 | .074 |
| | | | 1/4" | .246 | .151 | -.026 |
| 2L | Over 2.50" O.D. | 38° | 3/16" | .250 | .020 | .074 |
| | | | 1/4" | .250 | .146 | -.021 |
| 3L | Under 2.20" O.D. | 32° | 1/4" | .360 | -.049 | .174 |
| | | | 5/16" | .360 | .094 | .062 |
| 3L | 2.20" to 3.19" O.D. | 34° | 1/4" | .364 | -.043 | .168 |
| | | | 5/16" | .364 | .094 | .062 |
| 3L | 3.20" to 4.20" O.D. | 36° | 1/4" | .368 | -.037 | .062 |
| | | | 5/16" | .368 | .095 | .061 |
| 3L | Over 4.20" O.D. | 38° | 1/4" | .372 | -.031 | .156 |
| | | | 5/16" | .372 | .095 | .061 |
| A/13 | 2.60" to 5.40" D.D. | 34° | 5/16" | .494 | -.118 | .274 |
| | | | 3/8" | .494 | .019 | .168 |
| | | | 1/2" | .494 | .297 | -.047 |
| A/13 | Over 5.40" D.D. | 38° | 5/16" | .504 | -.097 | .253 |
| | | | 3/8" | .504 | .030 | .157 |
| | | | 1/2" | .504 | .286 | .036 |
| B/17 | 4.60" to 7.00" D.D. | 34° | 1/2" | .637 | .062 | .188 |
| | | | 9/16" | .637 | .199 | .082 |
| | | | 5/8" | .637 | .340 | -.027 |
| B/17 | Over 7.00" D.D. | 38° | 1/2" | .650 | .074 | .176 |
| | | | 9/16" | .650 | .200 | .081 |
| | | | 5/8" | .650 | .331 | -.018 |
| C/22 | 7.00" to 7.99" D.D. | 34° | 5/8" | .879 | -.056 | .369 |
| | | | 3/4" | .879 | .218 | .157 |
| C/22 | 8.00" to 12.00" D.D. | 36° | 5/8" | .887 | -.041 | .354 |
| | | | 3/4" | .887 | .222 | .153 |
| C/22 | Over 12.00" D.D. | 38° | 5/8" | .895 | -.027 | .340 |
| | | | 3/4" | .895 | .226 | .149 |

V Belting

V belts in "classical" A, B, C, D and light duty 3L cross sections are designed to fit RMA compliant pulleys as per the groove details illustrated in Figure 2.




Figure 2

| Cross Section | Datum Diameter Range | Groove Angle | b_g (inches) | h_g min (inches) | S_g (inches) | S_e (inches) |
|---------------|----------------------|--------------|----------------|--------------------|----------------|----------------|
| A/13 | Up thru 5.4" | 34° ±0.33° | .494 ±.005 | .460 | .625 ±.025 | .375 +.090 |
| | Over 5.4" | 38° ±0.33° | .504 ±.005 | | | -.062 |
| B/17 | Up thru 7.0" | 34° ±0.33° | .637 ±.006 | .550 | .750 ±.025 | .500 +.120 |
| | Over 7.0" | 38° ±0.33° | .650 ±.006 | | | -.065 |
| C/22 | Up thru 7.99" | 34° ±0.33° | .879 | | | |
| | 8.0" thru 12.0" | 36° ±0.33° | .887 ±.007 | .750 | 1.000 ±.025 | .688 +.160 |
| | Over 12.0" | 38° ±0.33° | .895 | | | -.070 |
| D/32 | Up thru 12.99" | 34° ±0.33° | 1.259 | | | |
| | 13.0" thru 17.0" | 36° ±0.33° | 1.271 ±.008 | 1.020 | 1.438 ±.025 | .875 +.220 |
| | Over 17.0" | 38° ±0.33° | 1.283 | | | -.080 |
| 3L | 2.2" thru 3.1" | 34° ±0.33° | .364 ±.005 | .406 | .500 ±.025 | .313 +.062 |
| | 3.2" thru 4.2" | 36° ±0.33° | | | | -.032 |
| | Over 4.2" | 38° ±0.33° | | | | |

Dimensions in inches unless otherwise indicated.

Flat Belting

All flat belts have a natural tendency to move laterally. Therefore a flat or straight pulley is not recommended, as the belt would walk off the pulley. To keep the belt in the center of the pulley it must have a crown. Figure 3a illustrates a round crown and is the preferred method. A modified round crown as illustrated in Figure 3b is also acceptable. A flat pulley with guide flanges (Figure 3c) is not recommended. Even with the guide flanges the belt will move laterally and potentially could climb up onto them.




Figure 3a




Figure 3b




Figure 3c

Round Belting

Round belts are commonly run in pulleys with a round groove; see Figure 1a. In the absence of round groove pulleys, they can also be used in V-groove pulleys (Figure 1b). The table at right shows the dimensional data for a round belt used in a V-groove pulley.




Figure 1a




Figure 1b

| Pulley Size | Pulley Diameter (mm) | Groove Angle | Round Belt | Dimensions (mm) | | |
|-------------|----------------------|--------------|------------|-----------------|-------|-------|
| | | | | w | a | b |
| Z/10 | Up thru 80mm | 34° | 7 | 9.7 | -0.39 | 3.89 |
| | | | 8 | 9.7 | 1.82 | 2.18 |
| | | | 9.5 | 9.7 | 5.14 | -0.39 |
| Z/10 | Over 80mm | 38° | 7 | 9.7 | 0.17 | 3.34 |
| | | | 8 | 9.7 | 2.19 | 1.81 |
| | | | 9.5 | 9.7 | 5.25 | -0.50 |
| A/13 | Up thru 118mm | 34° | 9.5 | 12.7 | 0.23 | 4.52 |
| | | | 10 | 12.7 | 1.33 | 3.67 |
| | | | 12 | 12.7 | 5.75 | 0.25 |
| A/13 | Over 118mm | 38° | 9.5 | 12.7 | 0.90 | 3.85 |
| | | | 10 | 12.7 | 1.91 | 3.09 |
| | | | 12 | 12.7 | 5.98 | 0.02 |
| B/17 | Up thru 190mm | 34° | 12 | 16.3 | -0.14 | 6.14 |
| | | | 15 | 16.3 | 6.50 | 1.00 |
| | | | 16 | 16.3 | 8.71 | -0.71 |
| B/17 | Over 190mm | 38° | 12 | 16.3 | 0.76 | 5.24 |
| | | | 15 | 16.3 | 6.87 | 0.63 |
| | | | 16 | 16.3 | 8.90 | -0.90 |
| C/22 | Up thru 315mm | 34° | 20 | 22 | 8.22 | 1.78 |
| C/22 | Over 315mm | 38° | 20 | 22 | 9.00 | 1.23 |

Note: above dimensions are belt fit in groove under no tension. Dimensions in millimeters unless otherwise indicated.

V Belting

V belts in "classical" Z/10, A/13, B/17, C/22 and D/32 cross sections are designed to fit ISO and DIN 2215 compliant pulleys as per the groove details illustrated in Figure 2.




Figure 2

| Cross Section | Datum Diameter Range | Groove Angle | b _g (mm) | h _g Min (mm) | S _g (mm) | S _e (mm) |
|---------------|-----------------------------|----------------------|---------------------|-------------------------|---------------------|---------------------|
| Z/10 | Up thru 80mm Over 80mm | 34° ±1° 38° ±1° | 9.7 | 11 | 12 ±0.3 | 8 ±0.6 |
| A/13 | Up thru 118mm Over 118mm | 34° ±1° 38° ±1° | 12.7 | 14 | 15 ±0.3 | 10 ±0.6 |
| B/17 | Up thru 190mm Over 190mm | 34° ±1° 38° ±1° | 16.3 | 18 | 19 ±0.4 | 12.5 ±0.8 |
| C/22 | Up thru 315mm Over 315mm | 34° ±1° 38° ±30' | 22 | 24 | 25.5 ±0.5 | 17 ±1.0 |
| D/32 | Up thru 500mm Over 500mm | 36° ±30' 38° ±30' | 32 | 28 | 37 ±0.6 | 24 ±2.0 |

Dimensions in millimeters unless otherwise indicated.

Flat Belting

All flat belts have a natural tendency to move laterally. Therefore a flat or straight pulley is not recommended, as the belt would walk off the pulley. To keep the belt in the center of the pulley it must have a crown. Figure 3a illustrates a round crown and is the preferred method. A modified round crown as illustrated in Figure 3b is also acceptable. A flat pulley with guide flanges (Figure 3c) is not recommended. Even with the guide flanges the belt will move laterally and potentially could climb up onto them.




Figure 3a

Figure 3b

Figure 3c

Belt Installation Tension

All belts require a certain amount of tension to function properly in the application. The specific installation tension is determined from several factors including belt type, construction and working load. Belt details are in the Technical Data section of this catalog and working load is derived from your application.

Non-Reinforced Belting: When non-reinforced belting is stretched and released, elasticity is the property that brings the material back to its original shape. This “memory” is what gives our non-reinforced belting its self-tensioning properties. When a non-reinforced belt is first installed (stretched) the material does not return to 100% of its original length and continues to lose elasticity over its life span. This loss in elasticity is evident as tension decay. To overcome tension decay effects, a non-reinforced belt requires a relatively high install tension. Installation tensions ranging from 6% to 10% will normally be sufficient for most applications. If higher tensions are required, the application may exceed the belt’s load capacity.

Reinforced Belting: Reinforced belts contain a reinforcing tensile member which increases the belt’s modulus of elasticity. This reduces the belt’s ability to stretch and minimizes tension decay. This allows a reinforced belt to carry a greater load than a non-reinforced belt. Since an endless reinforced belt is essentially a fixed length, it cannot be stretched on like a non-reinforced belt. Consequently, reinforced belts require a mechanical take-up mechanism to apply the appropriate installation tension as well as accommodating any eventual small amount of tension decay that may occur. This mechanism should accommodate at least 4% of the belt’s length.

Belt Installation Length

In this section, we will refer to two different lengths that are defined as follows:

1. Reference Length: The length determined by taking a measuring tape and following the path of the belt around all of the pulleys, or through computer aided design (CAD) techniques. This length may also be obtained from the equation below. Take up mechanisms should be adjusted to the minimum position to allow for maximum adjustment of the belt prior to taking or calculating length. Note: this equation applies to two-pulley drives only.

$$L = 2C + \frac{\pi}{2}(D + d) + \frac{(D - d)^2}{4C}$$

where: L = reference length
 C = center of pulley shaft to center of pulley shaft distance
 D = pitch diameter of large pulley
 d = pitch diameter of small pulley

2. Install Length: The length the belt is made to prior to welding or joining.

Apply the following formulas to determine the Install Length from Reference Length:

Butt weld non-reinforced:

$$\text{Install Length} = \text{Reference Length} \div (1 + \% \text{ tension})$$

Example: Reference Length for a non-reinforced belt is 44" (1120mm), requires 8% tension and will be butt welded. Install Length is calculated on right.

$$\begin{aligned} \text{Install Length} &= 44" \div (1 + 8\%) & \text{Install Length} &= 1120\text{mm} \div (1 + 8\%) \\ &= 44" \div 1.08 & &= 1120\text{mm} \div 1.08 \\ &= 40.7" & &= 1037\text{mm} \end{aligned}$$

Overlap weld reinforced: Install Length = Reference Length + 1.5" (38mm)

Example: Reference Length for a reinforced belt is 44" (1120mm) and will be overlap welded. The overlap weld consumes 1.5" (38mm) of belt length. Install Length is calculated on right.

$$\begin{aligned} \text{Install Length} &= 44" + 1.5" & \text{Install Length} &= 1120\text{mm} + 38\text{mm} \\ &= 45.5" & &= 1158\text{mm} \end{aligned}$$

Butt weld reinforced: Install Length = Reference Length

Example: Reference Length for a reinforced belt is 44" (1120mm) and will be butt welded. The weld consumes a negligible amount of belt length, consequently, Install Length and Reference Length are the same. Install Length is calculated on right.

$$\begin{aligned} \text{Install Length} &= 44" & \text{Install Length} &= 1120\text{mm} \end{aligned}$$

Link Belting: Install length = Reference Length minus (1 - 2%)

Example: Reference Length for a link belt is 44" (1120mm).

Install Length removing 2% is calculated on right.

Remove links to get as close as possible to Install Length.

$$\begin{aligned} \text{Install Length} &= 44" - (44 \times .02) & \text{Install Length} &= 1120\text{mm} - (1120 \times .02) \\ &= 44" - 0.88" & &= 1120\text{mm} - 22.40 \\ &= 43.12" & &= 1097.60\text{mm} \end{aligned}$$

Temperature

The temperature range of polyurethane belting is determined by the thermoplastic resin. Like all thermoplastic resins its physical properties change with changes in temperature. At higher temperatures the material will soften, lose strength and can elongate excessively to the point of premature failure. At lower temperatures the material will become more brittle and stiff which can result in cracking. The temperature ranges are for guidance and listed under each individual belt type in the Material Properties section.

Minimum Pulley Diameter

The most common serious mistake in designing belt drives is the selection of a pulley diameter that is too small. In most cases, non-reinforced belts can operate on smaller diameter pulleys than belts with a reinforcing tensile member. Reinforced belts require a larger pulley diameter to prevent premature flex fatigue failure of the tensile member. Listed under each individual belt type’s technical data is the recommended minimum pulley diameter. Smaller diameters can be used only if a reduction in belt service life is acceptable.

Engineering Data – Selection Procedure, Conveying

- Refer to the Technical Data chart for the belt material and cross section selected.
- Use the following formula that meets your application requirements (Note: if belt supported by rollers use .17 for μ):
 - Horizontal Transport with Slider Bed

$$T_e = W_t \times \mu + B_{wt}$$
 - Horizontal Transport with Slider Bed and Product Accumulation

$$T_e = W_t \times \mu + B_{wt} + A_{wt}$$
 - Incline or Decline Transport with Slider Bed

$$T_e = \frac{W_t}{C} \times (H_t + \mu \times \sqrt{C^2 + H_t^2}) + B_{wt}$$
 - Incline or Decline Transport with Slider Bed and Product Accumulation

$$T_e = \frac{W_t}{C} \times (H_t + \mu \times \sqrt{C^2 + H_t^2}) + B_{wt} + A_{wt}$$
- Determine Tight Tension (T_1).
 Flat and round belts: $T_1 = T_e \times 2$
 V belts: $T_1 = T_e \times 1.25$
- Refer to the Technical Data chart for the material and cross section selected and compare T_1 to the Working Load at maximum % tension. If only one belt is desired, T_1 may not be greater than the Working Load at maximum % tension. If more than one belt is required, divide T_1 by the Working Load at maximum % tension to arrive at number of belts. Round up to the nearest whole number of belts.
- Find load per belt by dividing T_1 by number of belts. From the Technical Data chart, determine the percent installed tension for the load per belt.

Where:

T_e = Effective Tension
 W_t = Total Weight on Conveyor
 C = Conveyor Center Distance
 B_{wt} = Belt weight/unit length $\times C$
 A_{wt} = Accumulating weight $\times \mu'$
 (where μ' is the COF between belt and product)
 H_t = Incline or decline height
 μ = COF on slider bed material from chart

To determine the required belt length, please refer to the "Belt Installation Length" section on the previous page.

Engineering Data – Selection Example

| NON-REINFORCED | | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|------------------|-------------|--------------|-------|------------------|------|--------------------------------|-----|--------|------|--------|------|---------|------|--------|-------|
| Color | Part Number | (in) | (mm) | (in) | (mm) | 4% (N) | | 6% (N) | | 8% (N) | | 10% (N) | | lbs/ft | kg/m |
| Eagle® Orange 85 | L04OG856M | 6 | 152.4 | 1.89 | 48 | 1.7 | 7.7 | 2.7 | 11.8 | 3.5 | 15.8 | 4.4 | 19.4 | 0.023 | 0.034 |
| Eagle Orange 85 | 1032008 | 1/4 | 6.3 | 2 | 51 | 1.9 | 8.6 | 3 | 13.3 | 4 | 17.7 | 4.9 | 21.9 | 0.026 | 0.038 |

| NON-REINFORCED Product | Hardness | FDA Compliant | Coefficient of Friction | | | Contact Temperature Range | |
|------------------------|----------|---------------|-------------------------|-------|------|---------------------------|------------|
| | | | Stainless Steel | Steel | UHMW | °F | °C |
| Eagle Orange 85 | 85A | Yes | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |

Example 1

Type of belt being considered = Eagle Orange 85 in 1/4" round

Head-to-tail center distance (C) = 10 feet

Incline or decline = none

Product accumulation on belt(s)? = no

Total weight on belt(s) = 15 lbs.

Type of belt support = UHMW slider bed

- Horizontal Transport with Slider Bed.

Since the belt will run in UHMW slider bed the COF(μ) of .45 is used from Technical Data chart. From the chart the belt weight is .026 lbs/ft giving a total belt weight of .26 lbs (.026 \times 10').

$$T_e = 15 \text{ lbs} \times .45 + .26 = 7.01$$

- Determine Tight Tension (T_1).

$$\text{round belts } T_1 = 7.01 \times 2 = 14.02$$

- Refer to the Technical Data chart for the material and cross section selected and compare T_1 to the Working Load at 10% tension.

If only one belt is desired, T_1 may not be greater than the Working Load at 10% tension. If more than one belt is required, divide T_1 by the Working Load at 10% tension to arrive at number of belts.

Round up to the nearest whole number of belts.

$$1/4" \text{ round rated } 4.9 \text{ lbs @ } 10\% \text{ tension. } 14.02 \div 4.9 = 2.86 \text{ use } 3 \text{ belts}$$

- Find load per belt by dividing T_1 by number of belts. From the Technical Data chart, determine the percent installed tension for the load per belt.

$$\text{Load/belt} = 14.02 \div 3 = 4.67 \text{ lbs}$$

$$\text{Corresponding installed tension} = 9.7\%$$

Example 2

Eagle Orange 85 in 6mm round

Head-to-tail center distance (C) = 3 meters

Incline or decline = none

Product accumulation on belt(s)? = no

Total weight on belt(s) = 6 kg

Type of belt support = UHMW slider bed

- Horizontal Transport with Slider Bed.

Since the belt will run in UHMW slider bed the COF(μ) of .45 is used from Technical Data chart. From the chart the belt weight is .034 kgs/m giving a total belt weight of .102 kg (.034 \times 3m).

$$T_e = 6 \text{ kg} \times .45 + .102 = 2.802 \text{ kg}$$

- Determine Tight Tension (T_1).

$$\text{round belts } T_1 = 2.802 \times 2 = 5.604 \text{ kg} = 54.98 \text{ Newtons } (5.604 \times 9.81)$$

- Refer to the Technical Data chart for the material and cross section selected and compare T_1 to the Working Load at 10% tension.

If only one belt is desired, T_1 may not be greater than the Working Load at 10% tension. If more than one belt is required, divide T_1 by the Working Load at 10% tension to arrive at number of belts.

Round up to the nearest whole number of belts.

$$6 \text{ mm round rated } 19.4 \text{ N @ } 10\% \text{ tension. } 54.98 \div 19.4 = 2.83 \text{ use } 3 \text{ belts}$$

- Find load per belt by dividing T_1 by number of belts. From the Technical Data chart, determine the percent installed tension for the load per belt.

$$\text{Load/belt} = 54.98 \text{ N} \div 3 = 18.33 \text{ Newtons}$$

$$\text{Corresponding installed tension} = 9.6\%$$

Conveying - Engineering Data



| NON-REINFORCED Material and Color | Hardness | Compliance | Coefficient of Friction | | | Contact Temperature Range | |
|--------------------------------------|-----------------------|------------|-------------------------|-------|------|---------------------------|------------|
| | | | Stainless Steel | Steel | UHMW | °F | °C |
| Eagle® Blue 80 EC | 80A | EC, FDA | 0.80 | 0.70 | 0.55 | -22 to +150 | -30 to +66 |
| Eagle Clear 80 EC | 80A | EC, FDA | 0.80 | 0.70 | 0.55 | -22 to +150 | -30 to +66 |
| Eagle Blue 80 MD | 80A | FDA | 0.75 | 0.65 | 0.50 | -22 to +150 | -30 to +66 |
| Eagle Opaque 80 | 80A | - | 0.75 | 0.65 | 0.50 | -22 to +150 | -30 to +66 |
| Eagle Orange 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Clear 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 | 85A | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Red 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Blue 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Green 89 | 89A | - | 0.65 | 0.55 | 0.40 | -22 to +150 | -30 to +66 |
| Eagle Green 89 Textured | 89A | - | 0.50 | 0.40 | 0.30 | -22 to +150 | -30 to +66 |
| Eagle Green 89 T SureConnect* | 89A | - | 0.50 | 0.40 | 0.30 | -22 to +150 | -30 to +66 |
| Eagle Orange 89 SureConnect* | 89A | - | 0.65 | 0.55 | 0.40 | -22 to +150 | -30 to +66 |
| Eagle Red 90 | 90A | - | 0.60 | 0.50 | 0.38 | -22 to +150 | -30 to +66 |
| Eagle Beige 95 | 95A | FDA | 0.55 | 0.45 | 0.35 | -22 to +150 | -30 to +66 |
| Eagle Clear 95 | 95A | FDA | 0.55 | 0.45 | 0.35 | -22 to +150 | -30 to +66 |
| Eagle White 40D | 40D | - | 0.55 | 0.45 | 0.35 | -22 to +176 | -30 to +80 |
| Eagle Blue 55D | 55D | - | 0.50 | 0.40 | 0.30 | -22 to +176 | -30 to +80 |
| Eagle Blue 80 EC QC | 80A | EC, FDA | 0.50 | 0.40 | 0.30 | -22 to +150 | -30 to +66 |
| Eagle Clear 85 QC | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Red 85 QC | 85A | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Yellow 85 QC | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Blue 85 QC | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Red 85 CXF | 85A Base, 60A Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 SGT PU | 85A Base, 70A PU Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 SGT PVC | 85A Base, 50A PVC Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 SGT TPE | 85A Base, 55A TPE Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Green 89 SGT PVC | 89A Base, 50A PVC Top | - | 0.65 | 0.55 | 0.40 | -22 to +150 | -30 to +66 |
| Eagle Red 90 SGT PVC | 90A Base, 50A PVC Top | - | 0.60 | 0.50 | 0.38 | -22 to +150 | -30 to +66 |
| Eagle White 40D SGT PVC | 40D Base, 50A PVC Top | - | 0.55 | 0.45 | 0.35 | -22 to +150 | -30 to +66 |
| REINFORCED Material and Color | Hardness | Compliance | Coefficient of Friction | | | Contact Temperature Range | |
| | | | Stainless Steel | Steel | UHMW | °F | °C |
| Eagle Opaque 80 | 80A | - | 0.75 | 0.65 | 0.50 | -22 to +150 | -30 to +66 |
| Eagle Orange 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Hyfen 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 | 85A | FDA | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Green 89 | 89A | - | 0.65 | 0.55 | 0.40 | -22 to +150 | -30 to +66 |
| Eagle Green 89 Textured | 89A | - | 0.50 | 0.40 | 0.30 | -22 to +150 | -30 to +66 |
| Eagle Beige 95 | 95A | FDA | 0.55 | 0.45 | 0.35 | -22 to +150 | -30 to +66 |
| Eagle Hyfen 95 | 95A | FDA | 0.55 | 0.45 | 0.35 | -22 to +150 | -30 to +66 |
| Eagle Red 50D LCF Can Cable | 50D | - | n/a | n/a | n/a | -22 to +150 | -30 to +66 |
| Eagle Blue 55D Can Cable | 55D | - | n/a | n/a | n/a | -22 to +176 | -30 to +80 |
| Eagle Blue 55D Aramid Can Cable | 55D | - | n/a | n/a | n/a | -22 to +176 | -30 to +80 |
| Eagle Natural 55D Can Cable | 55D | - | n/a | n/a | n/a | -22 to +176 | -30 to +80 |
| Eagle Green 63D Can Cable | 63D | - | n/a | n/a | n/a | -22 to +176 | -30 to +80 |
| Eagle Natural 63D Can Cable | 63D | - | n/a | n/a | n/a | -22 to +176 | -30 to +80 |
| Eagle Ivory 85 RSGT PU | 85A Base, 70A PU Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 RSGT PVC | 85A Base, 50A PVC Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Ivory 85 RSGT TPE | 85A Base, 55A TPE Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Hyfen 85 CXF V | 85A Base, 60A Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |
| Eagle Hyfen 85 CXR V | 85A Base, 60A Top | - | 0.70 | 0.60 | 0.45 | -22 to +150 | -30 to +66 |

* Eagle SureConnect Connectors are Alloy Steel with a RoHS Compliant Zinc Coating

Note: Cogged Belting is not FDA compliant.



| NON-REINFORCED Material and Color | Hardness | Compliance | Contact Temperature Range | |
|--------------------------------------|----------|------------|---------------------------|------------|
| | | | °F | °C |
| Eagle Taper Edge Band | 60D | - | -22 to +176 | -30 to +80 |



| Product | Color | Compliance | Material | Temperature Range | |
|-----------------------------------|-----------------------|------------|--|-------------------|--------------|
| | | | | °F | °C |
| POWERTWIST MOVE® Belting | Purple | RoHS | Composite Polyester/Polyurethane | -40 to +240 | -40 to +116 |
| POWERTWIST MOVE SuperGrip Top PU | Purple, Orange Top | RoHS | Composite Polyester/Polyurethane Polyurethane grip top surface | -22 to +150 | -30 to +66 |
| POWERTWIST MOVE SuperGrip Top PVC | Purple, Green Top | RoHS | Composite Polyester/Polyurethane PVC grip top surface | -22 to +150 | -30 to +66 |
| POWERTWIST MOVE Friction Top® | Purple | RoHS | Composite Polyester/Polyurethane | -22 to +150 | -30 to +66 |
| POWERTWIST MOVE Bridge Top™ | Purple, White Inserts | RoHS | Composite Polyester/Polyurethane PTFE inserts | -40 to +450* | -40 to +232* |
| POWERTWIST MOVE RCS | Purple, White Tabs | RoHS | Composite Polyester/Polyurethane Polyurethane tabs | -22 to +150 | -30 to +66 |
| POWERTWIST Roller Drive™ | Red | RoHS | Composite Polyester/Polyurethane | -22 to +150 | -30 to +66 |
| POWERTWIST Antistatic† | Blue | RoHS | Composite Polyester/Polyurethane | -40 to +240 | -40 to +116 |

* Contact temperature

† ISO 1813:1998 inspected and certified by Fenner Drives.




Our Trackstar Guides are produced using only the highest quality virgin black UHMW-PE material to ensure minimum friction and maximum wear resistance.

| | ASTM Test | UHMW-PE |
|---|-----------|------------------------|
| Density (gm/cm3) | D792 | .930 – .936 |
| Tensile Strength at yield (psi at 73° F) | D638 | 3100 |
| Elongation at break (% at 73° F) | D638 | 350 |
| Relative volumetric abrasion loss* | N/A | 100 |
| Coefficient of friction on steel 73° F Static | N/A | .15 – .20 |
| Coefficient of friction on steel 73° F Dynamic | N/A | .10 – .20 |
| Hardness 73° F (Shore D) | D785 | 62 – 66 |
| Coefficient of linear thermal expansion (in/in/° F) | D696 | 1.1 x 10 ⁻⁴ |
| Continuous Service Temp in air (max) (°F) | D696 | 180 |
| Volume Resistivity (Ohm/cm) | D257 | >10 ¹⁵ |

* Industry standard testing method using slurry of 60% aluminum oxide and 40% water at a rotation speed of 1750 rpm for two hours. A lower number indicates better abrasion resistance.

Eagle® O-Rings

- O-Rings for line shaft, live roller and motion transfer conveyors
- High coefficient of friction
- Elastic with excellent memory
- Popular 1/8", 3/16", 1/4", 5mm and 6mm sizes in stock
- Contact Fenner Drives for part numbers



Twisted O-Rings

- Twisted O-Rings are an ideal fast fit solution for live roller conveyors
- Twisted loop construction packaged with metal hooks. Plastic hooks also available
- No need to dismantle drive components

Eagle Fabricated Belts

Let us do the work for you and take the hassle out of fabricating your own endless belts

- Available in all Eagle Belting colors and durometers (except Can Cable)

- Rapid order turnaround

| TWISTED O-RINGS | | |
|--------------------|-------------|-----------------|
| Material and Color | Part Number | Dimensions |
| Eagle Clear 85 | 5050003 | 3/16" x 6" |
| Eagle Clear 85 | 5050011 | 3/16" x 10" |
| Eagle Clear 85 | 5050015 | 3/16" x 10-1/2" |
| Eagle Clear 85 | 5050012 | 3/16" x 11" |
| Eagle Clear 85 | 5050911 | 3/16" x 11-1/2" |
| Eagle Clear 85 | 5050016 | 3/16" x 12" |
| Eagle Clear 85 | 5050005 | 3/16" x 12-1/2" |
| Eagle Clear 85 | 5050002 | 3/16" x 12-3/4" |
| Eagle Clear 85 | 5050006 | 3/16" x 12-7/8" |
| Eagle Clear 85 | 5050007 | 3/16" x 13" |
| Eagle Clear 85 | 5050017 | 3/16" x 13-1/4" |
| Eagle Clear 85 | 5050009 | 3/16" x 13-1/2" |
| Eagle Clear 85 | 5050014 | 3/16" x 13-3/4" |
| Eagle Clear 85 | 5050008 | 3/16" x 14" |
| Eagle Clear 85 | 5050010 | 3/16" x 14-1/2" |

Additional sizes available upon request



Eagle Twisted O-Rings easily installed without dismantling line shaft.

50 pieces per box, packaged with metal hooks. Plastic hooks also available.

2mm, 3/32", 3mm, 1/8" Round Cross Sections

Round

Round Belting

| NON-REINFORCED Material and Color | Part Number* | Dimensions Ø (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | | | Weight | |
|--------------------------------------|--------------|---------------------------|-------------------------------|--------------------------------|-----------------|-----------------|------------------|--------|------|------|-----|------|-------|--------|--|
| | | | | 4% (lbs) (N) | 6% (lbs) (N) | 8% (lbs) (N) | 10% (lbs) (N) | lbs/ft | kg/m | | | | | | |
| Eagle Blue 80 EC | 4928000 | 2 | 0.55 | 14 | 0.1 | 0.7 | 0.2 | 1 | 0.3 | 1.4 | 0.4 | 1.7 | 0.002 | 0.004 | |
| Eagle Clear 80 EC | 4927000 | 2 | 0.55 | 14 | 0.1 | 0.7 | 0.2 | 1 | 0.3 | 1.4 | 0.4 | 1.7 | 0.002 | 0.004 | |
| Eagle Opaque 80 | L04OP802M | 2 | 0.55 | 14 | 0.2 | 0.9 | 0.4 | 1.6 | 0.5 | 2.2 | 0.6 | 2.7 | 0.003 | 0.004 | |
| Eagle Orange 85 | L04OG852M | 2 | 0.63 | 16 | 0.2 | 0.9 | 0.3 | 1.3 | 0.4 | 1.8 | 0.5 | 2.2 | 0.003 | 0.004 | |
| Eagle Clear 85 | L04C852M | 2 | 0.63 | 16 | 0.2 | 0.9 | 0.3 | 1.3 | 0.4 | 1.8 | 0.5 | 2.2 | 0.003 | 0.004 | |
| Eagle Green 89 | 4905402 | 2 | 0.71 | 18 | 0.3 | 1.4 | 0.5 | 2.4 | 0.7 | 3.2 | 0.9 | 4 | 0.003 | 0.004 | |
| Eagle Green 89 Textured | 4905302 | 2 | 0.71 | 18 | 0.2 | 1 | 0.4 | 1.7 | 0.5 | 2.3 | 0.7 | 2.9 | 0.003 | 0.004 | |
| Eagle Red 90 | 4940017 | 2 | 0.79 | 20 | 1.1 | 4.7 | 1.5 | 6.8 | 1.9 | 8.5 | 2.2 | 10 | 0.003 | 0.004 | |
| Eagle Orange 85 | 1032003 | 3/32 | 0.75 | 19 | 0.3 | 1.2 | 0.4 | 1.9 | 0.6 | 2.5 | 0.7 | 3.1 | 0.004 | 0.005 | |
| Eagle Clear 85 | 4908003 | 3/32 | 0.75 | 19 | 0.3 | 1.2 | 0.4 | 1.9 | 0.6 | 2.5 | 0.7 | 3.1 | 0.004 | 0.005 | |
| Eagle Clear 95 | 4907003 | 3/32 | 0.94 | 24 | 0.5 | 2.3 | 0.8 | 3.4 | 1 | 4.3 | 1.2 | 5.1 | 0.004 | 0.005 | |
| Eagle Orange 85 | 1032004 | 1/8 | 1 | 25 | 0.5 | 2.2 | 0.7 | 3.3 | 1 | 4.4 | 1.2 | 5.5 | 0.006 | 0.01 | |
| Eagle Clear 85 | 4908006 | 1/8 | 1 | 25 | 0.5 | 2.2 | 0.7 | 3.3 | 1 | 4.4 | 1.2 | 5.5 | 0.006 | 0.01 | |
| Eagle Clear 95 | 4907006 | 1/8 | 1.25 | 32 | 0.9 | 4 | 1.3 | 6 | 1.7 | 7.7 | 2.1 | 9.1 | 0.007 | 0.01 | |
| Eagle Blue 80 EC | 4928001 | 3 | 0.83 | 21 | 0.4 | 1.7 | 0.6 | 2.5 | 0.8 | 3.5 | 1 | 4.3 | 0.005 | 0.008 | |
| Eagle Clear 80 EC | 4927001 | 3 | 0.83 | 21 | 0.4 | 1.7 | 0.6 | 2.5 | 0.8 | 3.5 | 1 | 4.3 | 0.005 | 0.008 | |
| Eagle Opaque 80 | L04OP803M | 3 | 0.83 | 21 | 0.5 | 2.1 | 0.8 | 3.5 | 1.1 | 4.9 | 1.4 | 6.2 | 0.006 | 0.009 | |
| Eagle Orange 85 | L04OG853M | 3 | 0.94 | 24 | 0.4 | 1.9 | 0.7 | 3 | 0.9 | 4 | 1.1 | 4.9 | 0.006 | 0.009 | |
| Eagle Clear 85 | L04C853M | 3 | 0.94 | 24 | 0.4 | 1.9 | 0.7 | 3 | 0.9 | 4 | 1.1 | 4.9 | 0.006 | 0.009 | |
| Eagle Blue 85 | L04BL853M | 3 | 0.94 | 24 | 0.4 | 1.9 | 0.7 | 3 | 0.9 | 4 | 1.1 | 4.9 | 0.006 | 0.009 | |
| Eagle Green 89 | L04G893MS | 3 | 1.06 | 27 | 0.7 | 3.2 | 1.2 | 5.2 | 1.6 | 7.2 | 2 | 9 | 0.006 | 0.009 | |
| Eagle Green 89 Textured | 4905303 | 3 | 1.06 | 27 | 0.5 | 2.3 | 0.9 | 3.8 | 1.2 | 5.2 | 1.5 | 6.5 | 0.006 | 0.009 | |
| Eagle Red 90 | 4940020 | 3 | 1.18 | 30 | 2.4 | 10.5 | 3.4 | 15.1 | 4.3 | 19 | 5 | 22.2 | 0.006 | 0.009 | |
| Eagle White 40D | L04BY403M | 3 | 1.42 | 36 | 1.9 | 8.3 | 2.9 | 12.8 | 3.8 | 16.8 | 4.5 | 20.2 | 0.006 | 0.008 | |

4mm, 5mm, 3/16" Round Cross Sections



Round

Round Belting

| NON-REINFORCED | Part Number* | Dimensions Ø (in) (mm) | | Minimum Pulley Ø (in) (mm) | | Working Load @ Percent Tension | | | | | | | | Weight | |
|-------------------------|--------------|---------------------------|--------|-------------------------------|----|--------------------------------|-----------|-----------|-----------|-----------|-----------|-----------|------|--------|-------|
| | | | | | | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m |
| Material and Color | | | | | | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | | | |
| Eagle® Blue 80 EC | 4928002 | | 4 | 1.1 | 28 | 0.6 | 2.8 | 0.9 | 4.2 | 1.3 | 5.6 | 1.5 | 6.7 | 0.009 | 0.014 |
| Eagle Clear 80 EC | 4927002 | | 4 | 1.1 | 28 | 0.6 | 2.8 | 0.9 | 4.2 | 1.3 | 5.6 | 1.5 | 6.7 | 0.009 | 0.014 |
| Eagle Opaque 80 | L04OP804 | | 4 | 1.1 | 28 | 0.8 | 3.7 | 1.4 | 6.2 | 2 | 8.7 | 2.5 | 11 | 0.01 | 0.015 |
| Eagle Orange 85 | L04OG854 | | 4 | 1.26 | 32 | 0.8 | 3.4 | 1.2 | 5.3 | 1.6 | 7 | 1.9 | 8.6 | 0.01 | 0.015 |
| Eagle Clear 85 | L04C854 | | 4 | 1.26 | 32 | 0.8 | 3.4 | 1.2 | 5.3 | 1.6 | 7 | 1.9 | 8.6 | 0.01 | 0.015 |
| Eagle Red 85 | L04R8504 | | 4 | 1.26 | 32 | 0.8 | 3.4 | 1.2 | 5.3 | 1.6 | 7 | 2 | 8.7 | 0.01 | 0.015 |
| Eagle Blue 85 | L04BL854 | | 4 | 1.26 | 32 | 0.8 | 3.4 | 1.2 | 5.3 | 1.6 | 7 | 2 | 8.7 | 0.01 | 0.015 |
| Eagle Green 89 | 4905404 | | 4 | 1.42 | 36 | 1.3 | 5.7 | 2.1 | 9.3 | 2.9 | 12.8 | 3.6 | 16 | 0.01 | 0.015 |
| Eagle Green 89 Textured | 4905304 | | 4 | 1.42 | 36 | 0.9 | 4.1 | 1.5 | 6.8 | 2.1 | 9.3 | 2.6 | 11.6 | 0.01 | 0.015 |
| Eagle Red 90 | 4940021 | | 4 | 1.57 | 40 | 4.2 | 18.6 | 6 | 26.8 | 7.6 | 33.8 | 8.9 | 39.5 | 0.01 | 0.015 |
| Eagle White 40D | L04BY404 | | 4 | 1.89 | 48 | 3.3 | 14.8 | 5.1 | 22.8 | 6.7 | 29.8 | 8.1 | 36 | 0.01 | 0.015 |
| Eagle Blue 80 MD | 4941100 | 3/16 | | 1.31 | 33 | 0.8 | 3.5 | 1.2 | 5.4 | 1.6 | 7 | 1.9 | 8.6 | 0.013 | 0.02 |
| Eagle Orange 85 | 1032006 | 3/16 | | 1.5 | 38 | 1.1 | 4.9 | 1.7 | 7.5 | 2.2 | 10 | 2.8 | 12.3 | 0.014 | 0.021 |
| Eagle Clear 85 | 4908009 | 3/16 | | 1.5 | 38 | 1.1 | 4.9 | 1.7 | 7.5 | 2.2 | 10 | 2.8 | 12.3 | 0.014 | 0.021 |
| Eagle Red 90 | 4940022 | 3/16 | | 1.88 | 48 | 6 | 26.5 | 8.6 | 38.2 | 10.8 | 48.1 | 12.6 | 56.2 | 0.014 | 0.022 |
| Eagle Clear 95 | 4907009 | 3/16 | | 1.88 | 48 | 2 | 9.1 | 3 | 13.5 | 3.9 | 17.3 | 4.6 | 20.6 | 0.015 | 0.022 |
| Eagle Clear 85 QC | 4934009 | .188 x .080† | | 1.5 | 38 | 0.5 | 2 | 0.7 | 3.1 | 0.9 | 4.2 | 1.2 | 5.2 | 0.012 | 0.018 |
| Eagle Yellow 85 QC | 4934021 | .188 x .080† | | 1.5 | 38 | 0.5 | 2 | 0.7 | 3.1 | 0.9 | 4.2 | 1.2 | 5.2 | 0.012 | 0.018 |
| Eagle Blue 80 EC | 4928003 | | 5 | 1.38 | 35 | 0.9 | 4.2 | 1.4 | 6.3 | 1.9 | 8.4 | 2.4 | 10.6 | 0.015 | 0.022 |
| Eagle Clear 80 EC | 4927003 | | 5 | 1.38 | 35 | 0.9 | 4.2 | 1.4 | 6.3 | 1.9 | 8.4 | 2.4 | 10.6 | 0.015 | 0.022 |
| Eagle Opaque 80 | L04OP805M | | 5 | 1.38 | 35 | 1.3 | 5.7 | 2.2 | 9.7 | 3.1 | 13.6 | 3.9 | 17.2 | 0.016 | 0.024 |
| Eagle Orange 85 | 4940100 | | 5 | 1.57 | 40 | 1.2 | 5.4 | 1.9 | 8.3 | 2.5 | 11 | 3.1 | 13.6 | 0.016 | 0.024 |
| Eagle Clear 85 | L04C855M | | 5 | 1.57 | 40 | 1.2 | 5.3 | 1.9 | 8.2 | 2.5 | 11 | 3 | 13.5 | 0.016 | 0.024 |
| Eagle Red 85 | L04R855 | | 5 | 1.57 | 40 | 1.2 | 5.3 | 1.9 | 8.2 | 2.5 | 11 | 3 | 13.5 | 0.016 | 0.024 |
| Eagle Blue 85 | L04BL855M | | 5 | 1.57 | 40 | 1.2 | 5.3 | 1.9 | 8.2 | 2.5 | 11 | 3 | 13.5 | 0.016 | 0.024 |
| Eagle Green 89 | 4905405 | | 5 | 1.77 | 45 | 2 | 8.9 | 3.3 | 14.6 | 4.5 | 20.1 | 5.6 | 25.1 | 0.016 | 0.023 |
| Eagle Green 89 Textured | 4905305 | | 5 | 1.77 | 45 | 1.5 | 6.5 | 2.4 | 10.6 | 3.3 | 14.6 | 4.1 | 18.2 | 0.016 | 0.023 |
| Eagle Red 90 | L04R9005M | | 5 | 1.97 | 50 | 6 | 26.5 | 8.6 | 38.2 | 10.8 | 48.1 | 12.6 | 56.2 | 0.014 | 0.022 |
| Eagle Beige 95 | L04BE955M | | 5 | 1.97 | 50 | 5.3 | 23.6 | 7.5 | 33.4 | 9.4 | 41.8 | 11 | 48.8 | 0.016 | 0.024 |
| Eagle White 40D | L04BY405M | | 5 | 2.36 | 60 | 5.2 | 23.1 | 8 | 35.5 | 10.5 | 46.6 | 12.6 | 56.2 | 0.015 | 0.023 |
| Eagle Blue 80 EC QC | 4928020 | | 5 x 2† | 1.38 | 35 | 0.4 | 1.8 | 0.6 | 2.8 | 0.8 | 3.7 | 1 | 4.6 | 0.012 | 0.018 |
| Eagle Clear 85 QC | L04QC855M | | 5 x 2† | 1.57 | 40 | 0.5 | 2.3 | 0.8 | 3.5 | 1.1 | 4.7 | 1.3 | 5.8 | 0.013 | 0.02 |
| Eagle Red 85 QC | L04QR855M | | 5 x 2† | 1.57 | 40 | 0.5 | 2.3 | 0.8 | 3.5 | 1.1 | 4.7 | 1.3 | 5.8 | 0.013 | 0.02 |
| Eagle Blue 85 QC | L04QB855M | | 5 x 2† | 1.38 | 35 | 0.5 | 2.3 | 0.8 | 3.5 | 1.1 | 4.7 | 1.3 | 5.8 | 0.013 | 0.02 |
| QC Connectors | 4935009 | 25/pack | | | | | | | | | | | | | |
| REINFORCED | Part Number* | Dimensions Ø (in) (mm) | | Minimum Pulley Ø (in) (mm) | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | | | | | | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m |
| | | | | | | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | (lbs) (N) | | | |
| Eagle Hyfen 85 | 5218009 | 3/16 | | 2.06 | 52 | 2.8 | 12.5 | 6.8 | 30.2 | 11.2 | 49.8 | 15.5 | 68.9 | 0.014 | 0.021 |
| Eagle Green 89 | L04G895MRS | | 5 | 1.97 | 50 | 1.7 | 7.4 | 5 | 22.2 | 10.2 | 45.4 | 15.7 | 70.1 | 0.016 | 0.023 |
| Eagle Green 89 Textured | 4940056 | | 5 | 1.97 | 50 | 2.3 | 10.2 | 6.9 | 30.5 | 14 | 62.5 | 21.7 | 96.3 | 0.016 | 0.023 |

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

6mm, 1/4" Round Cross Sections



Round

Round Belting

| NON-REINFORCED | | Part Number* | | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|-------------------------|--------------|-------------------------|------|--------------|------|------------------|--------|--------------------------------|--------|----------|--------|-----------|---------|--------|-------|--------|--|
| Material and Color | Part Number* | (in) | (mm) | (in) | (mm) | 4% (lbs) | 4% (N) | 6% (lbs) | 6% (N) | 8% (lbs) | 8% (N) | 10% (lbs) | 10% (N) | lbs/ft | kg/m | | |
| Eagle® Blue 80 EC | 4928004 | 6 | 1.65 | 42 | 1.3 | 5.9 | 2.1 | 9.1 | 2.8 | 12.3 | 3.4 | 15.2 | 0.021 | 0.032 | | | |
| Eagle Clear 80 EC | 4927004 | 6 | 1.65 | 42 | 1.3 | 5.9 | 2.1 | 9.1 | 2.8 | 12.3 | 3.4 | 15.2 | 0.021 | 0.032 | | | |
| Eagle Opaque 80 | L04OP806M | 6 | 1.65 | 42 | 1.9 | 8.2 | 3.2 | 14 | 4.4 | 19.6 | 5.6 | 24.7 | 0.023 | 0.034 | | | |
| Eagle Orange 85 | L04OG856M | 6 | 1.89 | 48 | 1.7 | 7.7 | 2.7 | 11.8 | 3.5 | 15.8 | 4.4 | 19.4 | 0.023 | 0.034 | | | |
| Eagle Clear 85 | L04C856M | 6 | 1.89 | 48 | 1.7 | 7.7 | 2.7 | 11.8 | 3.5 | 15.8 | 4.4 | 19.4 | 0.023 | 0.034 | | | |
| Eagle Blue 85 | L04BL856M | 6 | 1.89 | 48 | 1.7 | 7.7 | 2.7 | 11.9 | 3.6 | 15.8 | 4.4 | 19.5 | 0.023 | 0.034 | | | |
| Eagle Green 89 | 4905406 | 6 | 2.13 | 54 | 2.9 | 12.8 | 4.7 | 21 | 6.5 | 28.9 | 8.1 | 36.1 | 0.023 | 0.034 | | | |
| Eagle Green 89 Textured | 4905306 | 6 | 2.13 | 54 | 2.1 | 9.3 | 3.4 | 15.3 | 4.7 | 21 | 5.9 | 26.2 | 0.023 | 0.034 | | | |
| Eagle White 40D | L04BY406M | 6 | 2.83 | 72 | 7.5 | 33.3 | 11.5 | 51.2 | 15.1 | 67.1 | 18.2 | 80.9 | 0.022 | 0.033 | | | |
| Eagle Blue 80 EC QC | 4928021 | 6 × 2.5 [†] | 1.65 | 42 | 0.6 | 2.5 | 0.9 | 3.9 | 1.2 | 5.3 | 1.5 | 6.6 | 0.018 | 0.026 | | | |
| Eagle Clear 85 QC | L04QC856M | 6 × 2.5 [†] | 1.89 | 48 | 0.7 | 3.2 | 1.1 | 5 | 1.5 | 6.7 | 1.9 | 8.3 | 0.019 | 0.028 | | | |
| Eagle Red 85 QC | L04QR856M | 6 × 2.5 [†] | 1.89 | 48 | 0.7 | 3.2 | 1.1 | 5 | 1.5 | 6.7 | 1.9 | 8.3 | 0.019 | 0.028 | | | |
| Eagle Blue 85 QC | L04QB856M | 6 × 2.5 [†] | 1.89 | 48 | 0.7 | 3.2 | 1.1 | 5 | 1.5 | 6.7 | 1.9 | 8.3 | 0.019 | 0.028 | | | |
| Eagle Blue 80 MD | 4941101 | 1/4 | 6.3 | 1.75 | 44 | 1.3 | 6 | 2.1 | 9.2 | 2.8 | 12.3 | 3.4 | 15.3 | 0.024 | 0.035 | | |
| Eagle Opaque 80 | 4940003 | 1/4 | 6.3 | 1.75 | 44 | 2.1 | 9.2 | 3.5 | 15.7 | 4.9 | 22 | 6.2 | 27.7 | 0.026 | 0.039 | | |
| Eagle Orange 85 | 1032008 | 1/4 | 6.3 | 2 | 51 | 1.9 | 8.6 | 3 | 13.3 | 4 | 17.7 | 4.9 | 21.9 | 0.026 | 0.038 | | |
| Eagle Clear 85 | 4908012 | 1/4 | 6.3 | 2 | 51 | 1.9 | 8.6 | 3 | 13.3 | 4 | 17.7 | 4.9 | 21.9 | 0.026 | 0.038 | | |
| Eagle Red 90 | 4940023 | 1/4 | 6.3 | 2.5 | 64 | 10.6 | 47.2 | 15.3 | 67.9 | 19.2 | 85.5 | 22.5 | 100 | 0.026 | 0.038 | | |
| Eagle Clear 95 | 4907012 | 1/4 | 6.3 | 2.5 | 64 | 3.6 | 16.1 | 5.4 | 24 | 6.9 | 30.8 | 8.2 | 36.6 | 0.026 | 0.039 | | |
| Eagle Clear 85 QC | 4934012 | 250 × .098 [‡] | 2 | 51 | 0.8 | 3.7 | 1.3 | 5.7 | 1.7 | 7.7 | 2.1 | 9.5 | 0.022 | 0.032 | | | |
| Eagle Yellow 85 QC | 4934022 | 250 × .098 [‡] | 2 | 51 | 0.8 | 3.7 | 1.3 | 5.7 | 1.7 | 7.7 | 2.1 | 9.5 | 0.022 | 0.032 | | | |
| Eagle Blue 80 EC | 4928005 | 1/4 | 6.3 | 1.74 | 44 | 1.5 | 6.6 | 2.3 | 10.2 | 3.1 | 13.7 | 3.8 | 17 | 0.023 | 0.035 | | |
| Eagle Blue 85 | L04BL856.3 | 1/4 | 6.3 | 2 | 51 | 1.9 | 8.6 | 3 | 13.3 | 4 | 17.7 | 4.9 | 21.8 | 0.025 | 0.037 | | |
| QC Connectors | L04CON6S | 25/pack | | | | | | | | | | | | | | | |
| REINFORCED | | Part Number* | | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | Part Number* | (in) | (mm) | (in) | (mm) | 1% (lbs) | 1% (N) | 2% (lbs) | 2% (N) | 3% (lbs) | 3% (N) | 4% (lbs) | 4% (N) | lbs/ft | kg/m | | |
| Eagle Orange 85 | L04OG856MR | 6 | 2.36 | 60 | 0.7 | 3.2 | 2.5 | 11 | 4.8 | 21.5 | 6.9 | 30.8 | 0.023 | 0.034 | | | |
| Eagle Green 89 | L04G896MSR | 6 | 2.36 | 60 | 2.4 | 10.6 | 7.2 | 32 | 14.7 | 65.5 | 22.7 | 100.9 | 0.023 | 0.034 | | | |
| Eagle Green 89 Textured | 4940057 | 6 | 2.36 | 60 | 3.3 | 14.6 | 9.9 | 43.9 | 20.2 | 90 | 31.2 | 138.8 | 0.023 | 0.034 | | | |
| Eagle Orange 85 | 4940058 | 1/4 | 6.3 | 2.5 | 64 | 0.8 | 3.6 | 2.8 | 12.3 | 5.4 | 24.1 | 7.8 | 34.6 | 0.026 | 0.038 | | |
| Eagle Hyfen 85 | 5218012 | 1/4 | 6.3 | 2.75 | 70 | 3.7 | 16.5 | 12.4 | 55.2 | 20 | 89 | 27.8 | 123.7 | 0.026 | 0.038 | | |

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D × I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

7mm, 8mm, 5/16" Round Cross Sections



Round

Round Belting

| NON-REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|-------------------------|------------|--------------|--------------|------|------------------|-------|--------------------------------|-------|-------|-------|-------|-------|-------|--------|--------|--|
| Material and Color | (in) | | (mm) | (in) | (mm) | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| Eagle® Orange 85 | L04OG857M | | 7 | 2.2 | 56 | 2.4 | 10.5 | 3.6 | 16.2 | 4.8 | 21.6 | 6 | 26.6 | 0.031 | 0.046 | |
| Eagle Clear 85 | L04C857M | | 7 | 2.2 | 56 | 2.4 | 10.5 | 3.6 | 16.2 | 4.8 | 21.6 | 6 | 26.6 | 0.031 | 0.046 | |
| Eagle Green 89 | 4999637 | | 7 | 2.48 | 63 | 3.9 | 17.4 | 6.4 | 28.6 | 8.8 | 39.3 | 11 | 49.1 | 0.031 | 0.046 | |
| Eagle Green 89 Textured | 4905307 | | 7 | 2.48 | 63 | 2.9 | 12.7 | 4.7 | 20.9 | 6.4 | 28.7 | 8.1 | 35.8 | 0.031 | 0.046 | |
| Eagle Red 90 | L04R907 | | 7 | 2.76 | 70 | 12.9 | 57.4 | 18.6 | 82.7 | 23.4 | 104.1 | 27.4 | 121.8 | 0.031 | 0.047 | |
| Eagle Blue 80 MD | 4941102 | 5/16 | | 2.19 | 56 | 2.1 | 9.4 | 3.3 | 14.5 | 4.3 | 19.3 | 5.5 | 24.3 | 0.037 | 0.055 | |
| Eagle Orange 85 | 1032010 | 5/16 | | 2.5 | 64 | 3 | 13.5 | 4.7 | 20.8 | 6.2 | 27.7 | 7.7 | 34.1 | 0.04 | 0.059 | |
| Eagle Clear 85 | 4908015 | 5/16 | | 2.5 | 64 | 3 | 13.5 | 4.7 | 20.8 | 6.2 | 27.7 | 7.7 | 34.1 | 0.04 | 0.059 | |
| Eagle Clear 95 | 4907015 | 5/16 | | 3.13 | 79 | 5.7 | 25.2 | 8.4 | 37.4 | 10.8 | 48.1 | 12.9 | 57.2 | 0.041 | 0.061 | |
| Eagle Clear 85 QC | 4934015 | .313 x .126† | | 2.5 | 64 | 1.3 | 5.7 | 2 | 8.9 | 2.7 | 11.9 | 3.3 | 14.7 | 0.034 | 0.05 | |
| Eagle Yellow 85 QC | 4934023 | .313 x .126† | | 2.5 | 64 | 1.3 | 5.7 | 2 | 8.9 | 2.7 | 11.9 | 3.3 | 14.7 | 0.034 | 0.05 | |
| Eagle Blue 80 EC | 4928006 | | 8 | 2.2 | 56 | 2.4 | 10.5 | 3.6 | 16.2 | 4.8 | 21.5 | 6.1 | 26.9 | 0.038 | 0.056 | |
| Eagle Clear 80 EC | 4927006 | | 8 | 2.2 | 56 | 2.4 | 10.5 | 3.6 | 16.2 | 4.8 | 21.5 | 6.1 | 26.9 | 0.038 | 0.056 | |
| Eagle Opaque 80 | L04OP808M | | 8 | 2.2 | 56 | 3.3 | 14.7 | 5.6 | 25 | 7.8 | 34.9 | 9.9 | 43.9 | 0.041 | 0.061 | |
| Eagle Orange 85 | L04OG858M | | 8 | 2.52 | 64 | 3.1 | 13.7 | 4.7 | 21.1 | 6.3 | 28.1 | 7.8 | 34.7 | 0.041 | 0.06 | |
| Eagle Clear 85 | L04C858 | | 8 | 2.52 | 64 | 3.1 | 13.7 | 4.7 | 21.1 | 6.3 | 28.1 | 7.8 | 34.7 | 0.041 | 0.06 | |
| Eagle Blue 85 | L04BL858M | | 8 | 2.52 | 64 | 3.1 | 13.7 | 4.7 | 21.1 | 6.3 | 28.1 | 7.8 | 34.7 | 0.041 | 0.06 | |
| Eagle Green 89 | L04G898MS | | 8 | 2.83 | 72 | 5.1 | 22.8 | 8.4 | 37.4 | 11.5 | 51.3 | 14.4 | 64.1 | 0.04 | 0.06 | |
| Eagle Green 89 Textured | 4905308 | | 8 | 2.83 | 72 | 3.7 | 16.6 | 6.1 | 27.2 | 8.4 | 37.3 | 10.5 | 46.7 | 0.04 | 0.06 | |
| Eagle Red 90 | 4940024 | | 8 | 3.15 | 80 | 16.8 | 74.9 | 24.3 | 107.9 | 30.5 | 135.8 | 35.7 | 158.9 | 0.041 | 0.061 | |
| Eagle Beige 95 | L04BE958 | | 8 | 3.15 | 80 | 13.6 | 60.5 | 19.3 | 85.7 | 24.1 | 107 | 28.1 | 125.1 | 0.042 | 0.062 | |
| Eagle White 40D | L04BY408M | | 8 | 3.78 | 96 | 13.3 | 59.2 | 20.5 | 91 | 26.8 | 119.3 | 32.3 | 143.8 | 0.04 | 0.059 | |
| Eagle Blue 80 EC QC | 4928022 | | 8 x 3.2‡ | 2.2 | 56 | 1 | 4.6 | 1.6 | 7.1 | 2.2 | 9.6 | 2.7 | 11.9 | 0.032 | 0.047 | |
| Eagle Clear 85 QC | L04QC858M | | 8 x 3.2‡ | 2.52 | 64 | 1.3 | 5.8 | 2 | 9 | 2.7 | 12.1 | 3.4 | 14.9 | 0.034 | 0.051 | |
| Eagle Red 85 QC | L04QR858M | | 8 x 3.2‡ | 2.52 | 64 | 1.3 | 5.8 | 2 | 9 | 2.7 | 12.1 | 3.4 | 14.9 | 0.034 | 0.051 | |
| Eagle Blue 85 QC | L04QB858M | | 8 x 3.2‡ | 2.52 | 64 | 1.3 | 5.7 | 2 | 8.9 | 2.7 | 11.9 | 3.3 | 14.6 | 0.034 | 0.051 | |
| QC Connectors | L04CON8S | 25/pack | | | | | | | | | | | | | | |
| REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | (in) | | (mm) | (in) | (mm) | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| Eagle Green 89 | L04G897MRS | | 7 | 2.76 | 70 | 3.3 | 14.5 | 9.8 | 43.5 | 20.1 | 89.2 | 30.9 | 137.6 | 0.031 | 0.046 | |
| Eagle Green 89 Textured | 4940050 | | 7 | 2.76 | 70 | 4.5 | 19.9 | 13.5 | 59.9 | 27.6 | 122.7 | 42.5 | 189.2 | 0.031 | 0.046 | |
| Eagle Orange 85 | 4940059 | 5/16 | | 3.13 | 79 | 1.3 | 5.6 | 4.3 | 19.3 | 8.5 | 37.6 | 12.1 | 54 | 0.04 | 0.059 | |
| Eagle Hyfen 85 | 5218015 | 5/16 | | 3.44 | 87 | 3.7 | 16.5 | 12.4 | 55.2 | 20 | 89 | 27.8 | 123.7 | 0.04 | 0.059 | |
| Eagle Orange 85 | L04OG858R | | 8 | 3.15 | 80 | 1.3 | 5.7 | 4.4 | 19.6 | 8.6 | 38.2 | 12.3 | 54.8 | 0.041 | 0.06 | |
| Eagle Green 89 | L04G898MRS | | 8 | 3.15 | 80 | 4.3 | 18.9 | 12.8 | 56.8 | 26.2 | 116.4 | 40.4 | 179.5 | 0.04 | 0.06 | |
| Eagle Green 89 Textured | 4940051 | | 8 | 3.15 | 80 | 5.8 | 26 | 17.6 | 78.2 | 36 | 160.1 | 55.5 | 246.8 | 0.04 | 0.06 | |
| Eagle Beige 95 | L04BE958R | | 8 | 3.78 | 96 | 3.8 | 16.9 | 7 | 31.1 | 10.4 | 46.3 | 13.6 | 60.5 | 0.042 | 0.062 | |

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

9mm, 9.5mm, 3/8" Round Cross Sections Round Belting



| NON-REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|-----------------------------|-------------|--------------|--------------|------|------------------|------|--------------------------------|------|-------|------|-------|------|-------|--------|--------|--|
| Material and Color | (in) | | (mm) | (in) | (mm) | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m | |
| Eagle® Green 89 Textured | L04G899 | | 9 | 3.19 | 81 | 4.7 | 21 | 7.7 | 34.4 | 10.6 | 47.2 | 13.3 | 59 | 0.051 | 0.076 | |
| Eagle Blue 80 MD | 4941103 | 3/8 | 9.5 | 2.63 | 67 | 3 | 13.5 | 4.7 | 20.9 | 6.3 | 27.9 | 7.8 | 34.8 | 0.054 | 0.08 | |
| Eagle Opaque 80 | 4940005 | 3/8 | 9.5 | 2.63 | 67 | 4.7 | 20.8 | 8 | 35.4 | 11.1 | 49.4 | 14 | 62.3 | 0.058 | 0.087 | |
| Eagle Orange 85 | 1032012 | 3/8 | 9.5 | 3 | 76 | 4.4 | 19.4 | 6.7 | 29.9 | 9 | 39.9 | 11.1 | 49.2 | 0.057 | 0.086 | |
| Eagle Orange 89 SureConnect | 4934145 | 3/8 | 9.5 | 3 | 76 | 4.4 | 19.4 | 6.7 | 29.9 | 9 | 39.9 | 11.1 | 49.2 | 0.057 | 0.086 | |
| Eagle Clear 85 | 4908018 | 3/8 | 9.5 | 3 | 76 | 4.4 | 19.4 | 6.7 | 29.9 | 9 | 39.9 | 11.1 | 49.2 | 0.057 | 0.086 | |
| Eagle Red 90 | 4940025 | 3/8 | 9.5 | 3.75 | 95 | 23.9 | 106.1 | 34.4 | 152.9 | 43.3 | 192.4 | 50.6 | 225.1 | 0.058 | 0.086 | |
| Eagle Clear 95 | 4907018 | 3/8 | 9.5 | 3.75 | 95 | 8.2 | 36.3 | 12.1 | 53.9 | 15.6 | 69.3 | 18.5 | 82.4 | 0.059 | 0.088 | |
| Eagle Clear 85 QC | 4934018 | | .375 × .152† | 3 | 76 | 1.8 | 8.2 | 2.9 | 12.7 | 3.8 | 17.1 | 4.7 | 21 | 0.048 | 0.071 | |
| Eagle Yellow 85 QC | 4934025 | | .375 × .152† | 3 | 76 | 1.8 | 8.2 | 2.9 | 12.7 | 3.8 | 17.1 | 4.7 | 21 | 0.048 | 0.071 | |
| Eagle Blue 80 EC | 4928007 | 3/8 | 9.5 | 2.62 | 67 | 3.4 | 15 | 5.2 | 23.2 | 7 | 31 | 8.7 | 38.7 | 0.053 | 0.079 | |
| Eagle Blue 85 | L04BL859.5M | 3/8 | 9.5 | 3 | 76 | 4.4 | 19.4 | 6.7 | 29.9 | 9 | 39.9 | 11.1 | 49.2 | 0.057 | 0.085 | |
| Eagle Green 89 | L04G899.5MS | 3/8 | 9.5 | 3.39 | 86 | 7.2 | 32.1 | 11.8 | 52.7 | 16.3 | 72.4 | 20.3 | 90.4 | 0.057 | 0.084 | |
| Eagle Blue 80 EC QC | 4928023 | | 9.5 × 3.8† | 2.64 | 67 | 1.5 | 6.4 | 2.3 | 10.1 | 3 | 13.5 | 3.8 | 16.8 | 0.045 | 0.067 | |
| QC Connectors | L04CON10S | 20/pack | | | | | | | | | | | | | | |
| SureConnect Connectors | 4935031 | 5/pack | | | | | | | | | | | | | | |
| REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | (in) | | (mm) | (in) | (mm) | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m | |
| Eagle Orange 85 | 4940060 | 3/8 | 9.5 | 3.75 | 95 | 1.8 | 8 | 6.2 | 27.8 | 12.2 | 54.2 | 17.5 | 77.8 | 0.057 | 0.086 | |
| Eagle Hyfen 85 | 5218018 | 3/8 | 9.5 | 4.13 | 105 | 7.3 | 32.5 | 26.2 | 116.5 | 43.5 | 193.5 | 57.4 | 255.3 | 0.057 | 0.086 | |

Can Cable

| REINFORCED | | Part Number‡ | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|---------------------------|---------|--------------|--------------|------|------------------|------|--------------------------------|-------|-------|-------|--------|-------|-------|--------|--------|--|
| Material and Color | (in) | | (mm) | (in) | (mm) | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m | |
| Blue 55D Can Cable | 4816019 | 3/8 | 9.5 | 12 | 305 | 18.1 | 80.4 | 42.9 | 190.6 | 79.4 | 353.1 | 118.4 | 526.5 | 0.057 | 0.086 | |
| Natural 55D Can Cable | 4816018 | 3/8 | 9.5 | 12 | 305 | 18.1 | 80.4 | 42.9 | 190.6 | 79.4 | 353.1 | 118.4 | 526.5 | 0.057 | 0.086 | |
| Natural 63D Can Cable | 4899006 | 3/8 | 9.5 | 12 | 305 | 18.1 | 80.4 | 42.9 | 190.6 | 79.4 | 353.1 | 118.4 | 526.5 | 0.058 | 0.087 | |
| Red 50D LCF Can Cable | 4816020 | 3/8 | 9.5 | 10 | 254 | 23.8 | 105.9 | 57.8 | 257.2 | 104.3 | 463.8 | 152.3 | 677.2 | 0.058 | 0.087 | |
| Green 63D Can Cable | 4817018 | 3/8 | 9.5 | 12 | 305 | 18.1 | 80.4 | 42.9 | 190.6 | 79.4 | 353.1 | 118.4 | 526.5 | 0.058 | 0.087 | |
| Blue 55D Aramid Can Cable | 4899012 | 3/8 | 9.5 | 12 | 305 | 41.7 | 185.5 | 149.1 | 663.2 | 281.1 | 1250.4 | — | — | 0.057 | 0.086 | |

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

10mm, 12mm, 12.7mm, 1/2" Round Cross Sections



Round

Round Belting

| NON-REINFORCED | Part Number* | Dimensions Ø (in) (mm) | | Minimum Pulley Ø (in) (mm) | | Working Load @ Percent Tension | | | | | | | | Weight | |
|------------------------------|--------------|------------------------------------|-----------|-------------------------------|-----|--------------------------------|-------|-------|-------|-------|-------|-------|-------|--------|-------|
| | | | | | | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m |
| Material and Color | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle® Blue 80 EC | 4928008 | | 10 | 2.76 | 70 | 3.7 | 16.4 | 5.8 | 25.6 | 7.7 | 34.1 | 9.6 | 42.6 | 0.059 | 0.088 |
| Eagle Clear 80 EC | 4927008 | | 10 | 2.76 | 70 | 3.7 | 16.4 | 5.8 | 25.6 | 7.7 | 34.1 | 9.6 | 42.6 | 0.059 | 0.088 |
| Eagle Opaque 80 | L04OP8010M | | 10 | 2.76 | 70 | 5.1 | 22.9 | 8.8 | 39 | 12.2 | 54.5 | 15.4 | 68.6 | 0.064 | 0.096 |
| Eagle Orange 85 | L04OG8510M | | 10 | 3.15 | 80 | 4.8 | 21.4 | 7.4 | 33 | 9.9 | 44 | 12.2 | 54.2 | 0.063 | 0.094 |
| Eagle Clear 85 | L04C8510M | | 10 | 3.15 | 80 | 4.8 | 21.4 | 7.4 | 33 | 9.9 | 44 | 12.2 | 54.2 | 0.063 | 0.094 |
| Eagle Blue 85 | L04BL8510M | | 10 | 3.15 | 80 | 4.8 | 21.4 | 7.4 | 33 | 9.9 | 44 | 12.2 | 54.2 | 0.063 | 0.094 |
| Eagle Green 89 | L04G8910MS | | 10 | 3.54 | 90 | 8 | 35.4 | 13.1 | 58.2 | 18 | 79.9 | 22.4 | 99.8 | 0.063 | 0.093 |
| Eagle Green 89 Textured | 4905310 | | 10 | 3.54 | 90 | 5.8 | 25.8 | 9.5 | 42.3 | 13.1 | 58.1 | 16.3 | 72.5 | 0.063 | 0.093 |
| Eagle Green 89 T SureConnect | 4934141 | | 10 | 3.54 | 90 | 5.8 | 25.8 | 9.5 | 42.3 | 13.1 | 58.1 | 16.3 | 72.5 | 0.063 | 0.093 |
| Eagle Red 90 | L04R9010M | | 10 | 3.94 | 100 | 26.3 | 116.9 | 37.9 | 168.4 | 47.6 | 211.9 | 55.7 | 248 | 0.064 | 0.095 |
| Eagle Beige 95 | L04BE9510M | | 10 | 3.94 | 100 | 21.2 | 94.5 | 30.1 | 133.8 | 37.6 | 167.2 | 43.9 | 195.5 | 0.065 | 0.097 |
| Eagle White 40D | L04BY4010M | | 10 | 4.72 | 120 | 20.8 | 92.5 | 32 | 142.2 | 41.9 | 186.5 | 50.5 | 224.6 | 0.062 | 0.092 |
| Eagle Blue 55D | L04BY5510M | | 10 | 5.12 | 130 | 39.3 | 174.6 | 60.4 | 268.7 | 78.5 | 349.2 | 93 | 413.8 | 0.063 | 0.094 |
| Eagle Red 85 QC | L04QR8510M | | 10 × 3.8† | 3.15 | 80 | 2.1 | 9.3 | 3.2 | 14.4 | 4.3 | 19.3 | 5.3 | 23.8 | 0.054 | 0.081 |
| Eagle Blue 85 QC | L04QB8510M | | 10 × 3.8† | 3.15 | 80 | 2.1 | 9.3 | 3.2 | 14.4 | 4.3 | 19.3 | 5.3 | 23.8 | 0.054 | 0.081 |
| Eagle Orange 85 | L04OG8512M | | 12 | 3.78 | 96 | 6.9 | 30.8 | 10.7 | 47.5 | 14.2 | 63.3 | 17.5 | 78 | 0.091 | 0.136 |
| Eagle Clear 85 | L04C8512M | | 12 | 3.78 | 96 | 6.9 | 30.8 | 10.7 | 47.5 | 14.2 | 63.3 | 17.5 | 78 | 0.091 | 0.136 |
| Eagle Green 89 | L04G8912MS | | 12 | 4.25 | 108 | 11.5 | 51.2 | 18.9 | 84.1 | 26 | 115.5 | 32.4 | 144.3 | 0.09 | 0.135 |
| Eagle Green 89 Textured | 4905312 | | 12 | 4.25 | 108 | 8.4 | 37.3 | 13.8 | 61.2 | 18.9 | 84.1 | 23.6 | 105.1 | 0.091 | 0.135 |
| Eagle Green 89 T SureConnect | 4934142 | | 12 | 4.25 | 108 | 8.4 | 37.3 | 13.8 | 61.2 | 18.9 | 84.1 | 23.6 | 105.1 | 0.091 | 0.135 |
| Eagle Red 90 | L04R9012M | | 12 | 4.72 | 120 | 37.8 | 168.4 | 54.5 | 242.5 | 68.6 | 305.2 | 80.3 | 357.2 | 0.092 | 0.137 |
| Eagle Red 85 QC | L04QR8512M | | 12 × 5.2† | 3.78 | 96 | 2.8 | 12.6 | 4.4 | 19.7 | 5.9 | 26.3 | 7.3 | 32.5 | 0.074 | 0.11 |
| Eagle Blue 85 QC | L04QB8512 | | 12 × 5.2† | 3.78 | 96 | 2.8 | 12.6 | 4.4 | 19.7 | 5.9 | 26.3 | 7.3 | 32.5 | 0.074 | 0.11 |
| Eagle Blue 80 MD | 4941105 | 1/2 | 12.7 | 3.5 | 89 | 5.4 | 23.9 | 8.4 | 37.3 | 11.2 | 49.7 | 13.8 | 61.6 | 0.095 | 0.142 |
| Eagle Orange 85 | 1032016 | 1/2 | 12.7 | 4 | 102 | 7.8 | 34.5 | 12 | 53.2 | 16 | 71 | 19.6 | 87.4 | 0.102 | 0.152 |
| Eagle Orange 89 SureConnect | 4934146 | 1/2 | 12.7 | 4 | 102 | 7.8 | 34.5 | 12 | 53.2 | 16 | 71 | 19.6 | 87.4 | 0.102 | 0.152 |
| Eagle Clear 85 | 4908024 | 1/2 | 12.7 | 4 | 102 | 7.8 | 34.5 | 12 | 53.2 | 16 | 71 | 19.6 | 87.4 | 0.102 | 0.152 |
| Eagle Red 90 | 4940026 | 1/2 | 12.7 | 5 | 127 | 42.4 | 188.6 | 61.1 | 271.7 | 76.9 | 342 | 90 | 400.2 | 0.103 | 0.153 |
| Eagle Clear 95 | 4907024 | 1/2 | 12.7 | 5 | 127 | 14.5 | 64.6 | 21.6 | 95.9 | 27.7 | 123.1 | 32.9 | 146.4 | 0.105 | 0.156 |
| Eagle Clear 85 QC | 4934024 | 500 × .205† | | 4 | 102 | 3.3 | 14.5 | 5.1 | 22.5 | 6.8 | 30.2 | 8.4 | 37.2 | 0.085 | 0.126 |
| Eagle Yellow 85 QC | 4934026 | 500 × .205† | | 4 | 102 | 3.3 | 14.5 | 5.1 | 22.5 | 6.8 | 30.2 | 8.4 | 37.2 | 0.085 | 0.126 |
| Eagle Red 85 | L04R8512.7 | 1/2 | 12.7 | 4 | 102 | 7.8 | 34.5 | 12 | 53.2 | 16 | 71 | 19.6 | 87.4 | 0.102 | 0.152 |
| Eagle Blue 85 | L04BL8512.7 | 1/2 | 12.7 | 4 | 102 | 7.8 | 34.5 | 12 | 53.2 | 15.9 | 70.9 | 19.6 | 87.4 | 0.102 | 0.152 |
| QC Connectors | L04CON10S | 20/pack (Use for 3/8" and 10mm) | | | | | | | | | | | | | |
| QC Connectors | L04CON13S | 20/pack (Use for 1/2" and 12-13mm) | | | | | | | | | | | | | |
| SureConnect Connectors | 4935031 | 5/pack (Use for 10mm) | | | | | | | | | | | | | |
| SureConnect Connectors | 4935032 | 5/pack (Use for 1/2" and 12mm) | | | | | | | | | | | | | |
| REINFORCED | Part Number* | Dimensions Ø (in) (mm) | | Minimum Pulley Ø (in) (mm) | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | | | | | | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m |
| Eagle Orange 85 | L04OG8510MR | | 10 | 3.94 | 100 | 2 | 8.8 | 6.9 | 30.6 | 13.4 | 59.7 | 19.3 | 85.7 | 0.063 | 0.094 |
| Eagle Green 89 | L04G8910MRS | | 10 | 3.94 | 100 | 6.6 | 29.5 | 20 | 88.8 | 40.9 | 181.9 | 63.1 | 280.5 | 0.063 | 0.093 |
| Eagle Green 89 Textured | 4940052 | | 10 | 3.94 | 100 | 9.1 | 40.6 | 27.5 | 122.1 | 56.2 | 250.1 | 86.7 | 385.6 | 0.063 | 0.093 |
| Eagle Beige 95 | L04BE9510R | | 10 | 4.72 | 120 | 6 | 26.7 | 11 | 48.9 | 16.2 | 72.1 | 21.2 | 94.3 | 0.065 | 0.097 |
| Eagle Orange 85 | L04OG8512R | | 12 | 4.72 | 120 | 2.9 | 12.7 | 9.9 | 44.1 | 19.3 | 85.9 | 27.7 | 123.4 | 0.091 | 0.136 |
| Eagle Green 89 | L04G8912MRS | | 12 | 4.72 | 120 | 9.6 | 42.6 | 28.8 | 127.9 | 58.9 | 262 | 90.8 | 404 | 0.09 | 0.135 |
| Eagle Green 89 Textured | 4940053 | | 12 | 4.72 | 120 | 13.2 | 58.5 | 39.5 | 175.9 | 81 | 360.2 | 124.9 | 555.4 | 0.09 | 0.135 |
| Eagle Orange 85 | 4940061 | 1/2 | 12.7 | 5 | 127 | 3.2 | 14.2 | 11.1 | 49.4 | 21.6 | 96.3 | 31.1 | 138.3 | 0.102 | 0.152 |
| Eagle Hyfen 85 | 5218024 | 1/2 | 12.7 | 5.5 | 140 | 7.3 | 32.5 | 26.2 | 116.5 | 43.5 | 193.5 | 57.4 | 255.3 | 0.102 | 0.152 |

* Standard package length 100' / 30.5m

† w (width) is the widest part of the belt. h (height) is the tallest part of the belt, including the belting top surface.

‡ Belt has a .156" radius guide.

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

13mm, 9/16" Round Cross Sections

Round Belting



| NON-REINFORCED | | Dimensions Ø (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
|-----------------------------|--------------|---------------------------|-------------------------------|--------------------------------|------|----------|-------|----------|-------|-----------|-------|--------|-------|-------|
| Material and Color | Part Number* | | | (lbs) 4% | (N) | (lbs) 6% | (N) | (lbs) 8% | (N) | (lbs) 10% | (N) | lbs/ft | kg/m | |
| Eagle® Clear 85 QC | L04QC8513 | 13 x 5.2 [†] | 4.09 | 104 | 3.5 | 15.3 | 5.4 | 23.8 | 7.2 | 31.9 | 8.9 | 39.4 | 0.09 | 0.134 |
| Eagle Red 85 QC | L04QR8513M | 13 x 5.2 [†] | 4.09 | 104 | 3.5 | 15.3 | 5.4 | 23.8 | 7.2 | 31.9 | 8.9 | 39.4 | 0.09 | 0.134 |
| Eagle Blue 80 MD | 4941106 | 9/16 | 3.94 | 100 | 6.9 | 30.6 | 10.6 | 47.1 | 14.2 | 63 | 17.6 | 78.2 | 0.121 | 0.18 |
| Eagle Orange 85 | 1032018 | 9/16 | 4.5 | 114 | 9.8 | 43.7 | 15.1 | 67.3 | 20.2 | 89.8 | 24.9 | 110.6 | 0.129 | 0.192 |
| Eagle Orange 89 SureConnect | 4934147 | 9/16 | 4.5 | 114 | 9.8 | 43.7 | 15.1 | 67.3 | 20.2 | 89.8 | 24.9 | 110.6 | 0.129 | 0.192 |
| Eagle Clear 85 | 4908027 | 9/16 | 4.5 | 114 | 9.8 | 43.7 | 15.1 | 67.3 | 20.2 | 89.8 | 24.9 | 110.6 | 0.129 | 0.192 |
| Eagle Red 90 | 4940036 | 9/16 | 5.63 | 143 | 53.7 | 238.6 | 77.3 | 343.8 | 97.3 | 432.7 | 113.8 | 506.3 | 0.13 | 0.194 |
| Eagle Clear 95 | 4907027 | 9/16 | 5.63 | 143 | 81.7 | 363.8 | 121.3 | 537.3 | 155.8 | 693.7 | 185.3 | 815.3 | 0.133 | 0.197 |
| QC Connectors | L04CON13S | 20/pack | | | | | | | | | | | | |
| SureConnect Connectors | 4935033 | 5/pack | | | | | | | | | | | | |
| REINFORCED | | Dimensions Ø (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
| Material and Color | Part Number* | | | (lbs) 1% | (N) | (lbs) 2% | (N) | (lbs) 3% | (N) | (lbs) 4% | (N) | lbs/ft | kg/m | |
| Eagle Orange 85 | 4940062 | 9/16 | 5.63 | 143 | 4.1 | 18 | 14 | 62.5 | 27.4 | 121.8 | 39.3 | 174.9 | 0.129 | 0.192 |
| Eagle Hyfen 85 | 5218027 | 9/16 | 6.19 | 157 | 16.7 | 74.3 | 36.6 | 162.8 | 58 | 258 | 75.8 | 337.2 | 0.129 | 0.192 |

15mm, 16mm, 5/8" Round Cross Sections

Round Belting



| NON-REINFORCED | | Dimensions Ø (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
|------------------------------|--------------|---------------------------|-------------------------------|--------------------------------|------|----------|-------|----------|-------|-----------|-------|--------|-------|-------|
| Material and Color | Part Number* | | | (lbs) 4% | (N) | (lbs) 6% | (N) | (lbs) 8% | (N) | (lbs) 10% | (N) | lbs/ft | kg/m | |
| Eagle® Opaque 80 | L04OP8015M | 15 | 4.13 | 105 | 11.6 | 51.6 | 19.7 | 87.7 | 27.6 | 122.6 | 34.7 | 154.4 | 0.145 | 0.216 |
| Eagle Blue 85 | L04BL8515 | 15 | 4.72 | 120 | 10.8 | 48.1 | 16.7 | 74.2 | 22.2 | 99 | 27.4 | 121.9 | 0.142 | 0.212 |
| Eagle Green 89 | L04G8915MS | 15 | 5.31 | 135 | 18 | 80 | 29.5 | 131.4 | 40.6 | 180.5 | 50.7 | 225.5 | 0.141 | 0.21 |
| Eagle Green 89 Textured | 4905315 | 15 | 5.31 | 135 | 13.1 | 58.1 | 21.5 | 95.4 | 29.5 | 131.1 | 36.8 | 163.8 | 0.141 | 0.21 |
| Eagle Green 89 T SureConnect | 4934143 | 15 | 5.31 | 135 | 13.1 | 58.1 | 21.5 | 95.4 | 29.5 | 131.1 | 36.8 | 163.8 | 0.141 | 0.21 |
| Eagle Red 90 | 4999315 | 15 | 5.91 | 150 | 59.1 | 262.9 | 85.2 | 378.8 | 107.2 | 476.8 | 125.4 | 557.9 | 0.144 | 0.214 |
| Eagle Beige 95 | L04BE9515M | 15 | 5.91 | 150 | 47.8 | 212.5 | 67.7 | 301.2 | 84.6 | 376.2 | 98.9 | 440 | 0.146 | 0.217 |
| Eagle White 40D | L04BY4015 | 15 | 7.09 | 180 | 46.8 | 208.1 | 71.9 | 319.9 | 94.3 | 419.6 | 113.6 | 505.4 | 0.139 | 0.207 |
| Eagle Blue 55D | L04BY5515 | 15 | 7.68 | 195 | 88.3 | 392.9 | 135.9 | 604.6 | 176.7 | 785.8 | 209.3 | 931 | 0.142 | 0.212 |
| Eagle Blue 80 MD | 4941107 | 5/8 | 4.38 | 111 | 8.4 | 37.5 | 13.1 | 58.2 | 17.4 | 77.6 | 21.7 | 96.4 | 0.149 | 0.222 |
| Eagle Orange 85 | 1032020 | 5/8 | 5 | 127 | 12.1 | 53.9 | 18.7 | 83.1 | 24.9 | 110.8 | 30.7 | 136.5 | 0.16 | 0.238 |
| Eagle Clear 85 | 4908030 | 5/8 | 5 | 127 | 12.1 | 53.9 | 18.7 | 83.1 | 24.9 | 110.8 | 30.7 | 136.5 | 0.16 | 0.238 |
| Eagle Clear 95 | 4907030 | 5/8 | 6.25 | 159 | 22.7 | 100.9 | 33.7 | 149.8 | 43.2 | 192.3 | 51.4 | 228.7 | 0.164 | 0.243 |
| Eagle Clear 85 QC | 4934030 | .625 x .273 [‡] | 5 | 127 | 5 | 22.1 | 7.7 | 34.2 | 10.3 | 45.9 | 12.7 | 56.6 | 0.129 | 0.192 |
| Eagle Yellow 85 QC | 4934020 | .625 x .273 [‡] | 5 | 127 | 5 | 22.1 | 7.7 | 34.2 | 10.3 | 45.9 | 12.7 | 56.6 | 0.129 | 0.192 |
| Eagle Clear 85 QC | L04QC8516M | 16 x 6.8 [†] | 5.04 | 128 | 5.1 | 22.7 | 7.9 | 35.2 | 10.6 | 47.2 | 13.1 | 58.2 | 0.133 | 0.198 |
| Eagle Red 85 QC | L04QR8516M | 16 x 6.8 [†] | 5.04 | 128 | 5.1 | 22.7 | 7.9 | 35.2 | 10.6 | 47.2 | 13.1 | 58.2 | 0.133 | 0.198 |
| QC Connectors | 4935030 | 15/pack | | | | | | | | | | | | |
| SureConnect Connectors | 4935033 | 5/pack | | | | | | | | | | | | |
| REINFORCED | | Dimensions Ø (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
| Material and Color | Part Number* | | | (lbs) 1% | (N) | (lbs) 2% | (N) | (lbs) 3% | (N) | (lbs) 4% | (N) | lbs/ft | kg/m | |
| Eagle Orange 85 | L04OG8515MR | 15 | 5.91 | 150 | 4.5 | 19.9 | 15.5 | 68.9 | 30.2 | 134.3 | 43.3 | 192.8 | 0.142 | 0.212 |
| Eagle Green 89 | L04G8915MRS | 15 | 5.91 | 150 | 15 | 66.5 | 44.9 | 199.9 | 92 | 409.3 | 141.9 | 631.2 | 0.141 | 0.21 |
| Eagle Green 89 Textured | 4940054 | 15 | 5.91 | 150 | 20.6 | 91.5 | 61.8 | 274.8 | 126.5 | 562.8 | 195.1 | 867.9 | 0.141 | 0.21 |
| Eagle Beige 95 | L04BE9515R | 15 | 7.09 | 180 | 13.5 | 60.1 | 24.7 | 109.9 | 36.5 | 162.4 | 47.8 | 212.6 | 0.146 | 0.217 |
| Eagle Hyfen 85 | 5218030 | 5/8 | 6.88 | 175 | 16.7 | 74.3 | 36.6 | 162.8 | 58 | 258 | 75.8 | 337.2 | 0.16 | 0.238 |

* Standard package length 100' / 30.5m

† w (width) is the widest part of the belt. h (height) is the tallest part of the belt, including the belting top surface.

‡ Belt has a .156" radius guide.

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

18mm, 3/4" Round Cross Sections

Round Belting



Round

| NON-REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|------------------------------|------------|--------------------------------|--------------|------|------------------|-------|--------------------------------|-------|-------|-------|--------|-------|--------|--------|--------|--|
| Material and Color | (in) | | (mm) | (in) | (mm) | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| Eagle® Green 89 | L04G8918MS | | 18 | 6.38 | 162 | 25.9 | 115.2 | 42.5 | 189.2 | 58.4 | 259.9 | 73 | 324.6 | 0.203 | 0.303 | |
| Eagle Green 89 Textured | 4940091 | | 18 | 6.38 | 162 | 18.8 | 83.7 | 30.9 | 137.5 | 42.4 | 188.8 | 53 | 235.9 | 0.203 | 0.303 | |
| Eagle Green 89 T SureConnect | 4934144 | | 18 | 6.38 | 162 | 18.8 | 83.7 | 30.9 | 137.5 | 42.4 | 188.8 | 53 | 235.9 | 0.203 | 0.303 | |
| Eagle White 40D | L04BY4018 | | 18 | 8.5 | 216 | 67.4 | 299.7 | 103.6 | 460.7 | 135.8 | 604.2 | 163.6 | 727.8 | 0.2 | 0.298 | |
| Eagle Blue 55D | L04BY5518 | | 18 | 9.21 | 234 | 127.2 | 565.8 | 195.7 | 870.6 | 254.4 | 1131.6 | 301.4 | 1340.7 | 0.205 | 0.305 | |
| Eagle Orange 85 | 1032024 | | 3/4 | 6 | 152 | 17.5 | 77.7 | 26.9 | 119.6 | 35.9 | 159.6 | 44.2 | 196.6 | 0.23 | 0.342 | |
| Eagle Orange 89 SureConnect | 4934148 | | 3/4 | 6 | 152 | 17.5 | 77.7 | 26.9 | 119.6 | 35.9 | 159.6 | 44.2 | 196.6 | 0.23 | 0.342 | |
| Eagle Clear 85 | 4908033 | | 3/4 | 6 | 152 | 17.5 | 77.7 | 26.9 | 119.6 | 35.9 | 159.6 | 44.2 | 196.6 | 0.23 | 0.342 | |
| Eagle Clear 95 | 4907033 | | 3/4 | 7.5 | 191 | 32.7 | 145.3 | 48.5 | 215.7 | 62.3 | 277 | 74 | 329.4 | 0.236 | 0.351 | |
| SureConnect Connectors | 4935034 | 5/pack (Use for 18mm and 3/4") | | | | | | | | | | | | | | |
| REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | (in) | | (mm) | (in) | (mm) | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| Eagle Green 89 Textured | 4940055 | | 18 | 7.09 | 180 | 29.6 | 131.7 | 89 | 395.7 | 182.2 | 810.5 | 280.9 | 1249.7 | 0.203 | 0.303 | |
| Eagle Orange 85 | 4940064 | | 3/4 | 7.5 | 191 | 7.2 | 32.1 | 25 | 111.1 | 48.7 | 216.6 | 69.9 | 311 | 0.23 | 0.342 | |
| Eagle Hyfen 85 | 5218033 | | 3/4 | 8.25 | 210 | 16.7 | 74.3 | 36.6 | 162.8 | 58 | 258 | 75.8 | 337.2 | 0.23 | 0.342 | |

20mm Round Cross Section

Round Belting



Round

| NON-REINFORCED | | Part Number* | Dimensions Ø | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|-------------------------|------------|--------------|--------------|------|------------------|-------|--------------------------------|-------|-------|-------|-------|-------|-------|--------|--------|--|
| Material and Color | (in) | | (mm) | (in) | (mm) | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| Eagle Green 89 | L04G8920MS | | 20 | 7.09 | 180 | 32 | 142.3 | 52.5 | 233.5 | 72.1 | 320.8 | 90.1 | 400.8 | 0.251 | 0.374 | |
| Eagle Green 89 Textured | 4940092 | | 20 | 7.09 | 180 | 23.2 | 103.4 | 38.1 | 169.7 | 52.4 | 233.1 | 65.5 | 291.2 | 0.251 | 0.374 | |
| Eagle White 40D | L04BY4020 | | 20 | 9.45 | 240 | 83.2 | 370 | 127.9 | 568.7 | 167.7 | 745.9 | 202 | 898.6 | 0.247 | 0.368 | |

* Standard package length 100' / 30.5m

† QC dimensions are shown O.D x I.D. (O.D. is the outer diameter of the belt. I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Conveying - Eagle® Polyurethane

6x4, 8x5, 10x4mm Cross Section

V Belting

| NON-REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
|----------------|--------------------|------------------|--------------|--------------------------------|-------------------------------|--------------------------------|------|-------|------|-------|------|-------|------|--------|-------|-------|
| | | | | | | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| | Eagle® Blue 80 EC | 6mm × 4mm | 4928009 | 6.5 × 4 | 1.1 | 28 | 0.8 | 3.7 | 1.5 | 6.7 | 2.1 | 9.4 | 2.7 | 12.1 | 0.015 | 0.023 |
| | Eagle Clear 80 EC | 6mm × 4mm | 4927009 | 6.5 × 4 | 1.1 | 28 | 0.8 | 3.7 | 1.5 | 6.7 | 2.1 | 9.4 | 2.7 | 12.1 | 0.015 | 0.023 |
| | Eagle Clear 85 | 6mm × 4mm | L04C850604 | 6.5 × 4 | 1.26 | 32 | 1 | 4.5 | 1.7 | 7.6 | 2.4 | 10.7 | 3 | 13.5 | 0.016 | 0.024 |
| | Eagle Blue 85 | 6mm × 4mm | L04BL850604 | 6.5 × 4 | 1.25 | 32 | 1 | 4.5 | 1.7 | 7.6 | 2.3 | 10.7 | 3 | 13.5 | 0.016 | 0.024 |
| | Eagle Blue 80 EC | 8mm × 5mm | 4928010 | 8 × 5 | 1.38 | 35 | 1.3 | 5.7 | 2.4 | 10.5 | 3.3 | 14.6 | 4.2 | 18.9 | 0.024 | 0.035 |
| | Eagle Clear 80 EC | 8mm × 5mm | 4927010 | 8 × 5 | 1.38 | 35 | 1.3 | 5.7 | 2.4 | 10.5 | 3.3 | 14.6 | 4.2 | 18.9 | 0.024 | 0.035 |
| | Eagle Opaque 80 | 8mm × 5mm | 4940006 | 8 × 5 | 1.38 | 35 | 1.6 | 7.1 | 3.3 | 14.7 | 5.2 | 23.1 | 7 | 31.2 | 0.026 | 0.039 |
| | Eagle Red 85 | 8mm × 5mm | L04R8585M | 8 × 5 | 1.57 | 40 | 1.5 | 6.8 | 2.6 | 11.5 | 3.6 | 16.2 | 4.6 | 20.5 | 0.025 | 0.038 |
| | Eagle Blue 85 | 8mm × 5mm | L04BL8585M | 8 × 5 | 1.57 | 40 | 1.5 | 6.8 | 2.6 | 11.5 | 3.6 | 16.2 | 4.6 | 20.5 | 0.025 | 0.038 |
| | Eagle Red 90 | 8mm × 5mm | 4940027 | 8 × 5 | 2 | 50 | 10.8 | 48.1 | 15.6 | 69.3 | 19.6 | 87.2 | 22.9 | 102 | 0.026 | 0.039 |
| | Eagle White 40D | 8mm × 5mm | L04BY400805 | 8 × 5 | 2.36 | 60 | 6 | 26.5 | 10.2 | 45.3 | 14 | 62.4 | 17.3 | 77.2 | 0.025 | 0.037 |
| | Eagle Blue 80 EC | 10mm × 4mm T-Top | 4928011 | 10 × 4 | 1.1 | 28 | 1 | 4.6 | 1.9 | 8.5 | 2.7 | 11.8 | 3.4 | 15.3 | 0.019 | 0.028 |
| | Eagle Clear 80 EC | 10mm × 4mm T-Top | 4927011 | 10 × 4 | 1.1 | 28 | 1 | 4.6 | 1.9 | 8.5 | 2.7 | 11.8 | 3.4 | 15.3 | 0.019 | 0.028 |

Z/10, 3L Cross Section

V Belting

| NON-REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
|----------------|--------------------|---------------|--------------|--------------------------------|-------------------------------|--------------------------------|------|-------|------|-------|------|-------|------|--------|-------|-------|
| | | | | | | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| | Eagle Orange 85 | 3L | 1032030 | 3/8 × 7/32 | 1.75 | 44 | 2.1 | 9.5 | 3.6 | 16.1 | 5.1 | 22.6 | 6.4 | 28.6 | 0.035 | 0.053 |
| | Eagle Clear 85 | 3L | 4912063 | 3/8 × 7/32 | 1.75 | 44 | 2.2 | 9.7 | 3.7 | 16.5 | 5.2 | 23.1 | 6.6 | 29.3 | 0.035 | 0.053 |
| | Eagle Blue 85 | 3L | L04BL853L | 3/8 × 7/32 | 1.75 | 45 | 2.1 | 9.5 | 3.6 | 16.1 | 5.1 | 22.6 | 6.4 | 28.6 | 0.035 | 0.053 |
| | Eagle Clear 95 | 3L | 4911063 | 3/8 × 7/32 | 2.19 | 56 | 4 | 17.9 | 6.6 | 29.2 | 8.8 | 39.3 | 10.8 | 47.9 | 0.036 | 0.054 |
| | Eagle Orange 85 | 3L Crown-Top | 1032032 | 9/16 × 1/4 | 2 | 51 | 3 | 13.2 | 5 | 22.4 | 7.1 | 31.5 | 9 | 39.9 | 0.049 | 0.073 |
| | Eagle Orange 85 | 3L T-Top | 1032031 | 9/16 × 19/64 | 2.38 | 60 | 3.5 | 15.7 | 6 | 26.5 | 8.4 | 37.2 | 10.6 | 47.2 | 0.058 | 0.087 |
| | Eagle Clear 85 | 3L T-Top | 4912064 | 9/16 × 19/64 | 2.38 | 60 | 3.6 | 16.1 | 6.1 | 27.2 | 8.6 | 38.2 | 10.9 | 48.3 | 0.058 | 0.087 |
| | Eagle Orange 85 | 3L Twin | 1032033 | 15/16 × 17/64 | 2.13 | 54 | 5.9 | 26.2 | 10 | 44.5 | 14 | 62.4 | 17.8 | 79 | 0.098 | 0.145 |
| | Eagle Clear 85 | 3L Twin | 4912065 | 15/16 × 17/64 | 2.13 | 54 | 6 | 26.9 | 10.2 | 45.6 | 14.4 | 63.9 | 18.2 | 81 | 0.098 | 0.145 |
| | Eagle Clear 95 | 3L Twin | 4911065 | 15/16 × 17/64 | 2.5 | 64 | 11.1 | 49.5 | 18.1 | 80.6 | 24.4 | 108.5 | 29.7 | 132.2 | 0.1 | 0.149 |
| | Eagle Blue 80 EC | Z/10 | 4928012 | 10 × 6.5 | 1.79 | 46 | 2.1 | 9.2 | 3.8 | 16.8 | 5.3 | 23.5 | 6.8 | 30.3 | 0.038 | 0.057 |
| | Eagle Clear 80 EC | Z/10 | 4927012 | 10 × 6.5 | 1.79 | 46 | 2.1 | 9.2 | 3.8 | 16.8 | 5.3 | 23.5 | 6.8 | 30.3 | 0.038 | 0.057 |
| | Eagle Opaque 80 | Z/10 | 4940008 | 10 × 6.5 | 1.79 | 46 | 2.5 | 11.3 | 5.2 | 23.3 | 8.3 | 36.8 | 11.1 | 49.5 | 0.041 | 0.062 |
| | Eagle Orange 85 | Z/10 | 4940114 | 10 × 6.5 | 1.88 | 52 | 2.5 | 10.9 | 4.2 | 18.5 | 5.8 | 26 | 7.4 | 32.9 | 0.041 | 0.061 |
| | Eagle Clear 85 | Z/10 | 4940118 | 10 × 6.5 | 2.05 | 52 | 2.5 | 11.2 | 4.3 | 19 | 6 | 26.6 | 7.6 | 33.7 | 0.041 | 0.061 |
| | Eagle Ivory 85 | Z/10 | L04I85Z | 10 × 6.5 | 2.05 | 52 | 6.9 | 30.8 | 10.6 | 47 | 13.9 | 61.7 | 16.8 | 74.8 | 0.04 | 0.06 |
| | Eagle Blue 85 | Z/10 | L04BL85Z | 10 × 6.5 | 1.88 | 52 | 2.5 | 10.8 | 4.2 | 18.3 | 5.8 | 25.6 | 7.4 | 32.5 | 0.041 | 0.061 |
| | Eagle Green 89 | Z/10 | L04G89Z | 10 × 6.5 | 2.3 | 59 | 12.4 | 55.3 | 19 | 84.5 | 24.9 | 110.6 | 30 | 133.4 | 0.04 | 0.06 |
| | Eagle Red 90 | Z/10 | 4940028 | 10 × 6.5 | 2.5 | 65 | 16.9 | 75.2 | 24.3 | 108.3 | 30.6 | 136.3 | 35.9 | 159.5 | 0.041 | 0.061 |
| | Eagle White 40D | Z/10 | L04BY40Z | 10 × 6.5 | 3.07 | 78 | 9.4 | 41.9 | 16.1 | 71.6 | 22.2 | 98.7 | 27.4 | 122 | 0.039 | 0.058 |
| | Eagle Blue 55D | Z/10 | L04BY55Z | 10 × 6.5 | 3.33 | 85 | 37.1 | 165.2 | 54.6 | 242.8 | 68.5 | 304.8 | 79.3 | 352.9 | 0.041 | 0.061 |
| REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | | |
| | | | | | | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m | |
| | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | | |
| | Eagle Beige 95 | 3L | 4940070 | 3/8 × 7/32 | 2.63 | 67 | 11.4 | 50.5 | 26.5 | 117.9 | 38.9 | 172.9 | 47.8 | 212.8 | 0.036 | 0.054 |
| | Eagle Hyfen 85 | 3L Twin | 5299010 | 15/16 × 17/64 | 2.92 | 74 | 15.5 | 68.8 | 21.8 | 96.8 | 28.4 | 126.4 | 34.7 | 154.4 | 0.095 | 0.142 |
| | Eagle Orange 85 | Z/10 | 4940065 | 10 × 6.5 | 2.38 | 65 | 2.4 | 10.7 | 5.7 | 25.3 | 9.1 | 40.4 | 12 | 53.3 | 0.04 | 0.06 |
| | Eagle Ivory 85 | Z/10 | L04I85ZR | 10 × 6.5 | 2.56 | 65 | 3.1 | 13.7 | 9.3 | 41.3 | 14.8 | 65.7 | 18.8 | 83.8 | 0.04 | 0.06 |

* Standard package length 100' / 30.5m

† QC dimensions are shown OD x I.D. (O.D. is the outer diameter of the belt, I.D. is the inner diameter of the belt.)

‡ Standard Can Cable package length 500' reel

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

A Cross Section V Belting




| NON-REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† | | Minimum Pulley Ø | Working Load @ Percent Tension | | | | | | | | Weight | | | | | | |
|----------------|-------------------------|-------------------|--------------|-------------------|------------|------------------|--------------------------------|--------------------------------|-------|------|-------|-------|-------|-------|--------|--------|-------|-------|--------|--------|------|
| | | | | (in) | (mm) | | 4% | 6% | 8% | 10% | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | lbs/ft | kg/m | |
| | Eagle® Blue 80 EC | A/13 | 4928013 | | 13 × 8 | 2.2 | 56 | 3.4 | 14.9 | 6.1 | 27.3 | 8.6 | 38.2 | 11.1 | 49.3 | 0.062 | 0.092 | | | | |
| | Eagle Clear 80 EC | A/13 | 4927013 | | 13 × 8 | 2.2 | 56 | 3.4 | 14.9 | 6.1 | 27.3 | 8.6 | 38.2 | 11.1 | 49.3 | 0.062 | 0.092 | | | | |
| | Eagle Blue 80 MD | A/13 | 4941108 | 1/2 × 5/16 | 13 × 8 | 2.2 | 56 | 2.8 | 12.6 | 4.8 | 21.5 | 6.8 | 30.4 | 8.8 | 38.9 | 0.061 | 0.091 | | | | |
| | Eagle Opaque 80 | A/13 | 4940009 | 1/2 × 5/16 | 13 × 8 | 2.2 | 56 | 4.1 | 18.1 | 8.4 | 37.3 | 13.2 | 58.8 | 17.8 | 79.2 | 0.066 | 0.099 | | | | |
| | Eagle Orange 85 | A/13 | 1032038 | 1/2 × 5/16 | 13 × 8 | 2.5 | 64 | 4 | 17.6 | 6.7 | 29.9 | 9.4 | 41.9 | 11.9 | 53.1 | 0.066 | 0.098 | | | | |
| | Eagle Clear 85 | A/13 | 4912066 | 1/2 × 5/16 | 13 × 8 | 2.5 | 64 | 4.1 | 18.1 | 6.9 | 30.6 | 9.7 | 43 | 12.2 | 54.4 | 0.066 | 0.098 | | | | |
| | Eagle Ivory 85 | A/13 | L04I85A | 1/2 × 5/16 | 13 × 8 | 2.52 | 64 | 11.2 | 50 | 17.2 | 76.4 | 22.5 | 100.2 | 27.3 | 121.4 | 0.065 | 0.096 | | | | |
| | Eagle Blue 85 | A/13 | L04BL85A | 1/2 × 5/16 | 13 × 8 | 2.5 | 64 | 4 | 18 | 6.8 | 30.4 | 9.5 | 42.7 | 12 | 54.1 | 0.066 | 0.098 | | | | |
| | Eagle Green 89 | A/13 | L04G89A | 1/2 × 5/16 | 13 × 8 | 2.83 | 72 | 20.2 | 89.8 | 30.8 | 137.2 | 40.4 | 179.6 | 48.7 | 216.6 | 0.066 | 0.098 | | | | |
| | Eagle Red 90 | A/13 | 4940029 | 1/2 × 5/16 | 13 × 8 | 3.13 | 80 | 27 | 120.2 | 38.9 | 173.1 | 49 | 217.9 | 57.3 | 255 | 0.066 | 0.098 | | | | |
| | Eagle Green 95 | A/13 | L04BE95A | 1/2 × 5/16 | 13 × 8 | 3.1 | 80 | 16.6 | 73.8 | 24.8 | 110.3 | 32 | 142.5 | 38.4 | 170.7 | 0.068 | 0.101 | | | | |
| | Eagle Clear 95 | A/13 | 4911066 | 1/2 × 5/16 | 13 × 8 | 3.13 | 79 | 7.5 | 33.2 | 12.2 | 54.2 | 16.4 | 72.9 | 20 | 88.9 | 0.067 | 0.1 | | | | |
| | Eagle White 40D | A/13 | L04BY40A | 1/2 × 5/16 | 13 × 8 | 3.78 | 96 | 15.5 | 69.1 | 26.6 | 118.1 | 36.6 | 162.8 | 45.2 | 201.2 | 0.064 | 0.096 | | | | |
| | Eagle Blue 55D | A/13 | L04BY55A | 1/2 × 5/16 | 13 × 8 | 4.09 | 104 | 60.3 | 268.3 | 88.6 | 394.3 | 111.3 | 495 | 128.8 | 573.1 | 0.066 | 0.098 | | | | |
| | Eagle Red 85 CXF | A/13 | 4924320 | 0.50 × 0.41 | 13 × 10.54 | 3.28 | 83 | 4.6 | 20.5 | 7.3 | 32.3 | 9.9 | 44 | 12.3 | 54.8 | 0.091 | 0.135 | | | | |
| | Eagle Ivory 85 SGT PU | A/13 | 493030030M | 0.50 × 0.47 | 13 × 12.06 | 3.28 | 83 | 11.2 | 50 | 17.2 | 76.4 | 22.5 | 100.2 | 27.3 | 121.4 | 0.085 | 0.127 | | | | |
| | Eagle Ivory 85 SGT PVC | A/13 | L04I85ASG | 0.50 × 0.53 | 13 × 13.51 | 3.28 | 83 | 11.2 | 50 | 17.2 | 76.4 | 22.5 | 100.2 | 27.3 | 121.4 | 0.095 | 0.142 | | | | |
| | Eagle Ivory 85 SGT TPE | A/13 | 493120030M | 0.50 × 0.48 | 13 × 12.34 | 3.28 | 83 | 11.2 | 50 | 17.2 | 76.4 | 22.5 | 100.2 | 27.3 | 121.4 | 0.028 | 0.124 | | | | |
| | Eagle Green 89 SGT PVC | A/13 | L04G89ASG | 0.50 × 0.53 | 13 × 13.51 | 3.69 | 94 | 20.2 | 89.8 | 30.8 | 137.2 | 40.4 | 179.6 | 48.7 | 216.6 | 0.096 | 0.143 | | | | |
| | Eagle Red 90 SGT PVC | A/13 | L04R90ASG | 0.50 × 0.53 | 13 × 13.51 | 3.69 | 94 | 27 | 120.2 | 38.9 | 173.1 | 49 | 217.9 | 57.3 | 255 | 0.096 | 0.143 | | | | |
| | Eagle White 40D SGT PVC | A/13 | L04BY40ASG | 0.50 × 0.53 | 13 × 13.51 | 5.34 | 136 | 15.5 | 69.1 | 26.6 | 118.1 | 36.6 | 162.8 | 45.2 | 201.2 | 0.095 | 0.141 | | | | |
| | Eagle Orange 85 | A/13 Hi-Ridge-Top | 1032040 | 1/2 × 5/8 | | 5 | 127 | 5.5 | 24.7 | 9.4 | 41.8 | 13.2 | 58.7 | 16.7 | 74.3 | 0.092 | 0.137 | | | | |
| | Eagle Clear 85 | A/13 Hi-Ridge-Top | 4911102 | 1/2 × 5/8 | | 5 | 127 | 5.3 | 23.7 | 9 | 40.1 | 12.7 | 56.3 | 16 | 71.3 | 0.086 | 0.128 | | | | |
| | Eagle Orange 85 | A/13 Lo-Ridge-Top | 1032039 | 1/2 × 7/16 | | 3.5 | 89 | 4.3 | 19.1 | 7.3 | 32.4 | 10.2 | 45.4 | 12.9 | 57.5 | 0.071 | 0.106 | | | | |
| | Eagle Clear 85 | A/13 Lo-Ridge-Top | 4912067 | 1/2 × 7/16 | | 3.5 | 89 | 4.3 | 19.3 | 7.3 | 32.6 | 10.3 | 45.8 | 13 | 58 | 0.07 | 0.104 | | | | |
| | Eagle Green 89 | A/13 Ridge-Top | L04G89AX | | 13 × 16 | 5.67 | 144 | 33 | 146.8 | 50.4 | 224.3 | 66 | 293.6 | 79.6 | 354.1 | 0.107 | 0.159 | | | | |
| | Eagle Orange 85 | A Twin | 1032041 | 1-3/16 × 5/16 | | 2.5 | 64 | 9.3 | 41.4 | 15.8 | 70.2 | 22.1 | 98.5 | 28.1 | 124.8 | 0.154 | 0.23 | | | | |
| | Eagle Clear 85 | A Twin | 4912068 | 1-3/16 × 5/16 | | 2.5 | 64 | 9.6 | 42.5 | 16.2 | 72 | 22.7 | 100.9 | 28.7 | 127.9 | 0.154 | 0.23 | | | | |
| | Eagle Orange 85 | AA | 1232550 | 1/2 × 13/32 | | 3.25 | 83 | 5.6 | 25.1 | 9.6 | 42.5 | 13.4 | 59.6 | 17 | 75.5 | 0.093 | 0.139 | | | | |
| REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | | | | | |
| | | | | (in) | (mm) | (in) | (mm) | 1% | 2% | 3% | 4% | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | lbs/ft | kg/m |
| | Eagle Opaque 80 | A/13 | L04OP80AR | 1/2 × 5/16 | 13 × 8 | 3.15 | 80 | 5.9 | 26.3 | 16 | 71.1 | 24 | 106.9 | 29.4 | 130.7 | 0.066 | 0.099 | | | | |
| | Eagle Orange 85 | A/13 | 4940066 | 1/2 × 5/16 | 13 × 8 | 3.13 | 80 | 3.9 | 17.3 | 9.3 | 41.2 | 14.8 | 65.8 | 19.5 | 86.6 | 0.065 | 0.097 | | | | |
| | Eagle Ivory 85 | A/13 | L04I85AR | 1/2 × 5/16 | 13 × 8 | 3.15 | 80 | 4.9 | 21.9 | 14.8 | 66 | 23.6 | 105.1 | 30.1 | 134.1 | 0.065 | 0.096 | | | | |
| | Eagle Green 89 | A/13 | L04G89AR | 1/2 × 5/16 | 13 × 8 | 3.15 | 80 | 3.8 | 16.8 | 14.3 | 63.5 | 53.9 | 239.9 | 88.7 | 394.8 | 0.065 | 0.096 | | | | |
| | Eagle Beige 95 | A/13 | 4940075 | 1/2 × 5/16 | 13 × 8 | 3.78 | 96 | 20.9 | 93 | 48.8 | 217.1 | 71.6 | 318.4 | 88.1 | 391.7 | 0.067 | 0.099 | | | | |
| | Eagle Beige 95 | A/13 Cogged | 4940071 | 1/2 × 5/16 | 13 × 8 | 2.78 | 71 | 20.9 | 93 | 48.8 | 217.1 | 71.6 | 318.4 | 88.1 | 391.7 | 0.067 | 0.099 | | | | |
| | Eagle Hyfen 95 | A | 5260200 | 1/2 × 3/8 | | 3.75 | 95 | 18.3 | 81.3 | 26.6 | 118.2 | 34.1 | 151.8 | 41.3 | 183.6 | 0.077 | 0.114 | | | | |
| | Eagle Hyfen 95 | A Cogged | 5220000 | 1/2 × 3/8 | | 2.75 | 70 | 18.3 | 81.3 | 26.6 | 118.2 | 34.1 | 151.8 | 41.3 | 183.6 | 0.077 | 0.114 | | | | |
| | Eagle Hyfen 85 | A Ridge-Top | 5299007 | 1/2 × 9/16 | | 6.19 | 157 | 17.4 | 77.4 | 25.1 | 111.5 | 33.8 | 150.2 | 42.8 | 190.2 | 0.1 | 0.148 | | | | |
| | Eagle Hyfen 85 | A Twin | 5299019 | 1-3/16 × 5/16 | | 3.44 | 87 | 45.5 | 202.2 | 34.4 | 153.2 | 44.9 | 199.9 | 54.9 | 244.2 | 0.151 | 0.224 | | | | |
| | Eagle Hyfen 85 CXF | A | 5260520 | 0.50 × 0.51 | | 4.53 | 115 | 17.4 | 77.4 | 25.1 | 111.5 | 33.8 | 150.2 | 42.8 | 190.2 | 0.103 | 0.153 | | | | |
| | Eagle Hyfen 85 CXR | A | 5260525 | 1.19 × 0.41 | | 4.53 | 115 | 17.4 | 77.4 | 25.1 | 111.5 | 33.8 | 150.2 | 42.8 | 190.2 | 0.088 | 0.131 | | | | |
| | Eagle Hyfen 85 CXF | A Twin | 5260572 | 0.50 × 0.51 | | 4.53 | 115 | 45.5 | 202.2 | 34.4 | 153.2 | 44.9 | 199.9 | 54.9 | 244.2 | 0.203 | 0.302 | | | | |
| | Eagle Hyfen 85 CXR | A Twin | 5260577 | 1.19 × 0.41 | | 4.53 | 115 | 45.5 | 202.2 | 34.4 | 153.2 | 44.9 | 199.9 | 54.9 | 244.2 | 0.174 | 0.259 | | | | |
| | Eagle Ivory 85 SGT PU | A/13 | 493060030M | 0.50 × 0.47 | 13 × 12.06 | 4.11 | 104 | 4.9 | 21.9 | 14.8 | 66 | 23.6 | 105.1 | 30.1 | 134.1 | 0.085 | 0.127 | | | | |
| | Eagle Ivory 85 SGT PVC | A/13 | L04I85ARSG | 0.50 × 0.53 | 13 × 13.51 | 4.11 | 104 | 4.9 | 21.9 | 14.8 | 66 | 23.6 | 105.1 | 30.1 | 134.1 | 0.095 | 0.142 | | | | |
| | Eagle Ivory 85 SGT TPE | A/13 | 493150030M | 0.50 × 0.48 | 13 × 12.34 | 4.11 | 104 | 4.9 | 21.9 | 14.8 | 66 | 23.6 | 105.1 | 30.1 | 134.1 | 0.084 | 0.124 | | | | |

* Standard package length 100' / 30.5m
 † w (width) is the widest part of the belt. h (height) is the tallest part of the belt, including the belting top surface.
 Dimensions are for reference only.
 All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Conveying - Eagle® Polyurethane

B Cross Section



V Belting

| NON-REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† (in) (mm) | | Minimum Pulley Ø (in) (mm) | | Working Load @ Percent Tension | | | | | | | | Weight lbs/ft kg/m | |
|-------------------------|--------------------|---------------|---------------|--------------------------------|------|-------------------------------|-------|--------------------------------|-------|-------|-------|-------|-------|--------|-------|-----------------------|--|
| | | | | | | | | 4% | | 6% | | 8% | | 10% | | | |
| | | | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle® Blue 80 EC | B/17 | 4928014 | | 17 × 11.5 | 3.17 | 81 | 6.1 | 27.3 | 11.2 | 49.9 | 15.7 | 69.9 | 20.3 | 90.2 | 0.113 | 0.168 | |
| Eagle Clear 80 EC | B/17 | 4927014 | | 17 × 11.5 | 3.17 | 81 | 6.1 | 27.3 | 11.2 | 49.9 | 15.7 | 69.9 | 20.3 | 90.2 | 0.113 | 0.168 | |
| Eagle Blue 80 MD | B/17 | 4941109 | 21/32 × 7/16 | 17 × 11.5 | 3.17 | 81 | 5 | 22 | 8.4 | 37.3 | 11.8 | 52.6 | 15.1 | 67 | 0.113 | 0.168 | |
| Eagle Opaque 80 | B/17 | 4940010 | 21/32 × 7/16 | 17 × 11.5 | 3.17 | 81 | 7.4 | 33.1 | 15.3 | 68 | 24.1 | 107.2 | 32.5 | 144.5 | 0.121 | 0.18 | |
| Eagle Orange 85 | B/17 | 1032047 | 11/16 × 13/32 | 17.5 × 10 | 3.25 | 83 | 7 | 31.1 | 11.8 | 52.7 | 16.6 | 73.9 | 21.1 | 93.7 | 0.116 | 0.172 | |
| Eagle Clear 85 | B/17 | 4912069 | 11/16 × 13/32 | 17.5 × 10 | 3.25 | 83 | 7.2 | 31.9 | 12.1 | 54 | 17 | 75.8 | 21.6 | 96 | 0.116 | 0.172 | |
| Eagle Ivory 85 | B/17 | L04I85B | 21/32 × 7/16 | 17 × 11.5 | 3.62 | 92 | 20.6 | 91.6 | 31.4 | 139.8 | 41.2 | 183.4 | 49.9 | 222.2 | 0.118 | 0.175 | |
| Eagle Blue 85 | B/17 | L04BL85B | 21/32 × 7/16 | 17 × 11.5 | 3.25 | 92 | 7.3 | 31 | 12.4 | 52.5 | 17.4 | 73.7 | 22 | 93.4 | 0.121 | 0.18 | |
| Eagle Green 89 | B/17 | L04G89B | 21/32 × 7/16 | 17 × 11.5 | 4.07 | 104 | 37 | 164.4 | 56.4 | 251.1 | 73.9 | 328.7 | 89.1 | 396.4 | 0.12 | 0.178 | |
| Eagle Clear 95 | B/17 | 4911069 | 11/16 × 13/32 | 17.5 × 10 | 4.13 | 105 | 13.2 | 58.6 | 21.5 | 95.5 | 28.9 | 128.6 | 35.2 | 156.8 | 0.119 | 0.177 | |
| Eagle White 40D | B/17 | L04BY40B | 21/32 × 7/16 | 17 × 11 | 5.2 | 132 | 27.6 | 122.6 | 47.1 | 209.5 | 64.9 | 288.9 | 80.3 | 357 | 0.114 | 0.17 | |
| Eagle Blue 55D | B/17 | L04BY55B | 21/32 × 7/16 | 17 × 11.5 | 5.89 | 150 | 110.4 | 491 | 162.2 | 721.6 | 203.6 | 905.8 | 235.8 | 1048.7 | 0.121 | 0.18 | |
| Eagle Red 90 | B/17 | 4940030 | 21/32 × 7/16 | 17 × 11.5 | 4.5 | 115 | 49.3 | 219.3 | 71 | 315.9 | 89.4 | 397.5 | 104.6 | 465.2 | 0.12 | 0.178 | |
| Eagle Beige 95 | B/17 | L04BE95B | 21/32 × 7/16 | 17 × 11.5 | 4.5 | 115 | 30.4 | 135.1 | 45.4 | 201.9 | 58.6 | 260.8 | 70.2 | 312.3 | 0.124 | 0.184 | |
| Eagle Orange 85 | B/17 Ribbed | 1032046 | 11/16 × 13/32 | 17.5 × 10 | 3.25 | 83 | 6.5 | 28.7 | 10.9 | 48.6 | 15.3 | 68.3 | 19.4 | 86.5 | 0.107 | 0.159 | |
| Eagle Green 89 | B/17 Ridge-Top | L04G89BX | | 17 × 19.5 | 6.91 | 176 | 53.7 | 238.9 | 82 | 364.9 | 107.4 | 477.7 | 129.5 | 576.1 | 0.174 | 0.259 | |
| Eagle Orange 85 | B/17 Wing-Top | 1032048 | 11/16 × 5/8 | | 5 | 127 | 7.8 | 34.6 | 13.2 | 58.7 | 18.5 | 82.3 | 23.5 | 104.3 | 0.129 | 0.192 | |
| Eagle Orange 85 | BB | 1232600 | 11/16 × 9/16 | | 4.5 | 114 | 10.3 | 45.8 | 17.5 | 77.7 | 24.5 | 109 | 31.1 | 138.1 | 0.171 | 0.254 | |
| Eagle Clear 95 | BB | 4911070 | 11/16 × 9/16 | | 5.63 | 143 | 19.4 | 86.5 | 31.7 | 140.9 | 42.6 | 189.6 | 52 | 231.1 | 0.175 | 0.26 | |
| Eagle Red 85 CXF | B/17 | 4924330 | 0.69 × 0.51 | 17.5 × 12.54 | 4.28 | 109 | 8.1 | 36.1 | 12.8 | 57 | 17.4 | 77.5 | 21.7 | 96.7 | 0.15 | 0.223 | |
| Eagle Ivory 85 SGT PU | B/17 | 493040030M | 0.66 × 0.60 | 17 × 15.56 | 4.28 | 109 | 20.6 | 91.6 | 31.4 | 139.8 | 41.2 | 183.4 | 49.9 | 222.2 | 0.146 | 0.218 | |
| Eagle Ivory 85 SGT PVC | B/17 | L04I85BSG | 0.66 × 0.66 | 17 × 17.01 | 4.28 | 109 | 20.6 | 91.6 | 31.4 | 139.8 | 41.2 | 183.4 | 49.9 | 222.2 | 0.158 | 0.235 | |
| Eagle Ivory 85 SGT TPE | B/17 | 493130030M | 0.66 × 0.61 | 17 × 15.84 | 4.28 | 109 | 20.6 | 91.6 | 31.4 | 139.8 | 41.2 | 183.4 | 49.9 | 222.2 | 0.039 | 0.215 | |
| Eagle Green 89 SGT PVC | B/17 | L04G89BSG | 0.66 × 0.66 | 17 × 17.01 | 4.82 | 122 | 37 | 164.4 | 56.4 | 251.1 | 73.9 | 328.7 | 89.1 | 396.4 | 0.16 | 0.238 | |
| Eagle Red 90 SGT PVC | B/17 | L04R90BSG | 0.66 × 0.66 | 17 × 17.01 | 4.82 | 122 | 49.3 | 219.3 | 71 | 315.9 | 89.4 | 397.5 | 104.6 | 465.2 | 0.16 | 0.238 | |
| Eagle White 40D SGT PVC | B/17 | L04BY40BSG | 0.66 × 0.66 | 17 × 17.01 | 6.96 | 177 | 27.6 | 122.6 | 47.1 | 209.5 | 64.9 | 288.9 | 80.3 | 357 | 0.154 | 0.229 | |


| REINFORCED | Material and Color | Cross Section | Part Number* | Dimensions w × h† (in) (mm) | | Minimum Pulley Ø (in) (mm) | | Working Load @ Percent Tension | | | | | | | | Weight lbs/ft kg/m | |
|------------------------|--------------------|---------------|---------------|--------------------------------|------|-------------------------------|------|--------------------------------|------|-------|-------|-------|-------|--------|-------|-----------------------|--|
| | | | | | | | | 1% | | 2% | | 3% | | 4% | | | |
| | | | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle Hyfen 95 | B | 5260300 | 21/32 × 1/2 | | 5 | 127 | 26.9 | 119.6 | 39.1 | 173.8 | 50.2 | 223.3 | 60.7 | 270.1 | 0.131 | 0.196 | |
| Eagle Hyfen 95 | B Cogged | 5230000 | 21/32 × 1/2 | | 4 | 102 | 26.9 | 119.6 | 39.1 | 173.8 | 50.2 | 223.3 | 60.7 | 270.1 | 0.131 | 0.196 | |
| Eagle Hyfen 85 | B Ridge-Top | 5299009 | 21/32 × 11/16 | | 7.56 | 192 | 25.7 | 114.4 | 37 | 164.6 | 49.9 | 221.7 | 63.2 | 280.9 | 0.161 | 0.239 | |
| Eagle Opaque 80 | B/17 | L04OP80BR | 21/32 × 7/16 | 17 × 11.5 | 4.53 | 115 | 11 | 48.8 | 29.7 | 132 | 44.6 | 198.4 | 54.5 | 242.6 | 0.123 | 0.183 | |
| Eagle Orange 85 | B/17 | 4940067 | 21/32 × 7/16 | 17 × 11.5 | 4.38 | 115 | 7.1 | 31.6 | 16.9 | 75.2 | 27 | 120 | 35.5 | 158 | 0.119 | 0.177 | |
| Eagle Ivory 85 | B/17 | L04I85BR | 21/32 × 7/16 | 17 × 11.5 | 4.53 | 115 | 9 | 39.9 | 27.1 | 120.5 | 43.1 | 191.9 | 55 | 244.8 | 0.118 | 0.175 | |
| Eagle Green 89 | B/17 | 4940127 | 21/32 × 7/16 | 17 × 11.5 | 4.53 | 115 | 7 | 31.2 | 26.5 | 117.9 | 100.1 | 445.3 | 164.7 | 732.8 | 0.12 | 0.178 | |
| Eagle Beige 95 | B/17 | 4940076 | 21/32 × 7/16 | 17 × 11.5 | 5.43 | 138 | 38.8 | 172.7 | 90.6 | 403 | 132.9 | 591 | 163.5 | 727.2 | 0.124 | 0.184 | |
| Eagle Beige 95 | B/17 Cogged | 4940072 | 21/32 × 7/16 | 17 × 11.5 | 4.43 | 113 | 38.8 | 172.7 | 90.6 | 403 | 132.9 | 591 | 163.5 | 727.2 | 0.124 | 0.184 | |
| Eagle Ivory 85 | B/17 Ridge-Top | L04I85BRXH | | 17 × 19.5 | 7.68 | 195 | 13.3 | 59 | 40.1 | 178.3 | 63.8 | 283.8 | 81.4 | 362 | 0.174 | 0.259 | |
| Eagle Green 89 | B/17 Ridge-Top | L04G89BRXH | | 17 × 19.5 | 7.68 | 195 | 10.2 | 45.4 | 38.5 | 171.4 | 145.5 | 647.3 | 239.5 | 1065.1 | 0.174 | 0.259 | |
| Eagle Hyfen 85 CXF | B | 5260530 | 0.66 × 0.51 | | 5.89 | 150 | 25.7 | 114.4 | 37 | 164.6 | 49.9 | 221.7 | 63.2 | 280.9 | 0.141 | 0.21 | |
| Eagle Hyfen 85 CXR | B | 5260535 | 0.66 × 0.51 | | 5.89 | 150 | 25.7 | 114.4 | 37 | 164.6 | 49.9 | 221.7 | 63.2 | 280.9 | 0.122 | 0.181 | |
| Eagle Ivory 85 SGT PU | B/17 | 493020030M | 0.60 × 0.60 | 17 × 15.56 | 5.36 | 136 | 9 | 39.9 | 27.1 | 120.5 | 43.1 | 191.9 | 55 | 244.8 | 0.146 | 0.218 | |
| Eagle Ivory 85 SGT PVC | B/17 | L04I85BRSG | 0.66 × 0.66 | 17 × 17.01 | 5.36 | 136 | 9 | 39.9 | 27.1 | 120.5 | 43.1 | 191.9 | 55 | 244.8 | 0.158 | 0.235 | |
| Eagle Ivory 85 SGT TPE | B/17 | 493160030M | 0.66 × 0.61 | 17 × 15.84 | 5.36 | 136 | 9 | 39.9 | 27.1 | 120.5 | 43.1 | 191.9 | 55 | 244.8 | 0.144 | 0.215 | |

* Standard package length 100' / 30.5m

† w (width) is the widest part of the belt. h (height) is the tallest part of the belt, including the belting top surface. Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

C Cross Sections



V Belting

| NON-REINFORCED | | Part Number* | Dimensions w × h† | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|-------------------------|----------------|--------------|-------------------|------------|------------------|------|--------------------------------|-------|-------|-------|-------|--------|-------|--------|--------|-------|
| Material and Color | Cross Section | | (in) | (mm) | (in) | (mm) | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m |
| | | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle® Orange 85 | C/22 | 1032072 | 29/32 × 17/32 | 23 × 13.5 | 4.25 | 108 | 12.2 | 54.1 | 20.6 | 91.7 | 28.9 | 128.6 | 36.6 | 163 | 0.201 | 0.3 |
| Eagle Clear 85 | C/22 | 4912072 | 29/32 × 17/32 | 23 × 13.5 | 4.25 | 108 | 12.5 | 55.5 | 21.1 | 94 | 29.6 | 131.8 | 37.5 | 167 | 0.201 | 0.3 |
| Eagle Ivory 85 | C/22 | L04I85C | 7/8 × 9/16 | 22 × 14.5 | 4.57 | 116 | 33.9 | 150.6 | 51.7 | 229.8 | 67.8 | 301.7 | 82.1 | 365.4 | 0.194 | 0.289 |
| Eagle Blue 85 | C/22 | L04BL85C | 7/8 × 9/16 | 22 × 14.5 | 4.5 | 116 | 12 | 54 | 20.3 | 91.5 | 28.5 | 128.4 | 36.2 | 162.6 | 0.199 | 0.296 |
| Eagle Green 89 | C/22 | L04G89C | 7/8 × 9/16 | 22 × 14.5 | 5.14 | 131 | 60.8 | 270.3 | 92.8 | 412.9 | 121.5 | 540.5 | 146.5 | 651.9 | 0.197 | 0.293 |
| Eagle Red 90 | C/22 | 4999306 | 7/8 × 9/16 | 22 × 14.5 | 5.75 | 145 | 81.1 | 360.8 | 116.8 | 519.7 | 147.1 | 654.1 | 172.1 | 765.4 | 0.197 | 0.293 |
| Eagle Beige 95 | C/22 | L04BE95C | 7/8 × 9/16 | 22 × 14.5 | 5.7 | 145 | 49.9 | 222.2 | 74.6 | 332 | 96.4 | 428.9 | 115.5 | 513.6 | 0.204 | 0.303 |
| Eagle Clear 95 | C/22 | 4911072 | 29/32 × 17/32 | 23 × 13.5 | 5.31 | 135 | 22.9 | 102 | 37.4 | 166.2 | 50.3 | 223.7 | 61.3 | 272.7 | 0.206 | 0.307 |
| Eagle White 40D | C/22 | L04BY40C | 7/8 × 9/16 | 22 × 14.5 | 6.85 | 174 | 46.8 | 208 | 79.9 | 355.4 | 110.2 | 490 | 136.1 | 605.6 | 0.194 | 0.288 |
| Eagle Orange 85 | C/22 Ribbed | 1032054 | 29/32 × 17/32 | | 4.25 | 108 | 11.3 | 50.3 | 19.2 | 85.3 | 26.9 | 119.7 | 34.1 | 151.7 | 0.187 | 0.279 |
| Eagle Green 89 | C/22 Ridge-Top | 4999514 | | 22 × 24.5 | 8.68 | 221 | 85.6 | 380.7 | 130.7 | 581.4 | 171.1 | 761.2 | 206.4 | 917.9 | 0.278 | 0.413 |
| Eagle Green 89 | C/22 Ridge-Top | L04G89CX | | 22 × 28.5 | 10.1 | 257 | 98.7 | 439.2 | 150.8 | 670.8 | 197.4 | 878.1 | 238.1 | 1059 | 0.32 | 0.477 |
| Eagle Ivory 85 SGT PU | C/22 | 493050030M | 0.88 × 0.72 | 22 × 18.56 | 5.28 | 134 | 33.9 | 150.6 | 51.7 | 229.8 | 67.8 | 301.7 | 82.1 | 365.4 | 0.227 | 0.338 |
| Eagle Ivory 85 SGT PVC | C/22 | L04I85CSG | 0.88 × 0.78 | 22 × 20.01 | 5.28 | 134 | 33.9 | 150.6 | 51.7 | 229.8 | 67.8 | 301.7 | 82.1 | 365.4 | 0.245 | 0.365 |
| Eagle Ivory 85 SGT TPE | C/22 | 493140030M | 0.88 × 0.73 | 22 × 18.84 | 5.28 | 134 | 33.9 | 150.6 | 51.7 | 229.8 | 67.8 | 301.7 | 82.1 | 365.4 | 0.045 | 0.334 |
| Eagle Green 89 SGT PVC | C/22 | L04G89CSG | 0.88 × 0.78 | 22 × 20.01 | 5.94 | 151 | 60.8 | 270.3 | 92.8 | 412.9 | 121.5 | 540.5 | 146.5 | 651.9 | 0.248 | 0.37 |
| Eagle Red 90 SGT PVC | C/22 | L04R90CSG | 0.88 × 0.78 | 22 × 20.01 | 5.94 | 151 | 81.1 | 360.8 | 116.8 | 519.7 | 147.1 | 654.1 | 172.1 | 765.4 | 0.248 | 0.369 |
| Eagle White 40D SGT PVC | C/22 | L04BY40CSG | 0.88 × 0.78 | 22 × 20.01 | 8.59 | 218 | 46.8 | 208 | 79.9 | 355.4 | 110.2 | 490 | 136.1 | 605.6 | 0.24 | 0.358 |
| REINFORCED | | Part Number* | Dimensions w × h† | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | Cross Section | | (in) | (mm) | (in) | (mm) | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m |
| | | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle Hyfen 95 | C | 5260400 | 7/8 × 5/8 | | 6.25 | 159 | 39.8 | 177.2 | 57.9 | 257.6 | 74.4 | 330.8 | 90 | 400.3 | 0.226 | 0.337 |
| Eagle Hyfen 95 | C Cogged | 5240000 | 7/8 × 5/8 | | 5.25 | 133 | 39.8 | 177.2 | 57.9 | 257.6 | 74.4 | 330.8 | 90 | 400.3 | 0.226 | 0.337 |
| Eagle Orange 85 | C/22 | 4940068 | 7/8 × 9/16 | 22 × 14.5 | 5.62 | 145 | 11.7 | 52 | 27.8 | 123.7 | 44.4 | 197.4 | 58.4 | 260 | 0.196 | 0.291 |
| Eagle Ivory 85 | C/22 | L04I85CR | 7/8 × 9/16 | 22 × 14.5 | 5.71 | 145 | 14.8 | 65.7 | 44.6 | 198.3 | 71 | 315.7 | 90.5 | 402.7 | 0.194 | 0.289 |
| Eagle Green 89 | C/22 | L04G89CR | | 22 × 14.5 | 5.71 | 145 | 11.5 | 51.3 | 43.6 | 193.9 | 164.6 | 732.4 | 270.9 | 1205.1 | 0.197 | 0.293 |
| Eagle Beige 95 | C/22 | 4940077 | 7/8 × 9/16 | 22 × 14.5 | 6.85 | 174 | 63.8 | 284 | 149 | 662.7 | 218.5 | 971.9 | 268.8 | 1195.9 | 0.204 | 0.303 |
| Eagle Beige 95 | C/22 Cogged | 4940073 | 7/8 × 9/16 | 22 × 14.5 | 5.85 | 149 | 63.8 | 284 | 149 | 662.7 | 218.5 | 971.9 | 268.8 | 1195.9 | 0.204 | 0.303 |
| Eagle Ivory 85 | C/22 Ridge-Top | 5299103 | | 22 × 24.5 | 9.65 | 245 | 21.7 | 96.6 | 65.6 | 291.7 | 104.4 | 464.3 | 133.2 | 592.4 | 0.285 | 0.424 |
| Eagle Ivory 85 | C/22 Ridge-Top | L04I85CRXH | | 22 × 28.5 | 11.22 | 285 | 24.4 | 108.5 | 73.7 | 327.7 | 117.3 | 521.6 | 149.6 | 665.4 | 0.32 | 0.477 |
| Eagle Green 89 | C/22 Ridge-Top | 4999524 | | 22 × 24.5 | 9.65 | 245 | 16.2 | 72.3 | 61.4 | 273.1 | 231.8 | 1031.3 | 381.5 | 1697 | 0.278 | 0.413 |
| Eagle Green 89 | C/22 Ridge-Top | L04G89CRXH | | 22 × 28.5 | 11.22 | 285 | 18.7 | 83.4 | 70.8 | 315.1 | 267.5 | 1189.8 | 440.1 | 1957.8 | 0.32 | 0.477 |
| Eagle Hyfen 85 CXF | C | 5260540 | 0.88 × 0.63 | | 7.7 | 196 | 38 | 169.1 | 54.7 | 243.4 | 73.7 | 327.9 | 93.4 | 415.4 | 0.241 | 0.358 |
| Eagle Hyfen 85 CXR | C | 5260545 | 0.88 × 0.63 | | 7.7 | 196 | 38 | 169.1 | 54.7 | 243.4 | 73.7 | 327.9 | 93.4 | 415.4 | 0.215 | 0.32 |
| Eagle Ivory 85 SGT PU | C/22 | 493070030M | 0.88 × 0.72 | 22 × 18.56 | 6.61 | 168 | 14.8 | 65.8 | 44.6 | 198.3 | 71 | 315.7 | 90.5 | 402.7 | 0.227 | 0.338 |
| Eagle Ivory 85 SGT PVC | C/22 | L04I85CRSG | 0.88 × 0.78 | 22 × 20.01 | 6.61 | 168 | 14.8 | 65.8 | 44.6 | 198.3 | 71 | 315.7 | 90.5 | 402.7 | 0.245 | 0.365 |
| Eagle Ivory 85 SGT TPE | C/22 | 493170030M | 0.88 × 0.73 | 22 × 18.84 | 6.61 | 168 | 14.8 | 65.8 | 44.6 | 198.3 | 71 | 315.7 | 90.5 | 402.7 | 0.224 | 0.334 |

D Cross Section



V Belting

| NON-REINFORCED | | Part Number* | Dimensions w × h† | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
|--------------------|---------------|--------------|-------------------|-----------|------------------|------|--------------------------------|-------|-------|-------|-------|-----|-------|-------|--------|-------|
| Material and Color | Cross Section | | (in) | (mm) | (in) | (mm) | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m |
| | | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle Orange 85 | D/32 Ribbed | 1032062 | 1-5/16 × 3/4 | 33.5 × 19 | 6 | 152 | 22.9 | 101.8 | 38.8 | 172.5 | 54.4 | 242 | 68.9 | 306.7 | 0.379 | 0.564 |
| REINFORCED | | Part Number* | Dimensions w × h† | | Minimum Pulley Ø | | Working Load @ Percent Tension | | | | | | | | Weight | |
| Material and Color | Cross Section | | (in) | (mm) | (in) | (mm) | 1% | | 2% | | 3% | | 4% | | lbs/ft | kg/m |
| | | | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle Hyfen 85 CXF | D | 5260550 | 1.25 × 0.85 | | 10.88 | 276 | 77.1 | 343 | 111 | 493.6 | 149.5 | 665 | 189.4 | 842.4 | 0.448 | 0.667 |
| Eagle Hyfen 85 CXR | D | 5260555 | 1.25 × 0.85 | | 10.88 | 276 | 77.1 | 343 | 111 | 493.6 | 149.5 | 665 | 189.4 | 842.4 | 0.412 | 0.612 |

* Standard package length 100' / 30.5m
 † w (width) is the widest part of the belt h (height) is the tallest part of the belt, including the belting top surface.
 Dimensions are for reference only.
 All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Flat Belting



| NON-REINFORCED Material and Color | Cross Section | Part Number* | Dimensions w × h† (in) (mm) | Minimum Pulley Ø (in) (mm) | Working Load @ Percent Tension | | | | | | | | Weight | |
|--------------------------------------|---------------|--------------|--------------------------------|-------------------------------|--------------------------------|------|-------|------|-------|------|-------|------|--------|-------|
| | | | | | 4% | | 6% | | 8% | | 10% | | lbs/ft | kg/m |
| | | | | | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | (lbs) | (N) | | |
| Eagle® Orange 85 | .055" × .375" | 1032121 | .055 × .375 | 0.44 11 | 0.6 | 2.6 | 0.9 | 3.9 | 1.1 | 5 | 1.4 | 6.1 | 0.011 | 0.016 |
| Eagle Orange 85 | .062" × .5" | 1032126 | .062 × .500 | 0.5 13 | 0.9 | 3.9 | 1.3 | 5.8 | 1.7 | 7.6 | 2.1 | 9.2 | 0.016 | 0.024 |
| Eagle Orange 85 | .062" × .75"‡ | 1032210 | .062 × .750 | 0.5 13 | 2.3 | 10.1 | 3.4 | 15.1 | 4.4 | 19.7 | 5.4 | 23.9 | 0.042 | 0.062 |
| Eagle Orange 85 | .062" × 1.5" | 1032148 | .062 × 1.50 | 0.5 13 | 2.6 | 11.6 | 3.9 | 17.4 | 5.1 | 22.7 | 6.2 | 27.6 | 0.048 | 0.072 |
| Eagle Orange 85 | .062" × 1.75" | 1032155 | .062 × 1.75 | 0.5 13 | 3 | 13.5 | 4.6 | 20.3 | 6 | 26.5 | 7.2 | 32.2 | 0.056 | 0.084 |
| Eagle Orange 85 | .062" × 2" | 1032160 | .062 × 2.00 | 0.5 13 | 3.5 | 15.5 | 5.2 | 23.2 | 6.8 | 30.3 | 8.3 | 36.8 | 0.064 | 0.096 |
| Eagle Orange 85 | .062" × 3" | 1032170 | .062 × 3.00 | 0.5 13 | 5.2 | 23.2 | 7.8 | 34.8 | 10.2 | 45.5 | 12.4 | 55.2 | 0.097 | 0.144 |
| Eagle Orange 85 | .078" × .75" | 1032136 | .075 × .750 | 0.62 16 | 1.6 | 7.3 | 2.4 | 10.9 | 3.2 | 14.2 | 3.9 | 17.3 | 0.03 | 0.045 |
| Eagle Orange 85 | .090" × 1" | 1032142 | .090 × 1.00 | 0.72 18 | 2.5 | 11.2 | 3.8 | 16.8 | 4.9 | 21.9 | 6 | 26.6 | 0.047 | 0.069 |
| Eagle Orange 85 | .090" × 1.25" | 1032146 | .090 × 1.25 | 0.72 18 | 3.1 | 14 | 4.7 | 21 | 6.2 | 27.4 | 7.5 | 33.3 | 0.058 | 0.087 |
| Eagle Orange 85 | .090" × 1.5" | 1032151 | .090 × 1.50 | 0.72 18 | 3.8 | 16.8 | 5.7 | 25.2 | 7.4 | 33 | 9 | 40 | 0.07 | 0.104 |
| Eagle Orange 85 | .090" × 2" | 1032163 | .090 × 2.00 | 0.72 18 | 5 | 22.4 | 7.6 | 33.6 | 9.9 | 44 | 12 | 53.4 | 0.093 | 0.139 |
| Eagle Orange 85 | .125" × .625" | 1032133 | .125 × .625 | 1 25 | 2.2 | 9.7 | 3.3 | 14.5 | 4.3 | 19 | 5.2 | 23 | 0.04 | 0.06 |
| Eagle Orange 85 | .125" × 1" | 1032143 | .125 × 1.00 | 1 25 | 3.5 | 15.5 | 5.2 | 23.3 | 6.9 | 30.5 | 8.3 | 37 | 0.065 | 0.096 |
| Eagle Orange 85 | .250" × .625" | 1032134 | .250 × .625 | 2 51 | 4.4 | 19.4 | 6.5 | 29 | 8.5 | 38 | 10.4 | 46.1 | 0.081 | 0.12 |

* Standard package length 100' / 30.5m

† w (width) is the widest part of the belt. h (height) is the tallest part of the belt, including the belting top surface.


‡ Belt has a .156" radius guide.

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.

Eagle® Blue-Green Driver Pad


- Manufactured to OEM specifications
- Always a consistent profile with ideal hole alignment
- Contains 100% virgin material, allowing maximum performance
- Always in stock, ready to go to you!



| Part Number | Package Length |
|-------------|----------------|
| 4912092 | 250' |
| 4912096 | 500' |

Eagle® Taper Edge Bands

- Long lasting, minimal stretch replacement for PVC Bands on wallboard forming lines. Significantly increased life on lines exceeding 350'/min
- Fit and forget installation reduces labor and downtime costs
- Negligible band stretch — the same perfect impression day 1 and day 100
- Temperature resistance up to 180°F (82°C)



| COLOR | Part Number | | A† inches (mm) |
|-------|-------------|-------------|----------------------|
| | Left Side* | Right Side* | |
| Blue | 4938280BL | 4938280BR | 0.085 (2.2) |
| Red | 4938281BL | 4938281BR | 0.075 (1.9) |
| Green | 4938282BL | 4938282BR | 0.105 (2.7) |

| COLOR | Profile | Part Number | Dimensions mm (inches) |
|---------|---------|-------------|------------------------------|
| Natural | Square‡ | 4938286 | 1.4 × 60 (.06 × 2.36) |


* As belt travels toward you

† Also available in A dimensions .065" and .070" (1.7mm and 1.8mm)

‡ Non-stock product, minimum order quantity applies

Taper Edge Band Welding Kit

- Thermal splicing for a tough, seamless, flexible joint that maintains a perfect indentation
- Full weld in 12 minutes
- No board scrap generated from joint




| Profile | Part Number | Voltage | Plug |
|---------|-------------|---------|------|
| Blue | 5700301 | 115v | US |
| Red | 5700304 | 115v | US |
| Green | 5700305 | 115v | US |
| Blue | 5700306 | 240v | UK |
| Red | 5700307 | 240v | UK |
| Green | 5700308 | 240v | UK |
| Square | 5700309 | 240v | UK |

Kit includes: Platen Assembly, Controller, Cutting Shears, Finger Splice Template, Instructional Disc

Taper Edge Band Return Roller

- Prevents surface scoring due to Eagle Taper Edge Band rubbing against worn return support brackets
- Easy to install mounting bracket with hand knob for quick adjustment and release
- Solid polymer plain bearing allows low-friction rotation



| | Part Number |
|-----------------------------|-------------|
| Bracket and Roller Assembly | DA0041 |
| Roller | FX0395 |

Roller dimensions:



2.375" diameter × 8" width

(60.3mm diameter × 203.2mm width)

Eagle® Welding Kits

| Butt Welding Kit & Components – 120V | Part Numbers |
|---|--------------|
| Butt Welding Kit 120V – Large Clamp (US Plug) | 5700200 |
| Mini Butt Welding Kit 120V – Mini Clamp (US Plug) | 5700231 |
| Butt Welding Clamp | 5700201 |
| Mini Clamp | 5700227 |
| Hot Knife 120V with holder and 2" blade | 5700228 |
| Double Iron Hot Knife 120V with holder and 3" blade | 5700220 |
| Hot Knife Holder | 5700202 |
| Hot Knife Blade – 2" | 5700233 |
| Hot Knife Blade – 3" (Use with 5700220) | 5700218 |
| Cutting Shears | 5700153 |
| Flash Cutter | 1448000 |
| Clamping Plate (2 pcs) | 5700208 |
| Flat/V belt adapter Plate (2 pcs) | 5700209 |
| Black Knurled Knob (5 pcs) | 5700212 |
| Case | 5700203 |

| Butt Welding Kit & Components – 240V | Part Numbers |
|---|-----------------|
| Butt Welding Kit 240V – Large Clamp (US Plug) | 5700223 |
| Butt Welding Kit 240V – Large Clamp (UK Plug) | L04FULLWELD240V |
| Butt Welding Kit 240V – Large Clamp (Euro Plug) | L04FULLWELD240E |
| Mini Butt Welding Kit 240V – Mini Clamp (US Plug) | 5700232 |
| Mini Butt Welding Kit 240V – Mini Clamp (UK Plug) | L04MINIWELD240V |
| Mini Butt Welding Kit 240V – Mini Clamp (Euro Plug) | L04MINIWELD240E |
| Butt Welder Clamp | 5700201 |
| Mini Clamp | 5700227 |
| Hot Knife 240 V (US Plug) | 5700170 |
| Hot Knife 240 V (UK Plug) | L04HKNIFE240 |
| Cutting Shears | L04SHEARS |
| Flash Cutter | L04FCUTTER |
| Hot Knife Blade – 2" | L04S |
| Case (Large Clamp) | L04CASEBKST |
| Case (Mini Clamp) | L04CASEBLM |



Mini Clamp

Kit Includes: Hot Knife, Large Clamp or Mini Clamp, Flash Cutters, Cutting Shears, Carrying Case

| Butt Welding Kit & Components – 110V* | Part Numbers |
|--|-----------------|
| Butt Welding Kit 110V* – Large Clamp | L04FULLWELD110V |
| Mini Butt Welding Kit 110V* – Mini Clamp | L04MINIWELD110V |

* Unit designed to plug into a power transformer

| Eagle Freestyle® Cordless Welding | Part Numbers |
|-----------------------------------|--------------|
| Freestyle Welding Kit (US Plug) | 5700539 |
| Freestyle Welder | 5700537 |
| Freestyle Welder Blade Assembly | 5700366 |
| Freestyle Welder End Cap | 5700367 |
| Blade Replacement Tape 10/pk | 5700542 |
| Pack of 2 D cell NiMH batteries | 5700541 |
| Cutting Shears | 5700153 |
| Flash Cutter | 1448000 |



Kit includes: Welder, Flat Plate Adapters, Professional Battery Charger, (4) D Cell NiMH Batteries, Blade Release Tape, Cutting Shears, Flash Cutters, Tool Bag

| Overlap Welding Kit & Components | Part Numbers |
|---|--------------|
| Overlap Welding Kit 120V (US Plug) | 5700160K |
| Overlap Welding Kit 240V (UK Plug) | 5700161K |
| Flash Cutter | 5700152 |
| Case | 5700164 |
| Temperature Controller w/Control Box 120V (US Plug) | 5700300 |
| Temperature Controller w/Control Box 240V (UK Plug) | 5700310 |
| Heating Tip (Z Block) | 5700325 |
| Thumb Nuts | 5700330 |
| Hold Down Pin | 5700340 |
| Thermocouple Wire | 5700350 |
| Thermocouple Connector | 5700355 |
| Heating Element, Power Cord and Plug 120V (US Plug) | 5700360 |
| Heating Element, Power Cord and Plug 240V (UK Plug) | 5700361 |
| Plug Adapter – UK to EU | 5700351 |
| Spring | 5700380 |
| Heating Assembly Knob | 5700390 |
| 1/4" and 5/16" Die Set | 5700400 |
| 3/8" and 1/2" Die Set | 5700410 |
| 9/16", 5/8" and 16mm Die Set | 5700420 |
| 3/4" and 19mm Die | 5700430 |
| 5mm Die | 5700600 |
| 6mm Die | 5700601 |

| Overlap Welding Kit & Components | Part Numbers |
|----------------------------------|--------------|
| 7mm Die | 5700602 |
| 8mm Die | 5700603 |
| 9mm Die | 5700604 |
| 10mm Die | 5700605 |
| 12mm Die | 5700606 |
| 18mm Die | 5700608 |
| 20mm Die | 5700620 |
| Z/10 Die Set | 5700610 |
| A Hyfen Die Set | 5700440 |
| A/13 Die Set | 5700611 |
| A Ridge-Top Die Set | 5700470 |
| B Hyfen Die Set | 5700453 |
| B/17 Die Set | 5700612 |
| B Ridge-Top Die Set | 5700490 |
| C Hyfen Die Set | 5700457 |
| C/22 Die Set | 5700613 |
| D Hyfen Die Set | 5700460 |
| A Die Set for Hyfen CXF and CXR | 5700480 |
| B Die Set for Hyfen CXF and CXR | 5700472 |
| C Die Set for Hyfen CXF and CXR | 5700476 |
| D Die Set for Hyfen CXF and CXR | 5700474 |



Kit Includes: Welder, Control Box, Set of Dies, Flash Cutters, Cutting Shears, Carrying Case

Round Link Belting




Round


| LINK BELTING | Part Number | | Cross Section | | Minimum Pulley Ø | | Max Product Weight w/Idlers | | Max Product Weight w/UHMW | |
|-------------------------|-------------|---------|---------------|------|------------------|------|-----------------------------|------|---------------------------|------|
| | 25' | 10m | inches | mm | (in) | (mm) | (lbs) | (kg) | (lbs) | (kg) |
| POWERWIST MOVE® Belting | 0470125 | 0470133 | 5/16" | 8mm | 2.0 | 51 | 74 | 33 | 25 | 11 |
| POWERWIST MOVE Belting | 0470225 | 0470233 | 3/8" | 10mm | 3.0 | 76 | 190 | 86 | 65 | 30 |
| POWERWIST MOVE Belting | 0470325 | 0470333 | 1/2" | 13mm | 3.0 | 76 | 255 | 116 | 85 | 39 |
| POWERWIST MOVE Belting | 0470425 | 0470433 | 9/16" | 14mm | 5.5 | 140 | 450 | 204 | 155 | 70 |
| POWERWIST MOVE Belting | 0470525 | 0470533 | 3/4" | 19mm | 8.5 | 216 | 360 | 163 | 120 | 54 |



POWERWIST MOVE Round




POWERWIST MOVE V-Belt



POWERWIST MOVE SGT



POWERWIST MOVE Friction Top



POWERWIST MOVE RCS



POWERWIST Roller Drive



POWERWIST MOVE Bridge Top

Link V Belting



V



SGT

| LINK BELTING | Part Number | | | | Cross Section | Minimum Pulley Ø | | Max Product Weight w/Idlers | | Max Product Weight w/UHMW | |
|--|-------------|------------|-----------|---------|---------------|------------------|------|-----------------------------|------|---------------------------|------|
| | 25' | 100'/30.5m | 10m | 30m | | (in) | (mm) | (lbs) | (kg) | (lbs) | (kg) |
| POWERWIST MOVE Belting | 0470725 | | 0470733 | | A | 3.0 | 76 | 340 | 154 | 115 | 52 |
| POWERWIST MOVE SuperGrip Top PU | | 0430101 | | | A | 3.0 | 76 | 200 | 91 | 65 | 30 |
| POWERWIST MOVE SuperGrip Top PVC | | 0409100 | | | A | 3.0 | 76 | 200 | 91 | 65 | 30 |
| POWERWIST MOVE Friction Top® | | 0408081 | | | A | 2.5 | 64 | 200 | 91 | 65 | 30 |
| POWERWIST MOVE Bridge Top™ | | 0499020 | | | A | 3.0 | 76 | 340 | 154 | 115 | 52 |
| POWERWIST Antistatic | 0408505 | 0408501 | 040850010 | 0408500 | A | 3.0 | 76 | 340 | 154 | 115 | 52 |
| POWERWIST MOVE Belting | 0470825 | | 0470833 | | B | 5.5 | 140 | 612 | 278 | 204 | 93 |
| POWERWIST MOVE Super Grip Top PU | | 0435101 | | | B | 5.5 | 140 | 400 | 181 | 135 | 61 |
| POWERWIST MOVE Super Grip Top PVC | | 0409200 | | | B | 5.5 | 140 | 400 | 181 | 135 | 61 |
| POWERWIST MOVE Friction Top® | 0405082 | 0408082 | | | B | 5.0 | 127 | 400 | 181 | 135 | 61 |
| POWERWIST MOVE Bridge Top™ | 0499021 | 0499002 | | | B | 5.5 | 140 | 612 | 278 | 204 | 93 |
| POWERWIST MOVE Reduced Contact Surface (RCS) | | 0419300 | | | B | 5.5 | 140 | 612 | 278 | 204 | 93 |
| POWERWIST Roller Drive™ | 0410300-25 | 0410300 | 0411301 | 0411300 | B | 5.0 | 127 | 275 | 125 | 95 | 43 |
| POWERWIST Antistatic | 0408605 | 0408601 | 040860010 | 0408600 | B | 5.5 | 140 | 612 | 278 | 204 | 93 |
| POWERWIST MOVE Belting | 0470925 | | 0470933 | | C | 9.0 | 229 | 815 | 370 | 275 | 125 |
| POWERWIST MOVE Super Grip Top PU | | 0440101 | | | C | 9.0 | 229 | 650 | 295 | 220 | 100 |
| POWERWIST MOVE Super Grip Top PVC | | 0409300 | | | C | 9.0 | 229 | 650 | 295 | 220 | 100 |
| POWERWIST MOVE Belting | 0471025 | | 0471033 | | D | 13.2 | 335 | 1625 | 737 | 550 | 250 |
| POWERWIST MOVE Belting | 0470625 | | 0470633 | | Z/10 | | 45 | 230 | 105 | 78 | 36 |

* Standard package length 100' / 30.5m


† w (width) is the widest part of the belt. h (height) is the tallest part of the belt, including the belting top surface.

Dimensions are for reference only.

All listed items subject to a minimum order quantity. Consult factory for restrictions and availability.


Trackstar® Round Belt Guides

| | Belt Cross Section | Part Numbers | | | | Channel Type | A | B | D | H |
|--------------------------------|--------------------------|--------------------|-------------------------|------------------|-----------|--------------|------|------|------|------|
| | | Galvanized Channel | Stainless Steel Channel | Aluminum Channel | UHMW Only | | | | | |
| Belt Guide w/ Mounting Channel | 4mm, 5mm, 3/16" | GB1006-3G | GB1006-3S | GB1006-3A | GB1006 | C3 | 0.59 | 0.79 | 0.8 | 0.13 |
| | 6mm, 1/4" | GB1000-3G | GB1000-3S | GB1000-3A | GB1000 | C3 | 0.59 | 0.79 | 0.8 | 0.16 |
| | 7mm, 8mm, 5/6" | GB1001-3G | GB1001-3S | GB1001-3A | GB1001 | C3 | 0.59 | 0.79 | 0.8 | 0.19 |
| | 9mm, 9.5mm, 3/8" | GB1002-5G | GB1002-5S | | GB1002 | C5 | 0.59 | 1.1 | 0.84 | 0.22 |
| | 10mm, 12mm, 12.7mm, 1/2" | GB1003-5G | GB1003-5S | | GB1003 | C5 | 0.59 | 1.1 | 0.84 | 0.28 |
| | 13mm, 14mm, 9/16" | GB1004-5G | GB1004-5S | | GB1004 | C5 | 0.59 | 1.1 | 0.84 | 0.32 |
| | 15mm, 16mm, 5/8" | GB1005-5G | GB1005-5S | | GB1005 | C5 | 0.71 | 1.1 | 0.94 | 0.35 |
| | 18mm, 19mm, 20mm, 3/4" | GB1007-5G | GB1007-5S | | GB1007 | C5 | 1.02 | 1.1 | 1.26 | 0.41 |




Trackstar V Belt Guides

| | Belt Cross Section | Part Numbers | | | | Channel Type | A | B | D | H |
|------------------------------------|-----------------------------|--------------------|-------------------------|------------------|-----------|--------------|------|------|------|------|
| | | Galvanized Channel | Stainless Steel Channel | Aluminum Channel | UHMW Only | | | | | |
| V Belt Guide with Mounting Channel | 6x4, 8x5, 10x4 mm, Z/10, 3L | GB2000-3G | GB2000-3S | GB2000-3A | GB2000 | C3 | 0.59 | 0.79 | 0.8 | 0.16 |
| | A | GB2001-3G | GB2001-3S | GB2001-3A | GB2001 | C3 | 0.59 | 0.79 | 0.8 | 0.2 |
| | A Twin | GB2006-5G | GB2006-5S | | GB2006 | C5 | 0.59 | 1.42 | 0.84 | 0.2 |
| | B | GB2002-5G | GB2002-5S | | GB2002 | C5 | 0.59 | 1.1 | 0.84 | 0.29 |
| | C | GB2003-5G | GB2003-5S | | GB2003 | C5 | 0.71 | 1.1 | 0.96 | 0.4 |



Trackstar Flat Belt Guides


| | Part Numbers | | | | Channel Type | A | B | D |
|----------------------------------|--------------------|-------------------------|------------------|-----------|--------------|------|------|------|
| | Galvanized Channel | Stainless Steel Channel | Aluminum Channel | UHMW Only | | | | |
| Flat Guide with Mounting Channel | GR2001-3G | GR2001-3S | GR2001-3A | GR2001 | C3 | 0.39 | 0.79 | 0.60 |
| | GR2002-5G | GR2002-5S | - | GR2002 | C5 | 0.39 | 1.10 | 0.64 |
| | GR2003-9G | GR2003-9S | - | GR2003 | C9 | 0.59 | 1.50 | 0.96 |



Trackstar Guides are stocked in North America and supplied in 120" standard lengths. Subject to a minimum order quantity. Dimensions are in inches and are for reference only.

Trackstar® Mounting Channels

Installation is simple with standard 120" C channels in galvanized steel, 304 stainless steel, or anodized aluminum (C3 only). Either tack weld or bolt into place with optional mounting holes.




| | Part Numbers | Material | Mounting Holes | Centers |
|----------------------|--------------|----------------------|----------------|---------|
| C3 Mounting Channel | MC 0500 | Anodized Aluminum | None | - |
| | MC 1000 | Galvanized Steel | None | - |
| | MC 1001 | Galvanized Steel | .20 Diameter | 12 inch |
| | MC 1500 | #304 Stainless Steel | None | - |
| | MC 1501 | #304 Stainless Steel | .20 Diameter | 12 inch |
| C5 Mounting Channel | MC 2000 | Galvanized Steel | None | - |
| | MC 2001 | Galvanized Steel | .20 Diameter | 12 inch |
| | MC 2500 | #304 Stainless Steel | None | - |
| C9 Mounting Channel | MC 2501 | #304 Stainless Steel | .20 Diameter | 12 inch |
| | MC 3000 | Galvanized Steel | None | - |
| C10 Mounting Channel | MC 3500 | #304 Stainless Steel | None | - |
| C11 Mounting Channel | MC 4500 | #304 Stainless Steel | None | - |
| | MC 5000 | Galvanized Steel | None | - |
| | MC 5500 | #304 Stainless Steel | None | - |

Trackstar Channels are stocked in North America and supplied in 120" standard lengths. Subject to a minimum order quantity. Dimensions are in inches and are for reference only.

Trackstar Guide Rails


The "C" channel design features a two-piece construction for quick and easy replacement of UHMW inserts. "C" channel guide rails are available in Black or White (FDA/USDA approved material.)



| | Profile/Color | Part Numbers | | | |
|---------------|---------------|--------------------|-------------------------|------------------|-----------|
| | | Galvanized Channel | Stainless Steel Channel | Aluminum Channel | UHMW Only |
| C3 Guide Rail | Crowned/Black | GR1000-3G120.00 | GR1000-3S120.00 | GR1000-3A120.00 | GR1000 |
| | Crowned/White | GR1001-3G120.00 | GR1001-3S120.00 | GR1001-3A120.00 | GR1001 |
| | Flat/Black | GR1100-3G120.00 | GR1100-3S120.00 | GR1100-3A120.00 | GR1100 |
| | Flat/White | GR1101-3G120.00 | GR1101-3S120.00 | GR1101-3A120.00 | GR1101 |


Trackstar Guides are stocked in North America and supplied in 120" standard lengths. Subject to a minimum order quantity. Dimensions are in inches and are for reference only.

Trackstar® Single Chain Guide with Mounting Channel




| ANSI Chain | Part Number | | | | Channel Type | A | B | C | D | E |
|------------|-------------|-----------------|-----------|-----------|--------------|------|------|------|------|------|
| | Galvanized | Stainless Steel | Aluminum | UHMW Only | | | | | | |
| 25-1 | GC1025-3G | GC1025-3S | GC1025-3A | GC1025 | C3 | 0.59 | 0.79 | 0.86 | 0.80 | 0.79 |
| 35-1 | GC1035-3G | GC1035-3S | GC1035-3A | GC1035 | C3 | 0.59 | 0.79 | 0.90 | 0.80 | 0.79 |
| 40-1 | GC1040-3G | GC1040-3S | GC1040-3A | GC1040 | C3 | 0.59 | 0.79 | 0.95 | 0.80 | 0.79 |
| 50-1 | GC1050-3G | GC1050-3S | GC1050-3A | GC1050 | C3 | 0.59 | 0.79 | 1.00 | 0.80 | 0.79 |
| 60-1 | GC1060-5G | GC1060-5S | - | GC1060 | C5 | 0.59 | 1.10 | 1.06 | 0.83 | 1.10 |
| 80-1 | GC1080-5G | GC1080-5S | - | GC1080 | C5 | 0.71 | 1.10 | 1.26 | 0.95 | 1.34 |
| 81X | GC1081-5G | GC1081-5S | - | GC1081 | C5 | 1.25 | 1.10 | 1.95 | 1.50 | 1.75 |
| 100-1 | GC1100-9G | GC1100-9S | - | GC1100 | C9 | 0.79 | 1.50 | 1.54 | 1.16 | 1.75 |
| 120-1 | GC1120-9G | GC1120-9S | - | GC1120 | C9 | 0.79 | 1.50 | 1.60 | 1.16 | 2.12 |

Trackstar Single Chain Guide




| ANSI Chain | Part Number | A | B | C |
|------------|-------------|------|------|------|
| 25-1 | NC1025 | 0.59 | 0.79 | 0.66 |
| 35-1 | NC1035 | 0.59 | 0.79 | 0.69 |
| 40-1 | NC1040 | 0.59 | 0.79 | 0.75 |
| 50-1 | NC1050 | 0.59 | 0.79 | 0.79 |
| 60-1 | NC1060 | 0.59 | 1.10 | 0.82 |
| 80-1 | NC1080 | 0.71 | 1.34 | 1.02 |
| 81X | NC1081 | 1.00 | 1.75 | 1.45 |
| 100-1 | NC1100 | 1.00 | 1.61 | 1.38 |
| 120-1 | NC1120 | 1.25 | 2.01 | 1.69 |
| 140-1 | NC1140 | 1.50 | 2.17 | 2.00 |
| 160-1 | NC1160 | 1.50 | 2.61 | 2.06 |
| 180-1 | NC1180 | 1.50 | 2.88 | 2.20 |

Trackstar Double Chain Guide with Mounting Channel




| ANSI Chain | Part Number | | | | Channel Type | A | B | C | D | E |
|------------|-------------|-----------------|-----------|-----------|--------------|------|------|------|------|-------|
| | Galvanized | Stainless Steel | Aluminum | UHMW Only | | | | | | |
| 25-2 | GC2025-3G | GC2025-3S | GC2025-3A | GC2025 | C3 | 0.44 | 0.79 | 0.72 | 0.65 | 0.79 |
| 35-2 | GC2035-3G | GC2035-3S | GC2035-3A | GC2035 | C3 | 0.59 | 0.79 | 0.89 | 0.80 | 0.57* |
| 40-2 | GC2040-3G | GC2040-3S | GC2040-3A | GC2040 | C3 | 0.59 | 0.79 | 0.95 | 0.80 | 0.85 |
| 50-2 | GC2050-5G | GC2050-5S | - | GC2050 | C5 | 0.59 | 1.10 | 1.03 | 0.84 | 1.06 |
| 60-2 | GC2060-5G | GC2060-5S | - | GC2060 | C5 | 0.59 | 1.10 | 1.06 | 0.84 | 1.34 |
| 80-2 | GC2080-9G | GC2080-9S | - | GC2080 | C9 | 0.79 | 1.50 | 1.47 | 1.16 | 1.75 |
| 100-2 | GC2100-9G | GC2100-9S | - | GC2100 | C9 | 0.79 | 1.50 | 1.54 | 1.16 | 2.12 |

Trackstar Double Chain Guide



| ANSI Chain | Part Number | A | B | C |
|------------|-------------|------|------|------|
| 25-2 | NC2025 | 0.59 | 0.78 | 0.66 |
| 35-2 | NC2035 | 0.59 | 0.78 | 0.69 |
| 40-2 | NC2040 | 0.85 | 0.85 | 1.00 |
| 50-2 | NC2050 | 1.07 | 1.07 | 1.27 |
| 60-2 | NC2060 | 1.34 | 1.34 | 1.57 |
| 80-2 | NC2080 | 1.75 | 1.75 | 2.06 |


Trackstar Single Chain Guide with Mounting Channel



| ANSI Chain | Part Number | | | | Channel Type | A | B | D |
|------------|-------------|-----------------|-----------|-----------|--------------|------|------|------|
| | Galvanized | Stainless Steel | Aluminum | UHMW Only | | | | |
| 25-1 | GC3525-3G | GC3525-3S | GC3525-3A | GC3525 | C3 | 0.59 | 0.79 | 0.80 |
| 35-1 | GC3535-3G | GC3535-3S | GC3535-3A | GC3535 | C3 | 0.59 | 0.79 | 0.80 |
| 40-1 | GC3540-3G | GC3540-3S | GC3540-3A | GC3540 | C3 | 0.59 | 0.79 | 0.80 |
| 50-1 | GC3550-5G | GC3550-5S | - | GC3550 | C5 | 0.71 | 1.10 | 0.96 |
| 60-1 | GC3560-5G | GC3560-5S | - | GC3560 | C5 | 0.71 | 1.10 | 0.96 |
| 80-1 | GC3580-9G | GC3580-9S | - | GC3580 | C9 | 0.79 | 1.50 | 1.16 |


Trackstar Guides are stocked in North America and supplied in 120" standard lengths. Subject to a minimum order quantity. Dimensions are in inches and are for reference only.

Trackstar® Single Chain Guide




| ANSI Chain | Part Number | A | B |
|------------|-------------|------|------|
| 25-1 | NC3525 | 0.59 | 0.78 |
| 35-1 | NC3535 | 0.59 | 0.78 |
| 40-1 | NC3540 | 0.59 | 0.78 |
| 50-1 | NC3550 | 0.71 | 1.10 |
| 60-1 | NC3560 | 0.71 | 1.10 |
| 80-1 | NC3580 | 0.79 | 1.50 |

Trackstar Single Chain Guide with Mounting Channel




| ANSI Chain | Part Number | | | | Channel Type | A | B | C | D | L |
|------------|-------------|-----------------|-----------|-----------|--------------|------|------|------|------|------|
| | Galvanized | Stainless Steel | Aluminum | UHMW Only | | | | | | |
| 25-1 | GC3625-3G | GC3625-3S | GC3625-3A | GC3625 | C3 | 0.80 | 0.79 | 0.15 | 1.01 | 0.11 |
| 35-1 | GC3635-3G | GC3635-3S | GC3635-3A | GC3635 | C3 | 0.80 | 0.79 | 0.22 | 1.01 | 0.17 |
| 40-1 | GC3640-5G | GC3640-5S | - | GC3640 | C5 | 1.01 | 1.10 | 0.33 | 1.25 | 0.29 |
| 50-1 | GC3650-9G | GC3650-9S | - | GC3650 | C9 | 1.24 | 1.50 | 0.42 | 1.61 | 0.35 |
| 60-1 | GC3660-9G | GC3660-9S | - | GC3660 | C9 | 1.66 | 1.50 | 0.50 | 2.03 | 0.47 |
| 80-1 | GC3680-9G | GC3680-9S | - | GC3680 | C9 | 2.26 | 1.50 | 0.65 | 2.63 | 0.60 |

Trackstar Single Chain Guide




| ANSI Chain | Part Number | A | B | L |
|------------|-------------|------|------|------|
| 25-1 | NC3625 | 0.88 | 0.79 | 0.11 |
| 35-1 | NC3635 | 0.88 | 0.79 | 0.17 |
| 40-1 | NC3640 | 1.05 | 1.10 | 0.29 |
| 50-1 | NC3650 | 1.43 | 1.50 | 0.35 |
| 60-1 | NC3660 | 1.85 | 1.50 | 0.47 |

Trackstar Single Chain Guide with Mounting Channel



| ANSI Chain | Part Number | | | Channel Type | A | B | C | D |
|------------|-------------|-----------------|-----------|--------------|------|------|------|------|
| | Galvanized | Stainless Steel | UHMW Only | | | | | |
| 25-1 | GS1025-9G | GS1025-9S | GS1025 | C9 | 0.11 | 1.50 | 0.15 | 0.71 |
| 35-1 | GS1035-0G | GS1035-0S | GS1035 | C10 | 0.17 | 1.19 | 0.22 | 0.94 |
| 40-1 | GS1040-0G | GS1040-0S | GS1040 | C10 | 0.29 | 1.19 | 0.33 | 0.94 |
| 50-1 | GS1050-0G | GS1050-0S | GS1050 | C10 | 0.35 | 1.19 | 0.42 | 0.94 |
| 60-1 | GS1060-0G | GS1060-0S | GS1060 | C10 | 0.47 | 1.19 | 0.49 | 1.05 |
| 80-1 | GS1080-1G | GS1080-1S | GS1080 | C11 | 0.60 | 1.77 | 0.65 | 1.58 |
| 100-1 | GS1100-1G | GS1100-1S | GS1100 | C11 | 0.73 | 1.77 | 0.78 | 1.58 |


Trackstar Single Chain Guide with Mounting Channel




| ANSI Chain | Part Number | | | | Channel Type | A | B | C | D | E |
|------------|-------------|-----------------|-----------|-----------|--------------|------|------|------|------|------|
| | Galvanized | Stainless Steel | Aluminum | UHMW Only | | | | | | |
| 35-1 | GT1035-3G | GT1035-3S | GT1035-3A | GT1035 | C3 | 0.67 | 0.79 | 0.71 | 1.24 | 0.57 |
| 40-1 | GT1040-3G | GT1040-3S | GT1040-3A | GT1040 | C3 | 0.59 | 0.79 | 0.65 | 1.16 | 0.57 |
| 50-1 | GT1050-3G | GT1050-3S | GT1050-3A | GT1050 | C3 | 0.77 | 0.79 | 0.62 | 1.46 | 0.69 |
| 60-1 | GT1060-5G | GT1060-5S | - | GT1060 | C5 | 0.89 | 1.11 | 0.87 | 1.60 | 0.70 |

Trackstar Guides are stocked in North America and supplied in 120" standard lengths. Subject to a minimum order quantity. Dimensions are in inches and are for reference only.


Double Pitch Chain Guides




Style A




Style B



Style C



Style D



Style E

| Part Number | Chain Number | Dimensions (inches) | | | | | |
|----------------|--------------|---------------------|------|------|------|------|------|
| | | A | B | C | D | E | F |
| STYLE A | | | | | | | |
| DPA2040 | 2040 | 0.31 | 1.25 | 0.19 | - | 0.88 | - |
| DPA2050 | 2050 | 0.38 | 1.25 | 0.22 | - | 1.00 | - |
| DPA2060 | 2060 | 0.38 | 1.50 | 0.19 | - | 1.25 | - |
| DPA2080 | 2080 | 0.50 | 2.00 | 0.25 | - | 1.56 | - |
| DPA2100 | 2100 | 0.63 | 2.25 | 0.31 | - | 1.88 | - |
| DPA2120 | 2120 | 0.63 | 2.75 | 0.25 | - | 2.25 | - |
| DPA2081 | 81X | 1.00 | 3.00 | 0.38 | - | 2.50 | - |
| STYLE B | | | | | | | |
| DPB2040 | 2040 | 0.31 | 1.25 | 0.19 | - | 0.88 | - |
| DPB2050 | 2050 | 0.38 | 1.25 | 0.22 | - | 1.00 | - |
| DPB2060 | 2060 | 0.38 | 1.50 | 0.19 | - | 1.25 | - |
| DPB2080 | 2080 | 0.50 | 2.00 | 0.25 | - | 1.56 | - |
| DPB2100 | 2100 | 0.63 | 2.25 | 0.31 | - | 1.88 | - |
| DPB2120 | 2120 | 0.63 | 2.75 | 0.25 | - | 2.25 | - |
| STYLE C | | | | | | | |
| DPC2040 | 2040 | 0.31 | 1.00 | 0.14 | 0.08 | 0.69 | 0.25 |
| DPC2050 | 2050 | 0.38 | 1.25 | 0.19 | 0.10 | 0.81 | 0.31 |
| DPC2060 | 2060 | 0.50 | 1.50 | 0.21 | 0.12 | 1.13 | 0.44 |
| DPC2080 | 2080 | 0.50 | 2.00 | 0.25 | 0.13 | 1.44 | 0.56 |
| STYLE D | | | | | | | |
| DPD2040 | 2040 | 0.31 | 1.00 | 0.08 | - | - | 0.25 |
| DPD2050 | 2050 | 0.31 | 1.25 | 0.10 | - | - | 0.31 |
| DPD2060 | 2060 | 0.31 | 1.25 | 0.12 | - | - | 0.44 |
| DPD2080 | 2080 | 0.38 | 1.50 | 0.13 | - | - | 0.56 |
| DPD2100 | 2100 | 0.50 | 2.00 | 0.21 | - | - | 0.69 |
| DPD2120 | 2120 | 0.50 | 2.25 | 0.26 | - | - | 0.94 |
| STYLE E | | | | | | | |
| DPE2040 | 2040 | 0.31 | 1.00 | 0.08 | - | - | 0.25 |
| DPE2050 | 2050 | 0.31 | 1.25 | 0.10 | - | - | 0.31 |
| DPE2060 | 2060 | 0.31 | 1.25 | 0.12 | - | - | 0.44 |
| DPE2080 | 2080 | 0.38 | 1.50 | 0.13 | - | - | 0.56 |
| DPE2100 | 2100 | 0.50 | 2.00 | 0.21 | - | - | 0.69 |
| DPE2120 | 2120 | 0.50 | 2.25 | 0.26 | - | - | 0.94 |

Trackstar Guides are stocked in North America and supplied in 120" standard lengths. Subject to a minimum order quantity. Dimensions are in inches and are for reference only.

Chain Breakers



| Part Number | Description |
|-------------|--------------------------------|
| 5810100 | #1 Chain Breaker 25-60 Chain |
| 5810200 | #2 Chain Breaker 60-100 Chain |
| 5810300 | #3 Chain Breaker 100-160 Chain |

Chain Pullers



| Part Number | Description |
|-------------|---------------------------------|
| 5800350 | #35 Chain Puller 35 - 60 Chain |
| 5800500 | #50 Chain Puller 40 - 80 Chain |
| 5800800 | #80 Chain Puller 80 - 240 Chain |



WE SOLVE PROBLEMS

Count on Fenner Drives. We've got the right product for your application.

With over 100 years of manufacturing, technical and commercial expertise, Fenner Drives is a global leader in value-adding, problem-solving products for conveying and power transmission applications. Recognized widely for our expertise and innovation, we blend reliability, quality and value in our products while providing unsurpassed technical support and service.

Visit us at www.fennerdrives.com



www.fennerdrives.com

US and Canada • 1 800 243 3374

Latin America • 1 717 665 2421

Europe, Asia, Australia and Africa • +44 0 870 757 7007



Information subject to change without prior notification. Visit www.fennerdrives.com/catalogs for the most current information.